

Alibaba Cloud Lightning Cube

Case Study

Issue: 20190509

Legal disclaimer

Alibaba Cloud reminds you to carefully read and fully understand the terms and conditions of this legal disclaimer before you read or use this document. If you have read or used this document, it shall be deemed as your total acceptance of this legal disclaimer.








1. You shall download and obtain this document from the Alibaba Cloud website or other Alibaba Cloud-authorized channels, and use this document for your own legal business activities only. The content of this document is considered confidential information of Alibaba Cloud. You shall strictly abide by the confidentiality obligations. No part of this document shall be disclosed or provided to any third party for use without the prior written consent of Alibaba Cloud.
2. No part of this document shall be excerpted, translated, reproduced, transmitted, or disseminated by any organization, company, or individual in any form or by any means without the prior written consent of Alibaba Cloud.
3. The content of this document may be changed due to product version upgrades, adjustments, or other reasons. Alibaba Cloud reserves the right to modify the content of this document without notice and the updated versions of this document will be occasionally released through Alibaba Cloud-authorized channels. You shall pay attention to the version changes of this document as they occur and download and obtain the most up-to-date version of this document from Alibaba Cloud-authorized channels.
4. This document serves only as a reference guide for your use of Alibaba Cloud products and services. Alibaba Cloud provides the document in the context that Alibaba Cloud products and services are provided on an "as is", "with all faults" and "as available" basis. Alibaba Cloud makes every effort to provide relevant operational guidance based on existing technologies. However, Alibaba Cloud hereby makes a clear statement that it in no way guarantees the accuracy, integrity, applicability, and reliability of the content of this document, either explicitly or implicitly. Alibaba Cloud shall not bear any liability for any errors or financial losses incurred by any organizations, companies, or individuals arising from their download, use, or trust in this document. Alibaba Cloud shall not, under any circumstances, bear responsibility for any indirect, consequential, exemplary, incidental, special, or punitive damages, including lost profits arising from the use

or trust in this document, even if Alibaba Cloud has been notified of the possibility of such a loss.

5. By law, all the content of the Alibaba Cloud website, including but not limited to works, products, images, archives, information, materials, website architecture, website graphic layout, and webpage design, are intellectual property of Alibaba Cloud and/or its affiliates. This intellectual property includes, but is not limited to, trademark rights, patent rights, copyrights, and trade secrets. No part of the Alibaba Cloud website, product programs, or content shall be used, modified, reproduced, publicly transmitted, changed, disseminated, distributed, or published without the prior written consent of Alibaba Cloud and/or its affiliates. The names owned by Alibaba Cloud shall not be used, published, or reproduced for marketing, advertising, promotion, or other purposes without the prior written consent of Alibaba Cloud. The names owned by Alibaba Cloud include, but are not limited to, "Alibaba Cloud", "Aliyun", "HiChina", and other brands of Alibaba Cloud and/or its affiliates, which appear separately or in combination, as well as the auxiliary signs and patterns of the preceding brands, or anything similar to the company names, trade names, trademarks, product or service names, domain names, patterns, logos, marks, signs, or special descriptions that third parties identify as Alibaba Cloud and/or its affiliates).
6. Please contact Alibaba Cloud directly if you discover any errors in this document.

Generic conventions

Table -1: Style conventions

Style	Description	Example
	This warning information indicates a situation that will cause major system changes, faults, physical injuries, and other adverse results.	 Danger: Resetting will result in the loss of user configuration data.
	This warning information indicates a situation that may cause major system changes, faults, physical injuries, and other adverse results.	 Warning: Restarting will cause business interruption. About 10 minutes are required to restore business.
	This indicates warning information, supplementary instructions, and other content that the user must understand.	 Notice: Take the necessary precautions to save exported data containing sensitive information.
	This indicates supplemental instructions, best practices, tips, and other content that is good to know for the user.	 Note: You can use Ctrl + A to select all files.
>	Multi-level menu cascade.	Settings > Network > Set network type
Bold	It is used for buttons, menus, page names, and other UI elements.	Click OK.
Courier font	It is used for commands.	Run the <code>cd / d C :/ windows</code> command to enter the Windows system folder.
<i>Italics</i>	It is used for parameters and variables.	<code>bae log list --instanceid Instance_ID</code>
[] or [a b]	It indicates that it is an optional value, and only one item can be selected.	<code>ipconfig [-all -t]</code>

Style	Description	Example
<code>{}</code> or <code>{a b}</code>	It indicates that it is a required value, and only one item can be selected.	<code>swich {stand slave}</code>

Contents

Legal disclaimer.....	I
Generic conventions.....	I
1 Seamless migration of business data to OSS.....	1
2 Migrate data from a local NAS file system to OSS.....	11

1 Seamless migration of business data to OSS

This section describes how to migrate data from a cloud service to Alibaba Cloud OSS.

Background information

Company A is an Internet service provider that deploys the main business application in a cloud service provided by Cloud Service Provider B. The main business application of Company A provides online editing services for media files (such as images, videos). The existing data that is stored in Service Provider B includes 100,000,000 files and has a total size of about 320 TB with a daily increase of 20 GB. The bandwidth for both the storage service of Service Provider B and OSS is 250 Mbit/s. The business application requires a maximum bandwidth of 50 Mbit/s.

The company is considering a switch to OSS because of its further development needs. When you switch over businesses between two data stores, you must migrate existing data and incremental data to OSS. To ensure a successful migration of large amounts of data and business continuity, the following needs must be met:

- During the migration job, you must ensure business continuity and diminish the impacts of normal data access from end users.
- After the migration job is complete, you must check data integrity to ensure a seamless switch of the business to OSS.

Procedure

Based on the needs and background information, proceed as follows to migrate data:

1. With Data Transport, you can migrate existing data from a cloud service to OSS.
Before a migration job is complete, ensure that no updates occur on the customer side.
2. After existing data is migrated, you can create back-to-origin rules in OSS for users to access un-migrated incremental data.
3. Switch businesses to OSS.
4. After the business switchover is complete, you can migrate incremental data to OSS using Data Transport.
5. After all data is migrated and validated, delete the data at the source data address.

Step 1: Migrate existing data

1. Create an OSS bucket to store migrated data. For more information, see [Create a bucket](#).
2. Create the AccessKey of a RAM user that is used to migrate data.
 - To obtain the AccessKey of the storage service provided by Service Provider B, log on to storage service console to view the AccessKey.
 - To obtain the AccessKey of a RAM user, see [Create and authorize a RAM user](#).

3. Create data addresses and a full migration job. For more information, see [Data Transport](#) documents. Configure the required options on the Job Config tab as follows.

Create Job

For more detail please check [Product Manual](#)

×

Job Config

Performance

Select Data

* Job Name

b-oss

5/63

If no valid data address, please [Create Data Address](#)

* Source Data Address ?

[bos] bos-vip

▼

* Destination Data Address ?

[oss] oss-vip

▼

oss-cn-beijing-internal.aliyuncs.com

Schedule

Migration Type ?

Full

Incremental

Sync

After the full data migration is completed, the task will stop immediately and the incremental data will no longer be migrated. Submit a full migration multiple times with the same task, only migrate updated data

Start Time Point of File ?

All

Assign

Cancel

Next

Contact Us

Configure the required options on the Performance tab as follows.

Create Job

For more detail please check [Product Manual](#)×

Job Config

Performance

Data Prediction

Please input data size and count as exactly as possible for better performance of migration job. [How to predict data size and file count](#)

Data Size

320

TB

▼

File Count

1

100 Million

▼

Flow Control

Time Range

0:003:006:009:0012:0015:0018:0021:0024:00

Max Flow(MB/s)

200

Add

Start Time	End Time	Limitation	Operation
00:00	24:00	200 MB/s	

Contact Us

Previous

Create

4. To ensure that all data is migrated after migration, you need to [view a migration report](#) and compare data at both the source data address and the destination data address.

Note:

If a migration job fails, see [Common causes of a migration failure and solutions](#).

4

Issue: 20190509

Step 2: Create back-to-origin rules

It takes about 25 days to migrate the existing data. During the migration process, data is continuously growing at the source data address. To ensure business continuity and a seamless switchover, you need to create **Back - to - Origin** rules. When files that are requested by end users do not exist in OSS, OSS fetches these files from the source data address and return them to end users.

1. Log on to the [OSS console](#).
2. On the list of buckets, select the bucket where migrated data is located.
3. Select Basic Settings and click Configure in the Back-to-Origin section.

4. Click Create Rule. In the Create Rule dialog box, configure the required options.

Create Rule

Mode

Mirroring

Redirection

If you choose Mirroring and a requested file cannot be found on OSS, OSS will automatically fetch the file from the origin, save it locally, and return the content to the requester.

Prerequisite

☒ HTTP Status Code 404

☐ File Name Prefix

Origin URL

...

://

bcebos.com

/

testadte

/File Name

Example:

OSS address:
bucketname.oss-endpoint.com/image.jpg

Origin URL:
http://bcebos.com/testadte/image.jpg

Other Parameter

☐ Transfer queryString

3xx Response

☒ Follow the source station to redirect request

Set transmission rule of HTTP header

Allow

☐ Transmit all HTTP headers

☐ Transmit the specified HTTP header

Deny

☐ Prohibit the transmission of specified HTTP header

Configure

☐ Set the specified HTTP header parameter

OK

Cancel

- **Mode:** Select Mirroring.
- **Prerequisite:** HTTP Status Code 404 is selected by default. You can configure the File Name Prefix as needed.
- **Origin URL:** Enter the address of an endpoint.
- For more parameter settings, see [Create back-to-origin rules](#).

**Note:**

You can create a maximum of five back-to-origin rules. The five rules take effect at the same time. For multiple source data addresses, you can create multiple back-to-origin rules. You can enable OSS to fetch various types of data by setting different values for the File Name Prefix.

5. Click OK.

Step 3: Switch businesses to OSS

Change the previous data address where the business application obtain data to OSS

Step 4: Migrate incremental data

During the migration of existing data, about 100,000 files that reach a total size of about 500 GB are generated. You must migrate these incremental files to OSS.

1. Create an incremental migration job based on the steps described in Step 1.

Configure the required options on the Job Config tab as follows:

Create Job

For more detail please check [Product Manual](#)

Job Config

Performance

Select Data

* Job Name

b-oss

5/63

* Source Data Address ?

If no valid data address, please [Create Data Address](#)

[bos] bos-vip

* Destination Data Address ?

[oss] oss-vip

oss-cn-beijing-internal.aliyuncs.com

Schedule

Migration Type ?

Full

Incremental

Sync

The first migration is a full migration, and after completion, the incremental data is migrated at the specified migration interval and number of migrations. Incremental migrations are submitted multiple times with the same task, only the updated data is migrated.

Start Time Point of File ?

All

Assign

Migration Interval

1

Hour

Migration Times

1

Cancel

Next

Contact Us

Configure the required options on the Performance tab as follows:

Create Job

For more detail please check [Product Manual](#)

Job Config

Performance

Data Prediction

Please input data size and count as exactly as possible for better performance of migration job. [How to predict data size and file count](#)

Data Size

500

GB

File Count

10

10 Thous...

Flow Control

Time Range

0:00 3:00 6:00 9:00 12:00 15:00 18:00 21:00 24:00

Max Flow(MB/s)

200

Add

Start Time	End Time	Limitation	Operation
00:00	24:00	200 MB/s	

Contact Us

Previous

Create

2. Click Create to create a migration job.
3. To ensure that all data is migrated after migration, you need to [view a migration report](#) and compare data at both the source data address and the destination data address.

**Note:**

If a migration job fails, see [Common causes of a migration failure and solutions](#).

Step 5: Delete data at the source data address

After a migration job is complete, you can create a lifecycle rule for files at the source data address to avoid extra charges for storage. This rule sets an expiration date for files of one day after the time when the migration job is complete. All data at the source data address is deleted on the expiration date.

2 Migrate data from a local NAS file system to OSS

This section describes how to migrate data from a local Network Attached Storage (NAS) file system to Object Storage Service (OSS) for long-term storage.

Background information

Assume that an Hangzhou entertainment company stores data, such as media files and documents on its local NAS file server. The size of data that includes 5,000,000 files is about 20 TB. The NAS server is located in an on-premises server room. The SMB protocol is used on the server that is enabled with a firewall. As no Internet connection exists, the private IP of the server is 10.0.0.254.

To facilitate later maintenance and develop online applications, the company needs to migrate data from the NAS server to OSS.

Procedure

Based on the needs and background information, you can migrate data as follows:

1. Create a bucket in China (Hangzhou) and change the default storage location to the data address of the bucket.
2. Connect the NAS server to an Alibaba Cloud VPC using a dedicated leased line. Modify the firewall settings of the NAS server and enable access to the NAS server by all IP addresses in the VPC.
3. With Data Transport, proceed as follows to migrate data from NAS to OSS.

Step 1: Create a bucket and modify a storage location

1. In China (Hangzhou), create a bucket to store data. For more information, see [Create a bucket](#).
2. Set the bucket policy and only enable access to the bucket from company employees. For more information, see [Use bucket policies to authorize other users to access OSS resources](#).
3. Inform internal employees of changing the default storage location to the data address of the bucket.

Step 2: Connect the NAS server to a VPC

1. Connect the NAS server to a VPC using a dedicated leased line with a maximum bandwidth of 1 Gbit/s. For more information, see [Connect an on-premises IDC to a VPC through a physical connection](#).
2. Modify the firewall settings of the NAS server to enable access to the NAS server by all IP addresses of the 192.168.1.0/24 IP segment in the VPC.

Step 3: Migrate data from NAS to OSS using Data Transport

1. Create a RAM user and authorize the user to create migration jobs. Additionally, obtain the AccessKey of the RAM user. For more information, see [Create and authorize a RAM user](#).

2. Create a NAS data address. For more information about options, see [Migrate data from NAS to OSS](#). The options are shown in the following figure.

Create Data Address ⓘ For more detail please check [Product Manual](#) ✕

Data Type: NAS

② [How to config NAS data address](#)

* Data Name: nas-vip 7/63

* Data Region: China (Hangzhou)

NAS Type: Alibaba Cloud Others

* VPC: nas-vpc
vp-juh51zx

* Switches: nas-switch
vs-e5z9d3

* NAS Address: 10.0.0.254

Sub Folder:

Connection Method: SMB

Connection Password: No Password Use Password

* Username: administrator

* Password:


Cancel OK

Contact Us

3. Create an OSS data address. For more information about options, see [Migrate data from NAS to OSS](#). The options are shown in the following figure.

Create Data Address

For more detail please check [Product Manual](#)

 Data address can be used as source address or destination address. When you created data address, you can then [Create Migration Job](#)

Data Type

OSS

[How to config OSS data address](#)

* Data Name

oss-vip7/63

* Data Region

China (Hangzhou)

* OSS Endpoint

http://oss-cn-hangzhou-internal.aliyuncs.com

* AccessKey Id

LTA****VT4

* AccessKey Secret

.....

* OSS Bucket

z

OSS Prefix

Please select or input a prefix (empty means migrate all data)

Cancel

OK

Contact Us

4. Create a full migration job and configure performance options. For more information about options, see [Migrate data from NAS to OSS](#). The performance options are shown in the following figure.

Create Job

For more detail please check [Product Manual](#)

Job Config

Performance

Data Prediction

Please input data size and count as exactly as possible for better performance of migration job. [How to predict data size and file count](#)

Data Size

20

TB

File Count

5

Million

Flow Control

Time Range

0:00 3:00 6:00 9:00 12:00 15:00 18:00 21:00 24:00

Max Flow(MB/s)

5

Add

Start Time	End Time	Limitation	Operation
No Limit			

Previous

Create



Notice:

In this case, the customer is migrating data and has no bandwidth needs for other applications. Therefore, no flow control is set. In actual practice, you can set appropriate flow limits based on the usage status of the bandwidth.

5. A migration job requires about two days to complete. To ensure that all data is migrated after migration, you need to [view a migration report](#) and compare data at both the source data address and the destination data address.



Note:

If a migration job fails, see [Common causes of a migration failure and solutions](#).

6. After the data is migrated, subsequent data storage and management will be performed on OSS.