

Alibaba Cloud Apsara File Storage NAS

Product Introduction

Issue: 20190419

Legal disclaimer

Alibaba Cloud reminds you to carefully read and fully understand the terms and conditions of this legal disclaimer before you read or use this document. If you have read or used this document, it shall be deemed as your total acceptance of this legal disclaimer.

1. You shall download and obtain this document from the Alibaba Cloud website or other Alibaba Cloud-authorized channels, and use this document for your own legal business activities only. The content of this document is considered confidential information of Alibaba Cloud. You shall strictly abide by the confidentiality obligations. No part of this document shall be disclosed or provided to any third party for use without the prior written consent of Alibaba Cloud.
2. No part of this document shall be excerpted, translated, reproduced, transmitted, or disseminated by any organization, company, or individual in any form or by any means without the prior written consent of Alibaba Cloud.
3. The content of this document may be changed due to product version upgrades, adjustments, or other reasons. Alibaba Cloud reserves the right to modify the content of this document without notice and the updated versions of this document will be occasionally released through Alibaba Cloud-authorized channels. You shall pay attention to the version changes of this document as they occur and download and obtain the most up-to-date version of this document from Alibaba Cloud-authorized channels.
4. This document serves only as a reference guide for your use of Alibaba Cloud products and services. Alibaba Cloud provides the document in the context that Alibaba Cloud products and services are provided on an "as is", "with all faults" and "as available" basis. Alibaba Cloud makes every effort to provide relevant operational guidance based on existing technologies. However, Alibaba Cloud hereby makes a clear statement that it in no way guarantees the accuracy, integrity, applicability, and reliability of the content of this document, either explicitly or implicitly. Alibaba Cloud shall not bear any liability for any errors or financial losses incurred by any organizations, companies, or individuals arising from their download, use, or trust in this document. Alibaba Cloud shall not, under any circumstances, bear responsibility for any indirect, consequential, exemplary, incidental, special, or punitive damages, including lost profits arising from the use

or trust in this document, even if Alibaba Cloud has been notified of the possibility of such a loss.

5. By law, all the content of the Alibaba Cloud website, including but not limited to works, products, images, archives, information, materials, website architecture, website graphic layout, and webpage design, are intellectual property of Alibaba Cloud and/or its affiliates. This intellectual property includes, but is not limited to, trademark rights, patent rights, copyrights, and trade secrets. No part of the Alibaba Cloud website, product programs, or content shall be used, modified, reproduced, publicly transmitted, changed, disseminated, distributed, or published without the prior written consent of Alibaba Cloud and/or its affiliates. The names owned by Alibaba Cloud shall not be used, published, or reproduced for marketing, advertising, promotion, or other purposes without the prior written consent of Alibaba Cloud. The names owned by Alibaba Cloud include, but are not limited to, "Alibaba Cloud", "Aliyun", "HiChina", and other brands of Alibaba Cloud and/or its affiliates, which appear separately or in combination, as well as the auxiliary signs and patterns of the preceding brands, or anything similar to the company names, trade names, trademarks, product or service names, domain names, patterns, logos, marks, signs, or special descriptions that third parties identify as Alibaba Cloud and/or its affiliates).
6. Please contact Alibaba Cloud directly if you discover any errors in this document.

Generic conventions

Table -1: Style conventions

Style	Description	Example
	This warning information indicates a situation that will cause major system changes, faults, physical injuries, and other adverse results.	 Danger: Resetting will result in the loss of user configuration data.
	This warning information indicates a situation that may cause major system changes, faults, physical injuries, and other adverse results.	 Warning: Restarting will cause business interruption. About 10 minutes are required to restore business.
	This indicates warning information, supplementary instructions, and other content that the user must understand.	 Notice: Take the necessary precautions to save exported data containing sensitive information.
	This indicates supplemental instructions, best practices, tips, and other content that is good to know for the user.	 Note: You can use Ctrl + A to select all files.
>	Multi-level menu cascade.	Settings > Network > Set network type
Bold	It is used for buttons, menus, page names, and other UI elements.	Click OK.
<code>Courier font</code>	It is used for commands.	Run the <code>cd / d C :/ windows</code> command to enter the Windows system folder.
<i>Italics</i>	It is used for parameters and variables.	<code>bae log list --instanceid Instance_ID</code>
[] or [a b]	It indicates that it is an optional value, and only one item can be selected.	<code>ipconfig [-all -t]</code>

Style	Description	Example
{} or {a b}	It indicates that it is a required value, and only one item can be selected.	<code>swich {stand slave}</code>

Contents

Legal disclaimer.....	I
Generic conventions.....	I
1 Features.....	1
2 Scenarios.....	3
3 Storage types.....	5
4 NFS protocol limits.....	7
5 SMB protocol limits.....	9

1 Features

NAS provides a wide variety of features, such as scalable capacity, shared access, support for several standard protocols, security and compliance, encryption, flexible access modes, data transmission, and data backup.

Scalable capacity

The capacity of a file system is scalable. With an increasing or decreasing number of files, the capacity of the file system can be scaled up or down.

Shared access

Multiple computational instances share access to the same data source in a file system and use file locks to ensure data consistency.

Support for several standard protocols

Provides standard Network File System (NFS) and Server Message Block (SMB) protocols and supports mainstream Linux and Windows operating systems.

Security and compliance

Access control mechanisms, such as RAM authentication, VPC isolation, and security groups, ensure data security.

- For more information about access control by using permission groups, see [Manage the access permissions of a file system](#).
- For more information about authorization for RAM users, see [Manage the access permissions of file system resources](#).

Encryption

Encrypted data transmission prevents user data from being intercepted or sniffed during transmission.

Flexible access modes

Supports multiple access modes. You can access NAS from various networks, such as VPCs, on-premises IDCs, and dedicated networks.

Data transmission

Supports synchronous or asynchronous data transmission between NAS file systems or between NAS and OSS by using Data Transmission Service (DTS).

Data backup

Multiple copies of data can be generated by using flexible backup policies. These data backups are used to restore corrupted data.

2 Scenarios

To identify the target scenarios of Alibaba Cloud Network Attached Storage (NAS) more precisely, the application scenarios of NAS can be classified into the following five types:

Enterprise applications

With high scalability, elasticity, availability, and persistence, NAS can be used to store the files of enterprise applications and the applications delivered as services. NAS provides standard file system interfaces and semantics. Therefore, you can easily construct new applications or migrate your enterprise applications to Alibaba Cloud.

Media and entertainment workflows

Shared storage is used to process large files in media workflows, such as video editing, audio and video production, broadcast processing, and sound design and rendering. With the powerful data consistency model, high throughput, and shared file access, NAS can reduce the time required to complete the work flows and merge multiple local file repositories into a single repository that can be accessed by all users.

Big data analysis

NAS can provide the scale, performance, and features required by big data applications, for example, high throughput of computing nodes, post-write read consistency, and file operations with low latency. Many analysis workloads use file interfaces for data interactions and depend on file system semantics such as the file lock. In addition, the workloads also require to write a part of a file. NAS supports the required file system semantics and can provide scalable capacity and performance.

Content management and Web services

As a file system with high throughput and persistence, NAS can be used in content management systems and Web service applications to store and provide information for websites and online publishing and archiving applications. NAS follows the expected file system semantics, file naming conventions, and the privileges that Web developers are used to applying. Therefore, you can easily integrate NAS with Web applications and use it in websites and online publishing and archiving applications.

Container storage

Containers are ideal for microservices construction thanks to such features as fast presetting, portability, and process isolation. For the containers that access raw data at every start, a shared file system is required to allow these containers to access the file system no matter which instance they run on. NAS is ideal for container storage because it provides persistent shared access to file data.

3 Storage types

NAS provides the following storage types to meet your needs: NAS Capacity, NAS Performance, and NAS Extreme.

The features, benefits, and scenarios of each storage type are described in the following table.

Storage type	Feature	Benefit	Scenario
NAS Capacity	<ul style="list-style-type: none">• Scalable capacity and linear throughput (up to 10 Gbit/s).• Maximum throughput of 150 Mbit/s for a single TB and a maximum latency of 10 milliseconds.• Improved performance, applicable to large-capacity and high-throughput businesses.	High capacity and low cost.	Scalable capacity and cost-sensitive applications, such as big data analysis, file sharing, and data backup.
NAS Performance	<ul style="list-style-type: none">• Scalable capacity and linear throughput with increasing capacity with a maximum throughput of 20 Gbit/s.• Maximum throughput of 150 Mbit/s for a single TB and a maximum latency that is in milliseconds.• Improved performance, applicable to businesses that require large-capacity and high-throughput.	Low latency and high IOPS	Random I/O access, data-intensive, and latency-sensitive businesses, such as enterprise applications, websites, and containers.

Storage type	Feature	Benefit	Scenario
NAS Extreme	<ul style="list-style-type: none">· Maximum capacity of 32 TB. For Basic versions, the initial bandwidth is 150 Mbit/s and can be scaled up to 300 Mbit/s. For Premium versions, the initial bandwidth is 300 Mbit/s and can be scaled up to 1 Gbit/s.· A consistent latency of 100 microseconds.· Applicable to latency-sensitive businesses that handle large amounts of small files.	Ultra-low latency and high IOPS	High-Performance websites, DevOps , code repository, and CI integration environments.

4 NFS protocol limits

Network Attached Storage (NAS) supports the NFSv3 and NFSv4 protocols. However, you must pay attention to the following limits:

- Attributes not supported by NFSv4.0 include: `FATTR4_MIMETYPE`, `FATTR4_QUOTA_AVAIL_HARD`, `FATTR4_QUOTA_AVAIL_SOFT`, `FATTR4_QUOTA_USED`, `FATTR4_TIME_BACKUP`, and `FATTR4_TIME_CREATE`. If these attributes are attempted, an `NFS4ERR_ATTRNOTSUPP` error is returned to the client.
- Attributes not supported by NFSv4.1 include: `FATTR4_DIR_NOTIF_DELAY`, `FATTR4_DIRENT_NOTIF_DELAY`, `FATTR4_DACL`, `FATTR4_SACL`, `FATTR4_CHANGE_POLICY`, `FATTR4_FS_STATUS`, `FATTR4_LAYOUT_HINT`, `FATTR4_LAYOUT_TYPES`, `FATTR4_LAYOUT_ALIGNMENT`, `FATTR4_FS_LOCATIONS_INFO`, `FATTR4_MDSTHRESHOLD`, `FATTR4_RETENTION_GET`, `FATTR4_RETENTION_SET`, `FATTR4_RETENT_EVT_GET`, `FATTR4_RETENT_EVT_SET`, `FATTR4_RETENTION_HOLD`, `FATTR4_MODE_SET_MASKED`, and `FATTR4_FS_CHARSET_CAP`. If these attributes are attempted, an `NFS4ERR_ATTRNOTSUPP` error is returned to the client.
- OPs not supported by NFSv4.1 include: `OP_DELEGPURGE`, `OP_DELEGRETURN`, and `NFS4_OP_OPENATTR`. If these OPs are attempted, an `NFS4ERR_NOTSUPP` error is returned to the client.
- NFSv4 currently does not support Delegation.
- Issues concerning UID and GID
 - For the NFSv3 protocol, if the file's UID or GID exists in a Linux local account, then the corresponding user name or group name is displayed based on the mapping relations of the local UID and GID; if the file's UID or GID does not exist in the local account, then the UID or GID is displayed directly.
 - For the NFSv4 protocol, if the version of the local Linux kernel is earlier than 3.0, the UID and GID of all files is displayed as nobody; if the version is later than 3.0, then the display rule is the same as that of NFSv3 protocol.



Note:

If you use NFSv4 protocol to mount a file system, and the version of your Linux kernel is earlier than 3.0, we recommend that you do not change owner or

group of the file or directory. Otherwise, the UID and GID of the file or directory is changed to nobody.

- A single file system can be simultaneously mounted and accessed by up to 10,000 computing nodes.

5 SMB protocol limits

NAS supports the SMB protocol. However, you must pay attention to some limits.

Introduction

Server Message Block (SMB), also known as Common Internet File System (CIFS), usually refers to SMB protocols earlier than SMB2. SMB is an application-layer communication protocol used to access files, printers, and other shared resources on networks. The SMB mentioned in NAS documentations refers to SMB 2.0 and later versions, which are supported by Alibaba Cloud NAS.

Compared to NFS, the SMB protocol is more suitable for Windows clients. Many versions of Windows provide excellent support for the SMB protocol, and most Windows applications can access Alibaba Cloud NAS through the SMB protocol without modification. We recommend that you use SMB as the file system on your Windows clients.

Features

SMB provides the following functions:

- It supports SMB 2.0 and later versions, with corresponding support for Windows Vista, Windows Server 2008, and all later versions of Windows, but does not support Windows XP, Windows Server 2003, and earlier versions. The main reason is that SMB 1.0, in comparison to SMB 2.0 and later versions, has major design differences and serious defects in performance and functions, and Microsoft no longer provides support for earlier versions of Windows and Windows that only supports SMB 1.0.
- The file system capacity and performance can be linearly scaled in a single namespace. The maximum capacity for a single file system is petabyte-sized data with up to one billion of files.
- SMB supports secure access control in VPCs and classic networks to protect the privacy of user data. SMB provides mount point permission groups and supports RAM for console access (RAM APIs).
- Access method: Each mount point provides only one share, all named `myshare`. You can use `\\mount_point \ myshare` to access this SMB share.

Your multiple virtual hosts in an Alibaba Cloud classic or VPC network can simultaneously access the same SMB file system.

- The same as the NFS, SMB is based on the same distributed and highly-available underlying file system, so it provides the same SLA. The restrictions on file quantities and lengths are also the same as those in NFS.

Limits

Public cloud environments and traditional enterprise environments are different, especially in diversity and complexity of clients. A few SMB functions are not supported. These unsupported functions have no effect on the operation of most applications. The following functions are unsupported:

- Access by Linux clients
- Access to the same file system from both NFS and SMB, or direct access to an SMB file system over a WAN
- File and directory ACLs (file system ACLs are supported)
- File extended attributes and Oplocks and Lease-based client caching
- Sparse files, file compression, NIC status queries, reparse points, and other IOCTL/FSCTL operations
- Alternate data streams
- SMB Direct, SMB Multichannel, SMB Directory Leasing, Persistent File Handle, and other protocol functions provided by SMB 3.0 and later versions