

Alibaba Cloud Object Storage Service

SDK Reference

Issue: 20181130

Legal disclaimer

Alibaba Cloud reminds you to carefully read and fully understand the terms and conditions of this legal disclaimer before you read or use this document. If you have read or used this document, it shall be deemed as your total acceptance of this legal disclaimer.

1. You shall download and obtain this document from the Alibaba Cloud website or other Alibaba Cloud-authorized channels, and use this document for your own legal business activities only. The content of this document is considered confidential information of Alibaba Cloud. You shall strictly abide by the confidentiality obligations. No part of this document shall be disclosed or provided to any third party for use without the prior written consent of Alibaba Cloud.
2. No part of this document shall be excerpted, translated, reproduced, transmitted, or disseminated by any organization, company, or individual in any form or by any means without the prior written consent of Alibaba Cloud.
3. The content of this document may be changed due to product version upgrades, adjustments, or other reasons. Alibaba Cloud reserves the right to modify the content of this document without notice and the updated versions of this document will be occasionally released through Alibaba Cloud-authorized channels. You shall pay attention to the version changes of this document as they occur and download and obtain the most up-to-date version of this document from Alibaba Cloud-authorized channels.
4. This document serves only as a reference guide for your use of Alibaba Cloud products and services. Alibaba Cloud provides the document in the context that Alibaba Cloud products and services are provided on an "as is", "with all faults" and "as available" basis. Alibaba Cloud makes every effort to provide relevant operational guidance based on existing technologies. However, Alibaba Cloud hereby makes a clear statement that it in no way guarantees the accuracy, integrity, applicability, and reliability of the content of this document, either explicitly or implicitly. Alibaba Cloud shall not bear any liability for any errors or financial losses incurred by any organizations, companies, or individuals arising from their download, use, or trust in this document. Alibaba Cloud shall not, under any circumstances, bear responsibility for any indirect, consequential, exemplary, incidental, special, or punitive damages, including lost profits arising from the use or trust in this document, even if Alibaba Cloud has been notified of the possibility of such a loss.
5. By law, all the content of the Alibaba Cloud website, including but not limited to works, products, images, archives, information, materials, website architecture, website graphic layout, and webpage design, are intellectual property of Alibaba Cloud and/or its affiliates. This intellectual property includes, but is not limited to, trademark rights, patent rights, copyrights, and trade

secrets. No part of the Alibaba Cloud website, product programs, or content shall be used, modified, reproduced, publicly transmitted, changed, disseminated, distributed, or published without the prior written consent of Alibaba Cloud and/or its affiliates. The names owned by Alibaba Cloud shall not be used, published, or reproduced for marketing, advertising, promotion, or other purposes without the prior written consent of Alibaba Cloud. The names owned by Alibaba Cloud include, but are not limited to, "Alibaba Cloud", "Aliyun", "HiChina", and other brands of Alibaba Cloud and/or its affiliates, which appear separately or in combination, as well as the auxiliary signs and patterns of the preceding brands, or anything similar to the company names, trade names, trademarks, product or service names, domain names, patterns, logos, marks, signs, or special descriptions that third parties identify as Alibaba Cloud and/or its affiliates).

6. Please contact Alibaba Cloud directly if you discover any errors in this document.

Generic conventions

Table -1: Style conventions

Style	Description	Example
	This warning information indicates a situation that will cause major system changes, faults, physical injuries, and other adverse results.	 Danger: Resetting will result in the loss of user configuration data.
	This warning information indicates a situation that may cause major system changes, faults, physical injuries, and other adverse results.	 Warning: Restarting will cause business interruption. About 10 minutes are required to restore business.
	This indicates warning information, supplementary instructions, and other content that the user must understand.	 Note: Take the necessary precautions to save exported data containing sensitive information.
	This indicates supplemental instructions, best practices, tips, and other content that is good to know for the user.	 Note: You can use Ctrl + A to select all files.
>	Multi-level menu cascade.	Settings > Network > Set network type
Bold	It is used for buttons, menus, page names, and other UI elements.	Click OK .
Courier font	It is used for commands.	Run the <code>cd /d C:/windows</code> command to enter the Windows system folder.
<i>Italics</i>	It is used for parameters and variables.	<code>bae log list --instanceid Instance_ID</code>
[] or [a b]	It indicates that it is a optional value, and only one item can be selected.	<code>ipconfig [-all -t]</code>
{ } or {a b}	It indicates that it is a required value, and only one item can be selected.	<code>swich {stand slave}</code>

Contents

Legal disclaimer.....	I
Generic conventions.....	I
1 Introduction.....	1
2 Java.....	2
2.1 Preface.....	2
2.2 Installation.....	3
2.3 Quick start.....	4
2.4 Initialization.....	8
2.5 Manage a bucket.....	13
2.6 Upload objects.....	19
2.6.1 Overview.....	19
2.6.2 Simple upload.....	19
2.6.3 Form upload.....	22
2.6.4 Append upload.....	26
2.6.5 Resumable upload.....	27
2.6.6 Multipart upload.....	28
2.6.7 Upload progress bars.....	37
2.6.8 Upload callback.....	39
2.7 Download objects.....	40
2.7.1 Overview.....	40
2.7.2 Streaming download.....	41
2.7.3 Download to your local file.....	42
2.7.4 Range download.....	42
2.7.5 Resumable download.....	43
2.7.6 Conditional download.....	46
2.7.7 Download progress bars.....	47
2.8 Manage objects.....	48
2.8.1 Overview.....	48
2.8.2 Determine whether a specified object exists.....	49
2.8.3 Manage ACL for an object.....	49
2.8.4 Manage Object Meta.....	51
2.8.5 List objects.....	55
2.8.6 Delete objects.....	65
2.8.7 Copy objects.....	67
2.8.8 Restore an archive object.....	72
2.8.9 Manage a symbolic link.....	73
2.9 Data security.....	74
2.10 Authorized access.....	77
2.11 Manage lifecycle rules.....	82
2.12 CORS.....	84

2.13 Set logging.....	87
2.14 Static website hosting.....	89
2.15 Anti-leech.....	90
2.16 Cross-region replication.....	92
2.17 Image processing.....	95
2.18 Exception handling.....	102
2.19 FAQ.....	105
3 Python.....	115
3.1 Preface.....	115
3.2 Installation.....	116
3.3 Quick start.....	119
3.4 Initialization.....	121
3.5 Bucket.....	123
3.6 Upload objects.....	126
3.6.1 Overview.....	126
3.6.2 Simple upload.....	127
3.6.3 Append upload.....	130
3.6.4 Resumable upload.....	130
3.6.5 Multipart upload.....	132
3.6.6 Upload progress bars.....	133
3.6.7 Upload callback.....	134
3.7 Download objects.....	135
3.7.1 Overview.....	135
3.7.2 Streaming download.....	135
3.7.3 Download to your local file.....	136
3.7.4 Range download.....	137
3.7.5 Resumable download.....	137
3.7.6 Download progress bars.....	139
3.8 Manage objects.....	140
3.8.1 Overview.....	140
3.8.2 Determine whether a specified object exists.....	141
3.8.3 Manage ACL for an object.....	141
3.8.4 Manage Object Meta.....	143
3.8.5 List objects.....	145
3.8.6 Delete objects.....	146
3.8.7 Copy objects.....	147
3.8.8 Restore an archive object.....	149
3.8.9 Manage a symbolic link.....	149
3.9 Authorized access.....	150
3.10 Client-side encryption.....	152
3.11 Static website hosting.....	156
3.12 Manage lifecycle rules.....	157
3.13 CORS.....	159
3.14 Set logging.....	161

3.15 Anti-leech.....	162
3.16 Image processing.....	164
3.17 Chinese character and time.....	169
3.18 Exception handling.....	171
4 PHP.....	174
4.1 Preface.....	174
4.2 Installation.....	174
4.3 Quick start.....	177
4.4 Initialization.....	180
4.5 Bucket.....	184
4.6 Upload objects.....	190
4.6.1 Overview.....	190
4.6.2 Simple upload.....	191
4.6.3 File upload.....	192
4.6.4 Append upload.....	193
4.6.5 Multipart upload.....	195
4.6.6 Upload callback.....	202
4.7 Download objects.....	205
4.7.1 Overview.....	205
4.7.2 Download to your local file.....	205
4.7.3 Download to your local memory.....	206
4.7.4 Range download.....	207
4.7.5 Conditional download.....	208
4.8 Manage objects.....	209
4.8.1 Overview.....	209
4.8.2 Determine whether a specified object exists.....	210
4.8.3 Manage ACL for an object.....	210
4.8.4 Manage Object Meta.....	212
4.8.5 List objects.....	215
4.8.6 Delete objects.....	217
4.8.7 Copy objects.....	219
4.8.8 Restore an archive object.....	221
4.8.9 Manage a symbolic link.....	222
4.8.10 Enable MD5 verification.....	223
4.9 Authorized access.....	224
4.10 Static website hosting.....	227
4.11 Manage lifecycle rules.....	229
4.12 Set logging.....	232
4.13 CORS.....	235
4.14 Anti-leech.....	237
4.15 Bind a custom domain name.....	240
4.16 Image processing.....	242
4.17 Exception handling.....	248

5 Go.....	251
5.1 Preface.....	251
5.2 Installation.....	252
5.3 Quick start.....	253
5.4 Initialization.....	257
5.5 Bucket.....	259
5.6 Upload objects.....	266
5.6.1 Overview.....	266
5.6.2 Simple upload.....	266
5.6.3 Append upload.....	269
5.6.4 Resumable upload.....	270
5.6.5 Multipart upload.....	272
5.6.6 Progress bars.....	278
5.7 Download objects.....	279
5.7.1 Overview.....	279
5.7.2 Streaming download.....	279
5.7.3 Download to your local file.....	282
5.7.4 Resumable download.....	282
5.7.5 Conditional download.....	284
5.7.6 Download a compressed object.....	286
5.7.7 Progress bars.....	287
5.8 Manage objects.....	288
5.8.1 Overview.....	288
5.8.2 Determine whether a specified object exists.....	288
5.8.3 Manage ACL for an object.....	289
5.8.4 Manage Object Meta.....	290
5.8.5 List objects.....	293
5.8.6 Delete objects.....	300
5.8.7 Copy objects.....	301
5.8.8 Restore an archive object.....	306
5.8.9 Manage a symbolic link.....	308
5.9 Authorized access.....	310
5.10 Manage lifecycle rules.....	313
5.11 Set logging.....	316
5.12 Static website hosting.....	318
5.13 Anti-leech.....	319
5.14 CORS.....	322
5.15 Image processing.....	324
5.16 Error handling.....	332
6 C.....	336
6.1 Preface.....	336
6.2 Installation.....	337
6.3 Quick start.....	341

6.4 Initialization.....	348
6.5 Bucket.....	351
6.6 Upload objects.....	361
6.6.1 Overview.....	361
6.6.2 Simple upload.....	362
6.6.3 Append upload.....	364
6.6.4 Resumable upload.....	367
6.6.5 Multipart upload.....	369
6.6.6 Upload progress bars.....	374
6.6.7 Upload callback.....	376
6.7 Download objects.....	377
6.7.1 Overview.....	377
6.7.2 Download an object to a local file.....	378
6.7.3 Download to your local memory.....	379
6.7.4 Range download.....	381
6.7.5 Resumable download.....	382
6.7.6 Download progress bars.....	384
6.8 Manage objects.....	386
6.8.1 Overview.....	386
6.8.2 Manage ACL for an object.....	386
6.8.3 Manage Object Meta.....	388
6.8.4 List objects.....	390
6.8.5 Delete objects.....	397
6.8.6 Copy objects.....	401
6.8.7 Restore an archive object.....	406
6.8.8 Manage a symbolic link.....	408
6.9 Authorized access.....	410
6.10 Manage lifecycle rules.....	415
6.11 Image processing.....	420
6.12 CORS.....	429
6.13 Set logging.....	433
6.14 Anti-leech.....	437
6.15 Static website hosting.....	441
6.16 Error handling.....	445
6.17 FAQ.....	447
7 . NET.....	448
7.1 Preface.....	448
7.2 Installation.....	449
7.3 Quick start.....	451
7.4 Initialization.....	454
7.5 Manage a bucket.....	457
7.6 Upload objects.....	461
7.6.1 Overview.....	461
7.6.2 Simple upload.....	461

7.6.3 Append upload.....	465
7.6.4 Resumable upload.....	466
7.6.5 Multipart upload.....	467
7.6.6 Upload progress bars.....	474
7.6.7 Upload callback.....	475
7.7 Download objects.....	477
7.7.1 Overview.....	477
7.7.2 Streaming download.....	477
7.7.3 Range download.....	478
7.7.4 Resumable download.....	479
7.7.5 Download progress bars.....	480
7.8 Manage objects.....	481
7.8.1 Overview.....	482
7.8.2 Determine whether a specified object exists.....	482
7.8.3 Manage ACL for an object.....	482
7.8.4 Manage Object Meta.....	484
7.8.5 List objects.....	485
7.8.6 Delete objects.....	490
7.8.7 Copy objects.....	492
7.8.8 Restore an archive object.....	495
7.8.9 Manage a symbolic link.....	497
7.9 Authorized access.....	498
7.10 Manage lifecycle rules.....	500
7.11 Set logging.....	503
7.12 CORS.....	505
7.13 Anti-leech.....	507
7.14 Image processing.....	510
7.15 Static website hosting.....	517
7.16 Exception handling.....	519

1 Introduction

Before using OSS SDK, you must:

- Learn about and activate the [Alibaba Cloud OSS service](#).
- [Create an AccessKey](#).

This topic lists the topics that describe how to install, develop, and troubleshoot OSS SDKs in the following mainstream languages and provide parameters and examples.

Language	Reference
Java	Java SDK references
Python	Python SDK references
Android	Android SDK references
iOS	iOS SDK references
.NET	.NET SDK references
Node.js	Node.js SDK references
Browser.js	Browser.js SDK references
PHP	PHP SDK references
C	C SDK references
Ruby	Ruby SDK references
Go	Go SDK references
Media-C	Media-C SDK references

2 Java

2.1 Preface

This document is written based on OSS Java SDK 2.8.3.

Compatibility

- For SDK versions 2.x.x:
 - API: compatible
 - Namespace: compatible
- For SDK versions 1.0.x:
 - API: compatible
 - Namespace: incompatible. The Table Store code in version 1.0.x is removed from version 2.0.0. The package names `com.aliyun.openservices.*` and `com.aliyun.openservices.oss.*` are replaced with `com.aliyun.oss.*`.

SDK source code and API documents

For the source code of OSS Java SDK, see [GitHub](#). For more information, see [OSS Java SDK API documents](#).

Code samples

OSS SDK for Java provides a variety of code samples for your reference. The following table describes the content of code samples.

Sample file	Content
GetStartedSample.java	Quick start
CreateFolderSample.java	Create a folder in Simple upload .
AppendObjectSample.java	Append upload
UploadSample.java	Resumable upload
MultipartUploadSample.java	Multipart upload
GetProgressSample.java	Upload progress bars
CallbackSample.java	Upload callback
CRCSample.java	CRC for file upload
SimpleGetObjectSample.java	Download objects

Sample file	Content
DownloadSample.java	Resumable download
ObjectMetaSample.java	Manage Object Meta
ListObjectsSample.java	List objects
UploadPartCopySample.java	Copy objects
DeleteObjectsSample.java	Delete objects
BucketOperationsSample.java	Bucket configurations such as authorized access , lifecycle management , access log files, anti-leech , and CORS .
ImageSample.java	Image processing
PostObjectSample.java	PostObject is independent of Java SDK.
ConcurrentGetObjectSample.java	Download multiple objects at the same time. Resumable downloads are recommended.

2.2 Installation

This topic describes how to install OSS Java SDK.

Preparation

- Environment requirements

You must use Java 1.6 or later versions.

- Check the Java version

Run `java -version` to check Java version.

Download SDK

- [Direct download](#)
- [Download from GitHub](#)
- [Download previous versions](#)

Install SDK

- Method One: Add dependencies to Maven (recommended)

To use OSS Java SDK in Maven, you only need to add the corresponding dependencies to the pom.xml file. This example uses OSS Java SDK 2.8.3. Add the following content to `<dependencies>`:

```
<dependency>
```

```
<groupId>com.aliyun.oss</groupId>
<artifactId>aliyun-sdk-oss</artifactId>
<version>2.8.3</version>
</dependency>
```

- Method Two: Import jar files into Eclipse

Take OSS Java SDK 2.8.3 as an example. To import jar files into Eclipse, follow these steps:

1. Download the [Java SDK](#).
2. Decompress the Java SDK.
3. Copy the *aliyun-sdk-oss-2.8.3.jar* file and all files from the lib folder to your project.
4. Right-click your project name in Eclipse. Select **Properties > Java Build Path > Add JARs**.
5. Select all jar files you have copied in step 3 and import them to Libraries.

- Method Three: Import jar files into IntelliJ IDEA

Take OSS Java SDK 2.8.3 as an example. To import jar files into IntelliJ IDEA, follow these steps:

1. Download the [Java SDK](#).
2. Decompress the Java SDK.
3. Copy the *aliyun-sdk-oss-2.8.3.jar* file and all jar files from the lib folder to your project.
4. Right-click your project name in IntelliJ IDEA. Select **File > Project Structure > Modules > Dependencies > + > JARs or directories**.
5. Select all jar files you have copied in step 3 and import them to External Libraries.

2.3 Quick start

This topic describes how to use OSS Java SDK to perform routine operations such as bucket creation, object uploads, and object downloads.

Sample project

OSS Java SDK provides Maven-based and Ant-based sample projects. You can compile and run the sample projects on local devices or develop your own applications based on the sample projects. For the compilation and running method of the projects, see the README.md in the project directory.

- Maven sample project: [aliyun-oss-java-sdk-demo-mvn.zip](#).
- Ant sample project: [aliyun-oss-java-sdk-demo-ant.zip](#).

Create a bucket

A bucket is a global namespace in OSS. It is similar to a data container that stores files. Run the following code to create a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Create a bucket.
ossClient.createBucket(bucketName);

// Close your OSSClient instance.
ossClient.shutdown();
```

For more information about bucket naming rules, see naming conventions in [Basic concepts](#). For more information about how to create a bucket, see [Manage a bucket](#).

Upload objects

Run the following code to upload a file to OSS:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Upload content to the specified bucket and save it as the specified
// object name.
String content = "Hello OSS";
ossClient.putObject(bucketName, objectName, new ByteArrayInputStream(
    content.getBytes()));

// Close your OSSClient instance.
```

```
ossClient.shutdown();
```

For more information, see [Upload objects](#).

Download objects

Run the following code to obtain object content:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Call ossClient.getObject to return an OSSObject instance. The
// OSSObject instance contains the object content and Object Meta.
OSSObject ossObject = ossClient.getObject(bucketName, objectName);
// Call ossObject.getObjectContent to obtain object InputStream. Read
// the InputStream to obtain object content.
InputStream content = ossObject.getObjectContent();
if (content != null) {
    BufferedReader reader = new BufferedReader(new InputStreamReader(
        content));
    while (true) {
        String line = reader.readLine();
        if (line == null) break;
        System.out.println("\n" + line);
    }
    // If you do not close the reader after the data is read,
    // connection leaks may occur. Consequently, no available connections are
    // left and an exception occurs.
    content.close();
}

// Close your OSSClient instance.
ossClient.shutdown();
```

For more information, see [Download objects](#).

List objects

Use the following code to list objects in a bucket. You can list a maximum of 100 objects by default

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
```

```
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Use ossClient.listObjects to return an ObjectListing instance. The
// ObjectListing instance contains the response from listObject.
ObjectListing objectListing = ossClient.listObjects(bucketName);
// Use objectListing.getObjectSummaries to obtain the descriptions of
// all objects.
for (OSSObjectSummary objectSummary : objectListing.getObjectSummaries()) {
    System.out.println(" - " + objectSummary.getKey() + "    " +
        "(size = " + objectSummary.getSize() + ")");
}

// Close your OSSClient instance.
ossClient.shutdown();
```

For more information, see [List objects](#) in *Manage objects*.

Delete objects

For the complete code of deleting objects, see [GitHub](#).

Use the following code to delete a specified object:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Delete objects.
ossClient.deleteObject(bucketName, objectName);

// Close your OSSClient instance.
ossClient.shutdown();
```

For more information, see [Delete objects](#) in *Manage objects*.

2.4 Initialization

OSSClient serves as the OSS Java client to manage OSS resources such as buckets and objects.

To initiate an OSS request with Java SDK, you need to initiate an OSSClient instance first and then modify the default configuration items of ClientConfiguration.

Create an OSSClient instance

To create an OSSClient instance, you need to specify an endpoint. For more information about endpoints, see [Regions and endpoints](#) and [Bind a custom domain name](#).

- Use an OSS domain to create an OSSClient instance

Use the following code to create an OSSClient instance with a domain assigned by OSS:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// Close your OSSClient instance.
ossClient.shutdown();
```

You can use one or more OSSClients for your project. In other words, you can use multiple OSSClients simultaneously.

- Use a custom domain (CNAME) to create an OSSClient instance

Run the following code to create an OSSClient instance with CNAME:

```
String endpoint = "<yourEndpoint>";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create a ClientConfiguration instance. Modify parameters as
// required.
ClientConfiguration conf = new ClientConfiguration();
// Enable CNAME. CNAME indicates a custom domain bound to a bucket.
conf.setSupportCname(true);
```

```
// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret, conf);

// Close your OSSClient instance.
ossClient.shutdown();
```

**Note:**

ossClient.listBuckets is not available when CNAME is used.

- Create an OSSClient instance for Apsara Stack

Run the following code to create an OSSClient instance for Apsara Stack:

```
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create a ClientConfiguration instance. Modify parameters as
required.
ClientConfiguration conf = new ClientConfiguration();
// Disable CNAME.
conf.setSupportCname(false);

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret, conf);

// Close your OSSClient instance.
ossClient.shutdown();
```

- Use an IP address to create an OSSClient instance

Run the following code to create an OSSClient instance with an IP address:

```
// In some special cases, use the IP address as an endpoint. Specify
the actual IP address based on your requirements.
String endpoint = "http://10.10.10.10";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create ClientConfiguration.
ClientConfiguration conf = new ClientConfiguration();
// Enable OSS access with the level-2 domain. Access with the level-
2 domain is disabled by default. You need to configure this function
```

```

for OSS Java SDK versions 2.1.2 or earlier because OSS Java SDK
versions later than 2.1.2 automatically detect IP addresses.
conf.setSLDEnabled(true);

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret, conf);

// Close your OSSClient instance.
ossClient.shutdown();

```

- Use STS to create an OSSClient instance

Run the following code to create an OSSClient instance with Security Token Service (STS):

```

// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String securityToken = "<yourSecurityToken>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret, securityToken);

// Close your OSSClient instance.
ossClient.shutdown();

```

For more information, see [What is RAM and STS](#) and [Authorized access](#).

Configure an OSSClient instance

ClientConfiguration is a configuration class of OSSClient. ClientConfiguration is used to configure parameters such as user agents, host proxies, connection timeout, and the maximum number of connections. You can configure the following parameters.

Parameter	Description	Configuration method
MaxConnections	Specifies the maximum number of HTTP connections that can be enabled. The default value is 1024.	ClientConfiguration.setMaxConnections
SocketTimeout	Specifies the timeout time in milliseconds for data transmission at the sockets layer. The default value is 50,000.	ClientConfiguration.setSocketTimeout

Parameter	Description	Configuration method
ConnectionTimeout	Specifies the timeout time in milliseconds when connections are established. The default value is 50,000 milliseconds.	ClientConfiguration.setConnectionTimeout
ConnectionRequestTimeout	Specifies the timeout time in milliseconds for obtaining connections from the connection pool. No timeout is configured by default. No timeout is configured by default.	ClientConfiguration.setConnectionRequestTimeout
IdleConnectionTime	Specifies the idle connection timeout time. If the idle connection time in milliseconds exceeds the specified value, the connection is closed. The default value is 60,000.	ClientConfiguration.setIdleConnectionTime
MaxErrorRetry	Specifies the maximum number of retry attempts in the case of a request error. The default value is 3.	ClientConfiguration.setMaxErrorRetry
SupportCname	Specifies whether CNAME can be used as an endpoint. You can use CNAME as an endpoint by default.	ClientConfiguration.setSupportCname
SLDEnabled	Specifies whether access with the level-2 domain is enabled. Access with the level-2 domain is disabled by default.	ClientConfiguration.setSLDEnabled
Protocol	Specifies the protocol (HTTP or HTTPS) used to connect to OSS. The default value is HTTP.	ClientConfiguration.setProtocol
UserAgent	Specifies the user agent (the user agent in the HTTP header). The default value is "aliyun-sdk-java."	ClientConfiguration.setUserAgent

Parameter	Description	Configuration method
ProxyHost	Specifies the IP address to access the proxy host.	ClientConfiguration. setProxyHost
ProxyPort	Specifies the port for the proxy host.	ClientConfiguration. setProxyPort
ProxyUsername	Specifies the username verified by the proxy host.	ClientConfiguration. setProxyUsername
ProxyPassword	Specifies the password verified by the proxy host.	ClientConfiguration. setProxyPassword

Run the following code to configure parameters for an OSSClient instance with ClientConfiguration:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create ClientConfiguration. ClientConfiguration is a configuration
// class of OSSClient. You can use ClientConfiguration to configure
// parameters such as user agents, host proxies, connection timeout, and
// the maximum number of connections.
ClientConfiguration conf = new ClientConfiguration();

// Configure the maximum HTTP connections allowed by an OSSClient
// instance. The default value is 1024.
conf.setMaxConnections(200);
// Configure the timeout time in milliseconds for data transmission at
// SSL. The default value is 50,000.
conf.setSocketTimeout(10000);
// Configure the timeout time in milliseconds when connections are
// established. The default value is 50,000.
conf.setConnectionTimeout(10000);
// Configure the timeout time in milliseconds for retrieving
// connections from the connection pool. This function is disabled by
// default.
conf.setConnectionRequestTimeout(1000);
// Configure idle connection timeout. If the idle connection time in
// milliseconds exceeds the specified value, the connection is closed.
// The default value is 60,000.
conf.setIdleConnectionTime(10000);
// Configure the maximum number of retry attempts in the case of a
// request error. The default value is 3.
conf.setMaxErrorRetry(5);
// Check whether CNAME can be used as an endpoint. You can use CNAME
// as an endpoint by default.
conf.setSupportCname(true);
```



```
// Check whether access with the level-2 domain is enabled. Access
with the level-2 domain is disabled by default.
conf.setSLDEnabled(true);
// Configure the protocol (HTTP or HTTPS) used to connect to OSS. HTTP
is used by default.
conf.setProtocol(Protocol.HTTP);
// Configure the user agent (the user agent in the HTTP header). The
default value is "aliyun-sdk-java."
conf.setUserAgent("aliyun-sdk-java");
// Configure the port for the proxy host.
conf.setProxyHost("<yourProxyHost>");
// Configure the username verified by the proxy host.
conf.setProxyUsername("<yourProxyUserName>");
// Configure the password verified by the proxy host.
conf.setProxyPassword("<yourProxyPassword>");

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret, conf);

// Close your OSSClient instance.
ossClient.shutdown();
```

2.5 Manage a bucket

A bucket serves as a container that stores objects. Objects belong to a bucket.

Create a bucket

Run the following code to create a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret);

// Create a bucket.
String bucketName = "<yourBucketName>";
// The default storage class and ACL of the created bucket are set to
standard and private read respectively.
ossClient.createBucket(bucketName);

// Close your OSSClient.
ossClient.shutdown();
```

For more information about bucket naming rules, see [naming conventions](#) in *Basic concepts*.

You can specify the ACL and the storage class when you create a bucket, as shown in [Bucket-level permissions](#) and [Storage class](#). To create Infrequent Access or archive buckets, use Java SDK versions 2.6.0 or later. The sample code is as follows:

```
CreateBucketRequest createBucketRequest = new CreateBucketRequest(
    bucketName);
// Set the ACL to public read for a bucket. The default value is
Private.
createBucketRequest.setCannedACL(CannedAccessControlList.PublicRead);
// Set the storage class to Infrequent Access for a bucket. The
default value is Standard.
createBucketRequest.setStorageClass(StorageClass.IA);
ossClient.createBucket(createBucketRequest);
```

List buckets

Buckets are listed alphabetically. You can list all buckets or buckets that meet the specified conditions. To list Infrequent Access or archive buckets, use Java SDK versions 2.6.0 or later.

- List all buckets

Run the following code to list all buckets:

```
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// List buckets.
List<Bucket> buckets = ossClient.listBuckets();
for (Bucket bucket : buckets) {
    System.out.println("- " + bucket.getName());
}

// Close your OSSClient.
ossClient.shutdown();
```

- List buckets with a specified prefix

Run the following code to list buckets with a specified prefix:

```
ListBucketsRequest listBucketsRequest = new ListBucketsRequest();
// List buckets by a specified prefix. If no prefix is specified,
list all buckets.
listBucketsRequest.setPrefix("<yourBucketPrefix>");
BucketList bucketList = ossClient.listBuckets(listBucketsRequest);
```

```
for (Bucket bucket : bucketList.getBucketList()) {  
    System.out.println(" - " + bucket.getName());  
}
```

- List buckets by marker

The value of the marker parameter indicates the name of a bucket. Run the following code to list buckets after the specified bucket (the value of marker):

```
ListBucketsRequest listBucketsRequest = new ListBucketsRequest();  
// List buckets after the specified marker. If the marker is not  
// specified, list all buckets.  
listBucketsRequest.setMarker("<yourBucketMarker>");  
BucketList bucketList = ossClient.listBuckets(listBucketsRequest);  
for (Bucket bucket : bucketList.getBucketList()) {  
    System.out.println(" - " + bucket.getName());  
}
```

- List a specified number of buckets

Run the following code to list a specified number of buckets:

```
ListBucketsRequest listBucketsRequest = new ListBucketsRequest();  
// Set the number of buckets that can be listed to 500. The default  
// value is 100. The maximum value is 1,000.  
listBucketsRequest.setMaxKeys(500);  
BucketList bucketList = ossClient.listBuckets(listBucketsRequest);  
for (Bucket bucket : bucketList.getBucketList()) {  
    System.out.println(" - " + bucket.getName());  
}
```

Determine whether a bucket exists

Run the following code to determine whether a specified bucket exists:

```
// This example uses endpoint China (Hangzhou). Specify the actual  
// endpoint based on your requirements.  
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";  
// It is highly risky to log on with AccessKey of an Alibaba Cloud  
// account because the account has permissions on all the APIs in OSS.  
// We recommend that you log on as a RAM user to access APIs or perform  
// routine operations and maintenance. To create a RAM account, log on to  
// https://ram.console.aliyun.com.  
String accessKeyId = "<yourAccessKeyId>";  
String accessKeySecret = "<yourAccessKeySecret>";  
  
// Create an OSSClient instance.  
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);  
  
boolean exists = ossClient.doesBucketExist("<yourBucketName>");  
  
// Close your OSSClient.
```

```
ossClient.shutdown();
```

Configure an ACL for a bucket

The ACL of a bucket includes the following permissions.

Permission	Description	Value in Java SDK
Private	The bucket owner and the authorized users can read and write objects in the bucket. Other users cannot perform any operation on the objects.	CannedAccessControlList.Private
Public read	The bucket owner and the authorized users can read and write objects in the bucket. Other users can only read the objects in the bucket. Authorize this permission with caution.	CannedAccessControlList.PublicRead
Public read-write	All users can read and write objects in the bucket. Authorize this permission with caution.	CannedAccessControlList.PublicReadWrite

Run the following code to configure the ACL for a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Set the ACL for a bucket to private read and write.
ossClient.setBucketAcl("<yourBucketName>", CannedAccessControlList.Private);

// Close your OSSClient.
```

```
ossClient.shutdown();
```

Obtain the ACL for a bucket

Run the following code to obtain the ACL for a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);
// Obtain the access ACL for the bucket
AccessControlList acl = ossClient.getBucketAcl("<yourBucketName>");
System.out.println(acl.toString());

// Close your OSSClient.
ossClient.shutdown();
```

Obtain the region of a bucket

Run the following code to obtain the region for a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

String location = ossClient.getBucketLocation("<yourBucketName>");
System.out.println(location);

// Close your OSSClient.
ossClient.shutdown();
```

For more information about regions, see [Region](#) in *Basic concepts*.

Obtain bucket information

Run the following code to obtain bucket information:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We strongly recommend that you create a RAM account and use it for
// API access and daily O&M. Log on to https://ram.console.aliyun.com to
// create a RAM account.
String accessKeyId = "<accessKeyId>";
String accessKeySecret = "<accessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

Bucket information includes regions (region or location), creation
// dates (CreationDate), owners (Owner), and permissions (Grants).
BucketInfo info = ossClient.getBucketInfo("<yourBucketName>");
// Obtain region information.
info.getBucket().getLocation();
// Obtain the creation date.
info.getBucket().getCreationDate();
// Obtain owner information.
info.getBucket().getOwner();
// Obtain permission information.
info.getGrants();

// Close your OSSClient.
ossClient.shutdown();
```

Delete a bucket

Before a bucket is deleted, ensure that all objects in the bucket and fragments that are generated from multipart upload are deleted.



Note:

To delete the fragments that are generated from multipart upload, use

[*Bucket.ListMultipartUploads*](#) to list all fragments, and then use [*Bucket.AbortMultipartUpload*](#) to delete the fragments.

Run the following code to delete a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
```

```
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

/// Delete the bucket.
ossClient.deleteBucket("<yourBucketName>");

// Close your OSSClient.
ossClient.shutdown();
```

2.6 Upload objects

2.6.1 Overview

This topic is the overview of object upload in OSS Java SDK.

In OSS, an object is the basic unit for data operations. OSS Java SDK provides the following file upload methods:

- [Simple upload](#): supports the upload of a file up to 5 GB in size. It includes streaming upload and file upload.
- [Form upload](#): supports the upload of a file up to 5 GB in size.
- [Append upload](#): supports the upload of a file up to 5 GB in size.
- [Resumable upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files. It supports concurrent upload and you can define the size of each part.
- [Multipart upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files.



Note:

For more information about the usage scenarios of each upload method, see “Upload files” in OSS Developer Guide.

During the file upload, you can set [Object Meta](#), and view the upload progress in the [upload progress bar](#). After you complete the file upload, you can perform [upload callback](#).

2.6.2 Simple upload

Simple upload includes streaming upload and file upload. Streaming upload uses `InputStream` as the source object. File upload uses a local file as the source object.

For the complete simple upload code, see [GitHub](#).

Streaming upload

Use `ossClient.putObject` to upload a data stream to OSS.

- Upload a string

Run the following code to upload a string:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// Upload a string.
String content = "Hello OSS";
ossClient.putObject("<yourBucketName>", "<yourObjectName>", new
    ByteArrayInputStream(content.getBytes()));

// Close your OSSClient instance.
ossClient.shutdown();
```

- Upload a byte array

Run the following code to upload a byte array:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Upload a byte array.
byte[] content = "Hello OSS".getBytes();
ossClient.putObject("<yourBucketName>", "<yourObjectName>", new
    ByteArrayInputStream(content));

// Close your OSSClient instance.
ossClient.shutdown();
```

- Upload a network stream

Run the following code to upload a network stream:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// Upload a network stream.
InputStream inputStream = new URL("https://www.aliyun.com/").
    openStream();
ossClient.putObject("<yourBucketName>", "<yourObjectName>",
    inputStream);

// Close your OSSClient instance.
ossClient.shutdown();
```

- Upload a file stream

Run the following code to upload a file stream:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in
// OSS. To ensure cloud security, we recommend that you follow best
// practices of Resource Access Management and log on as a RAM user to
// access APIs or perform routine operations and maintenance. To create
// a RAM account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// Upload a file stream.
InputStream inputStream = new FileInputStream("<yourLocalFile>");
ossClient.putObject("<yourBucketName>", "<yourObjectName>",
    inputStream);

// Close your OSSClient instance.
```

```
ossClient.shutdown();
```

File upload

Run the following code to upload a local file:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret);

// Upload a file. <yourLocalFile> consists of a local file path and a
// file name that includes an extension, for example, /users/local/myfile
// .txt.
ossClient.putObject("<yourBucketName>", "<yourObjectName>", new File
("<yourLocalFile>"));

// Close your OSSClient instance.
ossClient.shutdown();
```

2.6.3 Form upload

Form upload uses an HTML form to upload a file to a specified bucket. The maximum size of files is 5 GB for each form upload.

For more information about the application scenarios of form upload, see [Form upload](#) in OSS Developer Guide.

Run the following code for form upload:

```
public class PostObjectSample {
    // Upload a file.
    private String localFilePath = "<yourLocalFile>";
    // This example uses endpoint China (Hangzhou). Specify the actual
    // endpoint based on your requirements.
    private String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
    // It is highly risky to log on with AccessKey of an Alibaba Cloud
    // account because the account has permissions on all the APIs in OSS.
    // We recommend that you log on as a RAM user to access APIs or perform
    // routine operations and maintenance. To create a RAM account, log on to
    // https://ram.console.aliyun.com.
    private String accessKeyId = "<yourAccessKeyId>";
    private String accessKeySecret = "<yourAccessKeySecret>";
    // Specify the bucket name.
    private String bucketName = "<yourBucketName>";
    // Specify the file name.
    private String objectName = "<yourObjectName>";
```

```

/**
 * Start form upload.
 * @throws Exception
 */
private void PostObject() throws Exception {
    // Add the bucket name to the URL. The URL format is http://
    yourBucketName.oss-cn-hangzhou.aliyuncs.com.
    String urlStr = endpoint.replace("http://", "http://" +
    bucketName+ ".");
    // Create Map for the form.
    Map<String, String> formFields = new LinkedHashMap<String,
    String>();
    // Specify the file name.
    formFields.put("key", this.objectName);
    // Configure Content-Disposition.
    formFields.put("Content-Disposition", "attachment;filename="
    + localFilePath);
    // Configure the callback parameter.
    Callback callback = new Callback();
    // Configure the IP address of the server you want to send the
    callback request to, for example, http://oss-demo.aliyuncs.com:23450
    or http://127.0.0.1:9090.
    callback.setCallbackUrl("<yourCallbackServerUrl>");
    // Configure the host field value in the callback request
    header, such as oss-cn-hangzhou.aliyuncs.com.
    callback.setCallbackHost("<yourCallbackServerHost>");
    // Configure the body field value for the callback request.
    callback.setCallbackBody("{\\\\"mimeType\\\\":${mimeType},\\\\"
    size\\\\":${size}}");
    // Configure Content-Type for the callback request.
    callback.setCallbackBodyType(CallbackBodyType.JSON);
    // Configure the custom parameters used for sending the
    callback request. Each custom parameter consists of a key and a value
    . The key must start with x:.
    callback.addCallbackVar("x:var1", "value1");
    callback.addCallbackVar("x:var2", "value2");
    // Configure the callback parameter for Map in the form.
    setCallback(formFields, callback);
    // Configure OSSAccessKeyId.
    formFields.put("OSSAccessKeyId", accessKeyId);
    String policy = "{\\"expiration\\": \\"2120-01-01T12:00:00.000Z
    \",\\"conditions\\": [[\\"content-length-range\\", 0, 104857600]]}";
    String encodePolicy = new String(Base64.encodeBase64(policy.
    getBytes()));
    // Configure the policy.
    formFields.put("policy", encodePolicy);
    // Generate the URL for signature.
    String signaturecom = com.aliyun.oss.common.auth.ServiceSig
    nature.create().computeSignature(accessKeySecret, encodePolicy);
    // Configure the signature.
    formFields.put("Signature", signaturecom);
    String ret = formUpload(urlStr, formFields, localFilePath);
    System.out.println("Post Object [" + this.objectName + "] to
    bucket [" + bucketName + "]");
    System.out.println("post reponse:" + ret);
}
private static String formUpload(String urlStr, Map<String, String
> formFields, String localFile)
    throws Exception {
    String res = "";
    HttpURLConnection conn = null;
    String boundary = "9431149156168";

```

```

        try {
            URL url = new URL(urlStr);
            conn = (URLConnection) url.openConnection();
            conn.setConnectTimeout(5000);
            conn.setReadTimeout(30000);
            conn.setDoOutput(true);
            conn.setDoInput(true);
            conn.setRequestMethod("POST");
            conn.setRequestProperty("User-Agent",
                "Mozilla/5.0 (Windows; U; Windows NT 6.1; zh-CN;
rv:1.9.2.6)");
            // Configure the MD5 value. The MD5 value is calculated
            based on the entire body.
            conn.setRequestProperty("Content-MD5", "<yourContentMD5
>");

            conn.setRequestProperty("Content-Type",
                "multipart/form-data; boundary=" + boundary);
            OutputStream out = new DataOutputStream(conn.getOutputStream());
            // Recursively read all Map data in the form and write the
            data to the OutputStream.
            if (formFields != null) {
                StringBuffer strBuf = new StringBuffer();
                Iterator<Entry<String, String>> iter = formFields.
entrySet().iterator();
                int i = 0;
                while (iter.hasNext()) {
                    Entry<String, String> entry = iter.next();
                    String inputName = entry.getKey();
                    String inputValue = entry.getValue();
                    if (inputValue == null) {
                        continue;
                    }
                    if (i == 0) {
                        strBuf.append("--").append(boundary).append("\
r\n");
                        strBuf.append("Content-Disposition: form-data
; name=\""
                            + inputName + "\"\r\n\r\n");
                        strBuf.append(inputValue);
                    } else {
                        strBuf.append("\r\n").append("--").append(
boundary).append("\r\n");
                        strBuf.append("Content-Disposition: form-data
; name=\""
                            + inputName + "\"\r\n\r\n");
                        strBuf.append(inputValue);
                    }
                    i++;
                }
                out.write(strBuf.toString().getBytes());
            }
            // Read the file and write it to the OutputStream.
            File file = new File(localFile);
            String filename = file.getName();
            String contentType = new MimeTypeMap().getMimeTypeFromExtension(
Type(file));
            if (contentType == null || contentType.equals("")) {
                contentType = "application/octet-stream";
            }
            StringBuffer strBuf = new StringBuffer();
            strBuf.append("\r\n").append("--").append(boundary)

```

```

        .append("\r\n");
        strBuf.append("Content-Disposition: form-data; name=\"file
\"; "
        + "filename=\"" + filename + "\"\r\n");
        strBuf.append("Content-Type: " + contentType + "\r\n\r\n
");
        out.write(strBuf.toString().getBytes());
        DataInputStream in = new DataInputStream(new FileInputStream
tream(file));
        int bytes = 0;
        byte[] bufferOut = new byte[1024];
        while ((bytes = in.read(bufferOut)) != -1) {
            out.write(bufferOut, 0, bytes);
        }
        in.close();
        byte[] endData = ("\r\n--" + boundary + "--\r\n").getBytes
());
        out.write(endData);
        out.flush();
        out.close();
        // Read the returned data.
        strBuf = new StringBuffer();
        BufferedReader reader = new BufferedReader(new InputStrea
mReader(conn.getInputStream()));
        String line = null;
        while ((line = reader.readLine()) != null) {
            strBuf.append(line).append("\n");
        }
        res = strBuf.toString();
        reader.close();
        reader = null;
    } catch (Exception e) {
        System.err.println("Send post request exception: " + e);
        throw e;
    } finally {
        if (conn != null) {
            conn.disconnect();
            conn = null;
        }
    }
    return res;
}

private static void setCallBack(Map<String, String> formFields,
Callback callback) {
    if (callback != null) {
        String jsonCb = OSSUtils.jsonizeCallback(callback);
        String base64Cb = BinaryUtil.toBase64String(jsonCb).
getBytes());
        formFields.put("callback", base64Cb);
        if (callback.hasCallbackVar()) {
            Map<String, String> varMap = callback.getCallbackVar
());
            for (Entry<String, String> entry : varMap.entrySet())
            {
                formFields.put(entry.getKey(), entry.getValue());
            }
        }
    }
}

public static void main(String[] args) throws Exception {
    PostObjectSample ossPostObject = new PostObjectSample();
    ossPostObject.PostObject();
}

```

```
}
}
```

2.6.4 Append upload

This topic describes how to use append upload.

You cannot perform copyObject for appended objects.

Run the following code for append upload:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

String content1 = "Hello OSS A \n";
String content2 = "Hello OSS B \n";
String content3 = "Hello OSS C \n";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret);

ObjectMetadata meta = new ObjectMetadata();
// Specify the content type of the object you want to upload.
meta.setContentType("text/plain");

// Configure parameters with AppendObjectRequest.
AppendObjectRequest appendObjectRequest = new AppendObjectRequest
("<yourBucketName>", "<yourObjectName>", new ByteArrayInputStream(
content1.getBytes()), meta);

// Configure a single parameter with AppendObjectRequest.
// Specify the bucket name.
//appendObjectRequest.setBucketName("<yourBucketName>");
// Specify the object name.
//appendObjectRequest.setKey("<yourObjectName>");
// Configure the type of content you want to append. Two types of
// content are available: InputStream and File. Select InputStream.
//appendObjectRequest.setInputStream(new ByteArrayInputStream(content1
.getBytes()));
// Configure the type of content you want to append. Two types of
// content are available: InputStream and File. Select File.
//appendObjectRequest.setFile(new File("<yourLocalFile>"));
// Specify object meta, because the specified object meta takes effect
// from the first append.
//appendObjectRequest.setMetadata(meta);

// Start the first append.
// Configure the position where the object is appended based on the
// previous object length.
appendObjectRequest.setPosition(0L);
```

```
AppendObjectResult appendObjectResult = ossClient.appendObject(
    appendObjectRequest);
// Calculate the 64-bit CRC value. The value is calculated based on
// the ECMA-182 standard. This value is calculated based on ECMA-182
// criteria.
System.out.println(appendObjectResult.getObjectCRC());

// Start the second append.
// nextPosition indicates the position provided for the next request,
// namely, the length of the current object.
appendObjectRequest.setPosition(appendObjectResult.getNextPosition());
appendObjectRequest.setInputStream(new ByteArrayInputStream(content2.
    getBytes()));
appendObjectResult = ossClient.appendObject(appendObjectRequest);

// Start the third append.
appendObjectRequest.setPosition(appendObjectResult.getNextPosition());
appendObjectRequest.setInputStream(new ByteArrayInputStream(content3.
    getBytes()));
appendObjectResult = ossClient.appendObject(appendObjectRequest);

// Close your OSSClient.
ossClient.shutdown();
```

For more information about append upload, see [Append object](#) in OSS Developer Guide. For the complete code of append upload, see [GitHub](#).

2.6.5 Resumable upload

You can use resumable upload to split a file you want to upload into several parts and upload them simultaneously. After you have uploaded all parts, you can combine these parts into a complete object. Thus, you can complete uploading the entire object.

For more information about resumable upload, see [Resumable upload](#) in the OSS Developer Guide. For the complete code of resumable upload, see [GitHub](#).

Run the following code for resumable upload:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

ObjectMetadata meta = new ObjectMetadata();
// Specify the content type of the object you want to upload.
meta.setContentType("text/plain");
```

```
// Configure parameters with UploadFileRequest.
UploadFileRequest uploadFileRequest = new UploadFileRequest("<
yourBucketName>", "<yourObjectName>");

// Configure parameters with UploadFileRequest.
// Specify the bucket name.
//uploadFileRequest.setBucketName("<yourBucketName>");
// Specify the object name.
//uploadFileRequest.setKey("<yourObjectName>");
// Specify the local file you want to upload.
uploadFileRequest.setUploadFile("<yourLocalFile>");
// Specify the number of threads for simultaneous upload. The default
value is 1.
uploadFileRequest.setTaskNum(5);
// Specify the size of a part you want to upload. The value can be
from 100 KB to 5 GB. The default size of a part is calculated as: file
size/10,000.
uploadFileRequest.setPartSize(1 * 1024 * 1024);
// Start resumable upload (that is disabled by default.).
uploadFileRequest.setEnableCheckpoint(true);
// Configure the file used to record the result of local part uploads
. You need to configure this parameter when you enable resumable
upload. This file stores progress information. If a part upload fails
, it can be continued based on the progress information recorded in
this file. After you have uploaded the file, the file is deleted. By
default, this file shares the same directory (uploadFile.ucp) as the
file you want to upload.
uploadFileRequest.setCheckpointFile("<yourCheckpointFile>");
// Configure object meta.
uploadFileRequest.setObjectMetadata(meta);
// Configure callback. Set the yourCallbackEvent parameter to Callback
.
uploadFileRequest.setCallback("<yourCallbackEvent>");

// Start resumable upload.
ossClient.uploadFile(uploadFileRequest);

// Close your OSSClient.
ossClient.shutdown();
```

2.6.6 Multipart upload

This topic describes how to use multipart upload.

For the complete code of multipart upload, see [GitHub](#).

To enable multipart upload, perform the following steps:

1. Initiate a multipart upload event.

You can call `ossClient.initiateMultipartUpload` to return the globally unique uploadId created in OSS.

2. Upload parts.

You can call `ossClient.uploadPart` to upload part data.

**Note:**

- For parts with a same uploadId, parts are sequenced by their part numbers. If you have uploaded a part and use the same part number to upload another part, the later part will replace the former part.
- OSS places the MD5 value of part data in ETag and returns the MD5 value to the user.
- SDK automatically configures Content-MD5. OSS calculates the MD5 value of uploaded data and compares it with the MD5 value calculated by SDK. If the two values vary, the error code of InvalidDigest is returned.

3. Complete multipart upload.

After you have uploaded all parts, call `partossClient.completeMultipartUpload` to combine these parts into a complete object.

The following code is used as a complete example that describes the process of multipart upload:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

/* Step 1: Initiate a multipart upload event.
*/
InitiateMultipartUploadRequest request = new InitiateMultipartUploadRequest(bucketName, objectName);
InitiateMultipartUploadResult result = ossClient.initiateMultipartUpload(request);
// An uploadId is returned. It is the unique identifier for a part
// upload event. You can initiate related operations (such as part upload
// cancelation and query) based on the uploadId.
String uploadId = result.getUploadId();

/* Step 2: Upload parts.
*/
// partETags is a set of PartETags. A PartETag consists of an ETag and
// a part number.
List<PartETag> partETags = new ArrayList<PartETag>();
// Calculate the total number of parts.
final long partSize = 1 * 1024 * 1024L; // 1MB
final File sampleFile = new File("<localFile>");
```

```

long fileLength = sampleFile.length();
int partCount = (int) (fileLength / partSize);
if (fileLength % partSize != 0) {
    partCount++;
}
// Upload each part simultaneously until all parts are uploaded.
for (int i = 0; i < partCount; i++) {
    long startPos = i * partSize;
    long curPartSize = (i + 1 == partCount) ? (fileLength - startPos) : partSize;
    InputStream instream = new FileInputStream(sampleFile);
    // Skip parts that have been uploaded.
    instream.skip(startPos);
    UploadPartRequest uploadPartRequest = new UploadPartRequest();
    uploadPartRequest.setBucketName(bucketName);
    uploadPartRequest.setKey(objectName);
    uploadPartRequest.setUploadId(uploadId);
    uploadPartRequest.setInputStream(instream);
    // Configure the size available for each part. Aside from the last part, all parts are sized 100 KB at least.
    uploadPartRequest.setPartSize(curPartSize);
    // Configure part numbers. Each part is configured with a part number. The value can be from 1 to 10,000. If you configure a number beyond the range, OSS returns an InvalidArgument error code.
    uploadPartRequest.setPartNumber(i + 1);
    // Do not upload each part sequentially. They can be uploaded from different OSSClients. Then they are sequenced and combined into a complete object based on part numbers.
    UploadPartResult uploadPartResult = ossClient.uploadPart(uploadPartRequest);
    // After you upload a part, OSS returns a result that contains a PartETag. The PartETag is stored in partETags.
    partETags.add(uploadPartResult.getPartETag());
}

/* Step 3: Complete multipart upload.
*/
// Sequence parts. partETags must be sequenced by part numbers in ascending order.
Collections.sort(partETags, new Comparator<PartETag>() {
    public int compare(PartETag p1, PartETag p2) {
        return p1.getPartNumber() - p2.getPartNumber();
    }
});
// You must provide all valid PartETags when you perform this operation. OSS verifies the validity of all parts one by one after it receives PartETags. After part verification is successful, OSS combines these parts into a complete object.
CompleteMultipartUploadRequest completeMultipartUploadRequest =
    new CompleteMultipartUploadRequest(bucketName, objectName, uploadId, partETags);
ossClient.completeMultipartUpload(completeMultipartUploadRequest);

// Close your OSSClient.

```

```
ossClient.shutdown();
```

Cancel a multipart upload event

You can call `ossClient.abortMultipartUpload` to cancel a multipart upload event. If you cancel a multipart upload event, you are not allowed to perform any other operations with this `uploadId` anymore. The uploaded parts will be deleted.

Run the following code to cancel a multipart upload event:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Cancel multipart upload. The uploadId is from InitiateMultipartUpload.
AbortMultipartUploadRequest abortMultipartUploadRequest =
    new AbortMultipartUploadRequest("<yourBucketName>", "<yourObjectName>", "<uploadId>");
ossClient.abortMultipartUpload(abortMultipartUploadRequest);

// Close your OSSClient.
ossClient.shutdown();
```

List uploaded parts

Call `ossClient.listParts` to list all uploaded parts with a specified `uploadId`.

- Simple list

Run the following code for simple list:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);
```

```
// List uploaded parts. The uploadId is returned from InitiateMu
ltipartUpload.
ListPartsRequest listPartsRequest = new ListPartsRequest("<
yourBucketName>", "<yourObjectName>", "<uploadId>");
// Configure uploadId.
//listPartsRequest.setUploadId(uploadId);
// Set the maximum number of parts that can be displayed on each
page to 100. The default number is 1,000.
listPartsRequest.setMaxParts(100);
// Specify the initial position in the list. Only the parts with
part numbers greater than this parameter value are listed.
listPartsRequest.setPartNumberMarker(2);
PartListing partListing = ossClient.listParts(listPartsRequest);

for (PartSummary part : partListing.getParts()) {
    // Obtain part numbers.
    part.getPartNumber();
    // Obtain the size of part data.
    part.getSize();
    // Obtain ETag.
    part.getETag();
    // Obtain the latest time parts are modified.
    part.getLastModified();
}

// Close your OSSClient.
ossClient.shutdown();
```

- List all uploaded parts

By default, listParts can only list a maximum of 1,000 parts at a time. To list more than 1,000 uploaded parts, run the following code:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// List all uploaded parts.
PartListing partListing;
ListPartsRequest listPartsRequest = new ListPartsRequest("<
yourBucketName>", "<yourObjectName>", "<uploadId>");

do {
    partListing = ossClient.listParts(listPartsRequest);

    for (PartSummary part : partListing.getParts()) {
        // Obtain part numbers.
        part.getPartNumber();
        // Obtain the part size.
```

```

        part.getSize();
        // Obtain ETag.
        part.getETag();
        // Obtain the latest time parts are modified.
        part.getLastModified();
    }
    // Specify the initial position for the list. Only the parts with
    // part numbers greater than the initial value are listed.
    listPartsRequest.setPartNumberMarker(partListing.getNextPartNumberMarker());
} while (partListing.isTruncated());

// Close your OSSClient.
ossClient.shutdown();

```

- List all uploaded parts on one or more pages

Run the following code to specify the maximum number of parts displayed on each page:

```

// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// List all uploaded parts on one or more pages.
PartListing partListing;
ListPartsRequest listPartsRequest = new ListPartsRequest("<
yourBucketName>", "<yourObjectName>", "<uploadId>");
// Set the maximum number of parts displayed on each page to 100.
listPartsRequest.setMaxParts(100);

do {
    partListing = ossClient.listParts(listPartsRequest);

    for (PartSummary part : partListing.getParts()) {
        // Obtain part numbers.
        part.getPartNumber();
        // Obtain the part size.
        part.getSize();
        // Gets the etag of the slice.
        part.getETag();
        // Obtain the latest time parts are modified.
        part.getLastModified();
    }

    listPartsRequest.setPartNumberMarker(partListing.getNextPartNumberMarker());
} while (partListing.isTruncated());

// Close your OSSClient.

```

```
ossClient.shutdown();
```

List all part upload events for a bucket

Call `ossClient.listMultipartUploads` to list all ongoing part upload events (events that have been initiated but not completed or have been canceled). You can configure the following parameters:

Parameter	Description	Configuration method
prefix	Specifies the prefix that must be included in the returned object name. Note that if you use a prefix for query, the returned object name will contain the prefix.	<code>ListMultipartUploadsRequest.setPrefix(String prefix)</code>
delimiter	Specifies a delimiter of a forward slash (/) used to group object names. The object between the specified prefix and the first occurrence of a delimiter of a forward slash (/) is commonPrefixes.	<code>ListMultipartUploadsRequest.setDelimiter(String delimiter)</code>
maxUploads	Specifies the maximum number of part upload events. The maximum value (also default value) you can set is 1,000.	<code>ListMultipartUploadsRequest.setMaxUploads(Integer maxUploads)</code>
keyMarker	Lists all part upload events with the object whose names start with a letter that comes after the keyMarker value in the alphabetical order. You can use this parameter with the uploadIdMarker parameter to specify the initial position for the specified returned result.	<code>ListMultipartUploadsRequest.setKeyMarker(String keyMarker)</code>
uploadIdMarker	You can use this parameter with the keyMarker parameter to specify the initial position for the specified returned result. If you do not configure keyMarker, the uploadIdMarker parameter is invalid. If you	<code>ListMultipartUploadsRequest.setUploadIdMarker(String uploadIdMarker)</code>

Parameter	Description	Configuration method
	configure keyMarker, the query result contains: - All objects whose names start with a letter that comes after the keyMarker value. - All objects whose names start with a letter that is the same as the keyMarker value in the alphabetical order and the value of uploadId greater than that of uploadIdMarker.	

- Simple list

Run the following code to list multipart upload events:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Lists multipart upload events. You can list 1,000 parts by
// default.
ListMultipartUploadsRequest listMultipartUploadsRequest = new
ListMultipartUploadsRequest(bucketName);
MultipartUploadListing multipartUploadListing = ossClient.listMultipartUploads(listMultipartUploadsRequest);

for (MultipartUpload multipartUpload : multipartUploadListing.
getMultipartUploads()) {
    // Obtain uploadId.
    multipartUpload.getUploadId();
    // Obtain object names.
    multipartUpload.getKey();
    // Obtain the time part upload events are initiated.
    multipartUpload.getInitiated();
}

// Close your OSSClient.
```

```
ossClient.shutdown();
```

If the returned result shows that the value of `isTruncated` is false, the values of `nextKeyMarker` and `nextUploadIdMarker` are returned and used as the initial position for the next object reading. If you fail to obtain all part upload events at a time, list them by pagination.

- List all part upload events

By default, `listMultipartUploads` can only list a maximum of 1,000 parts at a time. To list more than 1,000 parts, run the following code to list all parts:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Lists multipart upload events.
MultipartUploadListing multipartUploadListing;
ListMultipartUploadsRequest listMultipartUploadsRequest = new
ListMultipartUploadsRequest(bucketName);

do {
    multipartUploadListing = ossClient.listMultipartUploads(
listMultipartUploadsRequest);

    for (MultipartUpload multipartUpload : multipartUploadListing.
getMultipartUploads()) {
        // Obtain uploadId.
        multipartUpload.getUploadId();
        // Obtain object names.
        multipartUpload.getKey();
        // Obtain the time part upload events are initiated.
        multipartUpload.getInitiated();
    }

    listMultipartUploadsRequest.setKeyMarker(multipartUploadListing.
getNextKeyMarker());

    listMultipartUploadsRequest.setUploadIdMarker(multipartU
ploadListing.getNextUploadIdMarker());
} while (multipartUploadListing.isTruncated());

// Close your OSSClient.
ossClient.shutdown();
```

- List part upload events on one or more pages

Run the following code to list part upload events on one or more pages:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Lists multipart upload events.
MultipartUploadListing multipartUploadListing;
ListMultipartUploadsRequest listMultipartUploadsRequest = new
ListMultipartUploadsRequest(bucketName);
// Configure the number of part upload events that can be displayed
// on each page.
listMultipartUploadsRequest.setMaxUploads(50);

do {
    multipartUploadListing = ossClient.listMultipartUploads(
listMultipartUploadsRequest);

    for (MultipartUpload multipartUpload : multipartUploadListing.
getMultipartUploads()) {
        // Obtain uploadId.
        multipartUpload.getUploadId();
        // Obtain object names.
        multipartUpload.getKey();
        // Obtain the time part upload events are initiated.
        multipartUpload.getInitiated();
    }

    listMultipartUploadsRequest.setKeyMarker(multipartUploadListing.
getNextKeyMarker());
    listMultipartUploadsRequest.setUploadIdMarker(multipartU
ploadListing.getNextUploadIdMarker());
} while (multipartUploadListing.isTruncated());

// Close your OSSClient.
ossClient.shutdown();
```

2.6.7 Upload progress bars

You can use progress bars to indicate the upload or download progress.

The following code is used as an example to describe how to view progress information with `ossClient.putObject`:

```
public class PutObjectProgressListener implements ProgressListener {
```

```

private long bytesWritten = 0;
private long totalBytes = -1;
private boolean succeed = false;

@Override
public void progressChanged(ProgressEvent progressEvent) {
    long bytes = progressEvent.getBytes();
    ProgressEventType eventType = progressEvent.getEventType();
    switch (eventType) {
        case TRANSFER_STARTED_EVENT:
            System.out.println("Start to upload.....");
            break;
        case REQUEST_CONTENT_LENGTH_EVENT:
            this.totalBytes = bytes;
            System.out.println(this.totalBytes + " bytes in total will
be uploaded to OSS");
            break;
        case REQUEST_BYTE_TRANSFER_EVENT:
            this.bytesWritten += bytes;
            if (this.totalBytes != -1) {
                int percent = (int)(this.bytesWritten * 100.0 / this.
totalBytes);
                System.out.println(bytes + " bytes have been written
at this time, upload progress: " + percent + "%(" + this.bytesWritten
+ "/" + this.totalBytes + ")");
            } else {
                System.out.println(bytes + " bytes have been written
at this time, upload ratio: unknown" + "(" + this.bytesWritten +
"/...");
            }
            break;
        case TRANSFER_COMPLETED_EVENT:
            this.succeed = true;
            System.out.println("Succeed to upload, " + this.bytesWritt
en + " bytes have been transferred in total");
            break;
        case TRANSFER_FAILED_EVENT:
            System.out.println("Failed to upload, " + this.bytesWritt
en + " bytes have been transferred");
            break;
        default:
            break;
    }
}

public boolean isSucceed() {
    return succeed;
}

public static void main(String[] args) {
    // This example uses endpoint China (Hangzhou). Specify the
actual endpoint based on your requirements.
    String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
    // It is highly risky to log on with AccessKey of an Alibaba
Cloud account because the account has permissions on all the APIs
in OSS. We recommend that you log on as a RAM user to access APIs or
perform routine operations and maintenance. To create a RAM account,
log on to https://ram.console.aliyun.com.
    String accessKeyId = "<yourAccessKeyId>";
    String accessKeySecret = "<yourAccessKeySecret>";
    String bucketName = "<yourBucketName>";
    String objectName = "<yourObjectName>";

```

```

        // Create an OSSClient instance.
        OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

        try {
            // Upload with a progress bar displayed.
            ossClient.putObject(new PutObjectRequest(bucketName,
objectName, new FileInputStream("<yourLocalFile>")).
                <PutObjectRequest>withProgressListener(new
PutObjectProgressListener()));
        } catch (Exception e) {
            e.printStackTrace();
        }
        // Close your OSSClient instance.
        ossClient.shutdown();
    }
}

```

You can view progress information with `ossClient.putObject`, `ossClient.getObject`, or `ossClient.uploadPart`. However, you cannot view progress information with `ossClient.uploadFile` or `ossClient.downloadFile`.

For the complete code of upload progress bar, see [GitHub](#).

2.6.8 Upload callback

This topic describes how to use

For the complete code of upload callback, see [GitHub](#).

Run the following code for upload callback:

```

// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";
// Specify the IP address of the server you want to send the callback
// request to, for example, http://oss-demo.aliyuncs.com:23450 or http://
// 127.0.0.1:9090.
String callbackUrl = "<yourCallbackServerUrl>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

String content = "Hello OSS";
PutObjectRequest putObjectRequest = new PutObjectRequest(bucketName,
objectName, new ByteArrayInputStream(content.getBytes()));

```

```
// Configure upload callback parameters.
Callback callback = new Callback();
callback.setCallbackUrl(callbackUrl);
// Configure the value of the host field carried in the callback
request header, such as oss-cn-hangzhou.aliyuncs.com.
callback.setCallbackHost("oss-cn-hangzhou.aliyuncs.com");
// Configure the value of the body field carried in the callback
request.
callback.setCallbackBody("{\"\\\\"mimeType\\\\\\":${mimeType},\\\\\\"size\\\\\\":
${size}}");
// Configure Content-Type for the callback request.
callback.setCallbackBodyType(CallbackBodyType.JSON);
// Configure the custom parameters used to initiate a callback request
. Each custom parameter consists of a key and a value. The key must
start with x:.
callback.addCallbackVar("x:var1", "value1");
callback.addCallbackVar("x:var2", "value2");
putObjectRequest.setCallback(callback);

PutObjectResult putObjectResult = ossClient.putObject(putObjectRequest
);

// Read the message returned from upload callback.
byte[] buffer = new byte[1024];
putObjectResult.getCallbackResponseBody().read(buffer);
// If you do not close the reader after the data is read, connection
leaks may occur. Consequently, no available connections are left and
an exception occurs.
putObjectResult.getCallbackResponseBody().close();

// Close your OSSClient instance.
ossClient.shutdown();
```

For more information, see [Upload callback](#) in OSS Developer Guide.

2.7 Download objects

2.7.1 Overview

This topic is the overview of object download in OSS Java SDK.

OSS Java SDK provides the following download methods:

- [Streaming download](#)
- [Download to your local file](#)
- [Range download](#)
- [Resumable download](#)
- [Conditional download](#)

You can view the download progress shown in the [download progress bar](#).

2.7.2 Streaming download

If you have a large object to download or it is time-consuming to download the entire object at a time, you can use streaming download. Streaming download enables you to download part of the object each time until you have downloaded the entire object.

If you do not close `OssObject` after it is used, connection leaks may occur. Consequently, no connection is available and the program cannot run properly. Run the following code to close `OssObject`:

```
OssObject ossObject = ossClient.getObject(bucketName, objectName);
ossObject.close();
```

The following code is used for streaming downloads:

```
// This example uses the endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// ossObject includes the bucket name, key (object name), object meta
// (meta information), and InputStream.
OssObject ossObject = ossClient.getObject(bucketName, objectName);

// Read the object content.
System.out.println("Object content:");
BufferedReader reader = new BufferedReader(new InputStreamReader(
    ossObject.getObjectContent()));
while (true) {
    String line = reader.readLine();
    if (line == null) break;

    System.out.println("\n" + line);
}
// If you do not close the reader after the data is read, connection
// leaks may occur. Consequently, no connection is available and the
// program cannot run properly.
reader.close();

//Close your OSSClient.
ossClient.shutdown();
```

For the complete code of streaming download, see [GitHub](#).

2.7.3 Download to your local file

This topic describes how to download an object from OSS to a local file.

You can run the following code to download a specified object from OSSClient to your local file:

```
//This example uses the endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret);

// Download an object to your local file. If the name of the object
is the same as that of your local file, the object will replace the
local file. If the name of the object is different from that of your
local file, the object will be downloaded and a new file will be added
to your local device.
ossClient.getObject(new GetObjectRequest(bucketName, objectName), new
File("<yourLocalFile>"));

//Close your OSSClient.
ossClient.shutdown();
```

2.7.4 Range download

If you only need part of the data in an object, you can use range downloads to download specified content.

Run the following code for range download:

```
//This example uses the endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret);
```

```
GetObjectRequest getObjectRequest = new GetObjectRequest(bucketName,
objectName);
// Obtain data between the starting byte value of 0 and the maximum
byte value of 1,000 inclusive (that is, a total of 1,001 bytes). If
the specified value range is invalid, for example, the specified range
includes a negative number, or the specified value is larger than the
object size, the entire object is downloaded.
getObjectRequest.setRange(0, 1000);

// Start range download.
OSSObject ossObject = ossClient.getObject(getObjectRequest);

// Read data.
byte[] buf = new byte[1024];
InputStream in = ossObject.getObjectContent();
for (int n = 0; n != -1; ) {
    n = in.read(buf, 0, buf.length);
}

// If you do not close the reader after the data is read, connection
leaks may occur. Consequently, no connections are available and an
exception occurs.
in.close();

//Close your OSSClient.
ossClient.shutdown();
```

All data cannot be read at one time when it is streamed. To stream a 64 KB block of data, use the following code to read the data multiple times until the entire object is downloaded. For more information, see [InputStream.read](#).

```
byte[] buf = new byte[1024];
InputStream in = ossObject.getObjectContent();
for (int n = 0; n != -1; ) {
    n = in.read(buf, 0, buf.length);
}
in.close();
```

2.7.5 Resumable download

Large-sized objects may fail to be downloaded because the network is unstable or the Java program exits abnormally and the entire object needs to be downloaded again. However, the object may still fail to be downloaded after multiple attempts. Therefore, OSS provides resumable download.

To enable resumable download, you need to split the object you want to download into multiple parts and download them separately. After you have downloaded all parts, these parts will be combined into a complete object.

You can use `ossClient.downloadFile` to enable resumable download. `DownloadFileRequest` contains the following parameters:

Parameter	Description	Required or optional	Default value	Configuration methods
bucket	Specifies the name of a bucket.	Required	None	Constructor
key	Specifies the name of an object.	Required	None	Constructor
downloadFile	Specifies a local file. You can download an object to the local file.	Optional	Name of the object	Constructor or setDownloadFile
partSize	Specifies the size of a part. The value can be between 1 byte to 5 GB.	Optional	Size of an object/10000	setPartSize
taskNum	Specifies the number of parts you need to download simultaneously.	Optional	1	setTaskNum
enableCheckpoint	Specifies whether resumable download is enabled.	Optional	Disable	setEnabledCheckpoint
checkpointFile	Specifies the file to record the results of partial downloads. You need to configure this parameter to enable resumable download. This file stores information about the download progress. If you fail to download a part, the	Optional	downloadFile.ucp (share the same directory with DownloadFile)	setCheckpointFile

Parameter	Description	Required or optional	Default value	Configuration methods
	download will continue based on the recorded progress. After the object is downloaded to your local device , this file will be deleted.			

Run the following code for resumable download:

```
//This example uses the endpoint China East 1 (Hangzhou). Specify the
//actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
//It is highly risky to log on with AccessKey of an Alibaba Cloud
//account because the account has permissions on all the APIs in OSS.
//We recommend that you log on as a RAM user to access APIs or perform
//routine operations and maintenance. To create a RAM account, log on to
//https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Send a request to download 10 tasks simultaneously and start
//resumable download.
DownloadFileRequest downloadFileRequest = new DownloadFileRequest(
    bucketName, objectName);
downloadFileRequest.setDownloadFile("<yourDownloadFile>");
downloadFileRequest.setPartSize(1 * 1024 * 1024);
downloadFileRequest.setTaskNum(10);
downloadFileRequest.setEnableCheckpoint(true);
downloadFileRequest.setCheckpointFile("<yourCheckpointFile>");

// Download the object to your local file.
DownloadFileResult downloadRes = ossClient.downloadFile(downloadFileRequest);
// After the download succeeds, object meta is returned.
downloadRes.getObjectMeta();

//Close your OSSClient.
```

```
ossClient.shutdown();
```

2.7.6 Conditional download

You can configure one or more conditions for downloads. If the specified conditions are met, the object can be downloaded. If the specified conditions are not met, an error code is returned and the object cannot be downloaded. You can configure the following conditions:

Parameter	Description
If-Modified-Since	If the specified time is earlier than the time the object is modified, the object can be downloaded. Otherwise, an error (304 Not modified) is returned.
If-Unmodified-Since	If the specified time is later than or equal to the time the object is modified, the object can be downloaded. Otherwise, an error (412 Precondition failed) is returned.
If-Match	If the specified ETag matches that of an object, the object can be downloaded. Otherwise, an error (412 Precondition failed) is returned.
If-None-Match	If the specified ETag does not match that of an object, the object can be downloaded. Otherwise, an error (304 Not modified) is returned.

Both If-Modified-Since and If-Unmodified-Since can exist at the same time as object download conditions. Both If-Match and If-None-Match can exist at the same time as object download conditions.

`ossClient.getObjectMeta` can be used to obtain the ETag.

Run the following code for conditional download:

```
//This example uses the endpoint China East 1 (Hangzhou). Specify the
//actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
//account because the account has permissions on all the APIs in OSS.
//We recommend that you log on as a RAM user to access APIs or perform
//routine operations and maintenance. To create a RAM account, log on to
//https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";
```

```
// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

GetObjectRequest request = new GetObjectRequest(bucketName, objectName);
// Configure conditions.
request.setModifiedSinceConstraint(new Date());

// Download an object to a local file.
ossClient.getObject(request, new File("<yourLocalFile>"));

//Close your OSSClient.
ossClient.shutdown();
```

Conditional download supports `ossClient.getObject` and `ossClient.downloadFile`.

2.7.7 Download progress bars

You can use progress bars to indicate the upload or download progress.

The following code is used as an example to describe how to view progress information with `ossClient.getObject`:

```
static class GetObjectProgressListener implements ProgressListener {
    private long bytesRead = 0;
    private long totalBytes = -1;
    private boolean succeed = false;
    @Override
    public void progressChanged(ProgressEvent progressEvent) {
        long bytes = progressEvent.getBytes();
        ProgressEventType eventType = progressEvent.getEventType();
        switch (eventType) {
            case TRANSFER_STARTED_EVENT:
                System.out.println("Start to download.....");
                break;
            case RESPONSE_CONTENT_LENGTH_EVENT:
                this.totalBytes = bytes;
                System.out.println(this.totalBytes + " bytes in total will be downloaded to a local file");
                break;
            case RESPONSE_BYTE_TRANSFER_EVENT:
                this.bytesRead += bytes;
                if (this.totalBytes != -1) {
                    int percent = (int)(this.bytesRead * 100.0 / this.totalBytes);
                    System.out.println(bytes + " bytes have been read at this time, download progress: " + percent + "%(" + this.bytesRead + "/" + this.totalBytes + ")");
                } else {
                    System.out.println(bytes + " bytes have been read at this time, download ratio: unknown" + "(" + this.bytesRead + "/...)");
                }
                break;
            case TRANSFER_COMPLETED_EVENT:
                this.succeed = true;
        }
    }
}
```

```

        System.out.println("Succeed to download, " + this.
bytesRead + " bytes have been transferred in total");
        break;
        case TRANSFER_FAILED_EVENT:
            System.out.println("Failed to download, " + this.
bytesRead + " bytes have been transferred");
            break;
        default:
            break;
    }
}
public boolean isSuccess() {
    return succeed;
}
}
public static void main(String[] args) {
    // This example uses endpoint China (Hangzhou). Specify the actual
    endpoint based on your requirements.
    String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
    // It is highly risky to log on with AccessKey of an Alibaba Cloud
    account because the account has permissions on all the APIs in OSS.
    We recommend that you log on as a RAM user to access APIs or perform
    routine operations and maintenance. To create a RAM account, log on to
    https://ram.console.aliyun.com.
    String accessKeyId = "<yourAccessKeyId>";
    String accessKeySecret = "<yourAccessKeySecret>";
    String bucketName = "<yourBucketName>";
    String objectName = "<yourObjectName>";
    OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);
    try {
        // Download with a progress bar displayed.
        ossClient.getObject(new GetObjectRequest(bucketName,
objectName).
            <GetObjectRequest>withProgressListener(new
GetObjectProgressListener()),
            new File("<yourLocalFile>"));
    } catch (Exception e) {
        e.printStackTrace();
    }
    // Close your OSSClient instance.
    ossClient.shutdown();
}
}

```

You can view progress information with `ossClient.putObject`, `ossClient.getObject`, or `ossClient.uploadPart`. However, you cannot view progress information with `ossClient.uploadFile` or `ossClient.downloadFile`.

For the complete code of download progress bar, see [GitHub](#).

2.8 Manage objects

2.8.1 Overview

This topic is the overview of object management in OSS Java SDK.

You can perform the following operations on objects in a bucket with APIs:

- [Determine whether an object exists](#)
- [Manage ACL for an object](#)
- [Manage Object Meta](#)
- [List objects](#)
- [Delete an object](#)
- [Copy an object](#)
- [Restore an archive object](#)
- [Manage a symbolic link](#)

2.8.2 Determine whether a specified object exists

This topic describes how to determine whether a specified object exists

Run the following code to determine whether a specified object exists:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Determine whether the specified object exists.
boolean found = ossClient.doesObjectExist("<yourBucketName>", "<yourObjectName>");
System.out.println(found);

// Close your OSSClient.
ossClient.shutdown();
```

2.8.3 Manage ACL for an object

This topic describes how to manage ACL for an object.

The following table describes the permissions included in the Access Control List (ACL) for an object.

Permission	Description	Value
default	The ACL of an object is the same with that of its bucket.	CannedAccessControlList.Default

Permission	Description	Value
Private	Only the object owner and authorized users can read and write the object.	CannedAccessControlList.Private
Public read	Only the object owner and authorized users can read and write the object. Other users can only read the object . Authorize this permission with caution.	CannedAccessControlList.PublicRead
Public read-write	All users can read and write the object. Authorize this permission with caution.	CannedAccessControlList.PublicReadWrite

The ACL of objects take precedence over that of buckets. For example, if the ACL of a bucket is private, while the object ACL is public read-write, all users can read and write the object. If an object is not configured with an ACL, its ACL is the same as that of its bucket by default.

Configure an ACL for an object

You can run the following code to configure an ACL for an object:

```
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Configure the ACL for the object to public read.
ossClient.setObjectAcl("<yourBucketName>", "<yourObjectName>",
    CannedAccessControlList.PublicRead);

// Close your OSSClient.
ossClient.shutdown();
```

Obtain the ACL for an object

You can run the following code to obtain the ACL for an object:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
```

```
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Obtain the ACL for an object.
ObjectAcl objectAcl = ossClient.getObjectAcl("<yourBucketName>", "<yourObjectName>");
System.out.println(objectAcl.getPermission().toString());

// Close your OSSClient.
ossClient.shutdown();
```

2.8.4 Manage Object Meta

Object Meta includes HTTP headers and user-defined Object Meta. For more information, see [Object Meta](#) in OSS Developer Guide.

Configure HTTP headers

- Configure HTTP headers

Run the following code to configure HTTP headers:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

String content = "Hello OSS";

// Create Object Meta. You can configure HTTP headers with Object
// Meta.
ObjectMetadata meta = new ObjectMetadata();

String md5 = BinaryUtil.toBase64String(BinaryUtil.calculateMd5(
    content.getBytes()));
// Start object content verification with MD5 values. After the
// verification is started, the MD5 value calculated by OSS is compared
// with that of an object. If the two values are different, an error
// occurs.
meta.setContentMD5(md5);
// Specify the type of content you want to upload. The content type
// determines the form and format in which your browser reads an object
// . The object extension is used as the content type if the content
```

```

type is not specified. If no object extension exists, the default
value application/octet-stream is used.
meta.setContentType("text/plain");
// Specify the name of the content when you download an object.
meta.setContentDisposition("attachment; filename=\"DownloadFilename
\"");
// Configure the length for an object. If the actual object length
is greater than the configured length, only the configured length
will be uploaded. If the configured length is greater than the
actual object length, the entire object will be uploaded.
meta.setContentLength(content.length());
// Configure the cache action of a webpage when an object is
downloaded.
meta.setCacheControl("Download Action");
// Configure the expiration time (GMT is used).
meta.setExpirationTime(DateUtil.parseIso8601Date("2022-10-12T00:00:
00.000Z"));
// Configure the encoding format when an object is downloaded.
meta.setContentEncoding("utf-8");
// Configure the HTTP header.
meta.setHeader("<yourHeader>", "<yourHeaderValue>");
// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Upload the object.
ossClient.putObject("<yourBucketName>", "<yourObjectName>", new
ByteArrayInputStream(content.getBytes()), meta);

// Close your OSSClient.
ossClient.shutdown();

```

For more information about HTTP headers, see [RFC2616](#).

- Configure user-defined Object Meta

You can define user-defined Object Meta for object descriptions.

Run the following code to configure user-defined Object Meta:

```

// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

String content = "Hello OSS";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Create Object Meta.
ObjectMetadata meta = new ObjectMetadata();

```



```
// Set property to property-value for user-defined Object Meta. We
// recommend that you use Base64 encoding method.
meta.addUserMetadata("property", "property-value");

// Upload the object.
ossClient.putObject("<yourBucketName>", "<yourObjectName>", new
ByteArrayInputStream(content.getBytes()), meta);

// Obtain Object Meta.
ossClient.getObjectMetadata("<yourBucketName>", "<yourObjectName>");

// Close your OSSClient.
ossClient.shutdown();
```

When an object is downloaded, its Object Meta is also downloaded. An object can contain multiple pieces of Object Meta, with the total maximum size smaller than 8 KB.

Modify Object Meta

Run the following code to modify Object Meta:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String sourceBucketName = "<yourSourceBucketName>";
String sourceObjectName = "<yourSourceObjectName>";
String destinationBucketName = "<yourDestinationBucketName>";
String destinationObjectName = "<yourDestinationObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Replace the source object with the target object. Call ossClient.
// copyObject to modify Object Meta.
CopyObjectRequest request = new CopyObjectRequest(sourceBucketName,
sourceObjectName, destinationBucketName, destinationObjectName);

ObjectMetadata meta = new ObjectMetadata();
// Specify the type of content you want to upload. The content type
// determines the form and format that your browser uses to read an
// object. The object extension is used for the content type if the
// content type is not specified. If no object extension exists, the
// default value application/octet-stream is used.
meta.setContentType("text/plain");
// Specify the name of the content when you download an object.
meta.setContentDisposition("Download File Name");
// Configure the cache action of a webpage when an object is
// downloaded.
meta.setCacheControl("Download Action");
// Configure the expiration time (GMT is used).
meta.setExpirationTime(DateUtil.parseIso8601Date("2022-10-12T00:00:00.000Z"));
```

```
// Configure the encoding type when the object is downloaded.
meta.setContentEncoding("utf-8");
// Configure the HTTP header.
meta.setHeader("<yourHeader>", "<yourHeaderValue>");
// Set property to property-value for user-defined Object Meta.
meta.addUserMetadata("property", "property-value");
request.setNewObjectMetadata(meta);

//Modify Object Meta.
ossClient.copyObject(request);

// Close your OSSClient.
ossClient.shutdown();
```

Obtain Object Meta

The following table lists the methods you can use to obtain Object Meta.

Method	Description	Advantage
<code>ossClient.getSimplifiedObjectMeta</code>	Obtains ETag, Size, and LastModified (the latest time an object is modified.) for the object.	More lightweight and faster
<code>ossClient.getObjectMetadata</code>	Obtains all metadata.	None

Run the following code to obtain Object Meta:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Obtain partial Object Meta.
SimplifiedObjectMeta objectMeta = ossClient.getSimplifiedObjectMeta("<yourBucketName>", "<yourObjectName>");
System.out.println(objectMeta.getSize());
System.out.println(objectMeta.getETag());
System.out.println(objectMeta.getLastModified());

// Obtain all Object Meta.
ObjectMetadata metadata = ossClient.getObjectMetadata("<yourBucketName>", "<yourObjectName>");
System.out.println(metadata.getContentType());
System.out.println(metadata.getLastModified());
System.out.println(metadata.getExpirationTime());
```

```
// Close your OSSClient.  
ossClient.shutdown();
```

2.8.5 List objects

This topic describes how to list objects.

Objects are listed alphabetically. You can use `ossClient.listObjects` to list objects in a bucket. The following parameters can be used for `listObjects`:

- `ObjectListing listObjects(String bucketName)`: lists objects in a bucket. A maximum of 100 objects can be listed.
- `ObjectListing listObjects(String bucketName, String prefix)`: lists objects with the specified prefix in a bucket. A maximum of 100 objects can be listed.
- `ObjectListing listObjects(ListObjectsRequest listObjectsRequest)`: provides multiple filtering functions to flexibly query objects.

The following table describes parameters for `ObjectListing`.

Parameter	Description	Configuration method
<code>objectSummaries</code>	Specifies the returned Object Meta.	<code>List<OSSObjectSummary> getObjectSummaries()</code>
<code>prefix</code>	Specifies the prefix you configure to list required objects.	<code>String getPrefix()</code>
<code>delimiter</code>	Specifies a delimiter used to group objects.	<code>String getDelimiter()</code>
<code>marker</code>	Specifies the initial object in the list.	<code>String getMarker()</code>
<code>maxKeys</code>	Specifies the maximum number of objects that can be listed.	<code>int getMaxKeys()</code>
<code>nextMarker</code>	Specifies the initial position for the next object.	<code>String getNextMarker()</code>
<code>isTruncated</code>	Specifies whether all results are returned.	<code>boolean isTruncated()</code>
<code>commonPrefixes</code>	Specifies a set of objects whose names share a prefix and end with a forward slash (/) delimiter.	<code>List<String> getCommonPrefixes()</code>

Parameter	Description	Configuration method
encodingType	Specifies the encoding type used in the response.	String getEncodingType()

Simple list

Run the following code to list objects in a specified bucket. A maximum of 100 objects can be listed by default.

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String KeyPrefix = "<yourKeyPrefix>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// List objects. If you do not configure KeyPrefix, all objects in
// the bucket are listed. If you configure KeyPrefix, objects with a
// specified prefix in the bucket are listed.
ObjectListing objectListing = ossClient.listObjects(bucketName,
KeyPrefix);
List<OSSObjectSummary> sums = objectListing.getObjectSummaries();
for (OSSObjectSummary s : sums) {
    System.out.println("\t" + s.getKey());
}

// Close your OSSClient.
ossClient.shutdown();
```

List objects with ListObjectsRequest

You can configure parameters for ListObjectsRequest to flexibly query objects. The following table describes parameters for ListObjectsRequest.

Parameter	Description	Configuration method
prefix	Specifies the prefix that must be included in the returned objects.	setPrefix(String prefix)
delimiter	Specifies a delimiter of a forward slash (/) used to group objects based on their names	setDelimiter(String delimiter)

Parameter	Description	Configuration method
	. The substring between the specified prefix and the first occurrence of the delimiter of a forward slash (/) is commonPrefixes.	
marker	Lists the objects after the value of marker.	setMarker(String marker)
maxKeys	Specifies the maximum number of objects that can be listed. The default value is 100 . The maximum value is 1,000.	setMaxKeys(Integer maxKeys)
encodingType	Specifies the encoding type of an object name in the response body. Only the URL encoding type is supported.	setEncodingType(String encodingType)

- List a specified number of objects

Run the following code to list a specified number of objects:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Configure the maximum number.
final int maxKeys = 200;
// List objects.
ObjectListing objectListing = ossClient.listObjects(new ListObject
sRequest(bucketName).withMaxKeys(maxKeys));
List<OSSObjectSummary> sums = objectListing.getObjectSummaries();
for (OSSObjectSummary s : sums) {
    System.out.println("\t" + s.getKey());
}

// Close your OSSClient.
ossClient.shutdown();
```

- List objects by a specified prefix

Run the following code to list objects with a specified prefix:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Specify a prefix.
final String keyPrefix = "<yourkeyPrefix>";

// List objects with a specified prefix. By default, a maximum of
// 100 objects can be listed.
ObjectListing objectListing = ossClient.listObjects(new ListObject
sRequest(bucketName).withPrefix(keyPrefix));
List<OSSObjectSummary> sums = objectListing.getObjectSummaries();
for (OSSObjectSummary s : sums) {
    System.out.println("\t" + s.getKey());
}

// Close your OSSClient.
ossClient.shutdown();
```

- List objects by marker

The marker parameter indicates the name of an object from which the listing begins. Run the following code to specify an object (specified with marker) after which the listing begins:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);
final String marker = "<yourMarker>";

// List objects placed after the object (specified with marker). By
// default, a maximum of 100 objects can be listed.
ObjectListing objectListing = ossClient.listObjects(new ListObject
sRequest(bucketName).withMarker(marker));
```

```
List<OSSObjectSummary> sums = objectListing.getObjectSummaries();
for (OSSObjectSummary s : sums) {
    System.out.println("\t" + s.getKey());
}

// Close your OSSClient.
ossClient.shutdown();
```

- List all objects on one or more pages

Use the following code to list all objects on one or more pages. The maximum number of objects listed on each page is specified with maxKeys.

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

final int maxKeys = 200;
String nextMarker = null;
ObjectListing objectListing;

do {
    objectListing = ossClient.listObjects(new ListObjectsRequest(
        bucketName).withMarker(nextMarker).withMaxKeys(maxKeys));

    List<OSSObjectSummary> sums = objectListing.getObjectSummaries
    ();
    for (OSSObjectSummary s : sums) {
        System.out.println("\t" + s.getKey());
    }

    nextMarker = objectListing.getNextMarker();
} while (objectListing.isTruncated());

// Close your OSSClient.
ossClient.shutdown();
```

- List objects by a specified prefix on one or more pages

Run the following code to list objects by a specified prefix on one or more pages:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
```

```

routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// A maximum of 200 objects can be listed on each page.
final int maxKeys = 200;
final String keyPrefix = "<yourkeyPrefix>";
String nextMarker = "<yourNextMarker>";
ObjectListing objectListing;

do {
    objectListing = ossClient.listObjects(new ListObjectsRequest(
bucketName).withPrefix(keyPrefix).withMarker(nextMarker).withMaxKeys
(maxKeys));

    List<OSSObjectSummary> sums = objectListing.getObjectSummaries
());
    for (OSSObjectSummary s : sums) {
        System.out.println("\t" + s.getKey());
    }

    nextMarker = objectListing.getNextMarker();
} while (objectListing.isTruncated());

// Close your OSSClient.
ossClient.shutdown();

```

- Specify the name of an object for encoding.

You must encode the name of an object if the name contains the following special characters. OSS supports encoding with URL.

- Single quotation marks (')
- Double quotations marks (")
- ampersands (&)
- angle brackets (< >)
- Pause marker (,)
- Chinese characters

Run the following code to encode the name of a specified object:

```

// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform

```



```

    routine operations and maintenance. To create a RAM account, log on
    to https://ram.console.aliyun.com.
    String accessKeyId = "<yourAccessKeyId>";
    String accessKeySecret = "<yourAccessKeySecret>";
    String bucketName = "<yourBucketName>";

    // Create an OSSClient instance.
    OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

    final int maxKeys = 200;
    final String keyPrefix = "<yourkeyPrefix>";
    String nextMarker = "<yourNextMarker>";
    ObjectListing objectListing;

    do {
        ListObjectsRequest listObjectsRequest = new ListObjectsRequest(
        bucketName);
        listObjectsRequest.setPrefix(keyPrefix);
        listObjectsRequest.setMaxKeys(maxKeys);
        listObjectsRequest.setMarker(nextMarker);

        // Specify the name of an object for encoding.
        listObjectsRequest.setEncodingType("url");

        objectListing = ossClient.listObjects(listObjectsRequest);

        // Decode the object.
        for (OSSObjectSummary objectSummary: objectListing.getObjects
        ummaries()) {
            System.out.println("Key:" + URLDecoder.decode(objectSummary.
            getKey(), "UTF-8"));
        }

        // Decode the commonPrefixes parameter.
        for (String commonPrefixes: objectListing.getCommonPrefixes()) {
            System.out.println("CommonPrefixes:" + URLDecoder.decode(
            commonPrefixes, "UTF-8"));
        }

        // Decode the nextMarker parameter.
        if (objectListing.getNextMarker() != null) {
            nextMarker = URLDecoder.decode(objectListing.getNextMarker
            (), "UTF-8");
        }
    } while (objectListing.isTruncated());

    // Close your OSSClient.
    ossClient.shutdown();

```

Folder simulation

OSS does not use folders. All elements are stored as objects. To simulate a folder on the OSS console, you actually create a 0 MB object whose name ends with a forward slash (/). This object can be uploaded and downloaded. By default, the OSS console displays an object whose name ends with a forward slash (/) as a folder.

The delimiter and prefix parameters can be used to simulate folder functions.

- Prefix: specifies the prefix as the name of a folder. The folder is used to list all files (in the folder) and subfolders (directories in the folder) that start with this prefix. These files and subfolders are included in the Objects list.
- Delimiter: If the delimiter is specified as a forward slash (/), only the files and subfolders (directories) are displayed. Subfolders (directories) are included in the CommonPrefixes list, while the files and folders in subfolders are not displayed.

For more information about folders, see [Folder simulation](#). For the complete code of creating an object, see [GitHub](#).

Assume that the following objects are stored in a bucket: oss.jpg, fun/test.jpg, fun/movie/001.avi, and fun/movie/007.avi. Forward slashes (/) are used as delimiters for folders. The subsequent examples show how to simulate folder functions.

- List all objects in a bucket

Run the following code to list all objects in a bucket:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Create ListObjectsRequest.
ListObjectsRequest listObjectsRequest = new ListObjectsRequest(
bucketName);

// List objects.
ObjectListing listing = ossClient.listObjects(listObjectsRequest);

// Print all objects.
System.out.println("Objects:");
for (OSSObjectSummary objectSummary : listing.getObjectSummaries())
{
    System.out.println(objectSummary.getKey());
}

// Print all commonPrefixes.
System.out.println("CommonPrefixes:");
for (String commonPrefix : listing.getCommonPrefixes()) {
    System.out.println(commonPrefix);
}
```

```
// Disable the OSSClient.  
// Close your OSSClient.
```

The returned results are as follows:

```
Objects:  
fun/movie/001.avi  
fun/movie/007.avi  
fun/test.jpg  
oss.jpg  
  
CommonPrefixes:
```

- List all objects in a specified folder

Run the following code to list all objects in a specified folder:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the  
// actual endpoint based on your requirements.  
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";  
// It is highly risky to log on with AccessKey of an Alibaba Cloud  
// account because the account has permissions on all the APIs in OSS.  
// We recommend that you log on as a RAM user to access APIs or perform  
// routine operations and maintenance. To create a RAM account, log on  
// to https://ram.console.aliyun.com.  
String accessKeyId = "<yourAccessKeyId>";  
String accessKeySecret = "<yourAccessKeySecret>";  
String bucketName = "<yourBucketName>";  
  
// Create an OSSClient instance.  
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,  
    accessKeySecret);  
  
// Create ListObjectsRequest.  
ListObjectsRequest listObjectsRequest = new ListObjectsRequest(  
    bucketName);  
// Configure the Prefix parameter to obtain all objects in the fun  
// folder.  
listObjectsRequest.setPrefix("fun/");  
  
// Recursively list all objects in the fun folder.  
ObjectListing listing = ossClient.listObjects(listObjectsRequest);  
  
// Print all objects.  
System.out.println("Objects:");  
for (OSSObjectSummary objectSummary : listing.getObjectSummaries())  
{  
    System.out.println(objectSummary.getKey());  
}  
  
// Print all commonPrefixes.  
System.out.println("\nCommonPrefixes:");  
for (String commonPrefix : listing.getCommonPrefixes()) {  
    System.out.println(commonPrefix);  
}  
  
// Close your OSSClient.
```

```
ossClient.shutdown();
```

The returned results are as follows:

```
Objects:
fun/movie/001.avi
fun/movie/007.avi
fun/test.jpg

CommonPrefixes:
```

- List objects and subfolders in a folder

Use the following code to list objects and subfolders in a folder:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Create ListObjectsRequest.
ListObjectsRequest listObjectsRequest = new ListObjectsRequest(
bucketName);

// Set forward slashes (/) as the delimiter for folders.
listObjectsRequest.setDelimiter("/");

// List all objects and folders in the fun folder.
listObjectsRequest.setPrefix("fun/");

ObjectListing listing = ossClient.listObjects(listObjectsRequest);

// Print all objects.
System.out.println("Objects:");
// List objects in the fun folder in a objectSummaries list.
for (OSSObjectSummary objectSummary : listing.getObjectSummaries())
{
    System.out.println(objectSummary.getKey());
}

// Print all commonPrefixes.
System.out.println("\nCommonPrefixes:");
// commonPrefixes lists all subfolders in the fun folder. The fun/
// movie/001.avi and fun/movie/007.avi objects are not listed, because
// they are objects in the movie folder (a subfolder of the fun folder
// ).
for (String commonPrefix : listing.getCommonPrefixes()) {
    System.out.println(commonPrefix);
}
```

```
// Close your OSSClient.  
ossClient.shutdown();
```

The returned results are as follows:

```
Objects:  
fun/test.jpg  
  
CommonPrefixes:  
fun/movie/
```

2.8.6 Delete objects



Warning:

Delete objects with caution because deleted objects cannot be recovered.

Delete an object

Run the following code to delete a single object:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the  
actual endpoint based on your requirements.  
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";  
// It is highly risky to log on with AccessKey of an Alibaba Cloud  
account because the account has permissions on all the APIs in OSS.  
We recommend that you log on as a RAM user to access APIs or perform  
routine operations and maintenance. To create a RAM account, log on to  
https://ram.console.aliyun.com.  
String accessKeyId = "<yourAccessKeyId>";  
String accessKeySecret = "<yourAccessKeySecret>";  
String bucketName = "<yourBucketName>";  
String objectName = "<yourObjectName>";  
  
// Create an OSSClient instance.  
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);  
  
// Delete an object.  
ossClient.deleteObject(bucketName, objectName);  
  
// Close your OSSClient.  
ossClient.shutdown();
```

Delete multiple objects

You can delete a maximum of 1,000 objects simultaneously. Objects can be deleted in two modes : detail (verbose) and simple (quiet) modes.

- verbose: returns the list of objects that you have deleted successfully. The default mode is verbose.
- quiet: returns the list of objects that you failed to delete.

The following table describes the parameters for DeleteObjectsRequest.

Parameter	Description	Configuration method
Keys	Specifies the objects you want to delete.	setKeys(List<String>)
quiet	Specifies a mode that the deletion result uses. True indicates quiet. False indicates verbose. The default mode is verbose.	setQuiet(boolean)
encodingType	Encodes the name of the returned objects. Only URL is supported.	setEncodingType(String)

The following table describes the parameters for DeleteObjectsResult.

Parameter	Description	Configuration method
deletedObjects	Specifies the deletion result . verbose indicates the list of objects you have deleted successfully. quiet indicates the list of objects you failed to delete.	List<String> getDeletedObjects() ()
encodingType	Encodes the name of objects in deletedObjects.	getEncodingType()

Run the following code to delete multiple objects simultaneously:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Delete objects.
List<String> keys = new ArrayList<String>();
keys.add("key0");
keys.add("key1");
```

```
keys.add("key2");

DeleteObjectsResult deleteObjectsResult = ossClient.deleteObjects(new
DeleteObjectsRequest(bucketName).withKeys(keys));
List<String> deletedObjects = deleteObjectsResult.getDeletedObjects();

// Close your OSSClient.
ossClient.shutdown();
```

For the complete code of deleting multiple objects simultaneously, see [GitHub](#).

2.8.7 Copy objects

Copy a small-sized object

You can use `ossClient.copyObject` to copy an object smaller than 1 GB from a bucket (source bucket) to another bucket (target bucket) in the same region. `ossClient.copyObject` supports the following configuration methods.

Configuration method	Description
<code>CopyObjectResult copyObject(String sourceBucketName, String sourceKey, String destinationBucketName, String destinationKey)</code>	Allows you to specify a source bucket, source object, target bucket, and target object. After the copy operation is completed, the target object content and its Object Meta are the same as those of the source object. This is called simple copy.
<code>CopyObjectResult copyObject(CopyObjectRequest copyObjectRequest)</code>	Allows you to specify target Object Meta and copy conditions. If the URL of the source bucket is the same as that of the target object, the Object Meta of the source object is replaced with that of the target object.

The following table describes the parameters you can configure for `CopyObjectRequest`.

Parameter	Description	Configuration method
<code>sourceBucketName</code>	Specifies the name of the source bucket.	<code>setSourceBucketName(String sourceBucketName)</code>
<code>sourceKey</code>	Specifies the name of a source object.	<code>setSourceKey(String sourceKey)</code>
<code>destinationBucketName</code>	Specifies the name of a target bucket.	<code>setDestinationBucketName(String destinationBucketName)</code>
<code>destinationKey</code>	Specifies the name of a target object.	<code>setDestinationKey(String destinationKey)</code>

Parameter	Description	Configuration method
newObjectMetadata	Specifies the target Object Meta.	setNewObjectMetadata(ObjectMetadata newObjectMetadata)
matchingETagConstraints	Restrictions on copies. Specifies the conditions for object copy. If ETag of a source object is the same as what OSS calculates, the source object is copied. Otherwise, an error is returned.	setMatchingETagConstraints(List<String> matchingETagConstraints)
nonmatchingETagConstraints	Specifies the conditions for object copy. If ETag of a source object is different from the ETag the user provides, the source object is copied. Otherwise, an error is returned.	setNonmatchingETagConstraints(List<String> nonmatchingETagConstraints)
unmodifiedSinceConstraint	Specifies the conditions for object copy. If the specified time is later than or equal to the time an object is modified, the source object is copied. Otherwise, an error is returned.	setUnmodifiedSinceConstraint(Date unmodifiedSinceConstraint)
modifiedSinceConstraint	Specifies the conditions for object copy. If a source object is modified after the specified time, the source object is copied. Otherwise, an error is returned.	setModifiedSinceConstraint(Date modifiedSinceConstraint)

The following table describes the parameters you can configure for CopyObjectRequest.

Parameter	Description	Configuration method
ETag	Specifies the unique identifier of an object.	String getETag()
Lastmodified	Specifies the latest time an object is modified.	Date getLastModified()



Note:

Object copy rules are as follows:

- Users have permissions to read and write the source object.
 - Data cannot be copied across regions. For example, you cannot copy an object in a bucket from China East1 (Hangzhou) to China North1 (Qingdao).
 - The object size is limited to a maximum of 1 GB.
- Simple copy

Run the following code for simple copy:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

String sourceBucketName = "<yourSourceBucketName>";
String sourceObjectName = "<yourSourceObjectName>";
String destinationBucketName = "<yourDestinationBucketName>";
String destinationObjectName = "<yourDestinationObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// Copy an object.
CopyObjectResult result = ossClient.copyObject(sourceBucketName,
    sourceObjectName, destinationBucketName, destinationObjectName);
System.out.println("ETag: " + result.getETag() + " LastModified: "
    + result.getLastModified());

// Close your OSSClient.
ossClient.shutdown();
```

- CopyObjectRequest-based copy

Run the following code for CopyObjectRequest-based copy:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

String sourceBucketName = "<yourSourceBucketName>";
String sourceObjectName = "<yourSourceObjectName>";
```

```
String destinationBucketName = "<yourDestinationBucketName>";
String destinationObjectName = "<yourDestinationObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Create a CopyObjectRequest object.
CopyObjectRequest copyObjectRequest = new CopyObjectRequest
(sourceBucketName, sourceObjectName, destinationBucketName,
destinationObjectName);

// Configure Object Meta for a new object.
ObjectMetadata meta = new ObjectMetadata();
meta.setContentType("text/html");
copyObjectRequest.setNewObjectMetadata(meta);

// Copy the object.
CopyObjectResult result = ossClient.copyObject(copyObjectRequest);
System.out.println("ETag: " + result.getETag() + " LastModified: "
+ result.getLastModified());

// Close your OSSClient.
ossClient.shutdown();
```

Copy a large-sized object

To copy an object larger than 1 GB, you need to use UploadPartCopy. In other words, you need to split the object into multiple parts and copy each of them simultaneously. To enable UploadPartCopy, perform the following steps:

1. Use `ossClient.initiateMultipartUpload` to initiate an UploadPartCopy task.
2. Start UploadPartCopy with `ossClient.uploadPartCopy`. Aside from the last part, all parts must be larger than 100 KB.
3. Submit the UploadPartCopy task with `ossClient.completeMultipartUpload`.

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

String sourceBucketName = "<yourSourceBucketName>";
String sourceObjectName = "<yourSourceObjectName>";
String destinationBucketName = "<yourDestinationBucketName>";
String destinationObjectName = "<yourDestinationObjectName>";

ObjectMetadata objectMetadata = ossClient.getObjectMetadata(sourceBucketName, sourceObjectName);
// Obtain the size of the object you want to copy.
long contentLength = objectMetadata.getContentLength();
```

```

// Set the minimum size to 10 MB for each part.
long partSize = 1024 * 1024 * 10;

// Calculate the total number of parts.
int partCount = (int) (contentLength / partSize);
if (contentLength % partSize != 0) {
    partCount++;
}
System.out.println("total part count:" + partCount);

// Initiate an UploadPartCopy task. You can specify Object Meta for
// the target object with InitiateMultipartUploadRequest.
InitiateMultipartUploadRequest initiateMultipartUploadRequest = new
    InitiateMultipartUploadRequest(destinationBucketName, destinationObject
    Name);
InitiateMultipartUploadResult initiateMultipartUploadResult =
    ossClient.initiateMultipartUpload(initiateMultipartUploadRequest);
String uploadId = initiateMultipartUploadResult.getUploadId();

// Start the UploadPartCopy task.
List<PartETag> partETags = new ArrayList<PartETag>();
for (int i = 0; i < partCount; i++) {
    // Calculate the size of each part.
    long skipBytes = partSize * i;
    long size = partSize < contentLength - skipBytes ? partSize :
    contentLength - skipBytes;

    // Create UploadPartCopyRequest. You can specify conditions with
    UploadPartCopyRequest.
    UploadPartCopyRequest uploadPartCopyRequest =
        new UploadPartCopyRequest(sourceBucketName, sourceObjectName,
        destinationBucketName, destinationObjectName);
    uploadPartCopyRequest.setUploadId(uploadId);
    uploadPartCopyRequest.setPartSize(size);
    uploadPartCopyRequest.setBeginIndex(skipBytes);
    uploadPartCopyRequest.setPartNumber(i + 1);
    UploadPartCopyResult uploadPartCopyResult = ossClient.uploadPart
    Copy(uploadPartCopyRequest);

    // Save the returned ETag of parts to partETags.
    partETags.add(uploadPartCopyResult.getPartETag());
}

// Submit the UploadPartCopy task.
CompleteMultipartUploadRequest completeMultipartUploadRequest = new
    CompleteMultipartUploadRequest(
        destinationBucketName, destinationObjectName,
        uploadId, partETags);
ossClient.completeMultipartUpload(completeMultipartUploadRequest);

// Close your OSSClient.
ossClient.shutdown();

```

For more information about UploadPartCopy, see [UploadPartCopy](#). For the complete code of UploadPartCopy, see [GitHub](#).

2.8.8 Restore an archive object

This topic describes how to restore an archive object.

For the complete code of restoring an archive object, see [GitHub](#).

You must restore an archive object before you read it. Do not call `restoreObject` for non-archive objects.

The state conversion process of an archive object is as follows:

1. An archive object is in the frozen state.
2. After you submit it for restoration, the server restores the object. The object is in the restoring state.
3. You can read the object after it is restored. The restored state of the object lasts one day by default. You can prolong this period to a maximum of seven days. Once this period expires, the object returns to the frozen state.

Run the following code to restore an object:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

ObjectMetadata objectMetadata = ossClient.getObjectMetadata(bucketName, key);

// Verify whether the object is an archive object.// Verify that the
// file is an archive file.
StorageClass storageClass = objectMetadata.getObjectStorageClass();
if (storageClass == StorageClass.Archive) {
    // Restore the object.
    ossClient.restoreObject(bucketName, objectName);

    // Wait until the object is restored.
    do {
        Thread.sleep(1000);
        objectMetadata = ossClient.getObjectMetadata(bucketName, objectName);
    } while (! objectMetadata.isRestoreCompleted());
}
```

```
// Obtain the restored object.
OSSObject ossObject = ossClient.getObject(bucketName, objectName);
ossObject.getObjectContent().close();

// Close your OSSClient.
ossClient.shutdown();
```

For more information about the archive storage classes, see [Introduction to storage classes](#).

2.8.9 Manage a symbolic link

This topic describes how to manage a symbolic link.

Create a symbolic link

A symbolic link is a special object that maps to an object similar to a shortcut used in Windows.

You can configure user-defined Object Meta for symbolic links.

Run the following code to create a symbolic link:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String symLink = "<yourSymLink>";
String destinationObjectName = "<yourDestinationObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Create Object Meta.
ObjectMetadata metadata = new ObjectMetadata();
metadata.setContentType("text/plain");
// Set property to property-value for user-defined metadata.
metadata.addUserMetadata("property", "property-value");

// Create CreateSymlinkRequest.
CreateSymlinkRequest createSymlinkRequest = new CreateSymlinkRequest(
    bucketName, symLink, destinationObjectName);

// Configure Object Meta.
createSymlinkRequest.setMetadata(metadata);

// Create symbolic links.
// Create a symbolic link.

// Close your OSSClient.
```

```
ossClient.shutdown();
```

For more information about symbolic links, see [PutSymlink](#).

Obtain object content for a symbolic link

To obtain a symbolic link, you must have the read permission on it. Run the following code to obtain the object content for a symbolic link:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String symLink = "<yourSymLink>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Obtain a symbolic link.
OSSSymlink symbolicLink = ossClient.getSymlink(bucketName, symLink);
// Print the content of the object that the symbolic link directs to.
System.out.println(symbolicLink.getSymlink());
System.out.println(symbolicLink.getTarget());
System.out.println(symbolicLink.getRequestId());

// Close your OSSClient.
ossClient.shutdown();
```

For more information about symbolic links, see [GetSymlink](#).

2.9 Data security

OSS Java SDK provides data integrity checks and file encryption on the server and client to guarantee data security during file (object) uploads, downloads, and replication.

Data integrity checks

OSS Java SDK provides MD5 authentication and cyclic redundancy checks (CRC) to guarantee data integrity for object (file) uploads, downloads, and replication.

- MD5 authentication

If you configure Content-MD5 for file uploads, OSS calculates the MD5 value based on the received content. If the MD5 value is inconsistent with that of the uploaded file, `InvalidDigest` is returned. Thus, data integrity is guaranteed.

Run the following code for MD5 authentication during the file upload:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Upload a string.
String content = "Hello OSS";

ObjectMetadata meta = new ObjectMetadata();
// Configure MD5 authentication.
String md5 = BinaryUtil.toBase64String(BinaryUtil.calculateMd5(
content.getBytes()));
meta.setContentMD5(md5);

ossClient.putObject("<yourBucketName>", "<yourObjectName>", new
ByteArrayInputStream(content.getBytes()), meta);

// Close your OSSClient instance.
ossClient.shutdown();
```

**Note:**

MD5 authentication can be used for putObject, getObject, appendObject, postObject, and uploadPart.

- CRC64

CRC is enabled by default during object (file) uploads, downloads, and replication to guarantee data integrity.

Run the following code to check whether CRC takes effect during the file upload:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
```

```
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Upload a string.
String content = "Hello OSS";

PutObjectResult result = ossClient.putObject("<yourBucketName>", "<
yourObjectName>", new ByteArrayInputStream(content.getBytes()));

// Check whether CRC is enabled. True indicates it is enabled while
false indicates it is disabled.
if (ossClient.getClientConfiguration().isCrcCheckEnabled()) {
    // Check whether CRC takes effect based on the response.
    OSSUtils.checkChecksum(result.getClientCRC(), result.getServerC
RC(), result.getRequestId());
}
// Close your OSSClient instance.
ossClient.shutdown();
```

**Note:**

- You can use CRC64 authentication for putObject, getObject, appendObject, and uploadPart.
- CRC64 authentication affects the upload and download progress because CRC64 uses CPU space.

File encryption on the server

You can set the serverSideEncryption parameter in Object Meta to AES256 or KMS for file uploads to encrypt the file and save it on the server. For more information, see [Server-side encryption](#) in the OSS Developer Guide.

Run the following code for file encryption on the server during file uploads:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeys
ecret);

// Upload a string.
String content = "Hello OSS";

ObjectMetadata meta = new ObjectMetadata();
// Set the server-side encryption code to AES256 for the file.
```



```
meta.setServerSideEncryption(ObjectMetadata.AES_256_SERVER_SIDE_ENCRYPTION);

ossClient.putObject("<yourBucketName>", "<yourObjectName>", new
ByteArrayInputStream(content.getBytes()), meta);

// Close your OSSClient instance.
ossClient.shutdown();
```

Client-side encryption

To encrypt a file on the client, you can encrypt the data on your local device, upload it to OSS, download it to the local device, and decrypt it. For more information, see [Introduction to client-side encryption SDK](#) in OSS Developer Guide.

2.10 Authorized access

This topic describes how to authorize access to users.

Use STS for temporary access authorization

OSS supports Alibaba Cloud Security Token Service (STS) for temporary access authorization. STS is a web service that provides a temporary access token to a cloud computing user. Through the STS, you can assign a third-party application or a RAM user (you can manage the user ID) an access credential with a custom validity period and permissions. For more information about STS, see [STS introduction](#).

STS advantages:

- Your long-term key (AccessKey) is not exposed to a third-party application. You only need to generate an access token and send the access token to the third-party application. You can customize access permissions and the validity of this token.
- You do not need to keep track of permission revocation issues. The access token automatically becomes invalid when it expires.

For more information about the process of access to OSS with STS, see [RAM and STS scenario practices](#) in OSS Developer Guide.

Run the following code to create a signature request with STS:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>;
```

```
String accessKeySecret = "<yourAccessKeySecret>";
String securityToken = "<yourSecurityToken>";

// After a user obtains a temporary STS credential, the OSSClient is
// generated with the security token and temporary access key (AccessKeyId and AccessKeySecret).
// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret, securityToken);

// Perform operations on OSS.

// Close your OSSClient.
ossClient.shutdown();
```

Sign a URL to authorize temporary access

- Sign a URL

You can provide a signed URL to a visitor for temporary access. When you sign a URL, you can specify the expiration time for a URL to restrict the period of access from visitors.

- Sign a URL for access with HTTP GET

Use the following code to sign a URL that allows access with HTTP GET:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

// Set the expiration time of a URL to one hour.
Date expiration = new Date(new Date().getTime() + 3600 * 1000);
// Generate the URL that allows access with HTTP GET. Visitors can
// use a browser to access relevant content.
URL url = ossClient.generatePresignedUrl(bucketName, objectName,
    expiration);

// Close your OSSClient.
ossClient.shutdown();
```

- Sign a URL for access with other HTTP methods

A URL needs to be signed for temporary access from a visitor to perform other operations such as file upload and deletion. For example:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String securityToken = "<yourSecurityToken>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// After a user obtains a temporary STS credential, the OSSClient
// is generated with the security token and temporary access key (
// AccessKeyId and AccessKeySecret).
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret, securityToken);

GeneratePresignedUrlRequest request = new GeneratePresignedUrl
    Request(bucketName, objectName, HttpMethod.PUT);
// Set the expiration time of a URL to one hour.
Date expiration = new Date(new Date().getTime() + 3600 * 1000);
request.setExpiration(expiration);
// Set ContentType.
request.setContentType(DEFAULT_OBJECT_CONTENT_TYPE);
// Configure custom Object Meta.
request.addUserMetadata("author", "aliy");

// Sign a URL that allows access with HTTP PUT.
URL signedUrl = ossClient.generatePresignedUrl(request);

Map<String, String> requestHeaders = new HashMap<String, String>();
requestHeaders.put(HttpHeaders.CONTENT_TYPE, DEFAULT_OBJECT_CONTE
    NT_TYPE);
requestHeaders.put(OSS_USER_METADATA_PREFIX + "author", "aliy");

// Upload a file with the signed URL.
ossClient.putObject(signedUrl, new ByteArrayInputStream("Hello OSS".
    getBytes()), -1, requestHeaders, true);

// Close your OSSClient.
ossClient.shutdown();
```

Visitors can use a signed URL to upload a file by passing in the HttpMethod.PUT parameter.

- Add specified parameters to a URL

Run the following code to add specified parameters to a URL:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
```

```

    recommend that you log on as a RAM user to access APIs or perform
    routine operations and maintenance. To create a RAM account, log on
    to https://ram.console.aliyun.com.
    String accessKeyId = "<yourAccessKeyId>";
    String accessKeySecret = "<yourAccessKeySecret>";
    String bucketName = "<yourBucketName>";
    String objectName = "<yourObjectName>";

    // Create an OSSClient instance.
    OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
    accessKeySecret);

    // Create a request.
    GeneratePresignedUrlRequest generatePresignedUrlRequest = new
    GeneratePresignedUrlRequest(bucketName, objectName);
    // Set HttpMethod to PUT.
    generatePresignedUrlRequest.setMethod(HttpMethod.PUT);
    // Add custom Object Meta.
    generatePresignedUrlRequest.addUserMetadata("author", "baymax");
    // Add Content-Type.
    generatePresignedUrlRequest.setContentType("application/octet-stream
    ");
    // Set the expiration time of a URL to one hour.
    Date expiration = new Date(new Date().getTime() + 3600 * 1000);
    generatePresignedUrlRequest.setExpiration(expiration);
    // Generate the signed URL.
    URL url = ossClient.generatePresignedUrl(generatePresignedUrlRequest
    );

    // Close your OSSClient.
    ossClient.shutdown();

```

- Use a signed URL to obtain or upload an object

— Use a signed URL to obtain an object

Run the following code to obtain a specified object through a signed URL:

```

// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba
// Cloud account because the account has permissions on all APIs in
// OSS. We recommend that you log on as a RAM user to access APIs
// or perform routine operations and maintenance. To create a RAM
// account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

Date expiration = DateUtil.parseRfc822Date("Wed, 18 Mar 2022 14:20
:00 GMT");
GeneratePresignedUrlRequest request = new GeneratePresignedUrl
Request(bucketName, objectName, HttpMethod.GET);
// Configure the expiration time.
request.setExpiration(expiration);

```

```
// Generate a signed URL that allows HTTP GET access.
URL signedUrl = ossClient.generatePresignedUrl(request);
System.out.println("signed url for getObject: " + signedUrl);

// Use the signed URL to send a request.
Map<String, String> customHeaders = new HashMap<String, String>();
// Add a request header to GetObject.
customHeaders.put("Range", "bytes=100-1000");
OSSObject object = ossClient.getObject(signedUrl, customHeaders);

// Close your OSSClient.
ossClient.shutdown();
```

— Use a signed URL to upload a file

Run the following code to upload a file with a signed URL:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba
// Cloud account because the account has permissions on all APIs in
// OSS. We recommend that you log on as a RAM user to access APIs
// or perform routine operations and maintenance. To create a RAM
// account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Generate the signed URL.
Date expiration = DateUtil.parseRfc822Date("Thu, 19 Mar 2019 18:00
:00 GMT");
GeneratePresignedUrlRequest request = new GeneratePresignedUrl
Request(bucketName, objectName, HttpMethod.PUT);
// Configure the expiration time.
request.setExpiration(expiration);
// Configure Content-Type.
request.setContentType("application/octet-stream");
// Configure custom Object Meta.
request.addUserMetadata("author", "aliy");
// Generate a signed URL that allows access with HTTP PUT.
URL signedUrl = ossClient.generatePresignedUrl(request);
System.out.println("signed url for putObject: " + signedUrl);

// Use the signed URL to send a request.
File f = new File("<yourLocalFile>");
FileInputStream fin = new FileInputStream(f);
// Add a request header to PutObject.
Map<String, String> customHeaders = new HashMap<String, String>();
customHeaders.put("Content-Type", "application/octet-stream");
customHeaders.put("x-oss-meta-author", "aliy");

PutObjectResult result = ossClient.putObject(signedUrl, fin, f.
length(), customHeaders);

// Close your OSSClient.
```

```
ossClient.shutdown();
```

2.11 Manage lifecycle rules

This topic describes how to manage lifecycle rules.

You can use OSS to configure lifecycle rules to reduce storage costs. The lifecycle management rules can be used for automatic deletion of expired objects and fragments, or storage class conversion to Infrequent Access for objects that will expire soon. Each rule includes:

- Rule ID: It identifies a rule. Ensure that each rule ID in a bucket is unique.
- Policy: You can configure a policy by using the following configuration methods. Only one method can be configured for a bucket.
 - Configure by Prefix: You can create multiple rules with this method. Ensure that each prefix is unique.
 - Configure for Entire Bucket: You can configure only one rule with this method.
- Expired: You can configure the following configuration methods:
 - Set by Number of Days: It specifies the number of days from the last modification time of objects.
 - Set by Date: It specifies the date prior to which objects are created. If objects are created prior to the date, these objects are deleted.
- Status: This lifecycle rule takes effect or not.

The parts uploaded by uploadPart method also support lifecycle rules. The last modification time of an object is the time the multipart upload event is initiated.

For more information about lifecycle management, see [Manage object lifecycle](#).

Configure lifecycle rules

Run the following code to configure lifecycle rules:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
```

```

OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

SetBucketLifecycleRequest request = new SetBucketLifecycleRequest(bucketName);

// Configure the rule ID and object name prefix.
String ruleId0 = "rule0";
String matchPrefix0 = "A0/";
String ruleId1 = "rule1";
String matchPrefix1 = "A1/";
String ruleId2 = "rule2";
String matchPrefix2 = "A2/";
String ruleId3 = "rule3";
String matchPrefix3 = "A3/";

// Set the expiration duration to 3 days after last modified date.
request.AddLifecycleRule(new LifecycleRule(ruleId0, matchPrefix0, RuleStatus.Enabled, 3));

// Configure expiration date to delete objects that are created before the date.
LifecycleRule rule = new LifecycleRule(ruleId1, matchPrefix1, RuleStatus.Enabled);
rule.setCreatedBeforeDate(DateUtil.parseISO8601Date("2022-10-12T00:00:00.000Z"));
request.AddLifecycleRule(rule);

// Set the expiration duration to 3 days for parts in an object.
rule = new LifecycleRule(ruleId2, matchPrefix2, RuleStatus.Enabled);
LifecycleRule.AbortMultipartUpload abortMultipartUpload = new LifecycleRule.AbortMultipartUpload();
abortMultipartUpload.setExpirationDays(3);
rule.setAbortMultipartUpload(abortMultipartUpload);
request.AddLifecycleRule(rule);

// Configure expiration date to delete parts that are created before the date.
rule = new LifecycleRule(ruleId3, matchPrefix3, RuleStatus.Enabled);
abortMultipartUpload = new LifecycleRule.AbortMultipartUpload();
abortMultipartUpload.setCreatedBeforeDate(DateUtil.parseISO8601Date("2022-10-12T00:00:00.000Z"));
rule.setAbortMultipartUpload(abortMultipartUpload);
request.AddLifecycleRule(rule);

ossClient.setBucketLifecycle(request);

// Close your OSSClient.
ossClient.shutdown();

```

View lifecycle rules

Run the following code to view lifecycle rules:

```

// This example uses endpoint China (Hangzhou). Specify the actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS. We recommend that you log on as a RAM user to access APIs or perform

```

```
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

List<LifecycleRule> rules = ossClient.getBucketLifecycle(bucketName);
for (LifecycleRule rule : rules) {
    System.out.println(rule.getId());
    System.out.println(rule.getPrefix());
    System.out.println(rule.getExpirationDays());
    System.out.println(rule.getCreatedBeforeDate());
    if(rule.hasAbortMultipartUpload()) {
        System.out.println(rule.getAbortMultipartUpload().getExpirationDays());
        System.out.println(rule.getAbortMultipartUpload().getCreatedBeforeDate());
    }
}

// Close your OSSClient.
ossClient.shutdown();
```

Clear lifecycle rules

Run the following code to clear lifecycle rules:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

ossClient.deleteBucketLifecycle(bucketName);

// Close your OSSClient.
ossClient.shutdown();
```

2.12 CORS

This topic describes how to perform CORS.

Cross-origin resource sharing (CORS) allows web applications to access resources that belong to another region. OSS provides CORS APIs for convenient cross-origin access control.

For more information, see [Cross-origin resource sharing](#) and [PutBucketcors](#) in OSS Developer Guide.

Configure CORS rules

Run the following code to configure CORS rules for the specified bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

SetBucketCORSRequest request = new SetBucketCORSRequest(bucketName);

// Create a CORS rule. A maximum of 10 rules can be configured for
// each bucket.
ArrayList<CORSRule> putCorsRules = new ArrayList<CORSRule>();

CORSRule corRule = new CORSRule();

ArrayList<String> allowedOrigin = new ArrayList<String>();
// Specify the source of the cross-origin access request.
allowedOrigin.add("http://www.b.com");

ArrayList<String> allowedMethod = new ArrayList<String>();
// Specify the cross-region request methods (GET, PUT, DELETE, POST,
// and HEAD) that are allowed.
allowedMethod.add("GET");

ArrayList<String> allowedHeader = new ArrayList<String>();
// Specify whether the header specified in Access-Control-Request-
// Headers of pre-flight request (OPTIONS) is allowed.
allowedHeader.add("x-oss-test");

ArrayList<String> exposedHeader = new ArrayList<String>();
// Specify the response header that allows user access from applicatio
ns.
exposedHeader.add("x-oss-test1");
// AllowedOrigins and AllowedMethods allow only one wildcard asterisk
// (*). Wildcard asterisks (*) indicate that all sources of the cross-
// origin requests and operations are allowed.
corRule.setAllowedMethods(allowedMethod);
corRule.setAllowedOrigins(allowedOrigin);
// AllowedHeaders and ExposeHeaders do not allow wildcard asterisks
// (*).
corRule.setAllowedHeaders(allowedHeader);
corRule.setExposeHeaders(exposedHeader);
// Specify the cache time (seconds) for the response of browser pre-
// flight (OPTIONS) requests to a specific resource.
```

```
corRule.setMaxAgeSeconds(10);

// A maximum of 10 rules is allowed.
putCorsRules.add(corRule);
// The existing rules will be replaced.
request.setCorsRules(putCorsRules);
ossClient.setBucketCORS(request);

// Close your OSSClient.
ossClient.shutdown();
```

Obtain CORS rules

Run the following code to obtain CORS rules:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

ArrayList<CORSRule> corsRules;
// Obtain the CORS rule list.
corsRules = (ArrayList<CORSRule>) ossClient.getBucketCORSRules(bucketName);
for (CORSRule rule : corsRules) {
    for (String allowedOrigin1 : rule.getAllowedOrigins()) {
        // Obtain allowed sources of cross-origin requests.
        System.out.println(allowedOrigin1);
    }

    for (String allowedMethod1 : rule.getAllowedMethods()) {
        // Obtain the allowed cross-origin request method.
        System.out.println(allowedMethod1);
    }

    if (rule.getAllowedHeaders().size() > 0){
        for (String allowedHeader1 : rule.getAllowedHeaders()) {
            // Obtain the header list for allowed cross-origin requests.
            System.out.println(allowedHeader1);
        }
    }

    if (rule.getExposeHeaders().size() > 0) {
        for (String exposeHeader : rule.getExposeHeaders()) {
            // Obtain the header for an allowed cross-origin request.
            System.out.println(exposeHeader);
        }
    }

    if (null != rule.getMaxAgeSeconds()) {
```

```
        System.out.println(rule.getMaxAgeSeconds());
    }
}

// Close your OSSClient.
ossClient.shutdown();
```

Delete CORS rules

Run the following code to delete all CORS rules for the specified bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Delete all CORS rules for a specified bucket.
ossClient.deleteBucketCORSRules(bucketName);

// Close your OSSClient.
ossClient.shutdown();
```

2.13 Set logging

You can enable access logs to record bucket access to log files, which are stored in a specified bucket.

The log file format is as follows:

<TargetPrefix><SourceBucket>-YYYY-mm-DD-HH-MM-SS-UniqueString

For more information about access log files, see [Set access logging](#).

Enable access logging

Run the following code to enable bucket access logging:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
```

```
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

SetBucketLoggingRequest request = new SetBucketLoggingRequest("<yourSourceBucketName>");
// Configure the bucket that stores log files.
request.setTargetBucket("<yourTargetBucketName>");
// Configure the log file storage directory.
request.setTargetPrefix("<yourTargetPrefix>");
ossClient.setBucketLogging(request);

// Close your OSSClient.
ossClient.shutdown();
```

View access logging configurations

Run the following code to view the access logging configurations for a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS. We recommend that you log on as a RAM user to access APIs or perform routine operations and maintenance. To create a RAM account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

BucketLoggingResult result = ossClient.getBucketLogging("<yourSourceBucketName>");
System.out.println(result.getTargetBucket());
System.out.println(result.getTargetPrefix());

// Close your OSSClient.
ossClient.shutdown();
```

Disable access logging

Run the following code to disable access logging for a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS. We recommend that you log on as a RAM user to access APIs or perform routine operations and maintenance. To create a RAM account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
```

```
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

SetBucketLoggingRequest request = new SetBucketLoggingRequest("<yourSourceBucketName>");
request.setTargetBucket(null);
request.setTargetPrefix(null);
ossClient.setBucketLogging(request);

// Close your OSSClient.
ossClient.shutdown();
```

2.14 Static website hosting

You can set your bucket configuration to the static website hosting mode. After the configuration takes effect, you can access this static website with the bucket domain and be redirected to a specified index page or error page.

For more information about static website hosting, see [Static website hosting](#).

Configure static website hosting

Run the following code to configure static website hosting:

```
// This example uses endpoint China (Hangzhou). Specify the actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS. We recommend that you log on as a RAM user to access APIs or perform routine operations and maintenance. To create a RAM account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

SetBucketWebsiteRequest request = new SetBucketWebsiteRequest("<yourBucketName>");
request.setIndexDocument("index.html");
request.setErrorDocument("error.html");
ossClient.setBucketWebsite(request);

// Close your OSSClient.
ossClient.shutdown();
```

View static website hosting configurations

Run the following code to view static website hosting configurations:

```
// This example uses endpoint China (Hangzhou). Specify the actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS.
```

```
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret);

BucketWebsiteResult result = ossClient.getBucketWebsite("<yourBucket
Name>");
System.out.println(result.getIndexDocument());
System.out.println(result.getErrorDocument());

// Close your OSSClient.
ossClient.shutdown();
```

Delete static website hosting configurations

Run the following code to delete static website hosting configurations:

```
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeyS
ecret);

ossClient.deleteBucketWebsite("<yourBucketName>");

// Close your OSSClient.
ossClient.shutdown();
```

2.15 Anti-leech

This topic describes how to use anti-leech.

To prevent your data on OSS from being leeches, OSS supports anti-leeching through the referer field settings in the HTTP header, including the following parameters:

- **Referer whitelist:** Used to allow access only for specified domains to OSS data.
- **Empty referer:** Determines whether the referer can be empty. If it is not allowed, only requests with the referer filed in their HTTP or HTTPS headers can access OSS data.

For more information about anti-leaching, see [Anti-leeching settings](#).

Configure the referer whitelist

Run the following code to configure the referer whitelist:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

List<String> refererList = new ArrayList<String>();
// Add the referer field. The referer field allows question marks (?)
// and asterisks (*) for wildcard use.
refererList.add("http://www.aliyun.com");
refererList.add("http://www. *.com");
refererList.add("http://www?.aliyuncs.com");
// Configure the referer list for a bucket. Set the parameter to true
// , which allows the referer field to be empty.
BucketReferer br = new BucketReferer(true, refererList);
ossClient.setBucketReferer(bucketName, br);

// Close your OSSClient.
ossClient.shutdown();
```

Obtain a referer whitelist

Run the following code to obtain a referer whitelist:

```
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Obtain the referer list for a bucket.
BucketReferer br = ossClient.getBucketReferer(bucketName);
List<String> refererList = br.getRefererList();
for (String referer : refererList) {
    System.out.println(referer);
}
```

```
// Close your OSSClient.  
ossClient.shutdown();
```

Clear a referer whitelist

Run the following code to clear a referer whitelist:

```
// This example uses endpoint China (Hangzhou). Specify the actual  
// endpoint based on your requirements.  
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";  
// It is highly risky to log on with AccessKey of an Alibaba Cloud  
// account because the account has permissions on all the APIs in OSS.  
// We recommend that you log on as a RAM user to access APIs or perform  
// routine operations and maintenance. To create a RAM account, log on to  
// https://ram.console.aliyun.com.  
String accessKeyId = "<yourAccessKeyId>";  
String accessKeySecret = "<yourAccessKeySecret>";  
String bucketName = "<yourBucketName>";  
  
// Create an OSSClient instance.  
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);  
  
// You cannot clear a referer whitelist directly. To clear a referer  
// whitelist, you need to create the rule that allows an empty referer  
// field and replace the original rule with the new rule.  
BucketReferer br = new BucketReferer();  
ossClient.setBucketReferer(bucketName, br);  
  
// Close your OSSClient.  
ossClient.shutdown();
```

2.16 Cross-region replication

Cross-region replication is used to automatically and asynchronously copy objects across buckets in different regions. Any changes (creation, replacement, and deletion) to objects in the source bucket will be synchronized to the target bucket. This function is used to meet the requirements of cross-region disaster recovery and data replication.

For more information about cross-region replication, see [Manage cross-region replication](#).

Enable cross-region replication

Run the following code to enable cross-region replication:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the  
// actual endpoint based on your requirements.  
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";  
// It is highly risky to log on with AccessKey of an Alibaba Cloud  
// account because the account has permissions on all the APIs in OSS.  
// We recommend that you log on as a RAM user to access APIs or perform  
// routine operations and maintenance. To create a RAM account, log on to  
// https://ram.console.aliyun.com.  
String accessKeyId = "<yourAccessKeyId>";  
String accessKeySecret = "<yourAccessKeySecret>";
```



```
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

AddBucketReplicationRequest request = new AddBucketReplicationRequest(bucketName);
request.setReplicationRuleID("<yourRuleId>");
request.setTargetBucketName("<yourTargetBucketName>");
// This example uses the target endpoint China (Beijing).
request.setTargetBucketLocation("oss-cn-beijing");
// Disable historical data replication. Historical data replication is enabled by default.
request.setEnableHistoricalObjectReplication(false);
ossClient.addBucketReplication(request);

// Close your OSSClient.
ossClient.shutdown();
```

View cross-region replication configurations

Use the following code to view the cross-region replication configurations for a bucket:

```
// This example uses endpoint China (Hangzhou). Specify the actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS. We recommend that you log on as a RAM user to access APIs or perform routine operations and maintenance. To create a RAM account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

List<ReplicationRule> rules = ossClient.getBucketReplication(bucketName);
for (ReplicationRule rule : rules) {
    System.out.println(rule.getReplicationRuleID());
    System.out.println(rule.getTargetBucketLocation());
    System.out.println(rule.getTargetBucketName());
}

// Close your OSSClient.
ossClient.shutdown();
```

View cross-region replication progress

Cross-region replication progress includes the progress of historical and real-time data synchronization.

- Percent signs (%) indicate the progress of historical data synchronization. This function only works for buckets for which historical data synchronization has been enabled.

- Time points (the point of latest time the data is written) indicate the progress of real-time data synchronization. If a time point is displayed, the data created before this time point has been synchronized.

Run the following code to view the cross-region replication progress:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

BucketReplicationProgress process = ossClient.getBucketReplicationProgress(bucketName, "<yourRuleId>");
System.out.println(process.getReplicationRuleID());
// Check whether historical data synchronization is enabled.
System.out.println(process.isEnableHistoricalObjectReplication());
// Print historical data synchronization progress.
System.out.println(process.getHistoricalObjectProgress());
// Print real-time data synchronization progress.
System.out.println(process.getNewObjectProgress());

// Close your OSSClient.
ossClient.shutdown();
```

View the target regions for synchronization

Run the following code to obtain the target regions to which buckets can be synchronized:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

List<String> locations = ossClient.getBucketReplicationLocation(bucketName);
for (String loc : locations) {
```

```
        System.out.println(loc);
    }

    // Close your OSSClient.
    ossClient.shutdown();
```

Disable cross-region replication

Use the following code to disable cross-region replication:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

// Disable cross-region replication. After this function is disabled
// , objects in the target bucket exist and all changes in the source
// objects cannot be synchronized.
ossClient.deleteBucketReplication(bucketName, "<yourRuleId>");

// Close your OSSClient.
ossClient.shutdown();
```

2.17 Image processing

Image Processing (IMG) is a massive, secure, cost-effective and highly reliable image processing service. After source images are uploaded to OSS, you can process images on any Internet device at any anytime, from anywhere through simple RESTful APIs.

For more information about IMG, see [Image Processing](#).

For the complete code of IMG, see [GitHub](#).

Basic features

OSS offers the following IMG features:

- [Retrieve dominant image tones](#)
- [Format conversion](#)
- [Resize images](#)
- [Incircle](#)

- [Adaptive orientation](#)
- [Brightness](#)
- [Add watermarks](#): allows you to add images, texts, or image-text watermarks to another image.
- [Image processing](#)
- [Image processing access rules](#): calls multiple IMG functions.

Usage

IMG uses standard HTTP GET. You can configure IMG parameters in QueryString of a URL.

If the ACL of an image object is private read and write, only authorized users are allowed for access.

- Anonymous access

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction>,<yourParamValue>
```

Parameter	Description
bucket	Specifies the name of a bucket.
endpoint	Specifies endpoint used to access a region.
object	Specifies the name of an image object.
image	Specifies the reserved identifier for IMG.
action	Specifies the operations on an image, such as scaling, cropping, and rotating.
param	Specifies the parameter that indicates the operation on an image.

— Basic operations

For example, scale an image to a width of 100 px. Adjust the height based on the ratio.

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

— Customized image styles

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=style/<yourStyleName>
```

- style: specifies a reserved identifier of a customized image style.
- yourStyleName: specifies the name of a custom image style. It is the name specified in the rule that is created on the OSS console.

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=style/oss-pic-style-w-100
```

— Cascade operations

Cascade operations allow you to perform multiple operations on an image sequentially.

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction1>,<yourParamValue1>/<yourAction2>,<yourParamValue2>/...
```

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100/rotate,90
```

— HTTPS access

IMG supports access through HTTPS. Example:

```
https://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

- Authorized access

Authorized access allows you to customize an image style, HTTPS access, and cascade operations.

Run the following code to generate a signed URL for IMG:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS. We recommend that you log on as a RAM user to access APIs or perform routine operations and maintenance. To create a RAM account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";
```

```
// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);
// Customize the image style.
String style = "image/resize,m_fixed,w_100,h_100/rotate,90";
// Set the expiration time to 10 minutes.
Date expiration = new Date(new Date().getTime() + 1000 * 60 * 10 );
GeneratePresignedUrlRequest req = new GeneratePresignedUrlRequest(
bucketName, objectName, HttpMethod.GET);
req.setExpiration(expiration);
req.setProcess(style);
URL signedUrl = ossClient.generatePresignedUrl(req);
System.out.println(signedUrl);
// Close your OSSClient.
ossClient.shutdown();sClient.shutdown();
```

- Access with SDK

You can use SDK to access and process an image object with any ACLs.

SDK allows you to customize image styles, HTTPS access, and cascade operations.

— Basic operations

Run the following code to perform basic operations on an image:

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in
OSS. We recommend that you log on as a RAM user to access APIs
or perform routine operations and maintenance. To create a RAM
account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";
// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);
// Scale the image.
String style = "image/resize,m_fixed,w_100,h_100";
GetObjectRequest request = new GetObjectRequest(bucketName,
objectName);
request.setProcess(style);
ossClient.getObject(request, new File("example-resize.jpg"));
// Crop the image.
style = "image/crop,w_100,h_100,x_100,y_100,r_1";
request = new GetObjectRequest(bucketName, objectName);
request.setProcess(style);
ossClient.getObject(request, new File("example-crop.jpg"));
// Rotate the image.
style = "image/rotate,90";
request = new GetObjectRequest(bucketName, objectName);
request.setProcess(style);
ossClient.getObject(request, new File("example-rotate.jpg"));
// Sharpen the image.
style = "image/sharpen,100";
request = new GetObjectRequest(bucketName, objectName);
```

```

request.setProcess(style);
ossClient.getObject(request, new File("example-sharpen.jpg"));
// Add watermarks.
style = "image/watermark,text_SGVsbG8g5Zu-54mH5pyN5YqhIQ";
request = new GetObjectRequest(bucketName, objectName);
request.setProcess(style);
ossClient.getObject(request, new File("example-watermark.jpg"));
// Convert the image format.
style = "image/format,png";
request = new GetObjectRequest(bucketName, objectName);
request.setProcess(style);
ossClient.getObject(request, new File("example-format.png"));
// Obtain image information.
style = "image/info";
request = new GetObjectRequest(bucketName, objectName);
request.setProcess(style);
ossClient.getObject(request, new File("example-info.txt"));
// Close your OSSClient.
ossClient.shutdown();

```

— Customize an image style

Run the following code to customize an image style:

```

// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba
// Cloud account because the account has permissions on all APIs in
// OSS. We recommend that you log on as a RAM user to access APIs
// or perform routine operations and maintenance. To create a RAM
// account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Customize the image style.
String style = "style/<yourCustomStyleName>";
GetObjectRequest request = new GetObjectRequest(bucketName,
objectName);
request.setProcess(style);

ossClient.getObject(request, new File("example-new.jpg"));

// Close your OSSClient.
ossClient.shutdown();

```

— Cascade operations

Run the following code to perform cascade operations on an image:

```

// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba
// Cloud account because the account has permissions on all APIs in

```

```

OSS. We recommend that you log on as a RAM user to access APIs
or perform routine operations and maintenance. To create a RAM
account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String objectName = "<yourObjectName>";

// Create an OSSClient instance.
OSSClient ossClient = new OSSClient(endpoint, accessKeyId,
accessKeySecret);

// Perform cascade operations.
String style = "image/resize,m_fixed,w_100,h_100/rotate,90";
GetObjectRequest request = new GetObjectRequest(bucketName,
objectName);
request.setProcess(style);

ossClient.getObject(request, new File("example-new.jpg"));

// Disable the OSSClient.
ossClient.shutdown();

```

Image processing persistence

Run the following code for image processing persistence:

```

// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
String endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance.
// To create a RAM account, log on to https://ram.console.aliyun.com.
String accessKeyId = "<yourAccessKeyId>";
String accessKeySecret = "<yourAccessKeySecret>";
String bucketName = "<yourBucketName>";
String sourceImage = "<yourSourceImageName>";

try {
    // Create an OSSClient instance.
    OSSClient ossClient = new OSSClient(endpoint, accessKeyId, accessKeySecret);

    // Image processing persistence: Scale the image.
    StringBuilder sbStyle = new StringBuilder();
    Formatter styleFormatter = new Formatter(sbStyle);
    String styleType = "image/resize,m_fixed,w_100,h_100";
    String targetImage = "example-resize.png";
    styleFormatter.format("%s|sys/saveas,o_%s,b_%s", styleType,
        BinaryUtil.toBase64String(targetImage.getBytes()),
        BinaryUtil.toBase64String(bucketName.getBytes()));
    System.out.println(sbStyle.toString());
    ProcessObjectRequest request = new ProcessObjectRequest(bucketName,
sourceImage, sbStyle.toString());
    GenericResult processResult = ossClient.processObject(request);
    String json = IOUtils.readStreamAsString(processResult.getResponse().
getContent(), "UTF-8");
    processResult.getResponse().getContent().close();
    System.out.println(json);
}

```



```
// Image processing persistence: Clip the image.
sbStyle.delete(0, sbStyle.length());
styleType = "image/crop,w_100,h_100,x_100,y_100,r_1";
targetImage = "example-crop.png";
styleFormatter.format("%s|sys/saveas,o_%s,b_%s", styleType,
    BinaryUtil.toBase64String(targetImage.getBytes()),
    BinaryUtil.toBase64String(bucketName.getBytes()));
System.out.println(sbStyle.toString());
request = new ProcessObjectRequest(bucketName, sourceImage, sbStyle.
toString());
processResult = ossClient.processObject(request);
json = IOUtils.readStreamAsString(processResult.getResponse().
getContent(), "UTF-8");
processResult.getResponse().getContent().close();
System.out.println(json);

// Image processing persistence: Rotate the object.
sbStyle.delete(0, sbStyle.length());
styleType = "image/rotate,90";
targetImage = "example-rotate.png";
styleFormatter.format("%s|sys/saveas,o_%s,b_%s", styleType,
    BinaryUtil.toBase64String(targetImage.getBytes()),
    BinaryUtil.toBase64String(bucketName.getBytes()));
request = new ProcessObjectRequest(bucketName, sourceImage, sbStyle.
toString());
processResult = ossClient.processObject(request);
json = IOUtils.readStreamAsString(processResult.getResponse().
getContent(), "UTF-8");
processResult.getResponse().getContent().close();
System.out.println(json);

// Image processing persistence: Sharpen the image.
sbStyle.delete(0, sbStyle.length());
styleType = "image/sharpen,100";
targetImage = "example-sharpen.png";
styleFormatter.format("%s|sys/saveas,o_%s,b_%s", styleType,
    BinaryUtil.toBase64String(targetImage.getBytes()),
    BinaryUtil.toBase64String(bucketName.getBytes()));
request = new ProcessObjectRequest(bucketName, sourceImage, sbStyle.
toString());
processResult = ossClient.processObject(request);
json = IOUtils.readStreamAsString(processResult.getResponse().
getContent(), "UTF-8");
processResult.getResponse().getContent().close();
System.out.println(json);

// Image processing persistence: Add watermarks.
sbStyle.delete(0, sbStyle.length());
styleType = "image/watermark,text_SGVsbG8g5Zu-54mH5pyN5YqhIQ";
targetImage = "example-watermark.png";
styleFormatter.format("%s|sys/saveas,o_%s,b_%s", styleType,
    BinaryUtil.toBase64String(targetImage.getBytes()),
    BinaryUtil.toBase64String(bucketName.getBytes()));
request = new ProcessObjectRequest(bucketName, sourceImage, sbStyle.
toString());
processResult = ossClient.processObject(request);
json = IOUtils.readStreamAsString(processResult.getResponse().
getContent(), "UTF-8");
processResult.getResponse().getContent().close();
System.out.println(json);
```

```
// Image processing persistence: Convert the image format.
sbStyle.delete(0, sbStyle.length());
styleType = "image/format,jpg";
targetImage = "example-formatconvert.jpg";
styleFormatter.format("%s|sys/saveas,o_%s,b_%s", styleType,
    BinaryUtil.toBase64String(targetImage.getBytes()),
    BinaryUtil.toBase64String(bucketName.getBytes()));
request = new ProcessObjectRequest(bucketName, sourceImage, sbStyle.
toString());
processResult = ossClient.processObject(request);
json = IOUtils.readStreamAsString(processResult.getResponse().
getContent(), "UTF-8");
processResult.getResponse().getContent().close();
System.out.println(json);

} catch (Exception e) {
    e.printStackTrace();
}
```

IMG tools

You can use the IMG viewer [ImageStyleViewer](#) to directly view the IMG result.

2.18 Exception handling

OSS Java SDK has two types of exceptions: `ClientException` and `OSSEException`. Both share the properties of `RuntimeException`.

Example for handling exceptions

Run the following code to handle exceptions:

```
try {
    // Perform operations on OSS, for example, object uploads.
    ossClient.putObject(...);
} catch (OSSEException oe) {
    System.out.println("Caught an OSSEException, which means your
request made it to OSS, "
        + "but was rejected with an error response for some reason
.");
    System.out.println("Error Message: " + oe.getErrorCode());
    System.out.println("Error Code: " + oe.getErrorCode());
    System.out.println("Request ID: " + oe.getRequestId());
    System.out.println("Host ID: " + oe.getHostId());
} catch (ClientException ce) {
    System.out.println("Caught an ClientException, which means the
client encountered "
        + "a serious internal problem while trying to communicate
with OSS, "
        + "such as not being able to access the network.");
    System.out.println("Error Message: " + ce.getMessage());
} finally {
    if (ossClient != null) {
        ossClient.shutdown();
    }
}
```

```
}
```

ClientException

The ClientException exception occurs when the client attempts to send requests and when the data is transmitted to OSS. For example, when a request is sent, ClientException may occur due to unavailable network connections. ClientException may occur during file uploads due to IO exceptions.

OSSEException

ServiceException indicates a server exception. The exception occurs because a server error message is parsed. OSSEException includes the error code and information returned from OSS. It is used to locate and handle problems.

The following table describes common OSSEException information.

Parameter	Description
Code	Specifies the error code returned by OSS.
Message	Specifies the detailed error information returned by OSS.
RequestId	Specifies the UUID. It is unique and used to identify a request. If a problem persists, send the RequestId to OSS developers for help.
HostId	Identifies an OSS cluster. Ensure that the value of HostId is consistent with the Host (endpoint to access a bucket) used in the request.

Common OSS error codes

Error Code	Description	HTTP status code
AccessDenied	Access denied	403
BucketAlreadyExists	The bucket already exists.	409
BucketNotEmpty	The bucket is not empty.	409
EntityTooLarge	The entity size exceeds the maximum limit.	400
EntityTooSmall	The entity size is below the minimum limit.	400
FileGroupTooLarge	The total file group size exceeds the maximum limit.	400

Error Code	Description	HTTP status code
FilePartNotExist	No such part exists.	400
FilePartStale	The part has expired.	400
InvalidArgument	The parameter format is invalid.	400
InvalidAccessKeyId	No such AccessKeyId exists.	403
InvalidBucketName	The bucket name is invalid.	400
InvalidDigest	The digest is invalid.	400
InvalidObjectName	The object name is invalid.	400
InvalidPart	The part is invalid.	400
InvalidPartOrder	The part order is invalid.	400
InvalidTargetBucketForLogging	The buckets that store log files are invalid.	400
InternalError	Internal OSS error	500
MalformedXML	The XML format is invalid.	400
MethodNotAllowed	The method is not allowed.	405
MissingArgument	Parameters are not configured.	411
MissingContentLength	The content length is not configured.	411
NoSuchBucket	No such bucket exists.	404
NoSuchKey	No such object exists.	404
NoSuchUpload	No such uploadId exists.	404
NotImplemented	The methods are not implemented.	501
PreconditionFailed	Precondition error	412
RequestTimeTooSkewed	The local time set for OSSClient is deviated from the time set for the OSS server by over 15 minutes.	403
RequestTimeout	Request timeout	400
SignatureDoesNotMatch	Signature mismatch	403

Error Code	Description	HTTP status code
InvalidEncryptionAlgorithmError	The specified encryption algorithm (the entropy encoding type) is invalid.	400

2.19 FAQ

Jar conflicts

- Cause analysis

If the following errors occur when you use OSS Java SDK, jar conflicts may exist in your project

```
Exception in thread "main" java.lang.NoClassDefFoundError: org/apache/http/ssl/TrustStrategy
    at com.aliyun.oss.OSSClient.<init>(OSSClient.java:268)
    at com.aliyun.oss.OSSClient.<init>(OSSClient.java:193)
    at com.aliyun.oss.demo.HelloOSS.main(HelloOSS.java:77)
Caused by: java.lang.ClassNotFoundException: org.apache.http.ssl.TrustStrategy
    at java.net.URLClassLoader$1.run(URLClassLoader.java:366)
    at java.net.URLClassLoader$1.run(URLClassLoader.java:355)
    at java.security.AccessController.doPrivileged(Native Method)
    at java.net.URLClassLoader.findClass(URLClassLoader.java:354)
    at java.lang.ClassLoader.loadClass(ClassLoader.java:425)
    at sun.misc.Launcher$AppClassLoader.loadClass(Launcher.java:308)
    at java.lang.ClassLoader.loadClass(ClassLoader.java:358)
    ... 3 more
```

Or

```
Exception in thread "main" java.lang.NoSuchFieldError: INSTANCE
    at org.apache.http.impl.io.DefaultHttpRequestWriterFactory.<init>(DefaultHttpRequestWriterFactory.java:52)
    at org.apache.http.impl.io.DefaultHttpRequestWriterFactory.<init>(DefaultHttpRequestWriterFactory.java:56)
    at org.apache.http.impl.io.DefaultHttpRequestWriterFactory.<clinit>(DefaultHttpRequestWriterFactory.java:46)
    at org.apache.http.impl.conn.ManagedHttpClientConnectionFactory.<init>(ManagedHttpClientConnectionFactory.java:82)
    at org.apache.http.impl.conn.ManagedHttpClientConnectionFactory.<init>(ManagedHttpClientConnectionFactory.java:95)
    at org.apache.http.impl.conn.ManagedHttpClientConnectionFactory.<init>(ManagedHttpClientConnectionFactory.java:104)
    at org.apache.http.impl.conn.ManagedHttpClientConnectionFactory.<clinit>(ManagedHttpClientConnectionFactory.java:62)
    at org.apache.http.impl.conn.PoolingHttpClientConnectionManager$InternalConnectionFactory.<init>(PoolingHttpClientConnectionManager.java:572)
    at org.apache.http.impl.conn.PoolingHttpClientConnectionManager.<init>(PoolingHttpClientConnectionManager.java:174)
    at org.apache.http.impl.conn.PoolingHttpClientConnectionManager.<init>(PoolingHttpClientConnectionManager.java:158)
```

```

at org.apache.http.impl.conn.PoolingHttpClientConnectionManager.<
init>(PoolingHttpClientConnectionManager.java:149)
at org.apache.http.impl.conn.PoolingHttpClientConnectionManager.<
init>(PoolingHttpClientConnectionManager.java:125)
at com.aliyun.oss.common.comm.DefaultServiceClient.createHttp
ClientConnectionManager(DefaultServiceClient.java:237)
at com.aliyun.oss.common.comm.DefaultServiceClient.<init>(
DefaultServiceClient.java:78)
at com.aliyun.oss.OSSClient.<init>(OSSClient.java:268)
at com.aliyun.oss.OSSClient.<init>(OSSClient.java:193)
at OSSManagerImpl.upload(OSSManagerImpl.java:42)
at OSSManagerImpl.main(OSSManagerImpl.java:63)

```

The cause is that OSS Java SDK uses Apache httpclient 4.4.1, while your project uses Apache httpclient or commons-httpclient jar that conflicts with Apache httpclient 4.4.1. To view the jar file and its version used for a project, open OSS Java SDK and run the `mvn dependency:tree` command. The following figure shows that a project that uses Apache httpclient 4.3.

```

[INFO] --- maven-dependency-plugin:2.2:tree (default-cli) @ maven-demo ---
[INFO] com.aliyun.oss:maven-demo:jar:0.1.1-SNAPSHOT
[INFO] +- junit:junit:jar:4.10:test
[INFO] | \- org.hamcrest:hamcrest-core:jar:1.1:test
[INFO] +- org.apache.httpcomponents:httpclient:jar:4.3:compile
[INFO] | +- org.apache.httpcomponents:httpcore:jar:4.3:compile
[INFO] | +- commons-logging:commons-logging:jar:1.1.3:compile
[INFO] | \- commons-codec:commons-codec:jar:1.6:compile
[INFO] \- com.aliyun.oss:aliyun-sdk-oss:jar:2.2.1:compile
[INFO]     +- org.jdom:jdom:jar:1.1:compile
[INFO]     \- net.sf.json-lib:json-lib:jar:jdk15:2.4:compile
[INFO]         +- commons-beanutils:commons-beanutils:jar:1.8.0:compile
[INFO]         +- commons-collections:commons-collections:jar:3.2.1:compile
[INFO]         +- commons-lang:commons-lang:jar:2.5:compile
[INFO]         \- net.sf.ezmorph:ezmorph:jar:1.0.6:compile

```

- There are two solutions to jar conflicts.
 - Use a unified version. If your project uses the version that conflicts with Apache httpclient 4.4.1, use Apache httpclient 4.4.1 and delete Apache httpclient dependencies of other versions in the pom.xml file. If your project uses commons-httpclient, jar conflicts may also exist. In this case, delete commons-httpclient.
 - Resolve dependency conflicts. If your project uses multiple third-party dependencies that have various Apache httpclient versions, dependency conflicts may exist in your project. Use exclusion to resolve the conflicts. For more information, see [Maven Guides](#).

OSS Java SDK is dependent on the following jar versions. Conflict solutions are similar to the httpclient method.

```

[INFO] com.aliyun.oss:maven-demo:jar:0.1.1-SNAPSHOT
[INFO] +- junit:junit:jar:4.10:test
[INFO] | \- org.hamcrest:hamcrest-core:jar:1.1:test
[INFO] \- com.aliyun.oss:aliyun-sdk-oss:jar:2.2.1:compile
[INFO]     +- org.apache.httpcomponents:httpclient:jar:4.4.1:compile
[INFO]     | +- org.apache.httpcomponents:httpcore:jar:4.4.1:compile
[INFO]     | +- commons-logging:commons-logging:jar:1.2:compile
[INFO]     | \- commons-codec:commons-codec:jar:1.9:compile
[INFO]     +- org.jdom:jdom:jar:1.1:compile
[INFO]     \- net.sf.json-lib:json-lib:jar:jdk15:2.4:compile
[INFO]         +- commons-beanutils:commons-beanutils:jar:1.8.0:compile
[INFO]         +- commons-collections:commons-collections:jar:3.2.1:compile
[INFO]         +- commons-lang:commons-lang:jar:2.5:compile
[INFO]         \- net.sf.ezmorph:ezmorph:jar:1.0.6:compile

```

Missing files

- Cause analysis

If the following errors occur when you use OSS Java SDK, your project may lack the necessary files for OSS Java SDK compilation and execution.

```

Exception in thread "main" java.lang.NoClassDefFoundError: org/
apache/http/auth/Credentials
    at com.aliyun.oss.OSSClient.<init>(OSSClient.java:268)
    at com.aliyun.oss.OSSClient.<init>(OSSClient.java:193)
    at com.aliyun.oss.demo.HelloOSS.main(HelloOSS.java:76)
Caused by: java.lang.ClassNotFoundException: org.apache.http.auth.
Credentials
    at java.net.URLClassLoader$1.run(URLClassLoader.java:366)
    at java.net.URLClassLoader$1.run(URLClassLoader.java:355)
    at java.security.AccessController.doPrivileged(Native Method
)
    at java.net.URLClassLoader.findClass(URLClassLoader.java:354
)
    at java.lang.ClassLoader.loadClass(ClassLoader.java:425)
    at sun.misc.Launcher$AppClassLoader.loadClass(Launcher.java:
308)
    at java.lang.ClassLoader.loadClass(ClassLoader.java:358)
    ... 3 more

```

Or

```

Exception in thread "main" java.lang.NoClassDefFoundError: org/
apache/http/protocol/HttpContext
    at com.aliyun.oss.OSSClient.<init>(OSSClient.java:268)
    at com.aliyun.oss.OSSClient.<init>(OSSClient.java:193)
    at com.aliyun.oss.demo.HelloOSS.main(HelloOSS.java:76)
Caused by: java.lang.ClassNotFoundException: org.apache.http.
protocol.HttpContext
    at java.net.URLClassLoader$1.run(URLClassLoader.java:366)
    at java.net.URLClassLoader$1.run(URLClassLoader.java:355)
    at java.security.AccessController.doPrivileged(Native Method
)
    at java.net.URLClassLoader.findClass(URLClassLoader.java:354
)
    at java.lang.ClassLoader.loadClass(ClassLoader.java:425)

```

```

308)    at sun.misc.Launcher$AppClassLoader.loadClass(Launcher.java:
        at java.lang.ClassLoader.loadClass(ClassLoader.java:358)
        ... 3 more

```

Or

```

Exception in thread "main" java.lang.NoClassDefFoundError: org/jdom/
input/SAXBuilder
    at com.aliyun.oss.internal.ResponseParsers.getXmlRootElement
(ResponseParsers.java:645)
    at ... ..
    at com.aliyun.oss.OSSClient.doesBucketExist(OSSClient.java:
471)
    at com.aliyun.oss.OSSClient.doesBucketExist(OSSClient.java:
465)
    at com.aliyun.oss.demo.HelloOSS.main(HelloOSS.java:82)
Caused by: java.lang.ClassNotFoundException: org.jdom.input.
SAXBuilder
    at java.net.URLClassLoader$1.run(URLClassLoader.java:366)
    at java.net.URLClassLoader$1.run(URLClassLoader.java:355)
    at java.security.AccessController.doPrivileged(Native Method
)
    at java.net.URLClassLoader.findClass(URLClassLoader.java:354
)
    at java.lang.ClassLoader.loadClass(ClassLoader.java:425)
    at sun.misc.Launcher$AppClassLoader.loadClass(Launcher.java:
308)
    at java.lang.ClassLoader.loadClass(ClassLoader.java:358)
    ... 11 more

```

Dependencies of OSS Java SDK are as follows:

- aliyun-sdk-oss-2.2.1.jar
- hamcrest-core-1.1.jar
- jdom-1.1.jar
- commons-codec-1.9.jar
- httpclient-4.4.1.jar
- commons-logging-1.2.jar
- httpcore-4.4.1.jar
- log4j-1.2.15.jar

In the preceding dependencies, all files except the log4j-1.2.15.jar file are required. You need to add this file to enable access logging.

- Solutions

Add OSS Java SDK dependencies to your project. Methods:

- If your project is in Eclipse, see [Method 2: Import a JAR package](#) to your Eclipse project in Java SDK.

- If your project is in Ant, add OSS Java SDK dependencies to the lib directory.
- If you directly use the .javac or .java files, run the `-classpath` command or the `-cp` command to specify the path where OSS Java SDK dependencies are stored or save the Java SDK dependencies to classpath.

Connection timeout

- Cause analysis

If the following errors occur when the OSS Java SDK program is run, possible causes are endpoint errors or unavailable networks:

```
com.aliyun.oss.ClientException: SocketException
    at com.aliyun.oss.common.utils.ExceptionFactory.createNetworkException(ExceptionFactory.java:71)
    at com.aliyun.oss.common.comm.DefaultServiceClient.sendRequestCore(DefaultServiceClient.java:116)
    at com.aliyun.oss.common.comm.ServiceClient.sendRequestImpl(ServiceClient.java:121)
    at com.aliyun.oss.common.comm.ServiceClient.sendRequest(ServiceClient.java:67)
    at com.aliyun.oss.internal.OSSOperation.send(OSSOperation.java:92)
    at com.aliyun.oss.internal.OSSOperation.doOperation(OSSOperation.java:140)
    at com.aliyun.oss.internal.OSSOperation.doOperation(OSSOperation.java:111)
    at com.aliyun.oss.internal.OSSBucketOperation.getBucketInfo(OSSBucketOperation.java:1152)
    at com.aliyun.oss.OSSClient.getBucketInfo(OSSClient.java:1220)
    at com.aliyun.oss.OSSClient.getBucketInfo(OSSClient.java:1214)
    at com.aliyun.oss.demo.HelloOSS.main(HelloOSS.java:94)
Caused by: org.apache.http.conn.HttpHostConnectException: Connect to oss-test.oss-cn-hangzhou-internal.aliyuncs.com:80 [oss-test.oss-cn-hangzhou-internal.aliyuncs.com/10.84.135.99] failed: Connection timed out: connect
    at org.apache.http.impl.conn.DefaultHttpClientConnectionOperator.connect(DefaultHttpClientConnectionOperator.java:151)
    at org.apache.http.impl.conn.PoolingHttpClientConnectionManager.connect(PoolingHttpClientConnectionManager.java:353)
    at org.apache.http.impl.execchain.MainClientExec.establishRoute(MainClientExec.java:380)
    at org.apache.http.impl.execchain.MainClientExec.execute(MainClientExec.java:236)
    at org.apache.http.impl.execchain.ProtocolExec.execute(ProtocolExec.java:184)
    at org.apache.http.impl.execchain.RedirectExec.execute(RedirectExec.java:110)
    at org.apache.http.impl.client.InternalHttpClient.doExecute(InternalHttpClient.java:184)
    at org.apache.http.impl.client.CloseableHttpClient.execute(CloseableHttpClient.java:82)
    at com.aliyun.oss.common.comm.DefaultServiceClient.sendRequestCore(DefaultServiceClient.java:113)
    ... 9 more
```

- Solution

You can use [OSSProbe](#) for fast troubleshooting.

org.apache.http.NoHttpResponseException: The target server failed to respond

- Cause analysis

The following error occurs when the OSS Java SDK program is run:

```
com.aliyun.oss.ClientException: Unknown
    at com.aliyun.oss.common.utils.ExceptionFactory.createNetworkException(ExceptionFactory.java:68) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.common.comm.DefaultServiceClient.sendRequestCore(DefaultServiceClient.java:115) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.common.comm.ServiceClient.sendRequestImpl(ServiceClient.java:121) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.common.comm.ServiceClient.sendRequest(ServiceClient.java:67) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.internal.OSSOperation.send(OSSOperation.java:92) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.internal.OSSOperation.doOperation(OSSOperation.java:140) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.internal.OSSOperation.doOperation(OSSOperation.java:111) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.internal.OSSMultipartOperation.initiateMultipartUpload(OSSMultipartOperation.java:206) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.aliyun.oss.OSSClient.initiateMultipartUpload(OSSClient.java:765) ~[aliyun-sdk-oss-2.1.0.jar:na]
    at com.taobao.agoo.dump.client.OssTools.multipartUpload(OssTools.java:79) ~[agoo-dump-client-2.0.0-SNAPSHOT.jar:na]
    at com.taobao.agoo.dump.biz.manager.TaskExecutorManager$UploadTask.run(TaskExecutorManager.java:114) ~[agoo-dump-biz-2.0.0-SNAPSHOT.jar:na]
    at java.util.concurrent.Executors$RunnableAdapter.call(Executors.java:471) [na:1.7.0_51]
    at java.util.concurrent.FutureTask.run(FutureTask.java:262) [na:1.7.0_51]
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1145) [na:1.7.0_51]
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:615) [na:1.7.0_51]
    at java.lang.Thread.run(Thread.java:744) [na:1.7.0_51]
Caused by: org.apache.http.NoHttpResponseException: The target server failed to respond
    at org.apache.http.impl.conn.DefaultHttpResponseParser.parseHead(DefaultHttpResponseParser.java:143) ~[httpclient-4.4.jar:4.4]
    at org.apache.http.impl.conn.DefaultHttpResponseParser.parseHead(DefaultHttpResponseParser.java:57) ~[httpclient-4.4.jar:4.4]
    at org.apache.http.impl.io.AbstractMessageParser.parse(AbstractMessageParser.java:261) ~[httpcore-4.4.jar:4.4]
    at org.apache.http.impl.DefaultBHttpClientConnection.receiveResponseHeader(DefaultBHttpClientConnection.java:165) ~[httpcore-4.4.jar:4.4]
    at org.apache.http.impl.conn.CPoolProxy.receiveResponseHeader(CPoolProxy.java:167) ~[httpclient-4.4.jar:4.4]
    at org.apache.http.protocol.HttpRequestExecutor.doReceiveResponse(HttpRequestExecutor.java:272) ~[httpcore-4.4.jar:4.4]
```

The preceding error may occur if expired connections are used. This error occurs only when an earlier version of Java SDK 2.1.2 is used.

- Solutions

Upgrade OSS Java SDK to 2.1.2 or a later version.

OSS Java SDK stops responding when the Java program is called

- Cause analysis

OSS Java SDK stops responding when the Java program is called. Run the `jstack -l pid` command to view the stacks. The exception is as follows:

```
"main" prio=6 tid=0x000000000291e000 nid=0xc40 waiting on condition
[0x0000000002dae000]
java.lang.Thread.State: WAITING (parking)
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <0x000000007d85697f8> (a java.util.concurrent
    .locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:186
    )
    at java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionO
    bject.await(AbstractQueuedSynchronizer.java:2043)
    at org.apache.http.pool.PoolEntryFuture.await(PoolEntryFuture.java:
    138)
    at org.apache.http.pool.AbstractConnPool.getPoolEntryBlocking(
    AbstractConnPool.java:306)
    at org.apache.http.pool.AbstractConnPool.access$000(AbstractCo
    nnPool.java:64)
    at org.apache.http.pool.AbstractConnPool$2.getPoolEntry(AbstractCo
    nnPool.java:192)
    at org.apache.http.pool.AbstractConnPool$2.getPoolEntry(AbstractCo
    nnPool.java:185)
    at org.apache.http.pool.PoolEntryFuture.get(PoolEntryFuture.java:
    107)
```

```

at org.apache.http.impl.conn.PoolingHttpClientConnectionManager.
leaseConnection(PoolingHttpClientConnectionManager.java:276)
at org.apache.http.impl.conn.PoolingHttpClientConnectionManager$1.
get(PoolingHttpClientConnectionManager.java:263)
at org.apache.http.impl.execchain.MainClientExec.execute(MainClient
Exec.java:190)
at org.apache.http.impl.execchain.ProtocolExec.execute(ProtocolExec
.java:184)
at org.apache.http.impl.execchain.RedirectExec.execute(RedirectExec
.java:110)
at org.apache.http.impl.client.InternalHttpClient.doExecute(
InternalHttpClient.java:184)
at org.apache.http.impl.client.CloseableHttpClient.execute(
CloseableHttpClient.java:82)
at com.aliyun.oss.common.comm.DefaultServiceClient.sendRequestCore(
DefaultServiceClient.java:113)
at com.aliyun.oss.common.comm.ServiceClient.sendRequestImpl(
ServiceClient.java:123)
at com.aliyun.oss.common.comm.ServiceClient.sendRequest(ServiceCli
ent.java:68)
at com.aliyun.oss.internal.OSSOperation.send(OSSOperation.java:94)
at com.aliyun.oss.internal.OSSOperation.doOperation(OSSOperation.
java:146)
at com.aliyun.oss.internal.OSSOperation.doOperation(OSSOperation.
java:113)
at com.aliyun.oss.internal.OSSObjectOperation.getObject(OSSObjectO
peration.java:229)
at com.aliyun.oss.OSSClient.getObject(OSSClient.java:629)
at com.aliyun.oss.OSSClient.getObject(OSSClient.java:617)
at samples.HelloOSS.main(HelloOSS.java:49)

```

The cause is due to the connection leak in the connection pool (possibly because `ossObject` is left unclosed after it is used).

- Solutions

Check your program and ensure that no connection leak occurs. Use the following code to close `ossObject`:

```

// Read an object.
OSSObject ossObject = ossClient.getObject(bucketName, objectName);
// Perform operations on OSS.
// Close your ossObject.
ossObject.close();

```

Connection closure

- Cause analysis

If the following errors occur when you use `ossClient.getObject`:

```

Exception in thread "main" org.apache.http.ConnectionClosedException
: Premature end of Content-Length delimited message body (expected:
11990526; received: 202880
at org.apache.http.impl.io.ContentLengthInputStream.read(ContentLen
gthInputStream.java:180)
at org.apache.http.impl.io.ContentLengthInputStream.read(ContentLen
gthInputStream.java:200)

```

```
at org.apache.http.impl.io.ContentLengthInputStream.close(
ContentLengthInputStream.java:103)
at org.apache.http.impl.execchain.ResponseEntityProxy.streamClosed(
ResponseEntityProxy.java:128)
at org.apache.http.conn.EofSensorInputStream.checkClose(EofSensorI
nputStream.java:228)
at org.apache.http.conn.EofSensorInputStream.close(EofSensorI
nputStream.java:174)
at java.io.FilterInputStream.close(FilterInputStream.java:181)
at java.io.FilterInputStream.close(FilterInputStream.java:181)
at com.aliyun.oss.event.ProgressInputStream.close(ProgressIn
putStream.java:147)
at java.io.FilterInputStream.close(FilterInputStream.java:181)
at samples.HelloOSS.main(HelloOSS.java:39)
```

The cause is that the time between two consecutive data reading exceeds one minute. OSS will close the connections if the time between two consecutive data reading exceeds one minute.

- Solution


If you only need to read part of the data during unfixed periods of time, use [Range download](#) to avoid connection closure during data reading.

Memory leaks

- Cause analysis

Memory leaks occur when the OSS Java SDK program is run for a period of time (from several hours to several days based on access traffic). We recommend that you use [Eclipse Memory Analyzer \(MAT\)](#) to analyze memory usage. For more information about usage methods, see [Use MAT for Head Dump File Analysis](#).

If the analysis result is similar to the following figure (PoolingHttpClientConnectionManager occupies 96 percent of memory), the cause may be that new OSSClient is run multiple times while `ossClient.shutdown` is not called. Consequently, memory leaks occur.



- a

Ensure that `ossClient.shutdown` is enabled after `OSSClient` is enabled.

InterruptedException occurs when `ossClient.shutdown` is called

- Error Cause

The following exception is thrown when `OSSClient.shutdown` is called:

```
java.lang.InterruptedException: sleep interrupted
    at java.lang.Thread.sleep(Native Method)
    at com.aliyun.oss.common.comm.IdleConnectionReaper.run(IdleConnectionReaper:76)
```

The cause is that the backend thread (`IdleConnectionReaper`) of `ossClient` will close connections periodically. If `ossClient.shutdown` is called when `IdleConnectionReaper` is in the Sleep mode, the preceding exception occurs.

- Solution

OSS Java SDK 2.3.0 has rectified this error.

For versions earlier than OSS Java SDK 2.3.0, use the following code to ignore the error:

```
try {
    ossClient.shutdown();
} catch (Exception e) {
```

```
}
```

Other errors

For more information about how to rectify other errors returned by OSS, see [Errors and troubleshooting](#).

3 Python

3.1 Preface

Source code

For the source code, see [GitHub](#).

Code samples

OSS Python SDK provides a variety of code samples for your reference or use. The following table describes the content of code samples.

Sample file	Content
object_basic.py	Quick start , including creating a bucket, and uploading, downloading, listing, and deleting objects
object_extra.py	Upload and manage objects, including managing Object , copying objects , append upload
upload.py	Upload objects, including resumable upload and multipart upload
download.py	Download objects, including streaming download , range download , resumable download
object_check.py	Data verification methods during uploads and downloads, including MD5 and CRC
object_progress.py	Upload progress bars and download progress bars
object_callback.py	Upload callback in object upload
object_post.py	Operations related to form upload
sts.py	STS usage, including obtaining the temporary user key for playing a role and using the temporary user key to access the OSS
image.py	Operations related to image processing
bucket.py	Bucket management , including creating, deleting, and listing buckets, configuring static website hosting , and configuring lifecycle rules .

3.2 Installation

Environment requirements

This version of Python SDK is applicable to Python 2.6, 2.7, 3.3, 3.4 and 3.5.

- Installation environment

Follow the instructions on [python official website](#) to install an appropriate version of Python.

- Check Python version

Run `python -V` to check the Python version.

In Windows, if a “Not an internal or external command” message prompts, edit the `Path` in environment variables to add the installation path of Python and pip. In general, pip is installed in the Script directory located in the installation path of Python.



Note:

You may need to restart your computer make sure the environment variable takes effect.

Download SDK

- [Download from GitHub](#)
- [Download previous versions](#)

For more information, see [OSS API documents](#).

Install Python-devel

Python SDK uses the `crcmod` library which depends on the `Python.h` to caculate CRC. Therefore , if the `Python.h` file is missing, Python SDK can be successfully installed while the installation of `crcmod` C extension mode fails, which significantly reduces the efficiency of operations, such as upload and download. Therefore, you must install the `python-devel` package if it is missing.

- You do not need to install the `python-devel` package in Windows and Mac OS X because header files that Python depends on are installed together with Python.

- For CentOS, RHEL, and Fedora, run the following command to install python-devel:

```
yum install python-devel
```

- For Debian and Ubuntu, run the following command to install python-devel:

```
apt-get install python-dev
```

Install SDK

- Install SDK by Pip

Run the following command:

```
pip install oss2
```



Note:

If Pip is not installed in your environment, see [Pip official website](#) to install Pip.

- Install SDK by source code

Download the SDK package of an appropriate version from [GitHub](#) and decompress the package. Make sure that the setup.py file exists in the directory and run the following command:

```
python setup.py install
```

Verification

- Verify the SDK version

1. Input python in the command line and press Enter to enter the Python environment.
2. Run the following command to verify the SDK version:

```
>>> import oss2
>>> oss2.__version__
'2.0.0'
```

If the preceding information is displayed, it means that you have successfully installed the Python SDK 2.0.0.

- Verify the crcmod

Two methods are available for crcmod to calculate CRC: the C extension mode (in which crcmod calls the extension library _crcfunext.so to calculate CRC) and the Python-only mode.

The performance of C extension mode is far better than the Python-only mode. The crcmod library is automatically installed when oss2 is installed. For more information about crcmod, see [crcmod introduction](#).

If you find that the speed of upload and download interfaces is significantly slow compared with other tools (such as [ossutil](#)) or other SDKs after the Python SDK is installed, it is probably because that the C extension mode of crcmod library is not installed successfully, resulting that the Python-only mode is used to calculate CRC in upload and download.

You can verify whether the C extension mode of crcmode is successfully installed as follows:

1. Input `python` in the command line and press Enter to enter the Python environment.
2. Input `import crcmod._crcfunext` and press Enter.
 - If no exception is reported, it indicates that the C extension mode has been successfully installed.
 - If the following message is displayed, it indicates that the C extension mode is not successfully installed.

```
>>> import crcmod._crcfunext
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
ImportError: No module named _crcfunext
```

The error occurs because the Python.h file that `_crcfunext.so` depends on is missing when the `crcmod` is compiled, resulting in that the `_crcfunext.so` fails to be generated. In this case, CRC is calculated in the Python-only method. The SDK is installed successfully. However, the efficiency of operations such as upload and download is low.

Perform the following operations if the problem occurs.

1. Run the following command to uninstall `crcmod`:

```
pip uninstall crcmod
```

2. [Install python-devel](#).

3. Run the following command to install crcmod again:

```
pip install crcmod
```

If the installation still fails, uninstall crcmod and run the following command to check detailed information:

```
pip install crcmod -v
```

Uninstall SDK

If the SDK fails to be installed, we recommend you to uninstall the SDK using pip and install it again. You can run the following command to uninstall the SDK.

```
pip uninstall oss2
```

3.3 Quick start

This topic describes how to use OSS Python SDK to perform routine operations such as bucket creation, object uploads, and object downloads.

Create a bucket

Run the following code to create a bucket:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Set the ACL of the bucket to private.
bucket.create_bucket(oss2.models.BUCKET_ACL_PRIVATE)
```

Upload objects

Run the following code to upload a file to OSS:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
```

```

routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2. Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2. Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# <yourLocalFile> consists of a local file path and a file name with
extension, for example: /users/local/myfile.txt
bucket.put_object_from_file('<yourObjectName>', '<yourLocalFile>')

```

Download objects

Run the following code to download a specified object to a local file:

```

# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2. Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2. Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# <yourLocalFile> consists of a local file path and a file name with
extension, for example: /users/local/myfile.txt
bucket.get_object_to_file('<yourObjectName>', '<yourLocalFile>')

```

List objects

Run the following code to list 10 objects in a specified bucket:

```

# -*- coding: utf-8 -*-
import oss2
from itertools import islice

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We strongly recommend that you create a RAM account and use it for
API access and daily O&M. Log on to https://ram.console.aliyun.com to
create a RAM account.
auth = oss2. Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2. Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# oss2.ObjectIterator is used to traverse objects.
for b in islice(oss2. ObjectIterator(bucket), 10):

```

```
print(b.key)
```

Delete objects

Run the following code to delete a specified object:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.delete_object('<yourObjectName>')
```

3.4 Initialization

This topic describes how to initialize OSS Python SDK.

Most operations in OSS Python SDK are performed through `oss2.Service` and `oss2.Bucket`.

- The `oss2.Service` class is used to list buckets.
- The `oss2.Bucket` class is used to upload, download, and delete objects, and configure buckets.

To initialize the two classes, you must specify an endpoint. The `oss2.Service` class does not support access with the custom domain (CNAME). For more information about endpoints, see [Regions and endpoints](#) and [Bind a custom domain name](#).

Initialize the `oss2.Service` class

For more information, see the bucket listing part in [Manage buckets](#).

Initialize the `oss2.Bucket` class.

- Use a OSS domain name to initialize the class

Run the following code to initialize the `oss2.Bucket` class with a OSS domain name.

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
```

```
# This case uses the Hangzhou endpoint as an example. Fill in the
region endpoint name according to the actual circumstances.
endpoint = 'http://oss-cn-hangzhou.aliyuncs.com'

bucket = oss2.Bucket(auth, endpoint, '<yourBucketName>')
```

- Use a custom domain name to initialize the class

Run the following code to initialize the oss2.Bucket class with a custom domain name

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')

# Use a custom domain name: my-domain.com as an example. is_cname
=True indicates that the CNAME is enabled. Cname means binding a
custom domain name to the storage space. CNAME indicates a custom
domain bound to a bucket.
cname = 'http://my-domain.com'
bucket = oss2.Bucket(auth, cname, '<yourBucketName>', is_cname=True)
```

- Set connection timeout

Run the following code to set connection timeout:

```
# -*- coding: utf-8 -*-
import oss2

// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
endpoint = 'http://oss-cn-hangzhou.aliyuncs.com'

# Set the connection timeout to 30 seconds.
bucket = oss2.Bucket(auth, endpoint, '<yourBucketName>', connect_t
imeout=30)
```

- Disable CRC verification

CRC verification is enabled by default during uploads and downloads to ensure data integrity during uploads and downloads. Run the following code to disable CRC verification:



We recommended that you do not disable CRC verification. If you disable CRC verification, the data integrity during uploads and downloads is not guaranteed.

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
endpoint = 'http://oss-cn-hangzhou.aliyuncs.com'

bucket = oss2.Bucket(auth, endpoint, '<yourBucketName>', enable_crc=
False)
```

3.5 Bucket

A bucket serves as a container that stores objects. Objects belong to a bucket.

Create a bucket

Run the following code to create a bucket:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# You can create a new bucket in a specified region by specifying the
endpoint and bucket name. This example uses endpoint China (Hangzhou
). Specify the actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# The default storage class and ACL of the created bucket are set to
standard and private read respectively.
bucket.create_bucket()
```

For more information about bucket naming rules, see [naming conventions](#) in [Basic concepts](#).

You can specify the ACL and the storage class when you create a bucket, as shown in [Bucket-level permissions](#) and [Storage class](#). The sample code is as follows:

```
# Set the bucket ACL to public read and set the storage class to
Infrequent Access.
```

```
bucket.create_bucket(oss2. BUCKET_ACL_PUBLIC_READ, oss2.models.  
BucketCreateConfig(oss2. BUCKET_STORAGE_CLASS_IA))
```

List buckets

Run the following code to list buckets:

```
# -*- coding: utf-8 -*-  
import oss2  
  
# It is highly risky to log on with AccessKey of an Alibaba Cloud  
# account because the account has permissions on all the APIs in OSS.  
# We recommend that you log on as a RAM user to access APIs or perform  
# routine operations and maintenance. To create a RAM account, log on to  
# https://ram.console.aliyun.com.  
auth = oss2. Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')  
# This example uses endpoint China (Hangzhou). Specify the actual  
# endpoint based on your requirements.  
service = oss2. Service(auth, 'http://oss-cn-hangzhou.aliyuncs.com')  
  
print([b.name for b in oss2. BucketIterator(service)])
```

Configure an ACL for a bucket

The ACL of a bucket includes the following permissions.

Permission	Description	Value
Private	The bucket owner and the authorized users can read and write objects in the bucket. Other users cannot perform any operation on the objects.	oss2. BUCKET_ACL_PRIVATE
Public read	The bucket owner and the authorized users can read and write objects in the bucket . Other users can only read the objects in the bucket. Authorize this permission with caution.	oss2. BUCKET_ACL_PUBLIC_READ
Public read-write	All users can read and write objects in the bucket. Authorize this permission with caution.	oss2. BUCKET_ACL_PUBLIC_READ_WRITE

Run the following code to configure an ACL for a bucket:

```
# -*- coding: utf-8 -*-  
import oss2
```



```
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2. Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2. Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Set the ACL for the bucket to private.
bucket.put_bucket_acl(oss2. BUCKET_ACL_PRIVATE)
```

Obtain the ACL for a bucket

Run the following code to obtain the ACL for a bucket:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2. Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2. Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

print(bucket.get_bucket_acl().acl)
```

Obtain bucket information

Run the following code to obtain bucket information:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2. Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2. Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Obtain bucket information
bucket_info = bucket.get_bucket_info()
print('name: ' + bucket_info.name)
print('storage class: ' + bucket_info.storage_class)
print('creation date: ' + bucket_info.creation_date)
print('intranet_endpoint: ' + bucket_info.intranet_endpoint)
print('extranet_endpoint ' + bucket_info.extranet_endpoint)
print('owner: ' + bucket_info.owner.id)
```

```
print('grant: ' + bucket_info.acl.grant)
```

Delete a bucket

Before a bucket is deleted, ensure that all objects in the bucket and fragments that are generated from multipart upload are deleted.



Note:

To delete the fragments that are generated from multipart upload, use [Bucket.ListMultipartUploads](#) to list all fragments, and then use [Bucket.AbortMultipartUpload](#) to delete the fragments.

Run the following code to delete a bucket:

```
# -*- coding: utf-8 -*-
import oss2
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')
try:
    # Delete the bucket.
    bucket.delete_bucket()
except oss2.exceptions.BucketNotEmpty:
    print('bucket is not empty.')
except oss2.exceptions.NoSuchBucket:
    print('bucket does not exist')
```

For buckets which are not empty, you can list and delete objects stored in these buckets first (stop uploading for objects uploaded by multipart upload), and then delete the buckets.

3.6 Upload objects

3.6.1 Overview

This topic is the overview of object upload in OSS Python SDK.

In OSS, an object is the basic unit for data operations. OSS Python SDK provides the following file upload methods:

- [Simple upload](#): supports the upload of a file up to 5 GB in size.
- [Append upload](#): supports the upload of a file up to 5 GB in size.

- [Resumable upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files. It supports concurrent upload and you can define the size of each part.
- [Multipart upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files.

**Note:**

For more information about the usage scenarios of each upload method, see “Upload files” in OSS Developer Guide.

During the file upload, you can set [Object Meta](#), and view the upload progress in the [upload progress bar](#). After you complete the file upload, you can perform [upload callback](#).

3.6.2 Simple upload

This topic describes how to use simple upload.

You can use the `bucket.put_object` method to upload a file. This method supports multiple types of inputs, which are listed in the following table.

Type	Upload method
String	Direct upload
Bytes	Direct upload
Unicode	Upload after converting to bytes encoded in UTF-8.
Local files	Upload as File object, which must be opened in the binary mode.
Network stream	Upload as Iterable object in the Chunked Encoding method.

- Upload a string

You can run the following code to upload a string:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on
# to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
```

```

bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Return value.
result = bucket.put_object('<yourObjectName>', 'content of object')
# HTTP return code.
print('http status: {0}'.format(result.status))
# Request ID. The request ID is the unique identification of a
request. We strongly recommend you to add this parameter in the
program log.
print('request_id: {0}'.format(result.request_id))
# Etag is a unique attribute of the value returned by put_object.
print('ETag: {0}'.format(result.etag))
# HTTP response header.
print('date: {0}'.format(result.headers['date']))

```

- Upload bytes

You can run the following code to upload bytes:

```

# -*- coding: utf-8 -*-

import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.put_object('<yourObjectName>', b'content of object')

```

- Upload Unicode

You can run the following code to upload Unicode:

```

# -*- coding: utf-8 -*-

import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.put_object('<yourObjectName>', u'content of object')

```

- Upload a local file

You can run the following code to upload a local file:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Files must be opened in the binary mode because the number of
bytes included in the file is required for upload.
with open('<yourLocalFile>', 'rb') as fileobj:
    # The seek method specifies that the read or write operations
    start from the 1000th byte. The upload starts from the 1000th byte
    until the end of the file.
    fileobj.seek(1000, os.SEEK_SET)
    # The tell method is used to return to the current location.
    current = fileobj.tell()
    bucket.put_object('<yourObjectName>', b'content of object')
```

OSS Python SDK provides a more convenient method to upload local files:

```
bucket.put_object_from_file('<yourObjectName>', '<yourLocalFile>')
```

- Upload a network stream

You can run the following code to upload a network stream:

```
# -*- coding: utf-8 -*-
import oss2
import requests

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# The requests.get method returns an Iterable object, and the Python
SDK uploads the network stream in the Chunked Encoding method.
input = requests.get('http://www.aliyun.com')
```

```
bucket.put_object('<yourObjectName>', input)
```

3.6.3 Append upload

This topic describes how to use append upload.

Run the following code for append upload:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Set the position (the Position parameter) where the object is
# appended to 0.
result = bucket.append_object('<yourObjectName>', 0, 'content of first
append')
# If the object is not uploaded for the first time, you can use the
# bucket.head_object method or the next_position attribute returned in
# the last append upload to get the append position.
bucket.append_object('<yourObjectName>', result.next_position, '
content of second append')
```

If the object already exists, exceptions occur in the following two scenarios:

- The file cannot be uploaded with append upload. In this case, an `ObjectNotAppendable` exception occurs.
- The file can be uploaded with append upload, but the append position does not match the current file length. In this case, a `PositionNotEqualToLength` exception occurs.

3.6.4 Resumable upload

You can use resumable upload to split a file you want to upload into several parts and upload them simultaneously. After you have uploaded all parts, you can combine these parts into a complete object. Thus, you can complete uploading the entire object.

You can use the `oss2.resumable_upload` method to upload a specified file with resumable upload. You can configure the following parameters.

Parameter	Description	Required or not	Default value
bucket	Specifies the bucket name.	Required	None

Parameter	Description	Required or not	Default value
key	Specifies the object name.	Required	None
filename	Specifies the name of the local file to upload.	Required	None
store	Specifies the directory where the progress information is stored.	Optional	Directory '.py-oss-upload' under the HOME directory
headers	Specifies the HTTP header.	Optional	None
multipart_threshold	Specifies a object length threshold. If the object length is larger than the threshold, the resumable upload is used.	Optional	10 MB
part_size	Specifies the part size.	Optional	Auto-calculated
progress_callback	Specifies the upload progress callback function.	Optional	None
num_threads	Specifies the number of concurrent upload threads.	Optional	1

Run the following code for resumable upload:

```
# -*- coding: utf-8 -*-
import oss2
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')
# When the file length is larger than or be equal to the value of
the optional parameter multipart_threshold (10 MB by default), the
resumable upload is used. If you do not use the store parameter to
specify the directory, a py-oss-upload directory is created under the
HOME directory to save upload progress information.
```

```
oss2.resumable_upload(bucket, '<yourObjectName>', '<yourLocalFile>')
```

Python SDK 2.1.0 and later support resumable upload with optional parameters, as shown in the following code:

```
# If you use the store parameter to specify the directory, the
# progress information is stored in the specified directory. If you use
# the num_threads to set the number of concurrent upload threads, ensure
# that the value of oss2.defaults.connection_pool_size is no less than
# the thread number.. The number of concurrent threads is 1 by default.
oss2.resumable_upload(bucket, '<yourObjectName>', '<yourLocalFile>',
    store=oss2.ResumableStore(root='/tmp'),
    multipart_threshold=100*1024,
    part_size=100*1024,
    num_threads=4)
```

For more information about resumable upload, see [Resumable upload](#) in the OSS Developer Guide.

3.6.5 Multipart upload

This topic describes how to use multipart upload.

To enable multipart upload, perform the following steps:

1. Initialization (using `bucket.init_multipart_upload`): Obtain the Upload ID.
2. Upload parts (using `bucket.upload_part`): Upload data parts. You can upload multiple parts concurrently.
3. Completing multipart upload (using `bucket.complete_multipart_upload`): After you have uploaded all parts, combine these parts into a complete object.

Run the following code for multipart upload:

```
# -*- coding: utf-8 -*-
import os
from oss2 import SizedFileAdapter, determine_part_size
from oss2.models import PartInfo
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all APIs in OSS. We
# recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

key = '<yourObjectName>'
filename = '<yourLocalFile>'
```



```

total_size = os.path.getsize(filename)
# Use determine_part_size to determine the part size.
part_size = determine_part_size(total_size, preferred_size=100 * 1024)

# Initialize a multipart upload event.
upload_id = bucket.init_multipart_upload(key).upload_id
parts = []

# Upload parts one by one.
with open(filename, 'rb') as fileobj:
    part_number = 1
    offset = 0
    while offset < total_size:
        num_to_upload = min(part_size, total_size - offset)
        # The SizedFileAdapter(fileobj, size) method generates a new object
        # , and re-calculates the initial append location.
        result = bucket.upload_part(key, upload_id, part_number,
                                   SizedFileAdapter(fileobj,
num_to_upload))
        parts.append(PartInfo(part_number, result.etag))

        offset += num_to_upload
        part_number += 1

# Complete multipart upload.
bucket.complete_multipart_upload(key, upload_id, parts)

# Verify the multipart upload.
with open(filename, 'rb') as fileobj:
    assert bucket.get_object(key).read() == fileobj.read()

```

3.6.6 Upload progress bars

You can use progress bars to indicate the upload or download progress.

For the complete code of progress bars, see [GitHub](#).

The following code is used as an example to describe how to view progress information with `bucket.put_object`:

```

# -*- coding: utf-8 -*-
from __future__ import print_function
import os, sys
import oss2
# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')
# If the length of the data to be uploaded cannot be determined, the
# value of total_bytes is None.
def percentage(consumed_bytes, total_bytes):
    if total_bytes:
        rate = int(100 * (float(consumed_bytes) / float(total_bytes)))

```

```

        print('\r{0}% '.format(rate), end='')
        sys.stdout.flush()
# progress_callback is an optional parameter used to implement
# progress bars.
bucket.put_object('<yourObjectName>', 'a'*1024*1024, progress_callback
=percentage)

```

3.6.7 Upload callback

This topic describes how to use upload callback.

For the complete code of upload callback, see [GitHub](#).

Run the following code for upload callback:

```

# -*- coding: utf-8 -*-
import json
import base64
import os
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Prepare callback parameters.
callback_dict = {}
# Configure the IP address of the server you want to send the callback
# request to, for example, http://oss-demo.aliyuncs.com:23450 or http
# ://127.0.0.1:9090.
callback_dict['callbackUrl'] = 'http://oss-demo.aliyuncs.com:23450'
# Configure the value of the Host field carried in the callback
# request header, such as oss-cn-hangzhou.aliyuncs.com.
callback_dict['callbackHost'] = 'oss-cn-hangzhou.aliyuncs.com'
# Configure the value of the body field carried in the callback
# request.
callback_dict['callbackBody'] = 'filename=${object}&size=${size}&
mime=${mimeType}'
# Configure Content-Type for the callback request.
callback_dict['callbackBodyType'] = 'application/x-www-form-urlencoded'

# The callback parameter is in the JSON format and Base64-encoded.
callback_param = json.dumps(callback_dict).strip()
base64_callback_body = base64.b64encode(callback_param)
# Encoded callback parameters are carried in the request header and
# are sent to OSS.
headers = {'x-oss-callback': base64_callback_body}

# Upload and callback.

```

```
result = bucket.put_object('<yourObjectName>', 'a'*1024*1024, headers)
```

The `put_object`, `put_object_from_file`, and `complete_multipart_upload` methods provide upload callback features. For more information about upload callback, see [Upload callback](#) in the Development Guide.

3.7 Download objects

3.7.1 Overview

This topic is the overview of object download in OSS Python SDK.

OSS Python SDK provides the following download methods:

- [Streaming download](#)
- [Download to your local file](#)
- [Range download](#)
- [Resumable download](#)

You can view the download progress shown in the [download progress bar](#).

3.7.2 Streaming download

If you have a large object to download or it is time-consuming to download the entire object at a time, you can use streaming download. Streaming download enables you to download part of the object each time until you have downloaded the entire object.

Run the following code for streaming download:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
// This example uses the endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# The return value of bucket.get_object is a file-like object, which
# is also an iterable object.
object_stream = bucket.get_object('<yourObjectName>')
print(object_stream.read())

# The get_object interface returns a stream, which must be read by
# read() before being used to calculate the CRC checksum of the returned
```

```
object data. Therefore, you must perform CRC verification after
calling the interface.
if object_stream.client_crc != object_stream.server_crc:
    print "The CRC checksum between client and server is inconsistent
!"
```

Run the following code to download data to a local file:

```
import shutil

# object_stream is a file-like object. Therefore, you can use the
shutil.copyfileobj method to download data to a local file.
object_stream = bucket.get_object('<yourObjectName>')
with open('<yourLocalFile>', 'wb') as local_fileobj:
    shutil.copyfileobj(object_stream, local_fileobj)
```

Run the following code to copy an object to another object using streaming copy.

```
# object_stream is an iterable object, which can be copied to another
object using streaming copy.
object_stream = bucket.get_object('<yourObjectName>')
bucket.put_object('<yourBackupObjectName>', object_stream)
```

3.7.3 Download to your local file

This topic describes how to download an object from OSS to a local file.

You can run the following code to download the specified OSS object to a local file:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses the endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Download an object to your local file. If the name of the object is
the same as that of your local file, the object will replace the local
file. If the name of the object is different from that of your local
file, the object will be downloaded and a new file will be added to
your local device.
```

```
bucket.get_object_to_file('<yourObjectName>', '<yourLocalFile>')
```

3.7.4 Range download

If you only need part of the data in an object, you can use range downloads to download specified content.

Run the following code for range download:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses the endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Obtain the data ranging from byte 0 to the 99th byte of the object
# (including byte 0 and the 99th byte , a total of 100 bytes). If the
# specified value range is invalid, for example, the specified range
# includes a negative number, or the specified value is larger than the
# object size, the entire object is downloaded.
object_stream = bucket.get_object('<yourObjectName>', byte_range=(0,
99))
```

3.7.5 Resumable download

Large-sized objects may fail to be downloaded because the network is unstable or the program exits abnormally and the entire object needs to be downloaded again. However, the object may still fail to be downloaded after multiple attempts. Therefore, OSS provides resumable download.

The process of resumable download is as follows:

1. A temporary local file is created. The file name consists of the original object name and a random suffix.
2. Read the OSS object based on the range you specified in the Range header in the HTTP request and write the read content to the corresponding position of the temporary file.
3. After the download is complete, rename the temporary file as the target file. If the target file already exists, it is overwritten. If the target file does not exist, a new file is created.

You can use `oss2.resumable_download` to enable resumable download. It contains the following parameters:

Parameter	Description	Required or optional	Default value
bucket	Specifies the name of a bucket.	Required	None
key	Specifies the name of an object.	Required	None
filename	Specifies the name of a local file. The OSS object is download to the local file.	Required	None
store	Specifies the local file that records the download progress information. Download progress information is stored in the file . If the download fails at a point, the next download starts from the point based on the recorded progress information.	Optional	The .py-OSS-download directory created under the HOME directory
multipart_threshold	Specifies a length threshold for the object size. If the object size exceeds the threshold , resumable download is enabled.	Optional	10 MB
part_size	Specifies the size of a part.	Optional	Auto-calculated
progress_callback	Specifies the download progress callback function	Optional	None
num_threads	Specifies the number of parts you need to download simultaneously.	Optional	1

Run the following code for resumable download:

```
# -*- coding: utf-8 -*-
import oss2
```

```
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

oss2.resumable_download(bucket, '<yourObjectName>', '<yourLocalFile>')
```

Python SDK 2.1.0 and later support optional parameters for resumable download, as shown in the following code:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Make sure that the value of oss2.defaults.connection_pool_size
is no less than the number of the download threads, and the value
of part_size is no less than the value of oss2.defaults.multiget_p
art_size.
oss2.resumable_download(bucket, '<yourObjectName>', '<yourLocalFile>',
    store=oss2.ResumableDownloadStore(root='/tmp'),
    multiget_threshold=20*1024*1024,
    part_size=10*1024*1024,
    num_threads=3)
```

**Note:**

Do not allow multiple programs (threads) to download the same object to the same target file simultaneously by calling the method. Because the progress information of the threads overwrites each other, and the temporary file names specified by the threads may conflict.

3.7.6 Download progress bars

You can use progress bars to indicate the upload or download progress.

For the complete code of progress bars, see [GitHub](#).

The following code is used as an example to describe how to view progress information with `bucket.get_object_to_file`:

```
# -*- coding: utf-8 -*-
from __future__ import print_function
import os, sys
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')
# If the HTTP response header does not carry Content-Length, the value
# of total_bytes is None.
def percentage(consumed_bytes, total_bytes):
    if total_bytes:
        rate = int(100 * (float(consumed_bytes) / float(total_bytes)))
        print('\r{0}% '.format(rate), end='')

        sys.stdout.flush()

# progress_callback is an optional parameter used to implement
# progress bar.
bucket.get_object_to_file('<yourObjectName>', '<yourLocalFile>',
progress_callback=percentage)
```

3.8 Manage objects

3.8.1 Overview

This topic is the overview of object management in OSS Python SDK.

You can perform the following operations on objects in a bucket with APIs:

- [Determine whether an object exists](#)
- [Manage ACL for an object](#)
- [Manage Object Meta](#)
- [List objects](#)
- [Delete an object](#)
- [Copy an object](#)
- [Restore an archive object](#)
- [Manage a symbolic link](#)

3.8.2 Determine whether a specified object exists

This topic describes how to determine whether a specified object exists.

Run the following code to determine whether a specified object exists:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

exist = bucket.object_exists('<yourObjectName>')
# If the returned value is true, it indicates that the specified
object exists. If the returned value is false, it indicates that the
specified object does not exist.
if exist:
    print('object exist')
else:
    print('object not exist')
```

3.8.3 Manage ACL for an object

The following table describes the permissions included in the Access Control List (ACL) for an object.

Permission	Description	Value
default	The ACL of an object is the same with that of its bucket.	oss2.OBJECT_ACL_DEFAULT
Private	Only the object owner and authorized users can read and write the object.	oss2.OBJECT_ACL_PRIVATE
Public read	Only the object owner and authorized users can read and write the object. Other users can only read the object. Authorize this permission with caution.	oss2.OBJECT_ACL_PUBLIC_READ
Public read-write	All users can read and write the object. Authorize this permission with caution.	oss2.OBJECT_ACL_PUBLIC_READ_WRITE

The ACL of objects take precedence over that of buckets. For example, if the ACL of a bucket is private, while the object ACL is public read-write, all users can read and write the object. If an object is not configured with an ACL, its ACL is the same as that of its bucket by default.

Configure an ACL for an object

Run the following code to configure an ACL for an object:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Configure the ACL for the object.
bucket.put_object_acl('<yourObjectName>', oss2.OBJECT_ACL_PUBLIC_READ
)
```

Obtain the ACL for an object

You can run the following code to obtain the ACL for an object:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')
```

```
print(bucket.get_object_acl('<yourObjectName>').acl)
```

3.8.4 Manage Object Meta

This topic details how to manage Object Meta. For more information, see [Object Meta](#) in the OSS Developer Guide.

Configure HTTP headers

OSS supports user-defined HTTP headers. Run the following code to configure HTTP headers:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.put_object('<yourObjectName>', '{"age": 1}', headers={'Content-
Type': 'application/json; charset=utf-8'})
```

For more information about HTTP headers, see [RFC2616](#).

Configure user-defined Object Meta

You can define user-defined Object Meta for object descriptions. Run the following code to configure user-defined Object Meta:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.put_object('', 'a novel', headers={'x-oss-meta-author': 'O.
Henry', 'Content-Type': 'application/json; charset=utf-8'})
```



Note:

Parameters with the x-oss-meta- prefix are used as the headers of user-defined Object Meta. For more information, see [PutObject](#).

Modify Object Meta

Run the following code to modify Object Meta:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with the AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operation and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.update_object_meta('<yourObjectName>', {'x-oss-meta-author': 'O
. Henry'})
# User-defined Object Meta is cleared each time the bucket.update_obj
# ect_meta is called and must be configured again.
bucket.update_object_meta('<yourObjectName>', {'x-oss-meta-price': '
100 dollar'})
```

Run the following code to change Object Meta, such as Content-Type:

```
bucket.update_object_meta('<yourObjectName>', {'x-oss-meta-author': 'O
. Henry'})
# User-defined Object Meta is cleared each time the bucket.update_obj
# ect_meta is called and must be configured again.
bucket.update_object_meta('<yourObjectName>', {'Content-Type': 'text/
plain'})
```

Obtain Object Meta

You can use the APIs provided by OSS Python SDK to obtain Object Meta.

Method	Description	Advantage
get_object_meta	Obtains the ETag, Size (object size), and LastModified (the time when the object is last modified) of an object.	Simpler and faster
head_object	Obtains all Object Meta.	None

Run the following code to obtain Object Meta:

```
# -*- coding: utf-8 -*-
import oss2
```

```
# We recommend that you do not log on with the AccessKey of an Alibaba
# Cloud account because the Alibaba Cloud account has permissions
# on all APIs in OSS. Instead, we recommend that you log on as an
# authorized RAM user to access APIs or perform routine operation and
# maintenance. To create a RAM account, log on to https://ram.console.
# aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses the endpoint China East 1 (Hangzhou). In actual
# scenarios, specify your required endpoint.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Obtain part of Object Meta.
simplifiedmeta = bucket.get_object_meta("<yourObjectName>")
print(simplifiedmeta.headers['Last-Modified'])
print(simplifiedmeta.headers['Content-Length'])
print(simplifiedmeta.headers['ETag'])

# Obtain all Object Meta.
objectmeta = bucket.head_object("<yourObjectName>")
print(objectmeta.headers['Content-Type'])
print(objectmeta.headers['Last-Modified'])
print(objectmeta.headers['x-oss-object-type'])
```

3.8.5 List objects

Objects are listed alphabetically. You can use OSS Python SDK to list objects in different methods.

Simple list

Run the following code to list 10 objects in a specified bucket.

```
# -*- coding: utf-8 -*-
import oss2
from itertools import islice

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

for b in islice(oss2.ObjectIterator(bucket), 10):
    print(b.key)
```

List objects by a specified prefix

Run the following code to list objects with a specified prefix:

```
# -*- coding: utf-8 -*-
import oss2
```

```
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# List objects by a specified prefix 100 objects are listed by default
for obj in oss2.ObjectIterator(bucket, prefix = 'img-'):
    print(obj.key)
```

List all objects in a bucket

Run the following code to list all objects in a bucket:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Set the delimiter parameter to a slash (/).
for obj in oss2.ObjectIterator(bucket, delimiter = '/'):
    # Determine whether the obj is a directory using the is_prefix method
    if obj.is_prefix(): # directory
        print('directory: ' + obj.key)
    else: # object
        Print ('file: ' + obj.Key)
```

3.8.6 Delete objects

This topic describes how to delete objects.



Warning:

Delete objects with caution because deleted objects cannot be recovered.

Delete an object

Run the following code to delete a single object:

```
# -*- coding: utf-8 -*-
import oss2
```

```
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.delete_object('<yourObjectName>')
```

Delete multiple objects

Run the following code to delete multiple objects simultaneously:

```
# Delete 3 objects. You can delete a maximum of 1,000 objects
simultaneously.
result = bucket.batch_delete_objects(['<yourObjectName-a>', '<
yourObjectName-b>', '<yourObjectName-c>'])
# Print the names of deleted objects.
print('\n'.join(result.deleted_keys))
```

3.8.7 Copy objects

You can copy an object from a bucket (source bucket) to another bucket (target bucket) in the same region.

You must note the following limits before copy an object:

- You must have the read and write permission on the source object.
- You cannot copy an object from a region to another region. For example, you cannot copy an object from a bucket in Hangzhou region to a bucket in Qingdao region.

Simple copy

You can use simple copy for objects smaller than 1 GB. Run the following code for simple copy:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all APIs in OSS. We
recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourDestinationBucketName>')
```

```
bucket.copy_object('<yourSourceBucketName>', '<yourSourceObjectName>',
                  '<yourDestinationObjectName>')
```

Copy a large-sized object

To copy an object larger than 1 GB, you need to use UploadPartCopy. To enable UploadPartCopy, perform the following steps:

1. Use bucket.init_multipart_upload to initiate an UploadPartCopy task.
2. Start UploadPartCopy with bucket.upload_part_copy. Aside from the last part, all parts must be larger than 100 KB.
3. Submit the UploadPartCopy task with bucket.complete_multipart_copy.

Run the following code for UploadPartCopy task

```
# -*- coding: utf-8 -*-
import oss2
from oss2.models import PartInfo
from oss2 import determine_part_size

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all APIs in OSS. We
# recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

src_object = '<yourSourceObjectName>'
dst_object = '<yourDestinationObjectName>'

total_size = bucket.head_object(src_object).content_length
part_size = determine_part_size(total_size, preferred_size=100 * 1024)

# Initiate an UploadPartCopy task
upload_id = bucket.init_multipart_upload(dst_object).upload_id
parts = []

# Copy parts one by one.
part_number = 1
offset = 0
while offset < total_size:
    num_to_upload = min(part_size, total_size - offset)
    byte_range = (offset, offset + num_to_upload - 1)

    result = bucket.upload_part_copy(bucket.bucket_name, src_object,
    byte_range, dst_object, upload_id, part_number)
    parts.append(PartInfo(part_number, result.etag))

    offset += num_to_upload
    part_number += 1

# Complete the UploadPartCopy task.
```



```
bucket.complete_multipart_upload(dst_object, upload_id, parts)
```

For more information about UploadPartCopy, see [UploadPartCopy](#)

3.8.8 Restore an archive object

This topic describes how to restore an archive object.

You must restore an archive object before you read it. Do not call `restoreObject` for non-archive objects.

The state conversion process of an archive object is as follows:

1. An archive object is in the frozen state.
2. After you submit it for restoration, the server restores the object. The object is in the restoring state.
3. You can read the object after it is restored. The restored state of the object lasts one day by default. You can prolong this period to a maximum of seven days. Once this period expires, the object returns to the frozen state.

Run the following code to restore an object:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all APIs in OSS. We
# recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')
objectName = '<yourObjectName>'

bucket.restore_object(objectName)
```

For more information about the archive storage classes, see [Introduction to storage classes](#).

3.8.9 Manage a symbolic link

This topic describes how to manage a symbolic link.

Create a symbolic link

A symbolic link is a special object that maps to an object similar to a shortcut used in Windows.

Run the following code to create a symbolic link:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all APIs in OSS. We
# recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

objectName = '<yourObjectName>'
symlink = "<yourSymlink>";

bucket.put_symlink(objectName, symlink)
```

For more information about symbolic links, see [PutSymlink](#).

Obtain object content for a symbolic link

To obtain a symbolic link, you must have the read permission on it. Run the following code to obtain the object content for a symbolic link:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all APIs in OSS. We
# recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

symlink = "<yourSymlink>";

bucket.get_symlink(symlink)
```

For more information about symbolic links, see [GetSymlink](#).

3.9 Authorized access

This topic describes how to authorize access to users.

Sign a URL to authorize temporary access

You can provide a signed URL to a visitor for temporary access. When you sign a URL, you can specify the expiration time for a URL to restrict the period of access from visitors.

Run the following code to download objects with a signed URL:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all APIs in OSS. We
# recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Set the expiration time of the URL to one hour.
print(bucket.sign_url('GET', '<yourObjectName>', 60))
```

Use STS for temporary access authorization

For the complete code of using STS, see [GitHub](#).

You can use Security Token Service (STS) for temporary access authorization. For more information about STS, see [Introduction](#) in the access control API (STS) reference. For more information about accounts and authorization, see [STS temporary access authorization](#) in best practices.

You must install the official Python STS client first:

```
pip install aliyun-python-sdk-sts
```

Please use version 2.0.6 and later. Run the following code to upload files with STS temporary authorization:

```
# -*- coding: utf-8 -*-

from aliyunsdkcore import client
from aliyunsdksts.request.v20150401 import AssumeRoleRequest
import json
import oss2

# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
endpoint = 'oss-cn-hangzhou.aliyuncs.com'
# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all APIs in OSS. We
# recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
access_key_id = '<yourAccessKeyId>'
access_key_secret = '<yourAccessKeySecret>'
bucket_name = '<yourBucketName>'
# role_arn is the resource name of the role.
role_arn = '<yourRoleArn>'
```

```
clt = client.AcsClient(access_key_id, access_key_secret, 'cn-hangzhou')
req = AssumeRoleRequest.AssumeRoleRequest()

# Set the format of returned values to JSON.
req.set_accept_format('json')
req.set_RoleArn(role_arn)
req.set_RoleSessionName('session-name')
body = clt.do_action(req)

# Use the AccessKeyId and AccessKeySecret to apply for a temporary
token from STS.
token = json.loads(body)

# Use the authentication information in the temporary token to
initialize the StsAuth instance.
auth = oss2.StsAuth(token['Credentials']['AccessKeyId'],
                    token['Credentials']['AccessKeySecret'],
                    token['Credentials']['SecurityToken'])

# Use the StsAuth instance to initialize the bucket.
bucket = oss2.Bucket(auth, endpoint, bucket_name)

# Upload a string.
bucket.put_object('object-name.txt', b'hello world')
```

3.10 Client-side encryption

Client-side encryption is performed locally on data before the data is uploaded to OSS.

For the complete code of client-side encryption, see [GitHub](#).

You can use the following two methods to manage keys:

- Manually manage keys (RSA).
- Use Key Management Service (KMS) to manage keys.

Using the two methods, you can prevent the keys from being leaked and therefore ensure the security of data on the client. Additionally, others cannot decrypt the data to obtain the original data even the data is leaked.

For detailed information about client-side encryption, see [Introduction to client-side encryption](#) [SDK](#) in the OSS Developer Guide.

Encryption meta information

Parameter	Description	Required or not
x-oss-meta-oss-crypto-key	Specifies the encrypted key, which is a string encoded with Base64 after being encrypted by the RSA algorithm.	Required

Parameter	Description	Required or not
x-oss-meta-oss-crypto-start	Specifies the initial value of the encrypted data, which is generated randomly. The initial value is a string encoded with Base64 after being encrypted by the RSA algorithm.	Required
x-oss-meta-oss-cek-alg	Specifies the encryption algorithm with the following available values: AES, GCM, and NoPadding.	Required
x-oss-meta-oss-wrap-alg	Specifies the encryption algorithm with the following available values: rsa and kms.	Required
x-oss-meta-oss-matdesc	Specifies the description of the Content Encryption Key (CEK) in the JSON format. This parameter does not take effect currently.	Optional
x-oss-meta-unencrypted-content-length	Specifies the length of data before encryption. This parameter is not generated if the content-length is not specified.	Optional
x-oss-meta-unencrypted-content-md5	Specifies the MD5 of the data before encryption. If the MD5 is not specified, this parameter is not generated.	Optional

Upload and download objects with the keys manually managed

You can upload and download objects with the keys manually managed. The code is as follows:

```
# -*- coding: utf-8 -*-
import os
import oss2
from oss2.crypto import LocalRsaProvider

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
```

```
# Create a bucket and use the RSA method to encrypted the data. This
method
bucket = oss2.CryptoBucket(auth, '<yourEndpoint>', '<yourBucketName>',
crypto_provider=LocalRsaProvider())

key = 'motto.txt'
content = b'a' * 1024 * 1024
filename = 'download.txt'

# Upload an object.
bucket.put_object(key, content, headers={'content-length': str(1024 *
1024)})

# Download an object.
result = bucket.get_object(key)

# Perform verification.
content_got = b''
for chunk in result:
    content_got += chunk
assert content_got == content

# Download an object to a local file.
result = bucket.get_object_to_file(key, filename)

# Perform verification.
with open(filename, 'rb') as fileobj:
    assert fileobj.read() == content

os.remove(filename)
```

Upload and download objects with the keys managed by KMS

- Prerequisites
 1. You have activated the Alibaba Cloud Key Management Service.
 2. The key ID for your region has been generated.
 3. You have created the custom authorization policies as follows: Log on to the RAM console, select **> RAM > Policies > Custom Policy > Create Authorization Policy**, and associate corresponding users with the policy.

Refer to the following format to create a custom policy:

```
{
  "Version": "1",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "kms:CreateKey",
        "kms:GenerateDataKey",
        "kms:ListKeys",
        "kms:Encrypt",
        "kms:Decrypt"
      ],
      "Resource": [
```

```

        "acs:kms:<yourRegion>:<yourloginUserId>:key/*"
    ]
}
]
}

```

- Sample code

```

# -*- coding: utf-8 -*-
import os
import oss2
from oss2.crypto import AliKMSPProvider

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on
# to https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')

# Create a bucket and use the KMS method to encrypt the data. This
# method only applies to scenarios where objects are uploaded or
# downloaded entirely.
bucket = oss2.CryptoBucket(auth, '<yourEndpoint>', 'liusiman123456',
    crypto_provider=AliKMSPProvider('<yourAccessKeyId>', '<yourAccessKeySecret>',
    '<yourRegion>', '<yourCMK>', '1234'))

key = 'motto.txt'
content = b'a' * 1024 * 1024
filename = 'download.txt'

# Upload an object.
bucket.put_object(key, content, headers={'content-length': str(1024 * 1024)})

# Download an object.
result = bucket.get_object(key)

# Perform verification.
content_got = b''
for chunk in result:
    content_got += chunk
assert content_got == content

# Download an object to a local file.
result = bucket.get_object_to_file(key, filename)

# Perform verification.
with open(filename, 'rb') as fileobj:
    assert fileobj.read() == content

```

```
os.remove(filename)
```

3.11 Static website hosting

You can set your bucket configuration to the static website hosting mode. After the configuration takes effect, you can access this static website with the bucket domain and be redirected to a specified index page or error page.

For more information about static website hosting, see [Static website hosting](#).

Configure static website hosting

Run the following code to configure static website hosting:

```
# -*- coding: utf-8 -*-
import oss2
from oss2.models import BucketWebsite

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Enable the static website hosting mode. Set the index page to index.
# html and the error page to error.html.
bucket.put_bucket_website(BucketWebsite('index.html', 'error.html'))
```

View static website hosting configurations

Run the following code to view static website hosting configurations:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
# endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

try:
    # If the static website hosting mode is not enabled, a NoSuchWebsite
    # exception is thrown by get_bucket_website.
    website = bucket.get_bucket_website()
    print('Index file is {0}, error file is {1}'.format(website.
    index_file, website.error_file))
```



```
except oss2.exceptions.NoSuchWebsite as e:
    print('Website is not configured, request_id={0}'.format(e.request_id))
```

Delete static website hosting configurations

Run the following code to delete static website hosting configurations:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.delete_bucket_website()
```

3.12 Manage lifecycle rules

You can use OSS to configure lifecycle rules to reduce storage costs. The lifecycle management rules can be used for automatic deletion of expired objects and fragments, or storage class conversion to Infrequent Access for objects that will expire soon. Each rule includes:

- Rule ID: It identifies a rule. Ensure that each rule ID in a bucket is unique.
- Policy: You can configure a policy by using the following configuration methods. Only one method can be configured for a bucket.
 - Configure by Prefix: You can create multiple rules with this method. Ensure that each prefix is unique.
 - Configure for Entire Bucket: You can configure only one rule with this method.
- Expired: You can configure the following configuration methods:
 - Set by Number of Days: It specifies the number of days from the last modification time of objects.
 - Set by Date: It specifies the date prior to which objects are created. If objects are created prior to the date, these objects are deleted.
- Status: This lifecycle rule takes effect or not.

The parts uploaded by upload_part method also support lifecycle rules. The last modification time of an object is the time the multipart upload event is initiated.

For more information about lifecycle management, see [Manage object lifecycle](#).

Configure lifecycle rules

Run the following code to configure lifecycle rules:

```
# -*- coding: utf-8 -*-
import oss2
from oss2.models import LifecycleExpiration, LifecycleRule, BucketLife
cycle, AbortMultipartUpload
import datetime

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This case uses the Hangzhou endpoint as an example. Fill in the
region endpoint name according to the actual circumstances.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Set the expiration duration to 3 days after last modified date.
rule1 = LifecycleRule('rule1', 'tests/',
                      status=LifecycleRule.ENABLED,
                      expiration=LifecycleExpiration(days=3))

# Configure expiration date to delete objects that are created before
the date.
rule2 = LifecycleRule('rule2', 'logging-',
                      status=LifecycleRule.DISABLED,
                      expiration=LifecycleExpiration(created_before_date=datetime.date(2018
, 12, 12)))

# Set the expiration duration to 3 days for parts in an object.
rule3 = LifecycleRule('rule3', 'tests1/',
                      status=LifecycleRule.ENABLED,
                      abort_multipart_upload=AbortMultipartUpload(days=3))

# Configure expiration date to delete parts that are created before
the date.
rule4 = LifecycleRule('rule4', 'logging1-',
                      status=LifecycleRule.DISABLED,
                      abort_multipart_upload = AbortMultipartUpload(
created_before_date=datetime.date(2018, 12, 12)))

lifecycle = BucketLifecycle([rule1, rule2, rule3, rule4])

bucket.put_bucket_lifecycle(lifecycle)
```

View lifecycle rules

Run the following code to view lifecycle rules:

```
# -*- coding: utf-8 -*-
import oss2
```

```
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

lifecycle = bucket.get_bucket_lifecycle()

for rule in lifecycle.rules:
    if rule.abort_multipart_upload is None:
        print('id={0}, prefix={1}, status={2}, days={3}, created_be
fore_date={4}'
              .format(rule.id, rule.prefix, rule.status,
                        rule.expiration.days,
                        rule.expiration.created_before_date))
    else:
        print('id={0}, prefix={1}, status={2}, days={3}, created_be
fore_date={4}'
              .format(rule.id, rule.prefix, rule.status,
                        rule.abort_multipart_upload.days,
                        rule.abort_multipart_upload.created_before_date
        ))
```

Clear lifecycle rules

Run the following code to clear lifecycle rules:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.delete_bucket_lifecycle()

# An exception occurs when you view lifecycle rules again.
try:
    lifecycle = bucket.get_bucket_lifecycle()
except oss2.exceptions.NoSuchLifecycle:
    print('lifecycle is not configured')
```

3.13 CORS

Cross-origin resource sharing (CORS) allows web applications to access resources that belong to another region. OSS provides CORS APIs for convenient cross-origin access control.

For more information, see [Cross-origin resource sharing](#) and [PutBucketcors](#) in the OSS Developer Guide.

Configure CORS rules

Run the following code to configure CORS rules for the specified bucket:

```
# -*- coding: utf-8 -*-
import oss2
from oss2.models import BucketCors, CorsRule

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

rule = CorsRule(allowed_origins=['*'],
                 allowed_methods=['GET', 'HEAD'],
                 allowed_headers=['*'],
                 max_age_seconds=1000)

# The existing rules will be replaced.
bucket.put_bucket_cors(BucketCors([rule]))
```

Obtain CORS rules

Run the following code to obtain CORS rules:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

try:
    cors = bucket.get_bucket_cors()
except oss2.exceptions.NoSuchCors:
    print('cors is not set')
else:
    for rule in cors.rules:
        print('AllowedOrigins={0}'.format(rule.allowed_origins))
        print('AllowedMethods={0}'.format(rule.allowed_methods))
        print('AllowedHeaders={0}'.format(rule.allowed_headers))
        print('ExposeHeaders={0}'.format(rule.expose_headers))
```

```
print('MaxAgeSeconds={0}'.format(rule.max_age_seconds))
```

Delete CORS rules

Run the following code to delete all CORS rules for the specified bucket:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.delete_bucket_cors()
```

3.14 Set logging

You can enable access logs to record bucket access to log files, which are stored in a specified bucket.

The log file format is as follows:

<TargetPrefix><SourceBucket>-YYYY-mm-DD-HH-MM-SS-UniqueString

For more information about access log files, see [Set access logging](#).

Enable access logging

Run the following code to enable bucket access logging:

```
# -*- coding: utf-8 -*-
import oss2
from oss2.models import BucketLogging

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Enable access logging. Store log files in the current bucket and set
the log file storage directory to 'logging/'.
```

```
bucket.put_bucket_logging(BucketLogging(bucket.bucket_name, 'logging/'))
```

View access logging configurations

Run the following code to view the access logging configurations for a bucket:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

logging = bucket.get_bucket_logging()
print('TargetBucket={0}, TargetPrefix={1}'.format(logging.target_buc
ket, logging.target_prefix))
```

Disable access logging

Run the following code to disable access logging for a bucket:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

bucket.delete_bucket_logging()
```

3.15 Anti-leech

To prevent your data on OSS from being leeches, OSS supports anti-leeching through the referer field settings in the HTTP header, including the following parameters:

- Referrer whitelist: Used to allow access only for specified domains to OSS data.
- Empty referer: Determines whether the referer can be empty. If it is not allowed, only requests with the referer filed in their HTTP or HTTPS headers can access OSS data.

For more information about anti-leaching, see [Anti-leeching settings](#) in the OSS Developer Guide.

Configure the referer whitelist

Run the following code to configure the referer whitelist:

```
# -*- coding: utf-8 -*-
import oss2
from oss2.models import BucketReferer

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# Configure to allow empty Referers (True indicates that an empty
Referer is allowed, and False indicates that an empty Referer is not
allowed), and configure the referer whitelist.
bucket.put_bucket_referer(BucketReferer(True, ['http://aliyun.com', '
http://*.aliyuncs.com']))
```

Obtain a referer whitelist

Run the following code to obtain a referer whitelist:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

config = bucket.get_bucket_referer()
print('allow empty referer={0}, referers={1}'.format(config.allow_empt
y_referer, config.referers))
```

Clear a referer whitelist

Run the following code to clear a referer whitelist:

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
```

```
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

# You cannot clear a referer whitelist directly. To clear a referer
whitelist, you need to create the rule that allows an empty referer
field and replace the original rule with the new rule.
bucket.put_bucket_referer(BucketReferer(True, []))
```

3.16 Image processing

Image Processing (IMG) is a massive, secure, cost-effective and highly reliable image processing service. After source images are uploaded to OSS, you can process images on any Internet device at any anytime, from anywhere through simple RESTful APIs.

For more information about IMG, see [Image Processing](#).

For the complete code of IMG, see [GitHub](#).

Basic features

OSS offers the following IMG features:

- [Retrieve dominant image tones](#)
- [Format conversion](#)
- [Resize images](#)
- [Incircle](#)
- [Adaptive orientation](#)
- [Brightness](#)
- [Add watermarks](#): allows you to add images, texts, or image-text watermarks to another image.
- [Image processing](#)
- [Image processing access rules](#): calls multiple IMG functions.

Usage

IMG uses standard HTTP GET. You can configure IMG parameters in QueryString of a URL.

If the ACL of an image object is private read and write, only authorized users are allowed for access.

- Anonymous access

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction>,<yourParamValue>
```

Parameter	Description
bucket	Specifies the name of a bucket.
endpoint	Specifies endpoint used to access a region.
object	Specifies the name of an image object.
image	Specifies the reserved identifier for IMG.
action	Specifies the operations on an image, such as scaling, cropping, and rotating.
param	Specifies the parameter that indicates the operation on an image.

— Basic operations

For example, scale an image to a width of 100 px. Adjust the height based on the ratio.

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

— Customized image styles

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=style/<yourStyleName>
```

- style: specifies a reserved identifier of a customized image style.
- yourStyleName: specifies the name of a custom image style. It is the name specified in the rule that is created on the OSS console.

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=style/oss-pic-style-w-100
```

— Cascade operations

Cascade operations allow you to perform multiple operations on an image sequentially.

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-
-process=image/<yourAction1>,<yourParamValue1>/<yourAction2>,<
yourParamValue2>/...
```

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-
-process=image/resize,w_100/rotate,90
```

— HTTPS access

IMG supports access through HTTPS. Example:

```
https://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-
-process=image/resize,w_100
```

- Authorized access

Authorized access allows you to customize an image style, HTTPS access, and cascade operations.

Run the following code to generate a signed URL for IMG:

```
# -*- coding: utf-8 -*-
import oss2

# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
endpoint = 'http://oss-cn-hangzhou.aliyuncs.com'
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on
to https://ram.console.aliyun.com.
access_key_id = '<yourAccessKeyId>'
access_key_secret = '<yourAccessKeySecret>'
bucket_name = '<yourBucketName>'
key = 'example.jpg'

# Creates a bucket instance. All object-related methods must be
called by the bucket instance.
bucket = oss2.Bucket(oss2.Auth(access_key_id, access_key_secret),
endpoint, bucket_name)

# Upload a sample image.
bucket.put_object_from_file(key, 'example.jpg')

# Generate a signed URL. Set the expiration time to 10 minutes. The
unit of expiration time is second.
style = 'image/resize,m_fixed,w_100,h_100/rotate,90'
url = bucket.sign_url('GET', key, 10 * 60, params={'x-oss-process':
style})
```

```
print(url)
```

- Access with SDK

You can use SDK to access and process an image object.

SDK allows you to customize image styles, HTTPS access, and cascade operations.

— Basic operations

`get_object` and `get_object_to_file` support image processing.

Run the following code to perform basic operations on an image:

```
# -*- coding: utf-8 -*-
import os
import oss2

# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
endpoint = 'http://oss-cn-hangzhou.aliyuncs.com'
# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in
# OSS. We recommend that you log on as a RAM user to access APIs
# or perform routine operations and maintenance. To create a RAM
# account, log on to https://ram.console.aliyun.com.
access_key_id = '<yourAccessKeyId>'
access_key_secret = '<yourAccessKeySecret>'
bucket_name = '<yourBucketName>'
key = 'example.jpg'
new_pic = 'example-new.jpg'

# Creates a bucket instance. All object-related methods must be
# called by the bucket instance.
bucket = oss2.Bucket(oss2.Auth(access_key_id, access_key_secret
), endpoint, bucket_name)

# Upload a sample image.
bucket.put_object_from_file(key, 'example.jpg')

# Scale the image.
style = 'image/resize,m_fixed,w_100,h_100'
bucket.get_object_to_file(key, new_pic, process=style)

# Crop the image.
style = 'image/crop,w_100,h_100,x_100,y_100,r_1'
bucket.get_object_to_file(key, new_pic, process=style)

# Rotate the image.
style = 'image/rotate,90'
bucket.get_object_to_file(key, new_pic, process=style)

# Sharpen the image.
style = 'image/sharpen,100'
bucket.get_object_to_file(key, new_pic, process=style)

# Add watermarks.
style = 'image/watermark,text_SGVsbG8g5Zu-54mH5pyN5YqhIQ'
bucket.get_object_to_file(key, new_pic, process=style)
```

```
# Convert the image format.
style = 'image/format,png'
bucket.get_object_to_file(key, new_pic, process=style)

# Delete the sample image.
bucket.delete_object(key)
# Clear the local file.
os.remove(new_pic)
```

— Customize an image style

The following code is used to customize the image style:

```
# -*- coding: utf-8 -*-
import os
import oss2

# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
endpoint = 'http://oss-cn-hangzhou.aliyuncs.com'
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all APIs in OSS. We
recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log
on to https://ram.console.aliyun.com.
access_key_id = '<yourAccessKeyId>'
access_key_secret = '<yourAccessKeySecret>'
bucket_name = '<yourBucketName>'
key = 'example.jpg'
new_pic = 'example-new.jpg'

# Creates a bucket instance. All object-related methods must be
called by the bucket instance.
bucket = oss2.Bucket(oss2.Auth(access_key_id, access_key_secret
), endpoint, bucket_name)

# Upload a sample image.
bucket.put_object_from_file(key, 'example.jpg')

# Customize the image style.
style = 'style/oss-pic-style-w-100'

# Process the image.
bucket.get_object_to_file(key, new_pic, process=style)

# Delete the sample image.
bucket.delete_object(key)
# Clear the local file.
os.remove(new_pic)
```

— Cascade operations

Run the following code to perform cascade operations on an image:

```
# -*- coding: utf-8 -*-
import os
import oss2

# This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
endpoint = 'http://oss-cn-hangzhou.aliyuncs.com'
```

```
# It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all APIs in OSS. We
recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log
on to https://ram.console.aliyun.com.
access_key_id = '<yourAccessKeyId>'
access_key_secret = '<yourAccessKeySecret>'
bucket_name = '<yourBucketName>'
key = 'example.jpg'
new_pic = 'example-new.jpg'

# Creates a bucket instance. All object-related methods must be
called by the bucket instance.
bucket = oss2.Bucket(oss2.Auth(access_key_id, access_key_secret
), endpoint, bucket_name)

# Upload a sample image.
bucket.put_object_from_file(key, 'example.jpg')

// Perform cascade operations.
style = 'image/resize,m_fixed,w_100,h_100/rotate,90'

# Process the image.
bucket.get_object_to_file(key, new_pic, process=style)

# Delete the sample image.
bucket.delete_object(key)
# Clear the local file.
os.remove(new_pic)
```

IMG tools

You can use the IMG viewer [ImageStyleViewer](#) to directly view the IMG result.

3.17 Chinese character and time

This topic describes the Chinese characters and time used by OSS Python SDK.

Chinese character

Errors may occur if Chinese characters are used in the Python code. Therefore, you must declare the Chinese character encoding at the beginning of the code. For example:

```
# -*- coding: utf-8 -*-
```

- Data type

Python 2.x supports the following two data types:

Data type	Description
str	Character strings, corresponding to the bytes type in Python 3.x

Data type	Description
unicode	Unicode streams, of which the length is measured in characters. For example, the length of u'中文' is 2.

Python 3.x supports the following two data types:

Data type	Description
str	Character strings, corresponding to the unicode type in Python 2.x
bytes	Byte streams, of which the length is measured in bytes. For example, the length of b'中文' depends on the encoding, which is 6 if it is encoded with UTF-8.

- Input and output conventions

The following table describes the conventions of input parameter types for OSS Python SDK.

Input	Data type	Remarks
OSS object name	str	If the input type is bytes, it must be encoded with UTF-8.
Local file name	str, unicode	If the input type is bytes, it must be encoded with UTF-8, such as the yourLocalFile parameter in bucket.get_object_to_file.
Input data stream	bytes	For example, the data parameter in bucket.put_object.

The following table describes the conventions of output parameter types for OSS Python SDK.

Output	Data type	Remarks
Results parsed from the XML	str	For example, a string in the result obtained by bucket.list_object.
Downloaded content	bytes	Python SDK regards that the bytes type is encoded with UTF-8 by default. Therefore, make sure that the Python

Output	Data type	Remarks
		source file is also encoded with UTF-8.

- Type conversion functions

OSS Python SDK provides three functions for type conversion.

Function	Description
to_bytes	- Converts the unicode type to the str type in Python 2.x. Other types are returned without changes. - Converts the str type to the bytes type in Python 3.x. Other types are returned without changes.
to_unicode	- Converts the str type to the unicode type in Python 2.x. Other types are returned without changes. - Converts the bytes type to the str type in Python 3.x. Other types are returned without changes.
to_string	Acts as to_bytes in Python 2.x. Acts as to_unicode in Python 3.x.

Time

OSS Python SDK converts all timestamp strings retrieved from the server to [Unix Time](#), that is, the number of seconds since UTC 00:00 on January 1, 1970. For example, the last_modified time in the results returned by bucket.get_object is the Unix Time of the int type.

You can use the datetime.datetime.fromtimestamp() method to convert the time, obtaining the timestamp string.

3.18 Exception handling

OSS Python SDK has three types of exceptions: ClientError, RequestError, and ServerError, which are defined in the oss2.exceptions sub-module.

The following table lists the member variables of exceptions.

Variable	Type	Description
status	int	• ServerError: HTTP status code

Variable	Type	Description
		ClientError and RequestError: fixed values
request_id	str	- ServerError: request ID returned by the OSS server - ClientError and RequestError: empty string
Code and message	str	Correspond to text text in the Code and Message XML Tags in OSS error response .

Example for handling exceptions

The following code demonstrates how to handle exceptions when downloading an object that does not exist, and how to print the HTTP status code and request ID of the error messages.

```
# -*- coding: utf-8 -*-
import oss2

# It is highly risky to log on with AccessKey of an Alibaba Cloud
# account because the account has permissions on all the APIs in OSS.
# We recommend that you log on as a RAM user to access APIs or perform
# routine operations and maintenance. To create a RAM account, log on to
# https://ram.console.aliyun.com.
auth = oss2.Auth('<yourAccessKeyId>', '<yourAccessKeySecret>')
# This example uses endpoint China East 1 (Hangzhou). Specify the
# actual endpoint based on your requirements.
bucket = oss2.Bucket(auth, 'http://oss-cn-hangzhou.aliyuncs.com', '<
yourBucketName>')

try:
    stream = bucket.get_object('random-key.txt')
except oss2.exceptions.NoSuchKey as e:
    print('status={0}, request_id={1}'.format(e.status, e.request_id))
```

ClientError

ClientError is caused by input error on the client side. For example, a ClientError is thrown when an empty object name list is received when the bucket.batch_delete_objects method is used. The status value of ClientError objects is oss2.exceptions.OSS_CLIENT_ERROR_STATUS.

RequestError

When an exception is thrown by the underlying HTTP library, the Python SDK will convert the exception to RequestError. The status value of ClientError objects is fixed to oss2.exceptions.OSS_CLIENT_ERROR_STATUS.

ServerError

When an HTTP error code is returned by the OSS server, Python SDK converts it into a `ServerError`. `ServerError` is divided into multiple subclasses based on the HTTP status code and OSS error code. The `NotFound` subclass corresponds to all 404 exceptions, and the `Conflict` subclass corresponds to all 409 exceptions.

The following table lists common error codes.

Exception class	HTTP status code	OSS error code	Description
<code>NotModified</code>	304	Null	It is not modified.
<code>AccessDenied</code>	403	<code>AccessDenied</code>	The access is denied.
<code>NoSuchBucket</code>	404	<code>NoSuchBucket</code>	The bucket does not exist.
<code>NoSuchKey</code>	404	<code>NoSuchKey</code>	The file does not exist.
<code>NoSuchUpload</code>	404	<code>NoSuchUpload</code>	The multipart upload does not exist.
<code>NoSuchWebsite</code>	404	<code>NoSuchWebsiteConfiguration</code>	The static website hosting is not configured.
<code>NoSuchLifecycle</code>	404	<code>NoSuchLifecycle</code>	The lifecycle management is not configured.
<code>NoSuchCors</code>	404	<code>NoSuchCORSConfiguration</code>	CORS is not configured.
<code>BucketNotEmpty</code>	409	<code>BucketNotEmpty</code>	The bucket is not empty.
<code>PositionNotEqualToLength</code>	409	<code>PositionNotEqualToLength</code>	The Append position is not equal to the object length.
<code>ObjectNotAppendable</code>	409	<code>ObjectNotAppendable</code>	The object is not appendable.

4 PHP

4.1 Preface

Source code

For the source code, see [GitHub](#).

Code samples

OSS SDK for PHP provides a variety of code samples for your reference or use. The following table describes the content of code samples:

Sample file	Content
Object.php	Object operations, including upload objects , download objects , and manage objects
MultipartUpload.php	Multipart upload
Signature.php	Authorized access with the signed URL
Callback.php	Upload callback
Image.php	Image processing
Bucket.php	Bucket operations, including create a bucket , delete a bucket , list buckets , and ACL .
BucketLifecycle.php	Configure, view, and delete the lifecycle rules of a bucket
BucketLogging.php	Configure, view, and delete the access log files of a bucket
BucketReferer.php	Configure, view, and delete the anti-leech settings of a bucket
BucketWebsite.php	Configure, view, and delete the static website hosting settings of a bucket
BucketCors.php	Configure, view, and delete the CORS settings of a bucket

4.2 Installation

Preparation

OSS PHP SDK is applicable to PHP 5.3 and later versions. PHP 5.6.22 is used in this topic as an example.

- Installation environment

You must install PHP cURL extensions:

- In Windows, see [Compile and use Alibaba Cloud OSS PHP SDK in Windows](#) to install PHP cURL extension. In Windows, if you cannot find the required module, specify the `extension_dir` to `C:/Windows/System32/` in `php.ini`.
- In Ubuntu, you can use the `apt-get` package manager to install the PHP cURL extension by running `sudo apt-get install php-curl`.
- In CentOS, you can use the `yum` package manager to install the PHP cURL extension by running `sudo yum install php-curl`.

- Check PHP version

- Run `php -v` to check the current PHP version.
- Run `php -m` to check whether cURL extension is installed.

Download SDK

- [Download from GitHub](#)
- [Download previous versions](#)

For more information, see [OSS API documents](#).



Note:

We recommend that you use the latest version of the SDK. You can download documents of OSS PHP SDK 2.0.0 and earlier versions from [here](#).

Install SDK

You can install the SDK in three methods:

- Composer

You can install the SDK through composer as follows:

1. Run `composer require aliyuncs/oss-sdk-php` in the root directory of your project, or declare the dependency on Alibaba Cloud OSS SDK for PHP in `composer.json` as follows:

```
"require": {
    "aliyuncs/oss-sdk-php": "~2.x.x"
```

```
}
```

2. Run `composer install` to install the dependency. After the dependency is installed, check whether your directory structure complies with the following structure:

```
.
├── app.php
├── composer.json
├── composer.lock
└── vendor
```

The `app.php` is a user application. The `vendor/` directory contains the dependent library. You must introduce the dependency in `app.php`:

```
require_once __DIR__ . '/vendor/autoload.php';
```

**Note:**

- If your project references `autoload.php`, you do not need to introduce the file again after adding the SDK dependency.
- If a network error occurs when you use the Composer Dependency Manager, you can use the [Image Source](#) in the Composer China region by running the following command:
`composer config -g repositories.packagist composer http://packagist.phpcomposer.com.`

- Phar

You can install the SDK through phar as follows:

1. Select the required version and download the Phar package on [GitHub](#).
2. Introduce the file in your code:

```
require_once '/path/to/oss-sdk-php.phar';
```

Source code

You can install the SDK through source code as follows:

1. Select the required version and download the zip package on [GitHub](#).

2. Find the `autoload.php` file in the root directory of the unzipped package, and introduce the file in your code:

```
require_once '/path/to/oss-sdk/autoload.php';
```

4.3 Quick start

This topic describes how to use OSS PHP SDK to perform routine operations such as bucket creation, object uploads, and object downloads.

Create a bucket

Run the following code to create a bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);
    $ossClient->createBucket($bucket);
} catch (OssException $e) {
    print $e->getMessage();
}
```

For more information about bucket naming rules, see naming conventions in [Basic concepts](#). For more information about how to create a bucket, see [Manage a bucket](#).

Upload objects

Run the following code to upload a file to OSS:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
```

```

    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";
// Object name
$object = "<yourObjectName>";
$content = "Hi, OSS.";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);
    $ossClient->putObject($bucket, $object, $content);
} catch (OssException $e) {
    print $e->getMessage();
}

```

For more information, see [Upload objects](#).

Download objects

Run the following code to download an object:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name

```

```

$bucket= "<yourBucketName>";
// Object name
$object = "<yourObjectName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint
);
    $content = $ossClient->getObject($bucket, $object);
    print("object content: " . $content);
} catch (OssException $e) {
    print $e->getMessage();
}

```

For more information, see [Download objects](#).

List objects

Run the following code to list objects in a specified bucket. You can list a maximum of 100 objects by default.

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket= "<yourBucketName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint
);

    $listObjectInfo = $ossClient->listObjects($bucket);
    $objectList = $listObjectInfo->getObjectList();
    if (! empty($objectList)) {
        foreach ($objectList as $objectInfo) {
            print($objectInfo->getKey() . "\t" . $objectInfo->getSize() . "\t" .
$objectInfo->getLastModified() . "\n");
        }
    }
} catch (OssException $e) {
    print $e->getMessage();
}

```

```
}
```

For more information, see [List objects](#) in [Manage objects](#).

Delete objects

Run the following code to delete a specified object:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";
// Object name
$object = "<yourObjectName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);
    $ossClient->deleteObject($bucket, $object);
} catch (OssException $e) {
    print $e->getMessage();
}
```

For more information, see [Delete objects](#) in [Manage objects](#).

4.4 Initialization

OSSClient serves as the OSS Java client to manage OSS resources such as buckets and objects.

Create an OSSClient instance

To create an OSSClient instance, you need to specify an endpoint. For more information about endpoints, see [Regions and endpoints](#) and [Bind a custom domain name](#).

- Use an OSS domain to create an OSSClient instance

Run the following code to create an OSSClient instance with a domain assigned by OSS:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);
} catch (OssException $e) {
    print $e->getMessage();
}
```

- Use a custom domain (CNAME) to create an OSSClient instance

Run the following code to create an OSSClient instance with CNAME:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
$endpoint = "<yourEndpoint>";

try {
    // The true parameter indicates that the CNAME is enabled. CNAME
    // indicates a custom domain bound to a bucket.
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint, true);
}
```

```

    } catch (OssException $e) {
        print $e->getMessage();
    }

```

**Note:**

The `ossClient.listBuckets` method is not available when CNAME is used.

- Use STS to create an OSSClient instance

Run the following code to create an OSSClient instance with Security Token Service (STS):

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$securityToken = "<yourSecurityToken>";

try {
    $ossClient = new OssClient(
        $accessKeyId, $accessKeySecret, $endpoint, false, $
        securityToken);
} catch (OssException $e) {
    print $e->getMessage();
}

```

For more information, see [What is RAM and STS](#) and [Authorized access](#).

- Use a proxy server to create an OSSClient instance

Run the following code to create an OSSClient instance with a proxy server, which is supported by PHP 5.3 and later.

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

```

```

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// The address of the proxy server, for example, http://<username>:<
// password>@<proxy ip>:<proxy port>
$requestProxy = "<yourRequestProxy>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint, false, $requestProxy);
} catch (OssException $e) {
    print $e->getMessage();
}

```

Configure network parameters

Run the following code to configure the network parameters of an OSSClient instance:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";

try {
    $ossClient = new OssClient(
        $accessKeyId, $accessKeySecret, $endpoint);
    // Set the timeout time in seconds for data transmission at the
    // sockets layer. The default value is 5184000.
    $ossClient->setTimeout(3600);
    // Set the timeout time in seconds when connections are established.
    // The default value is 10.
    $ossClient->setConnectTimeout(10);
} catch (OssException $e) {
    print $e->getMessage();
}

```

```
}
```

4.5 Bucket

A bucket serves as a container that stores objects. Objects belong to a bucket.

For the complete code of the following scenarios, see [GitHub](#).

Create a bucket

Run the following code to create a bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);
    // Set the storage class to Infrequent Access for a bucket. The
    // default value is Standard.
    $options = array(
        OssClient::OSS_STORAGE => OssClient::OSS_STORAGE_IA
    );
    // Set the ACL to public read for a bucket. The default value is
    // Private.
    $ossClient->createBucket($bucket, OssClient::OSS_ACL_TYPE_PUBLIC_
    READ, $options);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

For more information about bucket naming rules, see naming conventions in [Basic concepts](#).

Determine whether a bucket exists

Run the following code to determine whether a specified bucket exists:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $res = $ossClient->doesBucketExist($bucket);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
if ($res === true) {
    print(__FUNCTION__ . ": OK" . "\n");
} else {
    print(__FUNCTION__ . ": FAILED" . "\n");
}
```

List buckets

Run the following code to list buckets:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
```

```

We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $bucketListInfo = $ossClient->listBuckets();
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
$bucketList = $bucketListInfo->getBucketList();
foreach($bucketList as $bucket) {
    print($bucket->getLocation() . "\t" . $bucket->getName() . "\t" .
$bucket->getCreatedate() . "\n");
}

```

Configure an ACL for a bucket

The ACL of a bucket includes the following permissions.

Permission	Description	Value
Private	The bucket owner and the authorized users can read and write objects in the bucket. Other users cannot perform any operation on the objects.	OssClient::OSS_ACL_TY PE_PRIVATE
Public read	The bucket owner and the authorized users can read and write objects in the bucket . Other users can only read the objects in the bucket. Authorize this permission with caution.	OssClient::OSS_ACL_TY PE_PUBLIC_READ
Public read-write	All users can read and write objects in the bucket. Authorize this permission with caution.	OssClient::OSS_ACL_TY PE_PUBLIC_READ_WRITE

You can run the following code to configure an ACL for a bucket:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}

```

```

}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";
// Set the ACL of the bucket to private.
$acl = OssClient::OSS_ACL_TYPE_PRIVATE;
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->putBucketAcl($bucket, $acl);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

Obtain the ACL for a bucket

Run the following code to obtain the ACL for a bucket:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";

```

```

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $res = $ossClient->getBucketAcl($bucket);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
print('acl: ' . $res);

```

Obtain the region of a bucket

Run the following code to obtain the region (or location) for a bucket:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $Regions = $ossClient->getBucketLocation($bucket);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
var_dump($Regions);

```

For more information about region, see region in the [Basic concepts](#).

Obtain bucket information

Run the following code to obtain bucket information:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $metas = $ossClient->getBucketMeta($bucket);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
var_dump($metas);
```

Delete a bucket

Before a bucket is deleted, ensure that all objects in the bucket and fragments that are generated from multipart upload are deleted.



Note:

To delete the fragments that are generated from multipart upload, use [Bucket.ListMultipartUploads](#) to list all fragments, and then use [Bucket.AbortMultipartUpload](#) to delete the fragments.

Run the following code to delete a bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
```

```

    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->deleteBucket($bucket);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.6 Upload objects

4.6.1 Overview

In OSS, an object is the basic unit for data operations. OSS PHP SDK provides the following file upload methods:

- [Simple upload](#): supports the upload of a file up to 5 GB in size.
- [Append upload](#): supports the upload of a file up to 5 GB in size.
- [Multipart upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files



Note:

For more information about the usage scenarios of each upload method, see “Upload files” in OSS Developer Guide. After you complete the file upload, you can perform [upload callback](#).

4.6.2 Simple upload

Simple upload applies to two scenarios: upload a string and upload a local file.

Upload a string

You can run the following code to upload a string to OSS:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";
// Object name
$object = "<yourObjectName>";
// Object content
$content = "Hello OSS";
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->putObject($bucket, $object, $content);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

Upload a local file

You can run the following code to upload a local file to OSS:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}
```

```

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Bucket name
$bucket = "<yourBucketName>";
// Object name
$object = "<yourObjectName>";
// <yourLocalFile> consists of the local file path and the file name (
// including the extension), such as /users/local/myfile.txt
$filePath = "<yourLocalFile>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->uploadFile($bucket, $object, $filePath);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.6.3 File upload

Run the following code to upload a file to OSS:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Specify the bucket name.
$bucket = "<yourBucketName>";
// Specify the object name.

```

```

$object = "<yourObjectName>";
// <yourLocalFile> consists of a local file path and a file name with
extension, for example: /users/local/myfile.txt
$filePath = "<yourLocalFile>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $ossClient->uploadFile($bucket, $object, $filePath);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.6.4 Append upload

You can append a string or a file to an OSS object.

You cannot perform copyObject for appended objects.

Append a string

Run the following code to append a string to an OSS object:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Specify the bucket name.
$bucket = "<yourBucketName>";
// Specify the object name.
$object = "<yourObjectName>";
// Specify the content of the string.
$content_array = array('Hello OSS', 'Hi OSS', 'OSS OK');
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $position = $ossClient->appendObject($bucket, $object, $content_ar
ray[0], 0);

```

```

    $position = $ossClient->appendObject($bucket, $object, $content_array[1], $position);
    $position = $ossClient->appendObject($bucket, $object, $content_array[2], $position);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

Append a file

Run the following code to append a local file to an OSS object:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud account because the account has permissions on all the APIs in OSS. We recommend that you log on as a RAM user to access APIs or perform routine operations and maintenance. To create a RAM account, log on to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
// Specify the bucket name.
$bucket = "<yourBucketName>";
// Specify the object name.
String objectName = "<yourObjectName>";
// Specify the first local file.
$filePath = "<yourLocalFile1>";
// Specify the second local file
$filePath1 = "<yourLocalFile2>";
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);

    $position = $ossClient->appendFile($bucket, $object, $filePath, 0);
    $position = $ossClient->appendFile($bucket, $object, $filePath1, $position);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}

```

```
print(__FUNCTION__ . ": OK" . "\n");
```

4.6.5 Multipart upload

To enable multipart upload, perform the following steps:

1. Initiate a multipart upload event.

You can call `$ossClient->initiateMultipartUpload` to return the globally unique uploadId created in OSS.

2. Upload parts.

You can call `$ossClient->uploadPart` to upload part data.



Note:

- For parts with a same uploadId, parts are sequenced by their part numbers. If you have uploaded a part and use the same part number to upload another part, the later part will replace the former part.
- Except for the last part, the minimum size of other size is 100 KB. The size of the last part is not limited.

3. Complete multipart upload.

Call `$ossClient->completeMultipartUpload` to combine these parts into a complete object.

For the complete code of multipart upload, see [GitHub](#).

The following code is used as a complete example that describes the process of multipart upload:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Core\OssUtil;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
```

```

$bucket= "<yourBucketName>";
$object = "<yourObjectName>";
$uploadFile = "<yourLocalFile>";

/**
 * Step 1: Initiate a multipart upload event and obtain the uploadId.
 */
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    // An uploadId is returned. It is the unique identifier for a
part upload event. You can initiate related operations (such as part
upload cancelation and query) based on the uploadId.
    $uploadId = $ossClient->initiateMultipartUpload($bucket, $object);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": initiateMultipartUpload FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": initiateMultipartUpload OK" . "\n");
/**
 * Step 2: Upload parts.
 */
$partSize = 10 * 1024 * 1024;
$uploadFileSize = filesize($uploadFile);
$pieces = $ossClient->generateMultiuploadParts($uploadFileSize, $
partSize);
$responseUploadPart = array();
$uploadPosition = 0;
$isCheckMd5 = true;
foreach ($pieces as $i => $piece) {
    $fromPos = $uploadPosition + (integer)$piece[$ossClient::
OSS_SEEK_TO];
    $toPos = (integer)$piece[$ossClient::OSS_LENGTH] + $fromPos - 1;
    $upOptions = array(
        $ossClient::OSS_FILE_UPLOAD => $uploadFile,
        $ossClient::OSS_PART_NUM => ($i + 1),
        $ossClient::OSS_SEEK_TO => $fromPos,
        $ossClient::OSS_LENGTH => $toPos - $fromPos + 1,
        $ossClient::OSS_CHECK_MD5 => $isCheckMd5,
    );
    // MD5 check.
    if ($isCheckMd5) {
        $contentMd5 = OssUtil::getMd5SumForFile($uploadFile, $fromPos,
$toPos);
        $upOptions[$ossClient::OSS_CONTENT_MD5] = $contentMd5;
    }
    try {
        // Upload parts.
        $responseUploadPart[] = $ossClient->uploadPart($bucket, $
object, $uploadId, $upOptions);
    } catch(OssException $e) {
        printf(__FUNCTION__ . ": initiateMultipartUpload, uploadPart
- part#{ $i} FAILED\n");
        printf($e->getMessage() . "\n");
        return;
    }
    printf(__FUNCTION__ . ": initiateMultipartUpload, uploadPart -
part#{ $i} OK\n");
}
}

```



```
// $uploadParts is an array composed by the ETags and part number (
// PartNumber) of each part.
$uploadParts = array();
foreach ($responseUploadPart as $i => $eTag) {
    $uploadParts[] = array(
        'PartNumber' => ($i + 1),
        'ETag' => $eTag,
    );
}
/**
 * Step 3: Complete multipart upload.
 */
try {
    // You must provide all valid $uploadParts when you perform this
    // operation. OSS verifies the validity of all parts one by one after
    // it receives $uploadParts. After part verification is successful, OSS
    // combines these parts into a complete object.
    $ossClient->completeMultipartUpload($bucket, $object, $uploadId, $
    uploadParts);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": completeMultipartUpload FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
printf(__FUNCTION__ . ": completeMultipartUpload OK\n");
```

In the example above, \$options includes the following parameters:

Parameter	Description
\$ossClient::OSS_FILE_UPLOAD	File upload
OssClient::OSS_PART_NUM	Part number
OssClient::OSS_SEEK_TO	Specifies a start location.
OssClient::OSS_LENGTH	Object length
OssClient::OSS_PART_SIZE	Part size
OssClient::OSS_CHECK_MD5	Determines whether MD5 check is enabled. The MD5 check is enabled if the value is true.

Cancel a multipart upload event

You can call \$ossClient->abortMultipartUpload to cancel a multipart upload event. If you cancel a multipart upload event, you are not allowed to perform any other operations with this uploadId anymore. The uploaded parts will be deleted.

Run the following code to cancel a multipart upload event:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
```

```

}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$upload_id = "<yourUploadId>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->abortMultipartUpload($bucket, $object, $upload_id);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

Upload of a local file using multipart upload

Run the following code to upload a local file using multipart upload:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$file = "<yourLocalFile>";

$options = array(

```

```

        OssClient::OSS_CHECK_MD5 => true,
        OssClient::OSS_PART_SIZE => 1,
    );
    try{
        $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

        $ossClient->multiuploadFile($bucket, $object, $file, $options);
    } catch(OssException $e) {
        printf(__FUNCTION__ . ": FAILED\n");
        printf($e->getMessage() . "\n");
        return;
    }
    print(__FUNCTION__ . ": OK" . "\n");

```

Upload a directory using multipart upload

Run the following code to upload a local directory (including all files in it) using multipart upload:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$localDirectory = ".";
$prefix = "samples/codes";
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $ossClient->uploadDir($bucket, $prefix, $localDirectory);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

List uploaded parts

Run the following code to list uploaded parts:

```

<? php

```

```

if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$uploadId = "<yourUploadId>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $listPartsInfo = $ossClient->listParts($bucket, $object, $uploadId
    );
    foreach ($listPartsInfo->getListPart() as $partInfo) {
        print($partInfo->getPartNumber() . "\t" . $partInfo->getSize
        () . "\t" . $partInfo->getETag() . "\t" . $partInfo->getLastModified
        () . "\n");
    }
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

List all multipart upload events

Run the following code to list all multipart upload events:

```

<? php
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform

```

```

routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";

$options = array(
    'delimiter' => '/',
    'max-uploads' => 100,
    'key-marker' => '',
    'prefix' => '',
    'upload-id-marker' => ''
);
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $listMultipartUploadInfo = $ossClient->listMultipartUploads($
bucket, $options);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": listMultipartUploads FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
printf(__FUNCTION__ . ": listMultipartUploads OK\n");
$listUploadInfo = $listMultipartUploadInfo->getUploads();
var_dump($listUploadInfo);

```

Parameters of \$options are described as follows:

Parameter	Description
delimiter	Specifies a delimiter of a forward slash (/) used to group object names. The object between the specified prefix and the first occurrence of a delimiter of a forward slash (/) is commonPrefixes.
key-marker	Lists all part upload events with the object whose names start with a letter that comes after the key-marker value in the alphabetical order. You can use this parameter with the upload-id-marker parameter to specify the initial position for the specified returned result.
max-uploads	Specifies the maximum number of part upload events. The maximum value (also default value) you can set is 1,000.
prefix	Specifies the prefix that must be included in the returned object name. Note that if you use a

Parameter	Description
	prefix for query, the returned object name will contain the prefix.
upload-id-marker	You can use this parameter with the key-marker parameter to specify the initial position for the specified returned result. If you do not configure keyMarker, the uploadIdMarker parameter is invalid. If you configure key-marker, the query result contains: • All objects whose names start with a letter that comes after the keyMarker value. • All objects whose names start with a letter that is the same as the key-marker value in the alphabetical order and the value of uploadId greater than that of upload-id-marker.

4.6.6 Upload callback

Configure callback for simple upload

Run the following code to configure callback for simple upload.

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);

// Configure callback for uploads.
// callbackUrl is the IP address of the callback server, such as http
// ://oss-demo.aliyuncs.com:23450 or http://127.0.0.1:9090.
```

```
// callbackHost is the value of the Host field carried in the callback
// request, such as oss-cn-hangzhou.aliyuncs.com.
$url =
    '{
        "callbackUrl": "<yourCallbackServerUrl>",
        "callbackHost": "<yourCallbackServerHost>",
        "callbackBody": "bucket=${bucket}&object=${object}&etag=${
etag}&size=${size}&mimeType=${mimeType}&imageInfo.height=${imageInfo
.height}&imageInfo.width=${imageInfo.width}&imageInfo.format=${
imageInfo.format}&my_var1=${x:var1}&my_var2=${x:var2}",
        "callbackBodyType": "application/x-www-form-urlencoded"
    }';

// Configure the custom parameters used to initiate a callback request
// . Each parameter consists of a key and a value. The key must start
// with x:.
$var =
    '{
        "x:var1": "value1",
        "x:var2": "value2"
    }';
$options = array(OssClient::OSS_CALLBACK => $url,
    OssClient::OSS_CALLBACK_VAR => $var
);
$result = $ossClient->putObject($bucket, $object, file_get_contents(
__FILE__), $options);
print_r($result['body']);
print_r($result['info']['http_code']);
```

Configure callback for multipart upload

Run the following code to configure callback for multipart upload:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}
use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Core\OssUtil;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$uploadFile = "<yourLocalFile>";

/**
 * Step 1: Initiate a multipart upload event and get the uploadId.
 */
```

```

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);
// An uploadId is returned. It is the unique identifier for a
multipart upload event. You can initiate related operations (such as
cancel or query a multipart upload event) based on the uploadId.
$uploadId = $ossClient->initiateMultipartUpload($bucket, $object);

print(__FUNCTION__ . ": initiateMultipartUpload OK" . "\n");
/*
 * Step 2: Upload parts.
 */
$partSize = 10 * 1024 * 1024;
$uploadFileSize = filesize($uploadFile);
$pieces = $ossClient->generateMultiuploadParts($uploadFileSize, $
partSize);
$responseUploadPart = array();
$uploadPosition = 0;
$isCheckMd5 = true;
foreach ($pieces as $i => $piece) {
    $fromPos = $uploadPosition + (integer)$piece[$ossClient::
OSS_SEEK_TO];
    $toPos = (integer)$piece[$ossClient::OSS_LENGTH] + $fromPos - 1;
    $upOptions = array(
        $ossClient::OSS_FILE_UPLOAD => $uploadFile,
        $ossClient::OSS_PART_NUM => ($i + 1),
        $ossClient::OSS_SEEK_TO => $fromPos,
        $ossClient::OSS_LENGTH => $toPos - $fromPos + 1,
        $ossClient::OSS_CHECK_MD5 => $isCheckMd5,
    );
    // Perform the MD5 verification.
    if ($isCheckMd5) {
        $contentMd5 = OssUtil::getMd5SumForFile($uploadFile, $fromPos,
$toPos);
        $upOptions[$ossClient::OSS_CONTENT_MD5] = $contentMd5;
    }
    try {
        // Upload the parts.
        $responseUploadPart[] = $ossClient->uploadPart($bucket, $
object, $uploadId, $upOptions);
    } catch (OssException $e) {
        printf(__FUNCTION__ . ": initiateMultipartUpload, uploadPart
- part#{ $i } FAILED\n");
        printf($e->getMessage() . "\n");
        return;
    }
    printf(__FUNCTION__ . ": initiateMultipartUpload, uploadPart -
part#{ $i } OK\n");
}
// $uploadParts is an array that consists of the ETags and the
PartNumbers of each part.
$uploadParts = array();
foreach ($responseUploadPart as $i => $eTag) {
    $uploadParts[] = array(
        'PartNumber' => ($i + 1),
        'ETag' => $eTag,
    );
}

/**
 * Step 3: Complete the upload.
 */

```



```
// The callbackUrl is the IP address of the callback server, such as
http://oss-demo.aliyuncs.com:23450 or http://127.0.0.1:9090.
// callbackHost is the value of the Host field carried in the callback
request, such as oss-cn-hangzhou.aliyuncs.com.
$json =
    '{
        "callbackUrl": "<yourCallbackServerUrl>",
        "callbackHost": "<yourCallbackServerHost>",
        "callbackBody": "{ \"mimeType\": \"${mimeType}\", \"size\": \"${size}\", \"x
:var1\": \"${x:var1}\", \"x:var2\": \"${x:var2}\" }",
        "callbackBodyType": "application/json"
    }';

// Configure the custom parameters used to initiate a callback request
. Each parameter consists of a key and a value. The key must start
with x:.
$var =
    '{
        "x:var1": "value1",
        "x:var2": "value2"
    }';
$options = array(OssClient::OSS_CALLBACK => $json,
    OssClient::OSS_CALLBACK_VAR => $var);
// To perform the operation, all valid $uploadParts must be provided
. OSS verifies the validity of all parts one by one after it receives
the $uploadParts. After all the data parts are verified, the OSS
combines these parts into a complete object.
$ossClient->completeMultipartUpload($bucket, $object, $uploadId, $
uploadParts, $options);

printf(__FUNCTION__ . ": completeMultipartUpload OK\n");
```

4.7 Download objects

4.7.1 Overview

This topic is the overview of object download in OSS PHP SDK.

For the complete code of object download, see [GitHub](#).

OSS PHP SDK provides the following download methods:

- [Download to your local file](#)
- [Download to local memory](#)
- [Range download](#)
- [Conditional download](#)

4.7.2 Download to your local file

You can run the following code to download the specified OSS object to a local file:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
```

```

}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
//This example uses the endpoint China East 1 (Hangzhou). Specify the
//actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$localfile = "<yourLocalFile>";
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $localfile
);

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->getObject($bucket, $object, $options);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK, please check localfile: 'upload-test-
object-name.txt'" . "\n");

```

4.7.3 Download to your local memory

Run the following code to download a specified object to local memory and print the content of the object.

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";

```

```
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";
$object = "<yourObjectName>";
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $content = $ossClient->getObject($bucket, $object);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print($content);
print(__FUNCTION__ . ": OK" . "\n");
```

4.7.4 Range download

If you only need part of the data in an object, you can use range downloads to download specified content.

Run the following code to download the content of an object in a range of [0, 4] to local memories:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

//It is highly risky to log on with AccessKey of an Alibaba Cloud
//account because the account has permissions on all the APIs in OSS.
//We recommend that you log on as a RAM user to access APIs or perform
//routine operations and maintenance. To create a RAM account, log on to
//https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
//This example uses the endpoint China East 1 (Hangzhou). Specify the
//actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";
$object = "<yourObjectName>";
// Obtain data between the starting byte value of 0 and the maximum
// byte value of 4 inclusive (that is, a total of 5 bytes). If the
// specified value range is invalid, for example, the specified range
// includes a negative number, or the specified value is larger than the
// object size, the entire object is downloaded.
$options = array(OssClient::OSS_RANGE => '0-4');
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $content = $ossClient->getObject($bucket, $object, $options);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
```

```

        printf($e->getMessage() . "\n");
        return;
    }
    print ($content);
    print(__FUNCTION__ . ": OK" . "\n");

```

4.7.5 Conditional download

You can configure one or more conditions for downloads. If the specified conditions are met, the object can be downloaded. If the specified conditions are not met, an error code is returned and the object cannot not downloaded. You can configure the following conditions:

Parameter	Description	Configuration method
If-Modified-Since	If the specified time is earlier than the time the object is modified, the object can be downloaded. Otherwise, an error (304 Not modified) is returned.	OssClient::OSS_IF_MODIFIED_SINCE
If-Unmodified-Since	If the specified time is later than or equal to the time the object is modified, the object can be downloaded. Otherwise , an error (412 Precondition failed) is returned.	OssClient::OSS_IF_UNMODIFIED_SINCE
If-Match	If the specified ETag matches that of an object, the object can be downloaded. Otherwise , an error (412 Precondition failed) is returned.	OssClient::OSS_IF_MATCH
If-None-Match	If the specified ETag does not match that of an object, the object can be downloaded. Otherwise, an error (304 Not modified) is returned.	OssClient::OSS_IF_NONE_MATCH



Note:

- Both If-Modified-Since and If-Unmodified-Since can exist at the same time as object download conditions. Both If-Match and If-None-Match can exist at the same time as object download conditions.
- \$ossClient->getObjectMeta can be used to obtain the ETag.

You can download an OSS object to local memories or a local file in conditional downloads. Run the following code for conditional download:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";

try{
    $options = array(
        OssClient::OSS_HEADERS => array(
            OssClient::OSS_IF_MODIFIED_SINCE => "Fri, 13 Nov 2015 14:
47:53 GMT"),
    );

    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $content = $ossClient->getObject($bucket, $object, $options);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print ($content);
print(__FUNCTION__ . ": OK" . "\n");
```

4.8 Manage objects

4.8.1 Overview

You can perform the following operations on objects in a bucket with APIs:

- [Determine whether an object exists](#)
- [Manage ACL for an object](#)
- [Manage Object Meta](#)

- [List objects](#)
- [Delete an object](#)
- [Copy an object](#)
- [Restore an archive object](#)
- [Manage a symbolic link](#)
- [Enable MD5 verification](#)

4.8.2 Determine whether a specified object exists

Use the following code to determine whether a specified object exists:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $exist = $ossClient->doesObjectExist($bucket, $object);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
var_dump($exist);
```

4.8.3 Manage ACL for an object

The following table describes the permissions included in the Access Control List (ACL) for an object.

Permission	Description	Value
default	The ACL of an object is the same with that of its bucket.	default
Private	Only the object owner and authorized users can read and write the object.	private
Public read	Only the object owner and authorized users can read and write the object. Other users can only read the object . Authorize this permission with caution.	public-read
Public read-write	All users can read and write the object. Authorize this permission with caution.	public-read-write

The ACL of objects take precedence over that of buckets. For example, if the ACL of a bucket is private, while the object ACL is public read-write, all users can read and write the object. If an object is not configured with an ACL, its ACL is the same as that of its bucket by default.

Configure an ACL for an object

You can run the following code to configure an ACL for a specified object:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
// Set the ACL for the object to public read, which is inherited from
// the bucket by default.
$acl = "public-read";
```

```
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $ossClient->putObjectAcl($bucket, $object, $acl);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

Obtain the ACL for an object

You can run the following code to obtain the ACL for a specified object:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $objectAcl = $ossClient->getObjectAcl($bucket, $object);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
var_dump($objectAcl);
```

4.8.4 Manage Object Meta

For more information about Object Meta, see [Object Meta](#) in OSS Developer Guide.

Configure Object Meta

Run the following code to configure Object Meta:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$content = file_get_contents(__FILE__);
$options = array(
    OssClient::OSS_HEADERS => array(
        'Expires' => '2012-10-01 08:00:00',
        'Content-Disposition' => 'attachment; filename="xxxxxx"',
        'x-oss-meta-self-define-title' => 'user define meta info',
    ));
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->putObject($bucket, $object, $content, $options);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

Modify Object Meta

Run the following code to modify Object Meta:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
```

```
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$fromBucket = "<yourFromBucketName>";
$fromObject = "<yourFromObjectName>";
$toBucket = "<yourToBucketName>";
$toObject = "<yourToObjectName>";
$copyOptions = array(
    OssClient::OSS_HEADERS => array(
        'Expires' => '2018-10-01 08:00:00',
        'Content-Disposition' => 'attachment; filename="xxxxxx"',
        'x-oss-meta-location' => 'location',
    ),
);
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->copyObject($fromBucket, $fromObject, $toBucket, $
    toObject, $copyOptions);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

Obtain Object Meta

Run the following code to obtain Object Meta:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";
```

```

$object = "<yourObjectName>";
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $ Objectmeta = $ ossclient-> getobjectmeta ($ bucket, $ object );
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
if (isset($ObjectMeta[strtolower('Content-Disposition')]) &&
    'attachment; filename="xxxxxx"' === $ObjectMeta[strtolower('
Content-Disposition')])
) {
    print(__FUNCTION__ . ": ObjectMeta checked OK" . "\n");
} else {
    print(__FUNCTION__ . ": ObjectMeta checked FAILED" . "\n");
}

```

4.8.5 List objects

List all objects in a bucket

Run the following code to list all objects in a bucket:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);

while (true) {
    try {
        $listObjectInfo = $ossClient->listObjects($bucket, $options);
    } catch (OssException $e) {
        printf(__FUNCTION__ . ": FAILED\n");
        printf($e->getMessage() . "\n");
        return;
    }
}

```

```

    // Obtain the nextMarker. Obtain the object list from the object
    next to the last object read by listObjects.
    $nextMarker = $listObjectInfo->getNextMarker();
    $listObject = $listObjectInfo->getObjectList();
    $listPrefix = $listObjectInfo->getPrefixList();

    if (! empty($listObject)) {
        print("objectList:\n");
        foreach ($listObject as $objectInfo) {
            print($objectInfo->getKey() . "\n");
        }
    }
    if (! empty($listPrefix)) {
        print("prefixList: \n");
        foreach ($listPrefix as $prefixInfo) {
            print($prefixInfo->getPrefix() . "\n");
        }
    }
    if ($nextMarker === '') {
        break;
    }
}

```

List objects with specified conditions

Run the following code to list objects with specified conditions:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint);

$prefix = 'dir/';
$delimiter = '/';
$nextMarker = '';
$maxkeys = 10;
$options = array(
    'delimiter' => $delimiter,
    'prefix' => $prefix,
    'max-keys' => $maxkeys,
    'marker' => $nextMarker,

```

```

);
try {
    $listObjectInfo = $ossClient->listObjects($bucket, $options);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
$objectList = $listObjectInfo->getObjectList(); // object list
$prefixList = $listObjectInfo->getPrefixList(); // directory list
if (! empty($objectList)) {
    print("objectList:\n");
    foreach ($objectList as $objectInfo) {
        print($objectInfo->getKey() . "\n");
    }
}
if (! empty($prefixList)) {
    print("prefixList: \n");
    foreach ($prefixList as $prefixInfo) {
        print($prefixInfo->getPrefix() . "\n");
    }
}
}

```

In the example above, \$options including the following parameters:

Parameter	Description	Required
delimiter	Specifies a delimiter used to group objects. CommonPrefixes indicates a set of objects which end with delimiter and have the same prefix.	No
prefix	Specifies the prefix you configure to list required objects.	No
max-keys	Specifies the maximum number of objects that can be listed. The default value is 100 . The maximum value is 1,000.	No
marker	Specifies the initial object in the list.	No

4.8.6 Delete objects

Delete an object

Run the following code to delete a single object:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}

```

```

}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->deleteObject($bucket, $object);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

Delete multiple objects

Run the following code to delete multiple objects simultaneously:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

$objects = array();

```

```

$objects[] = "<yourObjectName1>";
$objects[] = "<yourObjectName2>";
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $ossClient->deleteObjects($bucket, $objects);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.8.7 Copy objects

Simple copy

Run the following code to copy objects smaller than 1 GB:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$from_bucket = "<yourFromBucketName>";
$from_object = "<yourFromObjectName>";
$to_bucket = $bucket;
$to_object = $from_object . '.copy';

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $ossClient->copyObject($from_bucket, $from_object, $to_bucket, $
to_object);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}

```

```
print(__FUNCTION__ . ": OK" . "\n");
```

Copy a large-sized object

To copy an object larger than 1 GB, you need to use multipart copy. To use multipart copy, perform the following steps:

1. Use `$ossClient->initiateMultipartUpload` to initiate an UploadPartCopy task.
2. Use `$ossClient->uploadPartCopy` to start a multipart copy. Aside from the last part, all parts must be larger than 100 KB.
3. Submit the multipart copy task with `$ossClient->completeMultipartUpload`.

Run the following code for multipart copy:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";

$src_bucket = "<yourSourceBucketName>";
$src_object = "<yourSourceObjectName>";
$dst_bucket = "<yourDestinationBucketName>";
$dst_object = "<yourDestinationObjectName>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    // Initialize a multipart copy.
    $upload_id = $ossClient->initiateMultipartUpload($dst_bucket, $
    dst_object);

    $copyId = 1;
    // Copy the parts one-by-one.
    $eTag = $ossClient->uploadPartCopy( $src_bucket, $src_object, $
    dst_bucket, $dst_object,$copyId, $upload_id);
    $upload_parts[] = array(
        'PartNumber' => $copyId,
        'ETag' => $eTag,
    );
};
```



```

        // Complete the multipart copy.
        $result = $ossClient->completeMultipartUpload($dst_bucket, $
dst_object, $upload_id, $upload_parts);
    } catch(OssException $e) {
        printf(__FUNCTION__ . ": FAILED\n");
        printf($e->getMessage() . "\n");
        return;
    }
    print(__FUNCTION__ . ": OK" . "\n");

```

4.8.8 Restore an archive object

You must restore an archive object before you read it. Do not call `restoreObject` for non-archive objects.

The state conversion process of an archive object is as follows:

1. An archive object is in the frozen state.
2. After you submit it for restoration, the server restores the object. The object is in the restoring state.
3. You can read the object after it is restored. The restored state of the object lasts one day by default. You can prolong this period to a maximum of seven days. Once this period expires, the object returns to the frozen state.

Run the following code to restore an object:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

```

```

        $ossClient->restoreObject($bucket, $object);
    } catch (OssException $e) {
        printf(__FUNCTION__ . ": FAILED\n");
        printf($e->getMessage() . "\n");
        return;
    }
    print(__FUNCTION__ . ": OK" . "\n");

```

For more information about the archive storage classes, see [Introduction to storage classes](#).

4.8.9 Manage a symbolic link

Create a symbolic link

A symbolic link is a special object that maps to an object similar to a shortcut used in Windows.

You can configure user-defined Object Meta for symbolic links.

Run the following code to create a symbolic link:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$symlink = "<yourSymlink>";
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->putSymlink($bucket, $symlink, $object);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}

```

```
print(__FUNCTION__ . ": OK" . "\n");
```

Obtain object content for a symbolic link

To obtain a symbolic link, you must have the read permission on it. Run the following code to obtain the object content for a symbolic link:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$symlink = "<yourSymlink>";
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $symlinks = $ossClient->getSymlink($bucket, $symlink);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
var_dump($symlinks);
```

4.8.10 Enable MD5 verification

MD5 verification is performed to ensure data integrity during transmission. MD5 verification brings performance loss. MD5 verification is disabled by default during file uploads.

Run the following code to enable MD5 verification during file uploads:

```
<? php
if (is_file(__DIR__ . '/../Autopoload. php ')){
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}
```

```

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";

$options = array(OssClient::OSS_CHECK_MD5 => true);
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->uploadFile($bucket, $object, __FILE__, $options);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

The putObject, uploadFile, appendObject, appendFile and multiuploadFile methods support MD5 verification.

4.9 Authorized access

Sign a URL to authorize temporary access

You can provide a signed URL to a visitor for temporary access. When you sign a URL, you can specify the expiration time for a URL to restrict the period of access from visitors. For the complete code of authorizing access, see [GitHub](#).

- Sign a URL to download an object

Run the following code to sign a URL to download an object:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Http\RequestCore;
use OSS\Http\ResponseCore;

```

```
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$securityToken = "<yourSecurityToken>";

// Set the expiration time of the URL to 3600 seconds.
$timeout = 3600;
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint, false, $securityToken);

    // Generates a signed URL for access with GetObject.
    $signedUrl = $ossClient->signUrl($bucket, $object, $timeout);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": signedUrl: " . $signedUrl . "\n");

// You can access a signed URL by running code or input it in a
// browser.
$request = new RequestCore($signedUrl);
// The signed URL is accessed with GET by default.
$request->set_method('GET');
$request->add_header('Content-Type', '');
$request->send_request();
$res = new ResponseCore($request->get_response_header(), $request->
get_response_body(), $request->get_response_code());
if ($res->isOk()) {
    print(__FUNCTION__ . ": OK" . "\n");
} else {
    print(__FUNCTION__ . ": FAILED" . "\n");
};
```

- Sign a URL to upload a file

Run the following code to sign a URL to upload a file:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Http\RequestCore;
use OSS\Http\ResponseCore;
```

```
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$securityToken = "<yourSecurityToken>";

$timeout = 3600;
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint, false, $securityToken);

    // Generate a URL for access with PutObject.
    $signedUrl = $ossClient->signUrl($bucket, $object, $timeout, "
    PUT");
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": signedUrl: " . $signedUrl . "\n");

$content = "Hello OSS.";
$request = new RequestCore($signedUrl);
// The signed URL is accessed with PUT.
$request->set_method('PUT');
$request->add_header('Content-Type', '');
$request->add_header('Content-Length', strlen($content));
$request->set_body($content);
$request->send_request();
$res = new ResponseCore($request->get_response_header(),
    $request->get_response_body(), $request->get_response_code());
if ($res->isOk()) {
    print(__FUNCTION__ . ": OK" . "\n");
} else {
    print(__FUNCTION__ . ": FAILED" . "\n");
};
```

Use STS for temporary access authorization

OSS supports Alibaba Cloud Security Token Service (STS) for temporary access authorization.

For more information about STS, see [Introduction](#) of the access control API (STS) reference. For more information on accounts and authorization, see [STS temporary access authorization](#).

Run the following code to use STS for temporary file upload access authorization:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
```

```

    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all APIs in OSS. We
// recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$securityToken = "<yourSecurityToken>";

$content = "Hi, OSS.";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint, false, $securityToken);

    $ossClient->putObject($bucket, $object, $content);
} catch (OssException $e) {
    print $e->getMessage();
}

```

4.10 Static website hosting

You can set your bucket configuration to the static website hosting mode. After the configuration takes effect, you can access this static website with the bucket domain and be redirected to a specified index page or error page.

For more information about static website hosting, see [Static website hosting](#).

For the complete code of the following scenarios, see [GitHub](#).

Configure static website hosting

Run the following code to configure static website hosting:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Model\WebsiteConfig;

```

```
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

// Configure static website hosting: The index page is index.html and
// the error page is error.html.
$websiteConfig = new WebsiteConfig("index.html", "error.html");
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->putBucketWebsite($bucket, $websiteConfig);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

View static website hosting configurations

Run the following code to view static website hosting configurations:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

$websiteConfig = null;
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $websiteConfig = $ossClient->getBucketWebsite($bucket);
} catch(OssException $e) {
```



```

        printf(__FUNCTION__ . ": FAILED\n");
        printf($e->getMessage() . "\n");
        return;
    }
    print(__FUNCTION__ . ": OK" . "\n");
    print($websiteConfig->serializeToXml() . "\n");

```

Delete static website hosting configurations

Run the following code to delete static website hosting configurations:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->deleteBucketWebsite($bucket);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.11 Manage lifecycle rules

You can use OSS to configure lifecycle rules to reduce storage costs. The lifecycle management rules can be used for automatic deletion of expired objects and fragments, or storage class conversion to Infrequent Access for objects that will expire soon. Each rule includes:

- Rule ID: It identifies a rule. Ensure that each rule ID in a bucket is unique.
- Policy: You can configure a policy by using the following configuration methods. Only one method can be configured for a bucket.

- Configure by Prefix: You can create multiple rules with this method. Ensure that each prefix is unique.
- Configure for Entire Bucket: You can configure only one rule with this method.
- Expired: You can configure the following configuration methods:
 - Set by Number of Days: It specifies the number of days from the last modification time of objects.
 - Set by Date: It specifies the date prior to which objects are created. If objects are created prior to the date, these objects are deleted.
- Status: This lifecycle rule takes effect or not.

For more information about lifecycle management, see [Manage object lifecycle](#). For the complete code of lifecycle management, see [GitHub](#).

Configure lifecycle rules

Run the following code to configure lifecycle rules:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Model\LifecycleConfig;
use OSS\Model\LifecycleRule;
use OSS\Model\LifecycleAction;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

// Configure the rule ID and object name prefix.
$ruleId0 = "rule0";
$matchPrefix0 = "A0/";
$ruleId1 = "rule1";
$matchPrefix1 = "A1/";

$lifecycleConfig = new LifecycleConfig();
$actions = array();
// Set the expiration duration to 3 days after last modified date.
```

```

$actions[] = new LifecycleAction(OssClient::OSS_LIFECYCLE_EXPIRATION,
OssClient::OSS_LIFECYCLE_TIMING_DAYS, 3);
$lifecycleRule = new LifecycleRule($ruleId0, $matchPrefix0, "Enabled",
    $actions);
$lifecycleConfig->addRule($lifecycleRule);
$actions = array();
// Configure expiration date to delete objects that are created before
the date.
$actions[] = new LifecycleAction(OssClient::OSS_LIFECYCLE_EXPIRATION,
OssClient::OSS_LIFECYCLE_TIMING_DATE, '2022-10-12T00:00:00.000Z');
$lifecycleRule = new LifecycleRule($ruleId1, $matchPrefix1, "Enabled",
    $actions);
$lifecycleConfig->addRule($lifecycleRule);
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $ossClient->putBucketLifecycle($bucket, $lifecycleConfig);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

View lifecycle rules

Run the following code to view lifecycle rules:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";

$lifecycleConfig = null;
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $lifecycleConfig = $ossClient->getBucketLifecycle($bucket);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
}

```

```

        return;
    }
    print(__FUNCTION__ . ": OK" . "\n");
    print($lifecycleConfig->serializeToXml() . "\n");

```

Clear lifecycle rules

Run the following code to clear lifecycle rules:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->deleteBucketLifecycle($bucket);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.12 Set logging

You can enable access logs to record bucket access to log files, which are stored in a specified bucket.

The log file format is as follows:

```
<TargetPrefix><SourceBucket>-YYYY-mm-DD-HH-MM-SS-UniqueString
```

For more information about access log files, see [Set access logging](#). For the complete code of access logging, see [GitHub](#).

Enable access logging

Run the following code to enable bucket access logging:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";

$options = array();
// Configure the bucket that stores log files.
$targetBucket = "<yourBucketName>";
$targetPrefix = "access.log";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    // Enable access logging.
    $ossClient->putBucketLogging($bucket, $targetBucket, $targetPrefix
    , $options);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

View access logging configurations

Run the following code to view the access logging configurations for a bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
```

```
// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

$loggingConfig = null;
$options = array();
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    // View access log configurations.
    $loggingConfig = $ossClient->getBucketLogging($bucket, $options);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
print($loggingConfig->serializeToXml() . "\n");
```

Disable access logging

Run the following code to disable access logging for a bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    // Disable access logging.
    $ossClient->deleteBucketLogging($bucket);
```

```

} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.13 CORS

Cross-origin resource sharing (CORS) allows web applications to access resources that belong to another region. OSS provides CORS APIs for convenient cross-origin access control.

For more information, see [Cross-origin resource sharing](#) in OSS Developer Guide. For the complete code of CORS, see [GitHub](#).

Configure CORS rules

Run the following code to configure CORS rules for the specified bucket:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Model\CorsConfig;
use OSS\Model\CorsRule;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

$corsConfig = new CorsConfig();
$rule = new CorsRule();
// AllowedHeaders and ExposeHeaders do not allow wildcards.
$rule->addAllowedHeader("x-oss-header");
// AllowedMethods allows only one wildcard asterisk (*).
// Wildcard asterisks (*) indicate that all sources of the cross-origin
// requests and operations are allowed.
$rule->addAllowedOrigin("http://www.b.com");
$rule->addAllowedMethod("POST");
$rule->setMaxAgeSeconds(10);
// A maximum of 10 rules are allowed for each bucket.
$corsConfig->addRule($rule);

try{

```

```

    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    // The existing rules will be replaced.
    $ossClient->putBucketCors($bucket, $corsConfig);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

Obtain CORS rules

Run the following code to obtain CORS rules:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
account because the account has permissions on all the APIs in OSS.
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";

$corsConfig = null;
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $corsConfig = $ossClient->getBucketCors($bucket);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
print($corsConfig->serializeToXml() . "\n");

```

Delete CORS rules

Run the following code to delete all CORS rules for a specified bucket:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}

```



```

}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->deleteBucketCors($bucket);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

4.14 Anti-leech

To prevent your data on OSS from being leeches, OSS supports anti-leeching through the referer field settings in the HTTP header, including the following parameters:

- Referrer whitelist: Used to allow access only for specified domains to OSS data.
- Empty referer: Determines whether the referer can be empty. If it is not allowed, only requests with the referer filed in their HTTP or HTTPS headers can access OSS data.

For more information about anti-leeching, see [Anti-leeching settings](#). For the complete code of anti-leech, see [GitHub](#).

Configure the referer whitelist

Run the following code to configure the referer whitelist:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

```

```

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Model\RefererConfig;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

$refererConfig = new RefererConfig();
// Allow empty referers.
$refererConfig->setAllowEmptyReferer(true);
// Add the referer field. The referer field allows question marks (?)
// and asterisks (*) for wildcard use.
$refererConfig->addReferer("www.aliyun.com");
$refererConfig->addReferer("www.aliyuncs.com");
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    $ossClient->putBucketReferer($bucket, $refererConfig);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");

```

Obtain a referer whitelist

Run the following code to obtain a referer whitelist:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Model\RefererConfig;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";

```

```

$bucket= "<yourBucketName>";

$refererConfig = null;
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    $refererConfig = $ossClient->getBucketReferer($bucket);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
print($refererConfig->serializeToXml() . "\n");

```

Clear a referer whitelist

Run the following code to clear a referer whitelist:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;
use OSS\Model\RefererConfig;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China (Hangzhou). Specify the actual
// endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";

$refererConfig = new RefererConfig();
try{
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    // You cannot clear a referer whitelist directly. To clear a referer
    // whitelist, you need to create the rule that allows an empty referer
    // field and replace the original rule with the new rule.
    $ossClient->putBucketReferer($bucket, $refererConfig);
} catch(OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}

```

```
print(__FUNCTION__ . ": OK" . "\n");
```

4.15 Bind a custom domain name

You can bind a custom domain name to your OSS bucket and by adding a CNAME record in the Domain Name System (DNS). After you bind a custom domain name to a bucket, you can access the bucket with your own domain name. For example, if your domain name is "my-domain.com" and all your images were previously located at `http://img.my-domain.com/x.jpg`, after you migrate the image data to OSS, you can still access the images with the original IP address by binding a custom domain name to the bucket.

For more information, see [Bind a custom domain name](#) in the OSS Developer Guide.

Add a CNAME record

Run the following code to add a CNAME record for a bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    Quire_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

// Configure the custom domain name.
$myDomain = '<yourDomainName>';
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    // Add a CNAME record.
    $ossClient->addBucketCname($bucket, $myDomain);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
```

```
print(__FUNCTION__ . ": OK" . "\n");
```

View CNAME records

Run the following code to obtain CNAME records added to the bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on to
// https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";

try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
    endpoint);

    // View CNAME records.
    $cnameConfig = $ossClient->getBucketCname($bucket);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
var_dump($cnameConfig);
print(__FUNCTION__ . ": OK" . "\n");
```

Delete a CNAME record

Run the following code to delete a CNAME record added to a bucket:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;
use OSS\Core\OssException;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
```

```
We recommend that you log on as a RAM user to access APIs or perform
routine operations and maintenance. To create a RAM account, log on to
https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket= "<yourBucketName>";

// Configure the custom domain name.
$myDomain = '<yourDomainName>';
try {
    $ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

    // Delete a CNAME record.
    $ossClient->deleteBucketCname($bucket, $myDomain);
} catch (OssException $e) {
    printf(__FUNCTION__ . ": FAILED\n");
    printf($e->getMessage() . "\n");
    return;
}
print(__FUNCTION__ . ": OK" . "\n");
```

4.16 Image processing

Image Processing (IMG) is a massive, secure, cost-effective and highly reliable image processing service. After source images are uploaded to OSS, you can process images on any Internet device at any anytime, from anywhere through simple RESTful APIs.

For more information about IMG, see [Image Processing](#). For the complete code of image processing, see [GitHub](#).

Basic features

OSS offers the following IMG features:

- [Retrieve dominant image tones](#)
- [Format conversion](#)
- [Resize images](#)
- [Incircle](#)
- [Adaptive orientation](#)
- [Brightness](#)
- [Add watermarks](#): allows you to add images, texts, or image-text watermarks to another image.
- [Image processing](#)
- [Image processing access rules](#): calls multiple IMG functions.

Usage

IMG uses standard HTTP GET. You can configure IMG parameters in QueryString of a URL.

If the ACL of an image object is private read and write, only authorized users are allowed for access.

- Anonymous access

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction>,<yourParamValue>
```

Parameter	Description
bucket	Specifies the name of a bucket.
endpoint	Specifies endpoint used to access a region.
object	Specifies the name of an image object.
image	Specifies the reserved identifier for IMG.
action	Specifies the operations on an image, such as scaling, cropping, and rotating.
param	Specifies the parameter that indicates the operation on an image.

— Basic operations

For example, scale an image to a width of 100 PX. Adjust the height based on the ratio.

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

— Customized image styles

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=style/<yourStyleName>
```

- style: specifies a reserved identifier of a customized image style.
- yourStyleName: specifies the name of a custom image style. It is the name specified in the rule that is created on the OSS console.

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=style/oss-pic-style-w-100
```

— Cascade operations

Cascade operations allow you to perform multiple operations on an image sequentially.

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction1>,<yourParamValue1>/<yourAction2>,<yourParamValue2>/...
```

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100/rotate,90
```

— HTTPS access

IMG supports access through HTTPS. Example:

```
https://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

- Authorized access

Authorized access allows you to customize an image style, HTTPS access, and cascade operations.

Run the following code to generate a signed URL for IMG:

```
<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba Cloud
// account because the account has permissions on all the APIs in OSS.
// We recommend that you log on as a RAM user to access APIs or perform
// routine operations and maintenance. To create a RAM account, log on
// to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
// actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
```



```

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $endpoint
);

// Generate a signed URL that is valid for 3600 seconds and can be
directly accessed by browsers.
$timeout = 3600;
$options = array(
    OssClient::OSS_PROCESS => "image/resize,m_lfit,h_100,w_100" );
$signedUrl = $ossClient->signUrl($bucket, $object, $timeout, "GET",
    $options);

print("rtmp url: \n" . $signedUrl);

```

- Access with SDK

You can use SDK to access and process an image object.

SDK allows you to customize image styles, HTTPS access, and cascade operations.

— Basic operations

Run the following code to perform basic operations on an image:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba
Cloud account because the account has permissions on all APIs in
OSS. We recommend that you log on as a RAM user to access APIs
or perform routine operations and maintenance. To create a RAM
account, log on to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$download_file = "download.jpg";

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

// Upload a sample image.
$ossClient->uploadFile($bucket, $object, "example.jpg");

// Scale the image.
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => "image/resize,m_fixed,h_100,w_100
" );
$ossClient->getObject($bucket, $object, $options);

```

```

// Crop the image.
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => "image/crop,w_100,h_100,x_100,y_100,
r_1" );
$ossClient->getObject($bucket, $object, $options);

// Rotate the image.
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => "image/rotate,90" );
$ossClient->getObject($bucket, $object, $options);

// Sharpen the image.
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => "image/sharpen,100" );
$ossClient->getObject($bucket, $object, $options);

// Add watermarks.
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => "image/watermark,text_SGVsbG8g5Zu-
54mH5pyN5YqhIQ" );
$ossClient->getObject($bucket, $object, $options);

// Convert the image format.
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => "image/format,png" );
$ossClient->getObject($bucket, $object, $options);

// Obtain image information.
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => "image/info" );
$ossClient->getObject($bucket, $object, $options);

// Delete the sample image.
$ossClient->deleteObject($bucket, $object);

```

— Customize an image style

Run the following code to customize an image style:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba
Cloud account because the account has permissions on all APIs in
OSS. We recommend that you log on as a RAM user to access APIs
or perform routine operations and maintenance. To create a RAM
account, log on to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";

```

```

$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
  actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$download_file = "download.jpg";

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint);

// Upload a sample image.
$ossClient->uploadFile($bucket, $object, "example.jpg");

// Customize an image style
$style = "style/oss-pic-style-w-300";
$options = array(
    OssClient::OSS_FILE_DOWNLOAD => $download_file,
    OssClient::OSS_PROCESS => $style);
$ossClient->getObject($bucket, $object, $options);

// Delete the sample image.
$ossClient->deleteObject($bucket, $object);

```

— Cascade operations

Use the following code to perform cascade operations on an image:

```

<? php
if (is_file(__DIR__ . '/../autoload.php')) {
    require_once __DIR__ . '/../autoload.php';
}
if (is_file(__DIR__ . '/../vendor/autoload.php')) {
    require_once __DIR__ . '/../vendor/autoload.php';
}

use OSS\OssClient;

// It is highly risky to log on with AccessKey of an Alibaba
Cloud account because the account has permissions on all APIs in
OSS. We recommend that you log on as a RAM user to access APIs
or perform routine operations and maintenance. To create a RAM
account, log on to https://ram.console.aliyun.com.
$accessKeyId = "<yourAccessKeyId>";
$accessKeySecret = "<yourAccessKeySecret>";
// This example uses endpoint China East 1 (Hangzhou). Specify the
  actual endpoint based on your requirements.
$endpoint = "http://oss-cn-hangzhou.aliyuncs.com";
$bucket = "<yourBucketName>";
$object = "<yourObjectName>";
$download_file = "download.jpg";

$ossClient = new OssClient($accessKeyId, $accessKeySecret, $
endpoint, false);

// Upload a sample image.
$ossClient->uploadFile($bucket, $object, "example.jpg");

// Perform cascade operations.
$style = "image/resize,m_fixed,w_100,h_100/rotate,90";
$options = array(

```

```
OssClient::OSS_FILE_DOWNLOAD => $download_file,  
OssClient::OSS_PROCESS => $style);  
$ossClient->getObject($bucket, $object, $options);  
  
// Delete the sample image.  
$ossClient->deleteObject($bucket, $object);
```

IMG tools

You can use the IMG viewer [ImageStyleViewer](#) to directly view the IMG result.

4.17 Exception handling

OSS PHP SDK exceptions (OssException) include various errors, such as invalid parameters and file missing. You can use the getMessage method to obtain error messages.

For more information about OssException, see [GitHub](#).

Example for handling exceptions

The following code shows how to handle exceptions when creating a existing bucket and prints error messages.

```
try {  
    $ossClient->createBucket($bucket);  
} catch (OssException $e) {  
    print("Exception:" . $e->getMessage() . "\n");  
}
```

You can also obtain the following information:

Parameter	Description
HTTPStatus	HTTP status code. You can get the status code using the getHTTPStatus method.
ErrorCode	Specifies the error code returned by OSS. You can get the error code using the getErrorCode method.
ErrorMessage	Specifies the error messages returned by OSS . You can get the error messages using the getErrorMessage method.
RequestId	Specifies the UUID. It is unique and used to identify a request. If a problem persists, send the RequestId to OSS developers for help. You can get the RequestId using the getRequestId method.

Parameter	Description
Details	Specifies detailed error messages returned by OSS. You can get the detailed error messages using the getDetails method.

Common OSS error codes

Error code	Description	HTTP status code
AccessDenied	Access denied	403
BucketAlreadyExists	The bucket already exists.	409
BucketNotEmpty	The bucket is not empty.	409
EntityTooLarge	The entity size exceeds the maximum limit.	400
EntityTooSmall	The entity size is below the minimum limit.	400
FileGroupTooLarge	The total file group size exceeds the maximum limit.	400
FilePartNotExist	No such part exists.	400
FilePartStale	The part has expired.	400
InvalidArgument	The parameter format is invalid.	400
InvalidAccessKeyId	No such AccessKeyId exists.	403
InvalidBucketName	The bucket name is invalid.	400
InvalidDigest	The digest is invalid.	400
InvalidObjectName	The object name is invalid.	400
InvalidPart	The part is invalid.	400
InvalidPartOrder	The part order is invalid.	400
InvalidTargetBucketForLogging	The buckets that store log files are invalid.	400
InternalError	Internal OSS error	500
MalformedXML	The XML format is invalid.	400
MethodNotAllowed	The method is not allowed.	405
MissingArgument	Parameters are not configured.	411

Error code	Description	HTTP status code
MissingContentLength	The content length is not configured.	411
NoSuchBucket	No such bucket exists.	404
NoSuchKey	No such object exists.	404
NoSuchUpload	No such uploadId exists.	404
NotImplemented	The methods are not implemented.	501
PreconditionFailed	Precondition error	412
RequestTimeTooSkewed	The local time set for OSSClient is deviated from the time set for the OSS server by over 15 minutes.	403
RequestTimeout	Request timeout	400
SignatureDoesNotMatch	Signature mismatch	403
InvalidEncryptionAlgorithmError	The specified encryption algorithm (the entropy encoding type) is invalid.	400

5 Go

5.1 Preface

This topic describes how to use code samples.

SDK source code and API documents

For the source code of OSS Go SDK, see [GitHub](#). For more information, see [OSS Go SDK API documents](#).

Code samples

OSS Go SDK provides a variety of code samples for your reference or use. The following table describes the content of code samples:

Sample file	Content
new_bucket.go	Initialize the client
put_object.go	Upload objects, including simple upload and resumable upload .
append_object.go	Append upload
get_object.go	Download objects, including streaming download , conditional download , download object into compressed objects
delete_object.go	Delete objects
copy_object.go	Copy objects within a bucket , Copy objects across buckets and conditional copy
list_objects.go	List objects , including listing objects with a specified prefix and list a specified number of objects.
object_meta.go	Configure and read Object Meta
object_acl.go	Set and read ACL for an object
sign_url.go	Generate a signed URL
cname_sample.go	Bind custom domain (CNAME)
create_bucket.go	Create a bucket
list_buckets.go	List buckets with default or specified parameters
bucket_acl.go	Set ACL for buckets

Sample file	Content
bucket_referer.go	Configure, view, and delete the anti-leech settings of a bucket
bucket_logging.go	Configure, view, and delete the access logs of a bucket
bucket_lifecycle.go	Configure, view, and delete the lifecycle settings of a bucket
bucket_cors.go	Configure, view, and delete the CORS settings of a bucket

5.2 Installation

Preparation

- Environment requirements

You must use Golang 1.6 and later versions.

Refer to [Installing Go from source](#) to download and install the compiling and running environment of Go. After Go is installed, set the GOPATH to the path of your code. For more information about GOPATH, run `go help gopath`.

- Check the version of Go

Run `go version` to check the version of Go.

Download SDK

- [Download from GitHub](#)
- [Download previous versions](#)

Install SDK

Run the following command to install OSS Go SDK:

```
go get github.com/aliyun/aliyun-oss-go-sdk/oss
```



Note:

No messages are printed to the interface during installation. Please wait. In case of installation time-out, run the command again.

Check SDK version

Run the following code to check the version of OSS Go SDK:

```
package main

import (
    "fmt"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    fmt.Println("OSS Go SDK Version: ", oss.Version)
}
```

5.3 Quick start

This topic describes how to use OSS Go SDK to perform routine operations such as bucket creation, object uploads, and object downloads.

Create a bucket

Run the following code to create a bucket:

```
package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func handleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
func main() {
    // This example uses endpoint China (Hangzhou). Specify the actual
    // endpoint based on your requirements.
    endpoint := "http://oss-cn-hangzhou.aliyuncs.com"
    // It is highly risky to log on with AccessKey of an Alibaba Cloud
    // account because the account has permissions on all the APIs in OSS.
    // We recommend that you log on as a RAM user to access APIs or perform
    // routine operations and maintenance. To create a RAM account, log on to
    // https://ram.console.aliyun.com.
    accessKeyId := "<yourAccessKeyId>"
    accessKeySecret := "<yourAccessKeySecret>"
    bucketName := "<yourBucketName>"
    // Create an OSSClient instance.
    client, err := oss.New(endpoint, accessKeyId, accessKeySecret)
    if err != nil {
        handleError(err)
    }
    // Create a bucket.
    err = client.CreateBucket(bucketName)
    if err != nil {
        handleError(err)
    }
}
```

```
}
```

Upload objects

Run the following code to upload a file to OSS:

```
package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func handleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
func main() {
    // This example uses endpoint China (Hangzhou). Specify the actual
    // endpoint based on your requirements.
    endpoint := "http://oss-cn-hangzhou.aliyuncs.com"
    // It is highly risky to log on with AccessKey of an Alibaba Cloud
    // account because the account has permissions on all the APIs in OSS.
    // We recommend that you log on as a RAM user to access APIs or perform
    // routine operations and maintenance. To create a RAM account, log on to
    // https://ram.console.aliyun.com.
    accessKeyId := "<yourAccessKeyId>"
    accessKeySecret := "<yourAccessKeySecret>"
    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localFileName := "<yourLocalFileName>"
    // Create an OSSClient instance.
    client, err := oss.New(endpoint, accessKeyId, accessKeySecret)
    if err != nil {
        handleError(err)
    }
    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        handleError(err)
    }
    // Upload a file.
    err = bucket.PutObjectFromFile(objectName, localFileName)
    if err != nil {
        handleError(err)
    }
}
```

Download objects

Run the following code to download an object to local:

```
package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func handleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

```

}
func main() {
    // This example uses endpoint China (Hangzhou). Specify the actual
    // endpoint based on your requirements.
    endpoint := "http://oss-cn-hangzhou.aliyuncs.com"
    // It is highly risky to log on with AccessKey of an Alibaba Cloud
    // account because the account has permissions on all the APIs in OSS.
    // We recommend that you log on as a RAM user to access APIs or perform
    // routine operations and maintenance. To create a RAM account, log on to
    // https://ram.console.aliyun.com.
    accessKeyId := "<yourAccessKeyId>"
    accessKeySecret := "<yourAccessKeySecret>"
    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    downloadedFileName := "<yourDownloadedFileName>"
    // Create an OSSClient instance.
    client, err := oss.New(endpoint, accessKeyId, accessKeySecret)
    if err != nil {
        handleError(err)
    }
    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        handleError(err)
    }
    // Download the object.
    err = bucket.GetObjectToFile(objectName, downloadedFileName)
    if err != nil {
        handleError(err)
    }
}
}

```

List objects

Run the following code to list objects in a specified bucket. You can list a maximum of 100 objects by default.

```

package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }
    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }
}

```

```

// List objects.
marker := ""
for {
    lsRes, err := bucket.ListObjects(oss.Marker(marker))
    if err != nil {
        HandleError(err)
    }
    // Print the listed objects. A maximum of 100 objects are
    listed by default.
    for _, object := range lsRes.Objects {
        fmt.Println("Bucket: ", object.Key)
    }
    if lsRes.IsTruncated {
        marker = lsRes.NextMarker
    } else {
        break
    }
}
}

```

Delete objects

Run the following code to delete a specified object:

```

package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func handleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
func main() {
    // This example uses endpoint China (Hangzhou). Specify the actual
    endpoint based on your requirements.
    endpoint := "http://oss-cn-hangzhou.aliyuncs.com"
    // It is highly risky to log on with AccessKey of an Alibaba Cloud
    account because the account has permissions on all the APIs in OSS.
    We recommend that you log on as a RAM user to access APIs or perform
    routine operations and maintenance. To create a RAM account, log on to
    https://ram.console.aliyun.com.
    accessKeyId := "<yourAccessKeyId>"
    accessKeySecret := "<yourAccessKeySecret>"
    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    // Create an OSSClient instance.
    client, err := oss.New(endpoint, accessKeyId, accessKeySecret)
    if err != nil {
        handleError(err)
    }
    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        handleError(err)
    }
    // Delete the object.
    err = bucket.DeleteObject(objectName)
    if err != nil {
        handleError(err)
    }
}

```

```
}  
}
```

5.4 Initialization

OSSClient serves as the OSS Java client to manage OSS resources such as buckets and objects.

To create an OSSClient instance, you need to specify an endpoint. For more information about endpoints, see [Regions and endpoints](#) and [Bind a custom domain name](#).

The following table describes the parameters that you can configure:

Parameter	Description	Default value
UseCname	Specifies whether the CNAME is used.	No
Timeout	Specifies the request timeout time in seconds, including the connection timeout and socket read-write timeout.	30 seconds for the connection timeout and 60 seconds for the read-write timeout
SecurityToken	Specifies the securitytoken for temporary users	Null
EnableMD5	Specifies whether the MD5 verification is enabled. CRC verification is recommended because it is more efficient than MD5 verification.	No
EnableCRC	Specifies whether CRC verification is enabled.	Yes
Proxy	Specifies the proxy server, such as http: // 8.8.8.8 : 3128	Null
AuthProxy	Specifies a proxy server that requires an account and a password to login.	Null

Use an OSS domain to create an OSSClient instance

Run the following code to create an OSSClient instance with a domain assigned by OSS:

```
import "github.com/aliyun/aliyun-oss-go-sdk/oss"  
  
client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<  
yourAccessKeySecret>")  
if err != nil {
```

```
fmt.Println("Error:", err)
os.Exit(-1)
}
```

Use a custom domain (CNAME) to create an OSSClient instance

For the complete code of custom domain, see [GitHub](#).

Run the following code to create an OSSClient instance with CNAME:

```
import "github.com/aliyun/aliyun-oss-go-sdk/oss"

// oss.UseCname (true) indicates that the CNAME is enabled. CNAME
// indicates a custom domain bound to a bucket.
client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>", oss.UseCname(true))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```



Note:

If the CNAME is enabled, you cannot list buckets because the CNAME is bound to a certain bucket.

Use STS to create an OSSClient instance

Run the following code to create an OSSClient instance with Security Token Service (STS):

```
import "github.com/aliyun/aliyun-oss-go-sdk/oss"

client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>", oss.SecurityToken("<yourSecurityToken>"))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

For more information, see [What is RAM and STS](#) and [Authorized access](#).

Set timeout

Run the following code to set connection timeout:

```
import "github.com/aliyun/aliyun-oss-go-sdk/oss"

// oss.Timeout(10, 120) indicates that the HTTP connection timeout
// is set to 10 seconds (the default value is 30 seconds) and the HTTP
// read-write timeout is set to 120 seconds (the default value is 60
// seconds). The value 0 indicates that timeout never occurs, which is
// not recommend.
client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>", oss.Timeout(10, 120))
if err != nil {
    fmt.Println("Error:", err)
}
```

```
    os.Exit(-1)
}
```

CRC verification

CRC verification is enabled by default during uploads and downloads to ensure data integrity. Run the following code to disable CRC verification:



Warning:

We recommended that you do not disable CRC verification. If you disable CRC verification, the data integrity during uploads and downloads is not guaranteed.

```
import "github.com/aliyun/aliyun-oss-go-sdk/oss"

client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>", oss.EnableCRC(false))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

5.5 Bucket

A bucket serves as a container that stores objects. Objects belong to a bucket.

Create a bucket

For the complete code of creating a bucket, see [GitHub](#).

Run the following code to create a bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Create a bucket. The default storage class and ACL of the created bucket are set to standard and private read respectively.
    err = client.CreateBucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

```
}
}
```

For more information about bucket naming rules, see naming conventions in [Basic concepts](#). You can specify the ACL and the storage class when you create a bucket, as shown in [Bucket-level permissions](#) and [Storage class](#).

You can run the following code to create a bucket with specified permission:

```
// Create a bucket and set the bucket ACL to public read (which is
private by default).
err = client.CreateBucket("<yourBucketName>", oss.ACL(oss.ACLPublicR
ead))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

You can run the following code to creates a bucket of the archive class:

```
err = client.CreateBucket("<yourBucketName>", oss.StorageClass(oss.
StorageArchive))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

You can run the followign code to create a bucket of the Infrequent Access class:

```
err = client.CreateBucket("<yourBucketName>", oss.StorageClass(oss.
StorageIA))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

List buckets

For the complete code of listing buckets, see [GitHub](#).

- List all buckets

Buckets are displayed in alphabetical order. You can list all buckets or specify a bucket that meets certain conditions.

Run the following code to list all buckets:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
```



```

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // List all buckets.
    marker := ""
    for {
        lsRes, err := client.ListBuckets(oss.Marker(marker))
        if err != nil {
            fmt.Println("Error:", err)
            os.Exit(-1)
        }

        // 100 buckets are listed by default.
        for _, bucket := range lsRes.Buckets {
            fmt.Println("Bucket: ", bucket.Name)
        }

        if lsRes.IsTruncated {
            marker = lsRes.NextMarker
        } else {
            break
        }
    }
}

```

- List buckets with a specified prefix

Run the following code to list buckets with a specified prefix:

```

// List buckets by a specified prefix.
lsRes, err = client.ListBuckets(oss.Prefix("<yourBucketPrefix
>"))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
// Print the bucket list.
fmt.Println("Buckets with prefix: ", lsRes.Buckets)
for _, bucket := range lsRes.Buckets {
    fmt.Println("Bucket with prefix: ", bucket.Name)
}

```

- List buckets by marker

The value of the marker parameter indicates the name of a bucket. Run the following code to list buckets after the specified bucket (the value of marker):

```

// List buckets after the specified marker.
lsRes, err = client.ListBuckets(oss.Marker("<yourBucketMarker>"))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

```

```
// Print the bucket list.
fmt.Println("My buckets with marker :", lsRes.Buckets)
for _, bucket := range lsRes.Buckets {
    fmt.Println("Bucket with marker: ", bucket.Name)
}
```

- List a specified number of buckets

Run the following code to list a specified number (maxKeys) of buckets:

```
// Set the number of buckets that can be listed to 500. The default
value is 100. The maximum value is 1,000.
lsRes, err = client.ListBuckets(oss.MaxKeys(500))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Print the bucket list.
fmt.Println("My buckets max num:", lsRes.Buckets)
for _, bucket := range lsRes.Buckets {
    fmt.Println("Bucket with maxKeys: ", bucket.Name)
}
```

Determine whether a bucket exists

Run the following code to determine whether a specified bucket exists:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Determine whether a bucket exists.
    isExist, err := client.IsBucketExist("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("IsBucketExist result : ", isExist)
}
```

Configure an ACL for a bucket

The ACL of a bucket includes the following permissions.

Permission	Description	Value
Private	The bucket owner and the authorized users can read and write objects in the bucket. Other users cannot perform any operation on the objects.	oss.ACLPrivate
Public read	The bucket owner and the authorized users can read and write objects in the bucket. Other users can only read the objects in the bucket. Authorize this permission with caution.	oss.ACLPublicRead
Public read-write	All users can read and write objects in the bucket. Authorize this permission with caution.	oss.ACLPublicReadWrite

For more information about ACL, see [access control](#) in the developer guide. For the complete code of configure ACL for a bucket, see [GitHub](#).

Use the following code to configure the ACL for a bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Set the ACL for the bucket to public read.
    err = client.SetBucketACL("<yourBucketName>", oss.ACLPublicRead)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

```
}
```

Obtain the ACL for a bucket

Use the following code to obtain the ACL for a bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the ACL for the bucket
    aclRes, err := client.GetBucketACL("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Bucket ACL:", aclRes.ACL)
}
```

Obtain the region of a bucket

Run the following code to obtain the region (or location) of a bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the region of the bucket:
    loc, err := client.GetBucketLocation("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Bucket Location:", loc)
}
```

```
}
```

Obtain bucket information

Use the following code to obtain bucket information:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Bucket information includes regions (region or location), creation
    // dates (CreationDate), permissions (ACL), owners (Owner), and storage
    // class (StorageClass).
    res, err := client.GetBucketInfo("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("BucketInfo.Location: ", res.BucketInfo.Location)
    fmt.Println("BucketInfo.CreationDate: ", res.BucketInfo.CreationDate)
    fmt.Println("BucketInfo.ACL: ", res.BucketInfo.ACL)
    fmt.Println("BucketInfo.Owner: ", res.BucketInfo.Owner)
    fmt.Println("BucketInfo.StorageClass: ", res.BucketInfo.StorageClass)
    fmt.Println("BucketInfo.ExtranetEndpoint: ", res.BucketInfo.ExtranetEndpoint)
    fmt.Println("BucketInfo.IntranetEndpoint: ", res.BucketInfo.IntranetEndpoint)
}
```

Delete a bucket

Before a bucket is deleted, ensure that all objects in the bucket, and fragments that are generated from multipart upload are deleted.



Note:

To delete the fragments that are generated from multipart upload, use `Bucket.ListMultipartUploads` to list all fragments, and then use `Bucket.AbortMultipartUpload` to delete the fragments. For more information, see [Multipart upload](#).

Run the following code to delete a bucket:

```
package main
```

```
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Delete the bucket.
    err = client.DeleteBucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

5.6 Upload objects

5.6.1 Overview

In OSS, an object is the basic unit for data operations. OSS Go SDK provides the following file upload methods:

- [Simple upload](#): supports the upload of a file up to 5 GB in size.
- [Append upload](#): supports the upload of a file up to 5 GB in size.
- [Resumable upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files. It supports concurrent upload and you can define the size of each part.
- [Multipart upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files.



Note:

For more information about the usage scenarios of each upload method, see “Upload files” in OSS Developer Guide.

During the file upload, you can set [Object Meta](#), and view the upload progress in the [upload progress bar](#).

5.6.2 Simple upload

For the complete code of simple upload, see [GitHub](#).

Upload a string

You can run the following code to upload a string:

```
package main

import (
    "fmt"
    "os"
    "strings"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Upload a string.
    err = bucket.PutObject("<yourObjectName>", strings.NewReader("yourObjectValue"))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

Upload a byte array

You can run the following code to upload a byte array:

```
package main

import (
    "fmt"
    "os"
    "bytes"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

```
// Obtain the bucket.
bucket, err := client.Bucket("<yourBucketName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Upload a byte array.
err = bucket.PutObject("<yourObjectName>", bytes.NewReader([]byte("
yourObjectValueByteArray")))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
}
```

Upload a file stream

You can run the following code to upload a file stream:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Read the local file.
    fd, err := os.Open("<yourLocalFile>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    defer fd.Close()

    // Upload a file stream.
    err = bucket.PutObject("<yourObjectName>", fd)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```



```
}
```

Upload a local file

You can run the following code to upload a local file:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Upload a local file.
    err = bucket.PutObjectFromFile("<yourObjectName>", "<yourLocalFile>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

5.6.3 Append upload

You cannot perform copyObject for appended objects. When you call the AppendObject, if the target object does not exist, a new appendable object is created. If the target object exists, the uploaded content is appended to the end of the object.

Run the following code to upload a file with append upload:

```
package main

import (
    "fmt"
    "os"
    "strings"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
```

```

client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Obtain the bucket.
bucket, err := client.Bucket("<yourBucketName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

var nextPos int64 = 0
// If the object is appended for the first time, the append position
is 0, and the returned value is the position for the next append. The
position for the next append is the current length of the object.
nextPos, err = bucket.AppendObject("<yourObjectName>", strings.
.NewReader("YourObjectAppendValue1"), nextPos)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Start the second append.
nextPos, err = bucket.AppendObject("<yourObjectName>", strings.
.NewReader("YourObjectAppendValue2"), nextPos)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// You can append content to an object for multiple times.
}

```

You can specify the Object Meta only when you append an object for the first time (that is, the append position is 0).

```

// Specify the Object Meta in the first append upload.
nextPos, err = bucket.AppendObject("<yourObjectName>", strings.
.NewReader("YourObjectValue"), 0, oss.Meta("MyProp", "MyPropVal"))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

```

5.6.4 Resumable upload

You can use resumable upload to split a file you want to upload into several parts and upload them simultaneously. After you have uploaded all parts, you can combine these parts into a complete object. Thus, you can complete uploading the entire object.

Current upload progress is recorded into a checkpoint file during the upload. If a part fails to be uploaded during the process, the object is uploaded from the part recorded in the checkpoint

file when the upload restarts, that is, the resumable upload. After the upload is complete, the checkpoint is deleted.

**Note:**

- The SDK records the upload progress information in the checkpoint file. Therefore, you must ensure that the program has the write permission to the checkpoint file. Do not modify the checkpoint file because it includes verification information. If the checkpoint file is corrupted, all parts will be upload again.
- If the local file is changed during file upload, all the parts will be uploaded again.

You can use `Bucket.UploadFile` to achieve resumable upload. You can configure the following parameters.

Parameter	Description
objectKey	Specifies the name of the object uploaded to OSS.
filePath	Specifies the path of the local file.
partSize	Specifies the upload part size, ranging from 100 KB to 5 GB.
options	Specifies the options, including: • Routines: Specifies the number of parts that are uploaded at the same time. The default value is 1, which means that parts are not uploaded concurrently. • Checkpoint: Specifies whether the resumable upload is enabled and configures the checkpoint file. Resumable upload is disabled by default. For example, <code>oss.Checkpoint(true, "")</code> indicates that the resumable upload is enabled, and the checkpoint file is the <code>file.cp</code> stored in the directory that the local file needs to be uploaded is stored. The <code>file</code> is the name of the local file. You can also use <code>oss.Checkpoint(true, "your-cp-file.cp")</code> to specify the checkpoint file. • Other metadata information: See Manage Object Meta.

Run the following code for resumable upload:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // The part size is 100 KB. Parts are uploaded through three
    // goroutines concurrently. The resumable upload is enabled.
    // <yourObjectName> is the objectKey, "LocalFile" is the filePath,
    // and 100*1024 is the partSize.
    err = bucket.UploadFile("<yourObjectName>", "LocalFile", 100*1024,
        oss.Routines(3), oss.Checkpoint(true, ""))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

5.6.5 Multipart upload

1. Initiate a multipart upload event.

You can call `Bucket.InitiateMultipartUpload` to return the globally unique uploadId created in OSS.

2. Upload parts.

You can call `Bucket.UploadPart` to upload part data.



Note:

- For parts with a same uploadId, parts are sequenced by their part numbers. If you have uploaded a part and use the same part number to upload another part, the later part will replace the former part.

- OSS places the MD5 value of part data in ETag and returns the MD5 value to the user.
- SDK automatically configures Content-MD5. OSS calculates the MD5 value of uploaded data and compares it with the MDS value calculated by SDK. If the two values vary, the error code of InvalidDigest is returned.

3. Complete multipart upload.

After you have uploaded all parts, call `Bucket.CompleteMultipartUpload` to combine these parts into a complete object.

The following code is used as a complete example that describes the process of multipart upload:

```
package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localFilename := "<yourLocalFilename>"
    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    chunks, err := oss.SplitFileByPartNum(localFilename, 3)
    fd, err := os.Open(localFilename)
    defer fd.Close()
    // Step 1: Initiate a multipart upload event.
    imur, err := bucket.InitiateMultipartUpload(objectName)
    // Step 2: Upload parts.
    var parts []oss.UploadPart
    for _, chunk := range chunks {
        fd.Seek(chunk.Offset, os.SEEK_SET)
        // Call UploadPart to upload each part.
        part, err := bucket.UploadPart(imur, fd, chunk.Size, chunk.
Number)
        if err != nil {
            fmt.Println("Error:", err)
            os.Exit(-1)
        }
        parts = append(parts, part)
    }
    // Step 3: Complete multipart upload.
    cmur, err := bucket.CompleteMultipartUpload(imur, parts)
    if err != nil {
        fmt.Println("Error:", err)
    }
}
```

```

        os.Exit(-1)
    }
    fmt.Println("cmur:", cmur)
}

```

Cancel a multipart upload event

Run the following code to cancel a multipart upload event:

```

package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Initiate a multipart upload event.
    imur, err := bucket.InitiateMultipartUpload("<yourObjectName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Cancel the multipart upload event.
    err = bucket.AbortMultipartUpload(imur)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}

```

List uploaded parts

Run the following code to list uploaded parts in a multipart upload event:

```

package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

```

```

    }
    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localFilename := "<yourLocalFilename>"
    uploadID := "<yourUploadID>"
    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Split the local file into parts, 3 parts in this example.
    chunks, err := oss.SplitFileByPartNum(localFilename, 3)
    fd, err := os.Open(localFilename)
    defer fd.Close()
    // Initiate a multipart upload event.
    imur, err := bucket.InitiateMultipartUpload(objectName)
    uploadID = imur.UploadID
    fmt.Println("InitiateMultipartUpload UploadID: ", uploadID)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Upload parts.
    var parts []oss.UploadPart
    for _, chunk := range chunks {
        fd.Seek(chunk.Offset, os.SEEK_SET)
        // Call UploadPart to upload each part.
        part, err := bucket.UploadPart(imur, fd, chunk.Size, chunk.
Number)
        if err != nil {
            fmt.Println("Error:", err)
            os.Exit(-1)
        }
        fmt.Println("UploadPartNumber: ", part.PartNumber, ", ETag:
", part.ETag)
        parts = append(parts, part)
    }
    // List uploaded parts based on InitiateMultipartUploadResult
    lsRes, err := bucket.ListUploadedParts(imur)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Print the uploaded parts.
    fmt.Println("\nParts:", lsRes.UploadedParts)
    for _, upload := range lsRes.UploadedParts {
        fmt.Println("List PartNumber: ", upload.PartNumber, ", ETag:
", upload.ETag, ", LastModified: ", upload.LastModified)
    }
    // Generate InitiateMultipartUploadResult based on the objectName
    and UploadID, and then list all uploaded parts, which applies to
    scenarios where you know the objectName and UploadID.
    var imur_with_uploadid oss.InitiateMultipartUploadResult
    imur_with_uploadid.Key = objectName
    imur_with_uploadid.UploadID = uploadID
    // Lists uploaded parts.
    lsRes, err = bucket.ListUploadedParts(imur_with_uploadid)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}

```

```

// Print the uploaded parts.
fmt.Println("\nListUploadedParts by UploadID: ", uploadID)
for _, upload := range lsRes.UploadedParts {
    fmt.Println("List PartNumber: ", upload.PartNumber, ", ETag: ",
upload.ETag, ", LastModified: ", upload.LastModified)
}
// Complete multipart upload.
cmur, err := bucket.CompleteMultipartUpload(imur, parts)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println("cmur:", cmur)
}

```

List all part upload events for a bucket

Call `Bucket.ListMultipartUploads` to list all ongoing multipart upload events (events that have been initiated but not completed or have been canceled). You can configure the following parameters:

Parameter	Description
Delimiter	Specifies a delimiter of a forward slash (/) used to group object names. The object between the specified prefix and the first occurrence of a delimiter of a forward slash (/) is commonPrefixes.
MaxUploads	Specifies the maximum number of part upload events. The maximum value (also default value) you can set is 1,000.
KeyMarker	Lists all part upload events with the object whose names start with a letter that comes after the KeyMarker value in the alphabetical order.
Prefix	Specifies the prefix that must be included in the returned object name. Note that if you use a prefix for query, the returned object name will contain the prefix.

- Run the following code to list multipart upload events using default parameter values:

```

package main
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
func main() {
    // Create an OSSClient instance.

```



```

    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    // Lists all multipart upload events.
    marker := ""
    for {
        // 1000 records are listed at a time by default.
        lsRes, err := bucket.ListMultipartUploads(oss.Marker(marker
    ))
        if err != nil {
            fmt.Println("Error:", err)
            os.Exit(-1)
        }
        // Print multipart upload events.
        for _, upload := range lsRes.Uploads {
            fmt.Println("Upload: ", upload.Key, ", UploadID: ",
upload.UploadID)
        }
        if lsRes.IsTruncated {
            marker = lsRes.NextKeyMarker
        } else {
            break
        }
    }
}

```

- Run the following code to list multipart upload events with a specified prefix:

```

    lsRes, err := bucket.ListMultipartUploads(oss.Prefix("<
yourObjectNamePrefix>"))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Uploads:", lsRes.Uploads)

```

- Run the following code to list 100 multipart upload events in maximum at one time:

```

    lsRes, err := bucket.ListMultipartUploads(oss.MaxUploads(100))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Uploads:", lsRes.Uploads)

```

- Run the following code to list multipart upload events with a specified prefix and a maximum number:

```

    lsRes, err := bucket.ListMultipartUploads(oss.Prefix("<
yourObjectNamePrefix>"), oss.MaxUploads(100))

```

```

    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Uploads:", lsRes.Uploads)

```

5.6.6 Progress bars

You can use progress bars to indicate the upload or download progress.

The following code is used as an example to describe how to view progress information with `Bucket.PutObjectFromFile`:

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

// Define a progress bar listener.
type OssProgressListener struct {
}

// Define the progress event handler.
func (listener *OssProgressListener) ProgressChanged(event *oss.
ProgressEvent) {
    switch event.EventType {
    case oss.TransferStartedEvent:
        fmt.Printf("Transfer Started, ConsumedBytes: %d, TotalBytes %d.\n",
            event.ConsumedBytes, event.TotalBytes)
    case oss.TransferDataEvent:
        fmt.Printf("\rTransfer Data, ConsumedBytes: %d, TotalBytes %d, %d%
%.\"",
            event.ConsumedBytes, event.TotalBytes, event.ConsumedBytes*100/
event.TotalBytes)
    case oss.TransferCompletedEvent:
        fmt.Printf("\nTransfer Completed, ConsumedBytes: %d, TotalBytes %d.\
n",
            event.ConsumedBytes, event.TotalBytes)
    case oss.TransferFailedEvent:
        fmt.Printf("\nTransfer Failed, ConsumedBytes: %d, TotalBytes %d.\n",
            event.ConsumedBytes, event.TotalBytes)
    default:
    }
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localFile := "<yourLocalFile>"

```

```
// Obtain a bucket.
bucket, err := client.Bucket(bucketName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Upload with a progress bar displayed.
err = bucket.PutObjectFromFile(objectName, localFile, oss.Progress(&
OssProgressListener{}))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
}
```

5.7 Download objects

5.7.1 Overview

For the complete code of object download, see [GitHub](#).

OSS Go SDK provides the following download methods:

- [Streaming download](#)
- [Download to your local file](#)
- [Resumable download](#)
- [Conditional download](#)
- [Download a compressed object](#)

You can view the download progress shown in the [download progress bar](#).

5.7.2 Streaming download

Download an object to a stream.

Run the following code to download a specified object to a stream:

```
package main

import (
    "fmt"
    "os"
    "io/ioutil"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
```

```
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Obtain the bucket.
bucket, err := client.Bucket("<yourBucketName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Download an object to a stream.
body, err := bucket.GetObject("<yourObjectName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
// If you do not close the reader after the data is read, connection
// leaks may occur. Consequently, no connection is available and the
// program cannot run properly.
defer body.Close()

data, err := ioutil.ReadAll(body)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println("data:", string(data))
}
```

Download an object to the local cache

Run the following code to download a specified object to the local cache:

```
package main

import (
    "fmt"
    "os"
    "io"
    "bytes"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

```
// Download the object to the local cache.
body, err := bucket.GetObject("<yourObjectName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
defer body.Close()

buf := new(bytes.Buffer)
io.Copy(buf, body)
fmt.Println("buf:", buf)
}
```

Download an object to a local file stream

Run the following code to download a specified object to a local file stream:

```
package main

import (
    "fmt"
    "os"
    "io"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Download an object to a local file stream.
    body, err := bucket.GetObject("<yourObjectName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    defer body.Close()

    fd, err := os.OpenFile("LocalFile", os.O_WRONLY|os.O_CREATE, 0660)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    defer fd.Close()

    io.Copy(fd, body)
}
```

```
}
```

5.7.3 Download to your local file

This topic describes how to download an object from OSS to a local file.

Run the following code to download a specified object from OSSClient to your local file:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Download an object to your local file.
    err = bucket.GetObjectToFile("<yourObjectName>", "LocalFile")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

5.7.4 Resumable download

Large-sized objects may fail to be downloaded because the network is unstable or the program exits abnormally and the entire object needs to be downloaded again. However, the object may still fail to be downloaded after multiple attempts. Therefore, OSS provides resumable download.

To enable resumable download, you need to split the object you want to download into multiple parts and download them separately. After you have downloaded all parts, these parts will be combined into a complete object.

The progress information of the current download is recorded in a checkpoint file. If a part fails to be download, the next download starts from the part based on the progress information recorded

in the checkpoint file, achieving the resumable download. After the object is downloaded, the checkpoint file is deleted.

**Note:**

- OSS SDK records download progress information in a checkpoint file. Therefore, make sure that the program has the write permission to the checkpoint file. Do not modify the checkpoint file because it includes verification information. If the checkpoint file for an object is corrupted, the entire object is downloaded again.
- If the object being downloaded is modified (the etag of the object changes) during the download, or part files are missing or modified, the entire object is download again.

You can use `Bucket.DownloadFile` to enable resumable download. `DownloadFileRequest` contains the following parameters:

Parameter	Description
<code>objectKey</code>	Specifies the name of the object to be downloaded.
<code>filePath</code>	Specifies the path of the local file that you download the object to.
<code>partSize</code>	Specifies the size of a part. The value can be between 1 byte to 5 GB.
<code>options</code>	Specifies download options, including: • Routines: Specifies the number of parts you need to download simultaneously. The default value is 1. • Checkpoint: Specifies whether the resumable upload is enabled and configures the checkpoint file. The resumable upload is disabled by default. For example, <code>oss.Checkpoint(true, "")</code> indicates that the resumable download is enabled, and the checkpoint file is <code>file.cp</code>, in which <code>file</code> is the name of the local file. The checkpoint file is located in the directory where the local file is located. You can use <code>oss.Checkpoint(true, "your-cp-file.cp")</code> to specify the checkpoint file.

Parameter	Description
	If you want to set conditions for the download, see Conditional download.

Run the following code for resumable download:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Start the resumable download. Three parts are downloaded
    simultaneously.
    // <yourObjectName> is the objectKey, "LocalFile" is the filePath,
    and 100*1024 is the partSize.
    err = bucket.DownloadFile("<yourObjectName>", "LocalFile", 100*1024,
        oss.Routines(3), oss.Checkpoint(true, ""))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

5.7.5 Conditional download

You can configure one or more conditions for downloads. If the specified conditions are met, the object can be downloaded. If the specified conditions are not met, an error code is returned and the object cannot be downloaded. You can configure the following conditions: You can configure the following conditions:

Parameter	Description	Configuration method
IfModifiedSince	If the specified time is earlier than the time the object is	oss.IfModifiedSince

Parameter	Description	Configuration method
	modified, the object can be downloaded. Otherwise, an error (304 Not modified) is returned.	
IfUnmodifiedSince	If the specified time is later than or equal to the time the object is modified, the object can be downloaded. Otherwise, an error (412 Precondition failed) is returned.	oss.IfUnmodifiedSince
IfMatch	If the specified ETag matches that of an object, the object can be downloaded. Otherwise, an error (412 Precondition failed) is returned.	oss.IfMatch
IfNoneMatch	If the specified ETag does not match that of an object, the object can be downloaded. Otherwise, an error (304 Not modified) is returned.	oss.IfNoneMatch

Both If-Modified-Since and If-Unmodified-Since can exist at the same time as object download conditions. Both If-Match and If-None-Match can exist at the same time as object download conditions.

You can use `Bucket.GetObjectDetailedMeta` to Obtain the ETag.

```
package main

import (
    "fmt"
    "os"
    "time"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
```

```

if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Configure time conditions.
date := time.Date(2015, time.November, 10, 23, 0, 0, 0, time.UTC)

// The condition is not met, and the object will not be downloaded.
err = bucket.GetObjectToFile("<yourObjectName>", "LocalFile", oss.
IfModifiedSince(date))
if err == nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// The conditions are met, and the object will be downloaded.
err = bucket.GetObjectToFile("<yourObjectName>", "LocalFile", oss.
IfUnmodifiedSince(date))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
}
}

```

5.7.6 Download a compressed object

This topic describes how to download a compressed object.

You can download a compressed object. Currently, GZIP is supported for object compression.

Bucket.GetObject and Bucket.GetObjectToFile support compression in downloads.

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Download an compressed object.
    err = bucket.GetObjectToFile("<yourObjectName>", "LocalFile.gzip",
oss.AcceptEncoding("gzip"))
    if err != nil {

```

```

    fmt.Println("Error:", err)
    os.Exit(-1)
}
}

```

5.7.7 Progress bars

You can use progress bars to indicate the upload or download progress.

The following code is used as an example to describe how to view progress information with `Bucket.GetObjectToFile`:

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

// Define a progress bar listener.
type OssProgressListener struct {
}

// Define the progress event handler.
func (listener *OssProgressListener) ProgressChanged(event *oss.
ProgressEvent) {
    switch event.EventType {
    case oss.TransferStartedEvent:
        fmt.Printf("Transfer Started, ConsumedBytes: %d, TotalBytes %d.\n",
            event.ConsumedBytes, event.TotalBytes)
    case oss.TransferDataEvent:
        fmt.Printf("\rTransfer Data, ConsumedBytes: %d, TotalBytes %d, %d%
%.\"",
            event.ConsumedBytes, event.TotalBytes, event.ConsumedBytes*100/
event.TotalBytes)
    case oss.TransferCompletedEvent:
        fmt.Printf("\nTransfer Completed, ConsumedBytes: %d, TotalBytes %d.\
n",
            event.ConsumedBytes, event.TotalBytes)
    case oss.TransferFailedEvent:
        fmt.Printf("\nTransfer Failed, ConsumedBytes: %d, TotalBytes %d.\n",
            event.ConsumedBytes, event.TotalBytes)
    default:
    }
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localFile := "<yourLocalFile>"

```

```
// Obtain the bucket.
bucket, err := client.Bucket(bucketName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Download with a progress bar displayed.
err = bucket.GetObjectToFile(objectName, localFile, oss.Progress(&
OssProgressListener{}))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println("Transfer Completed.")
}
```

5.8 Manage objects

5.8.1 Overview

You can manage objects stored in buckets with APIs, including the following operations:

- [Determine whether an object exists](#)
- [Manage ACL for an object](#)
- [Manage Object Meta](#)
- [List objects](#)
- [Delete objects](#)
- [Copy objects](#)
- [Restore an archive object](#)
- [Manage a symbolic link](#)

5.8.2 Determine whether a specified object exists

This topic describes how to determine whether a specified object exists

Run the following code to determine whether a specified object exists:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
```

```

    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Obtain the bucket.
bucket, err := client.Bucket("<yourBucketName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Determine whether the specified object exists.
isExist, err := bucket.IsObjectExist("<yourObjectName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println("Exist:", isExist)
}

```

5.8.3 Manage ACL for an object

For the complete code demo of ACL, see [GitHub](#).

The following table describes the permissions included in the Access Control List (ACL) for an object.

Permission	Description	Value
default	The ACL of an object is the same with that of its bucket.	oss.ACLDefault
Private	Only the object owner and authorized users can read and write the object.	oss.ACLPrivate
Public read	Only the object owner and authorized users can read and write the object. Other users can only read the object . Authorize this permission with caution.	oss.ACLPublicRead
Public read-write	All users can read and write the object. Authorize this permission with caution.	oss.PublicReadWrite

The ACL privileges of objects take precedence over that of buckets. For example, if the ACL of a bucket is private, while the object ACL is public read-write, all users can read and write the object. If an object is not configured with an ACL, its ACL is the same as that of its bucket by default.

```
package main
```

```
import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Configure an ACL for an object.
    err = bucket.SetObjectACL("<yourObjectName>", oss.ACLPublicReadWrite)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the ALC for an object.
    aclRes, err := bucket.GetObjectACL("<yourObjectName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Object ACL:", aclRes.ACL)
}
```

5.8.4 Manage Object Meta

For more information about Object Meta, see [Object Meta](#) in OSS Developer Guide. For the complete code of Object Meta, see [GitHub](#).

Configure Object Meta

You can configure the Object Meta when uploading an object. The following table lists the Object Meta you can configure:

Parameter	Description
CacheControl	Specifies the cache action of a webpage when an object is downloaded.
ContentDisposition	// Specify the name of the object when it is downloaded.

Parameter	Description
ContentEncoding	Specifies the encoding format when an object is downloaded.
Expires	Specifies the cache expiration time (GMT is used).
ServerSideEncryption	Specifies the server-side encryption algorithm when the OSS creates an object. Valid value: AES256.
ObjectACL	Specifies the ACL for an object created by OSS.
Meta	Specifies the custom Object Meta, with X-OSS-Meta- as the prefix.

Run the following code to configure Object Meta:

```
package main

import (
    "fmt"
    "os"
    "time"
    "strings"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain the bucket.
    bucket, err := client.Bucket("<yourBucketName>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Configure Object Meta: The expiration time is 2049-01-10, 23:00:00
    // in the GMT format. The ACL is public read. The custom Object Meta is
    // MyProp (the value is MyPropVal).
    expires := time.Date(2049, time.January, 10, 23, 0, 0, 0, time.UTC)
    options := []oss.Option{
        oss.Expires(expires),
        oss.ObjectACL(oss.ACLPublicRead),
        oss.Meta("MyProp", "MyPropVal"),
    }

    // Use the data stream to upload.
```

```

err = bucket.PutObject("<yourObjectName>", strings.NewReader("
MyObjectValue"), options...)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Obtain Object Meta.
props, err := bucket.GetObjectDetailedMeta("<yourObjectName>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println("Object Meta:", props)
}

```

Modify Object Meta

Run the following code to modify one or more Object Meta at a time:

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Modify one Object Meta at a time.
    err = bucket.SetObjectMeta(objectName, oss.Meta("MyMeta", "MyMetaValu
e1"))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Modify multiple Object Metas at one time.
    options := []oss.Option{
        oss.Meta("MyMeta", "MyMetaValue2"),
        oss.Meta("MyObjectLocation", "HangZhou"),
    }
    err = bucket.SetObjectMeta(objectName, options...)
}

```



```
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Obtain Object Meta.
props, err := bucket.GetObjectDetailedMeta(objectName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println("Object Meta:", props)
}
```

Obtain Object Meta

Run the following code to obtain Object Meta:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Obtain Object Meta.
    props, err := bucket.GetObjectDetailedMeta(objectName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Object Meta:", props)
}
```

5.8.5 List objects

Objects are listed alphabetically. You can use `Bucket.ListObjects` to list objects in a bucket.

The following parameters can be used:

Parameter	Description
delimiter	Specifies a delimiter used to group objects. The substring between the specified prefix and the first occurrence of the delimiter of a forward slash (/) is commonPrefixes.
prefix	Specifies the prefix you configure to list required objects.
maxKeys	Specifies the maximum number of objects that can be listed. The default value is 100. The maximum value is 1,000.
marker	Specifies the initial object in the list.

For the complete code of ListObjects, see [GitHub](#).

Simple list

You can use the default parameters to obtain the object list of a bucket. 100 objects can be listed by default. Run the following code to list objects in a bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // List all objects.
    marker := ""
    for {
        lsRes, err := bucket.ListObjects(oss.Marker(marker))
        if err != nil {
```

```

    HandleError(err)
}

// Prints the object list. 100 records are returned by default.
for _, object := range lsRes.Objects {
    fmt.Println("Bucket: ", object.Key)
}

if lsRes.IsTruncated {
    marker = lsRes.NextMarker
} else {
    break
}
}
}
}

```

List a specified number of objects

Run the following code to list a specified number of objects:

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Configure the maximum number of the listed object and list objects.
    lsRes, err := bucket.ListObjects(oss.MaxKeys(200))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Print the results.
    fmt.Println("Objects:", lsRes.Objects)
    for _, object := range lsRes.Objects {
        fmt.Println("Object:", object.Key)
    }
}

```

```
}
```

List objects by a specified prefix

Run the following code to list objects with a specified prefix:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // List objects with a specified prefix. 100 objects are listed by default.
    lsRes, err := bucket.ListObjects(oss.Prefix("my-object-"))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Print the results.
    fmt.Println("Objects:", lsRes.Objects)
    for _, object := range lsRes.Objects {
        fmt.Println("Object:", object.Key)
    }
}
```

List objects by marker

The marker parameter indicates the name of an object from which the listing begins. Run the following code to specify an object (specified with marker) after which the listing begins:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
```

```

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // List objects placed after the object (specified with marker). 100
objects are listed by default.
    lsRes, err := bucket.ListObjects(oss.Marker("my-object-xx"))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Print the results.
    fmt.Println("Objects:", lsRes.Objects)
    for _, object := range lsRes.Objects {
        fmt.Println("Object:", object.Key)
    }
}

```

List all objects on one or more pages

Run the following code to list all objects on one or more pages. The maximum number of objects listed on each page is specified with `maxKeys`.

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)

```

```

if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// List all objects on multiple pages. 200 objects are listed in one
// page.
marker := oss.Marker("")
for {
    lsRes, err := bucket.ListObjects(oss.MaxKeys(200), marker)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    marker = oss.Marker(lsRes.NextMarker)

    fmt.Println("Objects:", lsRes.Objects)

    if ! lsRes.IsTruncated {
        break
    }
}
}

```

List objects by marker on one or more pages

Run the following code to specify an object (specified with marker) after which the listing begins on one or more pages: The maximum number of objects listed on each page is specified with `maxKeys`.

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // List objects placed after the object (specified with marker) on
    // multiple pages. 200 objects are listed in one page.
    marker = oss.Marker("my-object-xx")
}

```

```

for {
    lsRes, err := bucket.ListObjects(oss.MaxKeys(50), marker)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    marker = oss.Marker(lsRes.NextMarker)

    fmt.Println("Objects:", lsRes.Objects)

    if ! lsRes.IsTruncated {
        break
    }
}
}
}

```

List objects by a specified prefix on one or more pages

Run the following code to list objects by a specified prefix on one or more pages: The maximum number of objects listed on each page is specified with maxKeys.

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // List objects with a specified prefix on multiple pages. 80 objects
    // are listed in one page.
    prefix := oss.Prefix("my-object-")
    marker := oss.Marker("")
    for {
        lsRes, err := bucket.ListObjects(oss.MaxKeys(80), marker, prefix)
        if err != nil {
            fmt.Println("Error:", err)
            os.Exit(-1)
        }

        prefix = oss.Prefix(lsRes.Prefix)
    }
}

```

```
marker = oss.Marker(lsRes.NextMarker)

fmt.Println("Objects:", lsRes.Objects)

if ! lsRes.IsTruncated {
    break
}
}
```

5.8.6 Delete objects



Warning:

Delete objects with caution because deleted objects cannot be recovered.

For the complete code of deleting objects, see [GitHub](#).

Delete an object

Run the following code to delete a single object:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Delete an object.
    err = bucket.DeleteObject(objectName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```



```
}
```

Delete multiple objects

You can use `Bucket.DeleteObjects` to delete multiple objects and specify the `DeleteObjectsQuiet` parameter to determine whether the result of the delete operation is returned. The results of the deleted objects are returned by default.

Run the following code to delete multiple objects:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // The results of deleted objects are returned.
    delRes, err := bucket.DeleteObjects([]string{"my-object-1", "my-object-2"})
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Deleted Objects:", delRes.DeletedObjects)

    // The deletion results are not returned.
    _, err = bucket.DeleteObjects([]string{"my-object-3", "my-object-4"},
        oss.DeleteObjectsQuiet(true))
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

5.8.7 Copy objects

For the complete code of copying objects, see [GitHub](#).

Copy objects within the same bucket

Run the following code to copy objects within the same bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    destObjectName := "<yourDestObjectName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Copy an object to another object in the same bucket.
    _, err = bucket.CopyObject(objectName, destObjectName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

Copy objects to another bucket

You can copy an object from the current bucket to another bucket or from other buckets to the current bucket. Run the following code to copy objects to another bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
    }
}
```

```

    os.Exit(-1)
}

bucketName := "<yourBucketName>"
srcBucketName := "<yourSrcBucketName>"
dstBucketName := "<yourDstBucketName>"
srcObjectName := "<yourSrcObjectName>"
dstObjectName := "<yourDstObjectName>"

// Obtain the bucket.
bucket, err := client.Bucket(bucketName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Copy the source object (srcObjectName) from other buckets (
srcBucketName) to the current bucket.
bucket.CopyObjectFrom(srcBucketName, srcObjectName, dstObjectName)
if err != nil {
    fmt.Println("CopyObjectFrom Error:", err)
    os.Exit(-1)
}

// Copy the source object (srcObjectName) from the current bucket to
another bucket (dstBucketName).
bucket.CopyObjectTo(dstBucketName, dstObjectName, srcObjectName)
if err != nil {
    fmt.Println("CopyObjectTo Error:", err)
    os.Exit(-1)
}
}
}

```

- Process object metadata during copy

You can process the object metadata when copying the object by specifying the `MetadataDirective` parameter:

- `oss.MetaCopy`: The default value, indicating that the metadata of the target object is the same with that of the source object, that is, copying the source object metadata.
- `oss.MetaReplace`: Replace the source object metadata with the new metadata.



Note:

If you specify the `MetadataDirective` parameter to `oss.MetaReplace`, the metadata of the source object is overwritten and cannot be recovered. Therefore, perform this operation with caution.

The following metadata can be specified if the value of `MetadataDirective` is `oss.MetaReplace`:

Metadata	Description
CacheControl	Specifies the cache action of the web page when the new object is downloaded.
ContentDisposition	Specifies the name of the new object when it is downloaded.
ContentEncoding	Specifies the content encoding format when a new object is downloaded.
Expires	Specify the expiration time (in GMT) of the new object.
ServerSideEncryption	Specifies the server-side encryption algorithm used when the OSS creates an object. Valid value: AES256
ObjectACL	Specifies ACL of an OSS object when it is created.
Meta	Custom parameter prefixed with <code>X-Oss-Meta-</code> .

Run the following code to process object metadata during copy:

```
package main

import (
    "fmt"
    "os"
    "time"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    destObjectName := "<yourDestObjectName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Specify the metadata of the target object.
```

```

expires := time.Date(2049, time.January, 10, 23, 0, 0, 0, time.UTC)
options := []oss.Option{
    oss.MetadataDirective(oss.MetaReplace),
    oss.Expires(expires),
    oss.ObjectACL(oss.ACLPublicRead),
    oss.Meta("MyMeta", "MyMetaValue")}

// Overwrites the metadata of the source object with the specified
metadata.
_, err = bucket.CopyObject(objectName, destObjectName, options...)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
}

```

Conditional copy

You can set conditions for object copy. The object is copied only when the conditions are satisfied. Otherwise, an error is reported and the object does not get copied. Available conditions include:

Parameter	Description
CopySourceIfMatch	If the source object's ETag value is the same as the ETag provided by the user, the copy operation is executed. Otherwise, an error is returned.
CopySourceIfNoneMatch	If the source object's ETag value is not the same as the ETag provided by the user, the copy operation is actioned. Otherwise, an error is returned.
CopySourceIfModifiedSince	If the specified time in the input parameter is the same as or later than the actual modification time of the source object, the object is copied normally. Otherwise, an error is returned.
CopySourceIfUnmodifiedSince	If the source object has been modified after the time specified by the user, the object is copied. Otherwise, an error is returned.

CopySourceIfMatch and CopySourceIfNoneMatch can be used as conditions together.

CopySourceIfModifiedSince and CopySourceIfUnmodifiedSince can be used as conditions together.

Run the following code for conditional copy:

```

package main

import (

```

```

"fmt"
"os"
"time"
"github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // bucketName := "<yourBucketName>"
    // objectName := "<yourObjectName>"
    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    destMatchObjectName := "<yourMatchDestObjectName>"
    destUnMatchObjectName := "<yourUnmatchDestObjectName>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    date := time.Date(2011, time.November, 10, 23, 0, 0, time.UTC)

    // The conditions are satisfied, copy the object.
    _, err = bucket.CopyObject(objectName, destMatchObjectName, oss.
CopySourceIfModifiedSince(date))
    if err != nil {
        fmt.Println("CopyObject CopySourceIfModifiedSince Error:", err)
    }

    // The conditions are not met, the object is not copied.
    _, err = bucket.CopyObject(objectName, destUnMatchObjectName, oss.
CopySourceIfUnmodifiedSince(date))
    if err != nil {
        fmt.Println("CopyObject CopySourceIfUnmodifiedSince Error:", err)
    }
}

```

5.8.8 Restore an archive object

You must restore an archive object before you read it. Do not call `restoreObject` for non-archive objects.

The state conversion process of an archive object is as follows:

- An archive object is in the frozen state.
- After you submit it for restoration, the server restores the object. The object is in the restoring state.

- One minute later, the object enters the restored state and can be read. The restored state lasts for one day by default, and can be prolonged to a maximum of seven days. Once this period ends, the object returns to the frozen state.

For detailed information about archive storage class, see [Introduction to storage classes](#). For detailed information about related status code, see [RestoreObject](#). For the complete code of restoring an archive object, see [GitHub](#).

Run the following code to restore an object:

```
package main

import (
    "fmt"
    "os"
    "time"
    "strings"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localFilename := "<yourLocalFilename>"

    // Create a bucket.
    err = client.CreateBucket(bucketName, oss.StorageClass(oss.StorageArchive))
    if err != nil {
        HandleError(err)
    }

    // Obtain the bucket.
    archiveBucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // Upload the archived object.
    var val = "More than just cloud."
    err = archiveBucket.PutObject(objectName, strings.NewReader(val))
    if err != nil {
        HandleError(err)
    }

    // Check whether the object is an archive object.
```

```

meta, err := archiveBucket.GetObjectDetailedMeta(objectName)
if err != nil {
    HandleError(err)
}

fmt.Println("X-Oss-Storage-Class : ", meta.Get("X-Oss-Storage-Class"))
if meta.Get("X-Oss-Storage-Class") == string(oss.StorageArchive) {
    // Restore the archive object for read.
    err = archiveBucket.RestoreObject(objectName)
    if err != nil {
        HandleError(err)
    }

    // Wait until the object is restored.
    meta, err = archiveBucket.GetObjectDetailedMeta(objectName)
    for meta.Get("X-Oss-Restore") == "ongoing-request=\"true\"" {
        fmt.Println("x-oss-restore:" + meta.Get("X-Oss-Restore"))
        time.Sleep(1000 * time.Second)
        meta, err = archiveBucket.GetObjectDetailedMeta(objectName)
    }
}

// Download the restored object.
err = archiveBucket.GetObjectToFile(objectName, localFilename)
if err != nil {
    HandleError(err)
}

// Restore the object again.
err = archiveBucket.RestoreObject(objectName)

fmt.Println("ArchiveSample completed")
}

```

5.8.9 Manage a symbolic link

A symbolic link is a special object that maps to an object similar to a shortcut used in Windows.

You can configure user-defined Object Meta for symbolic links.

Run the following code to create a symbolic link:

```

package main

import (
    "fmt"
    "os"
    "strings"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}

```



```
bucketName := "<yourBucketName>"
// The symbolic link.
objectName := "<yourSymlinkName>"
// The target object that the symbolic link directs to
targetObjectName := "<yourSymlinkTargetName>"

// Obtain the bucket.
bucket, err := client.Bucket(bucketName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Create a symbolic link.
err = bucket.PutSymlink(objectName, targetObjectName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Upload a file to the object that the symbolic link directs to.
err = bucket.PutObject(targetObjectName, strings.NewReader("target"))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

err = bucket.PutSymlink(objectName, targetObjectName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Obtain the content of the object that the symbolic link directs to
meta, err := bucket.GetSymlink(objectName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println(meta.Get(oss.HTTPHeaderOssSymlinkTarget))
}
```

For more information about creating symbolic links, see [PutSymlink](#).

Obtain object content for a symbolic link

To obtain a symbolic link, you must have the read permission on it. Run the following code to obtain the object content for a symbolic link:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
```

```
// Create an OSSClient instance.
client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

bucketName := "<yourBucketName>"
// Symbolic Link name.
objectName := "<yourSymlinkObjectName>"

// Obtain the bucket.
bucket, err := client.Bucket(bucketName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Obtain the content of the object that the symbolic link directs to
.
meta, err := bucket.GetSymlink(objectName)
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
fmt.Println(meta.Get(oss.HTTPHeaderOssSymlinkTarget))
}
```

For more information about obtaining symbolic links, see [GetSymlink](#).

5.9 Authorized access

Sign a URL to authorize temporary access

You can provide a signed URL to a visitor for temporary access. When you sign a URL, you can specify the expiration time for a URL to restrict the period of access from visitors.

For the complete code of signing a URL to authorize temporary access, see [GitHub](#).

- Use a signed URL to upload a file

Run the following code to upload a file with a signed URL:

```
package main

import (
    "fmt"
    "os"
    "strings"

    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

```
func main() {
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localFilename := "<yourLocalFilename>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // Directly upload the file after the the URL is signed.
    signedURL, err := bucket.SignURL(objectName, oss.HTTPPut, 60)
    if err != nil {
        HandleError(err)
    }

    var val = "Choose Alibaba Cloud"
    err = bucket.PutObjectWithURL(signedURL, strings.NewReader(val))
    if err != nil {
        HandleError(err)
    }

    // Directly upload the file after the the URL is signed, in which
    you can configure optional parameters.
    options := []oss.Option{
        oss.Meta("myprop", "mypropval"),
        oss.ContentType("image/tiff"),
    }

    signedURL, err = bucket.SignURL(objectName, oss.HTTPPut, 60,
options...)
    if err != nil {
        HandleError(err)
    }

    err = bucket.PutObjectFromFileWithURL(signedURL, localFilename,
options...)
    if err != nil {
        HandleError(err)
    }
}
```

**Note:**

For more information about the optional parameters, see [Manage Object Meta](#) in [Manage objects](#).

- Use a signed URL to download an object

Run the following code to use a signed URL to download an object:

```
package main

import (
    "fmt"
    "os"
    "io/ioutil"

    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    localDownloadedFilename := "<yourDownloadedFilename>"

    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // Directly download the object to the stream after the URL is signed.
    signedURL, err := bucket.SignURL(objectName, oss.HTTPGet, 60)
    if err != nil {
        HandleError(err)
    }

    body, err := bucket.GetObjectWithURL(signedURL)
    if err != nil {
        HandleError(err)
    }
    // Read the object content.
    data, err := ioutil.ReadAll(body)
    body.Close()
    data = data // use data

    // Directly download the object to a local file after the URL is signed.
    err = bucket.GetObjectToFileWithURL(signedURL, localDownloadedFilename)
    if err != nil {
        HandleError(err)
    }
}
```

```
}
```

Use STS for temporary access authorization

OSS supports Alibaba Cloud Security Token Service (STS) for temporary access authorization.

STS is a web service that provides a temporary access token to a cloud computing user. Through the STS, you can assign a third-party application or a RAM user (you can manage the user ID) an access credential with a custom validity period and permissions. For more information about STS, see [STS introduction](#).

STS advantages:

- Your long-term key (AccessKey) is not exposed to a third-party application. You only need to generate an access token and send the access token to the third-party application. You can customize access permissions and the validity of this token.
- You do not need to keep track of permission revocation issues. The access token automatically becomes invalid when it expires.

For more information about the process of access to OSS with STS, see [RAM and STS scenario practices](#) in OSS Developer Guide.

Run the following code to create a signature request with STS:

```
import "github.com/aliyun/aliyun-oss-go-sdk/oss"

// After a user obtains a temporary STS credential, the OSSClient is
// generated with the security token and temporary access key (AccessKeyId
// and AccessKeySecret).
// Create an OSSClient instance.
client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>", oss.SecurityToken("<yourSecurityToken>"))
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

// Perform operations on OSS.
}
```

5.10 Manage lifecycle rules

You can use OSS to configure lifecycle rules to reduce storage costs. The lifecycle management rules can be used for automatic deletion of expired objects and fragments, or storage class conversion to Infrequent Access for objects that will expire soon. Each rule includes:

- Rule ID: It identifies a rule. Ensure that each rule ID in a bucket is unique.
- Policy: You can configure a policy by using the following configuration methods. Only one method can be configured for a bucket.

- Configure by Prefix: You can create multiple rules with this method. Ensure that each prefix is unique.
- Configure for Entire Bucket: You can configure only one rule with this method.
- Expired: You can configure the following configuration methods:
 - Set by Number of Days: It specifies the number of days from the last modification time of objects.
 - Set by Date: It specifies the date prior to which objects are created. If objects are created prior to the date, these objects are deleted.
- Status: This lifecycle rule takes effect or not.

The parts uploaded by `uploadPart` method also support lifecycle rules. The last modification time of an object is the time the multipart upload event is initiated.

For more information about lifecycle management, see [Manage object lifecycle](#). For the complete code of lifecycle management, see [GitHub](#).

Configure lifecycle rules

Run the following code to configure lifecycle rules:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    // Lifecycle rule 1 (id: "rule1", enable:true, prefix:"foo/", expiry :Days 3), indicates that an object with the prefix foo expires three days after the last modified date.
    rule1 := oss.BuildLifecycleRuleByDays("rule1", "foo/", true, 3)
    rules := []oss.LifecycleRule{rule1}

    // Configure lifecycle rules.
    bucketName := "<yourBucketName>"
    err = client.SetBucketLifecycle(bucketName, rules)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

```
}
```

View lifecycle rules

Run the following code to view lifecycle rules:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // View lifecycle rules.
    lcRes, err := client.GetBucketLifecycle(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Lifecycle Rules:", lcRes.Rules)
}
```

Clear lifecycle rules

Run the following code to clear lifecycle rules:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Clear lifecycle rules.
    err = client.DeleteBucketLifecycle(bucketName)
    if err != nil {
```

```
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

5.11 Set logging

You can enable access logs to record bucket access to log files, which are stored in a specified bucket.

The log file format is as follows:

<TargetPrefix><SourceBucket>-YYYY-mm-DD-HH-MM-SS-UniqueString

For more information about access log files, see [Set access logging](#). For the complete code of set logging, see [GitHub](#).

Enable access logging

Run the following code to enable bucket access logging:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"
    targetBucketName := "<yourTargetBucketName>"
    targetPrefix := "<yourTargetPrefix>"

    // Enable access logging for a bucket. targetBucketName is the bucket
    // that logs are stored, targetPrefix is the prefix of the stored log
    // files, that is, the path of the log files.
    err = client.SetBucketLogging(bucketName, targetBucketName,
        targetPrefix, true)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```



```
}
```

View access logging configurations

Run the following code to view the access logging configurations for a bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // View the access logging configurations for a bucket.
    logRes, err := client.GetBucketLogging(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Target Bucket: ", logRes.LoggingEnabled.TargetBucket)
    fmt.Println("Target Prefix: ", logRes.LoggingEnabled.TargetPrefix)
}
```

Disable access logging

Run the following code to disable access logging for a bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    // client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Disable access logging.
    err = client.DeleteBucketLogging(bucketName)
```

```
if err != nil {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

5.12 Static website hosting

You can set your bucket configuration to the static website hosting mode. After the configuration takes effect, you can access this static website with the bucket domain and be redirected to a specified index page or error page.

For more information about static website hosting, see [Static website hosting](#).

Configure static website hosting

Run the following code to configure static website hosting:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Configure static web hosting: The index page is index.html and the
    // error page is error.html.
    err = client.SetBucketWebsite(bucketName, "index.html", "error.html")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

View static website hosting configurations

Run the following code to view static website hosting configurations:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
```

```
func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // View static web hosting configurations.
    wsRes, err := client.GetBucketWebsite(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("indexWebsite: ", wsRes.IndexDocument.Suffix)
    fmt.Println("errorWebsite: ", wsRes.ErrorDocument.Key)
}
```

Delete static website hosting configurations

Run the following code to delete static website hosting configurations:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Delete static website hosting configurations.
    err = client.DeleteBucketWebsite(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

5.13 Anti-leech

To prevent your data on OSS from being leached, OSS supports anti-leeching through the referer field settings in the HTTP header, including the following parameters:

- Referrer whitelist: Used to allow access only for specified domains to OSS data.
- Empty referer: Determines whether the referer can be empty. If it is not allowed, only requests with the referer filed in their HTTP or HTTPS headers can access OSS data.

For more information about anti-leeching, see [Anti-leeching settings](#). For the complete code of configuring anti-leech, see [GitHub](#).

Configure the referer whitelist

Run the following code to configure the referer whitelist:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Add the referer field. Empty referer is not allowed. The referer
    // field allows question marks (?) and asterisks (*) for wildcard use.
    referers := []string{"http://www.aliyun.com",
                        "http://www.???.aliyuncs.com",
                        "http://www. *.com"}
    err = client.SetBucketReferer(bucketName, referers, false)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

Obtain a referer whitelist

Run the following code to obtain a referer whitelist:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
```

```

    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the referer whitelist.
    refRes, err := client.GetBucketReferer(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Referers: ", refRes.RefererList)
    fmt.Println("AllowEmptyReferer: ", refRes.AllowEmptyReferer)
}

```

Clear a referer whitelist

Run the following code to clear a referer whitelist:

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Clear the referer whitelist. // You cannot clear a referer
    whitelist directly. To clear a referer whitelist, you need to create
    the rule that allows an empty referer field and replace the original
    rule with the new rule.
    err = client.SetBucketReferer(bucketName, []string{}, true)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}

```

```
}
```

5.14 CORS

Cross-origin resource sharing (CORS) allows web applications to access resources that belong to another region. OSS provides CORS APIs for convenient cross-origin access control.

For more information, see [Cross-origin resource sharing](#) and [PutBucketcors](#) in OSS Developer Guide.

For the complete code of CORS, see [GitHub](#).

Configure CORS rules

Run the following code to configure CORS rules for the specified bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    rule1 := oss.CORSRule{
        AllowedOrigin: []string{"*"},
        AllowedMethod: []string{"PUT", "GET"},
        AllowedHeader: []string{},
        ExposeHeader: []string{},
        MaxAgeSeconds: 200,
    }

    rule2 := oss.CORSRule{
        AllowedOrigin: []string{"http://www.a.com", "http://www.b.com"},
        AllowedMethod: []string{"POST"},
        AllowedHeader: []string{"Authorization"},
        ExposeHeader: []string{"x-oss-test", "x-oss-test1"},
        MaxAgeSeconds: 100,
    }

    // Configure CORS rules.
    err = client.SetBucketCORS(bucketName, []oss.CORSRule{rule1, rule2})
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
}
```

```
}
```

Obtain CORS rules

Run the following code to obtain CORS rules:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Obtain the CORS rules.
    corsRes, err := client.GetBucketCORS(bucketName)
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }
    fmt.Println("Bucket CORS:", corsRes.CORSRules)
}
```

Delete CORS rules

Run the following code to delete all CORS rules for the specified bucket:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        fmt.Println("Error:", err)
        os.Exit(-1)
    }

    bucketName := "<yourBucketName>"

    // Delete CORS rules.
    err = client.DeleteBucketCORS(bucketName)
    if err != nil {
```

```
    fmt.Println("Error:", err)
    os.Exit(-1)
}
```

5.15 Image processing

Image Processing (IMG) is a massive, secure, cost-effective and highly reliable image processing service. After source images are uploaded to OSS, you can process images on any Internet device at any anytime, from anywhere through simple RESTful APIs.

For more information about IMG, see [Image Processing](#).

Basic features

OSS offers the following IMG features:

- [Retrieve dominant image tones](#)
- [Format conversion](#)
- [Resize images](#)
- [Incircle](#)
- [Adaptive orientation](#)
- [Brightness](#)
- [Add watermarks](#): allows you to add images, texts, or image-text watermarks to another image.
- [Image processing](#)
- [Image processing access rules](#): calls multiple IMG functions.

Usage

IMG uses standard HTTP GET. You can configure IMG parameters in QueryString of a URL.

If the ACL of an image object is private read and write, only authorized users are allowed for access.

- Anonymous access

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction>,<yourParamValue>
```

Parameter	Description
bucket	Specifies the name of a bucket.
endpoint	Specifies endpoint used to access a region.

Parameter	Description
object	Specifies the name of an image object.
image	Specifies the reserved identifier for IMG.
action	Specifies the operations on an image, such as scaling, cropping, and rotating.
param	Specifies the parameter that indicates the operation on an image.

— Basic operations

For example, scale an image to a width of 100 px. Adjust the height based on the ratio.

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

— Customized image styles

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=style/<yourStyleName>
```

- style: specifies a reserved identifier of a customized image style.
- yourStyleName: specifies the name of a custom image style. It is the name specified in the rule that is created on the OSS console.

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=style/oss-pic-style-w-100
```

— Cascade operations

Cascade operations allow you to perform multiple operations on an image sequentially.

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction1>,<yourParamValue1>/<yourAction2>,<yourParamValue2>/...
```

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100/rotate,90
```

— HTTPS access

IMG supports access through HTTPS. Example:

```
https://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

- Authorized access

Authorized access allows you to customize an image style, HTTPS access, and cascade operations.

Use the following code to generate a signed URL for IMG:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    ossImageName := "<yourImageName>"
    signedURL, err := bucket.SignURL(ossImageName, oss.HTTPGet, 600, oss.Process("image/format,png"))
    if err != nil {
        HandleError(err)
    } else {
        fmt.Println(signedURL)
    }
}
```

- Access with SDK

You can use SDK to access and process an image object.

SDK allows you to customize image styles, HTTPS access, and cascade operations.

— Basic operations

Run the following code to perform basic operations on an image:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>",
        "<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // Scale the image.
    sourceImageName := "example.png"
    targetImageName := "example-resize.png"
    style := "image/resize,m_fixed,w_100,h_100"
    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }

    // Crop the image.
    targetImageName = "example-crop.png"
    style = "image/crop,w_100,h_100,x_100,y_100,r_1"
    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }

    // Rotate the image.
    targetImageName = "example-rotate.png"
    style = "image/rotate,90"
    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }

    // Sharpen the image.
    targetImageName = "example-sharpen.png"
    style = "image/sharpen,100"
```

```

    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }

    // Add watermarks.
    targetImageName = "example-watermark.png"
    style = "image/watermark,text_SGVsbG8g5Zu-54mH5pyN5YqhIQ"
    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }

    // Convert the image format.
    targetImageName = "example-formatconvert.jpg"
    style = "image/format,jpg"
    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }
}

```

— Customize an image style

Run the following code to customize an image style:

```

package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>",
"<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // Customize the image style.
    sourceImageName := "example.png"
    targetImageName := "example-custom.png"
    style := "style/<yourCustomStyleName>"

```

```
    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }
}
```

— Cascade operations

Run the following code to perform cascade operations on an image:

```
package main

import (
    "fmt"
    "os"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>",
"<yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // Customize an image style.
    sourceImageName := "example.png"
    targetImageName := "example-resize.png"
    style := "image/resize,m_fixed,w_100,h_100/rotate,90"
    err = bucket.GetObjectToFile(sourceImageName, targetImageName
, oss.Process(style))
    if err != nil {
        HandleError(err)
    }
}
```

Image processing persistence

Run the following code for image processing persistence:

```
package main

import (
    "fmt"
    "os"
    "encoding/base64"
```

```

    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)

func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}

func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }

    // Obtain the bucket.
    bucketName := "<yourBucketName>"
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }

    // Image processing persistence: Scale the image. The target image
    is stored in the same bucket by default.
    sourceImageName := "example.png"
    targetImageName := "example-resize.png"
    style := "image/resize,m_fixed,w_100,h_100"
    process := fmt.Sprintf("%s|sys/saveas,o_%v", style, base64.
URLEncoding.EncodeToString([]byte(targetImageName)))
    result, err := bucket.ProcessObject(sourceImageName, process)
    if err != nil {
        HandleError(err)
    } else {
        fmt.Println(result)
    }

    // Image processing persistence: Scale the image. The target image
    is stored in the different bucket.
    targetBucketName := "<yourTargetBucketName>"
    targetImageName = "example-crop-different-bucket.png"
    style = "image/resize,m_fixed,w_100,h_100"
    process = fmt.Sprintf("%s|sys/saveas,o_%v,b_%v", style, base64
. URLEncoding.EncodeToString([]byte(targetImageName))), base64.
URLEncoding.EncodeToString([]byte(targetBucketName)))
    result, err = bucket.ProcessObject(sourceImageName, process)
    if err != nil {
        HandleError(err)
    } else {
        fmt.Println(result)
    }

    // Image processing persistence: Crop the image.
    targetImageName = "example-crop.png"
    style = "image/crop,w_100,h_100,x_100,y_100,r_1"
    process = fmt.Sprintf("%s|sys/saveas,o_%v", style, base64.
URLEncoding.EncodeToString([]byte(targetImageName)))
    result, err = bucket.ProcessObject(sourceImageName, process)
    if err != nil {
        HandleError(err)
    } else {

```

```
        fmt.Println(result)
    }

    // Image processing persistence: Rotate the image.
    targetImageName = "example-rotate.png"
    style = "image/rotate,90"
    process = fmt.Sprintf("%s|sys/saveas,o_%v", style, base64.
        URLEncoding.EncodeToString([]byte(targetImageName)))
    result, err = bucket.ProcessObject(sourceImageName, process)
    if err != nil {
        HandleError(err)
    } else {
        fmt.Println(result)
    }

    // Image processing persistence: Sharpen the image.
    targetImageName = "example-sharpen.png"
    style = "image/sharpen,100"
    process = fmt.Sprintf("%s|sys/saveas,o_%v", style, base64.
        URLEncoding.EncodeToString([]byte(targetImageName)))
    result, err = bucket.ProcessObject(sourceImageName, process)
    if err != nil {
        HandleError(err)
    } else {
        fmt.Println(result)
    }

    // Image processing persistence: Add watermarks.
    targetImageName = "example-watermark.png"
    style = "image/watermark,text_SGVsbG8g5Zu-54mH5pyN5YqhIQ"
    process = fmt.Sprintf("%s|sys/saveas,o_%v", style, base64.
        URLEncoding.EncodeToString([]byte(targetImageName)))
    result, err = bucket.ProcessObject(sourceImageName, process)
    if err != nil {
        HandleError(err)
    } else {
        fmt.Println(result)
    }

    // Image processing persistence: Covert the image format.
    targetImageName = "example-formatconvert.jpg"
    style = "image/format,jpg"
    process = fmt.Sprintf("%s|sys/saveas,o_%v", style, base64.
        URLEncoding.EncodeToString([]byte(targetImageName)))
    result, err = bucket.ProcessObject(sourceImageName, process)
    if err != nil {
        HandleError(err)
    } else {
        fmt.Println(result)
    }
}
```

```
}
```

5.16 Error handling

Client errors

Call errors in Go SDK are returned through a unified error interface. The error interface is defined as follows:

```
type error interface {
    Error() string
}
```

Other errors are also returned through this error interface. For example, HTTP request errors are returned as follows:

```
//net.Error
type Error interface {
    error
    Timeout() bool // Is the error a timeout
    Temporary() bool // Is the error temporary
}
```

Server errors

If the request errors occur when OSS Go SDK is used, corresponding errors are returned. In case of HTTP request errors and I/O errors, errors preset in Go are returned. In case of request processing errors of the OSS Server, the following error is returned through the error interface:

```
type ServiceError struct {
    Code      string // Error code returned by OSS to a user
    Message   string // Error details provided by OSS
    RequestId string // UUID that uniquely identifies the request
    HostId    string // OSS cluster that identifies the access
    StatusCode int    // HTTP status code
}
```

If the HTTP status code returned by OSS is not as expected, the following error is returned, also through the error interface:

```
type UnexpectedStatusCodeError struct {
    allowed []int // Expected HTTP status code returned by OSS
    got     int    // Actual HTTP status code returned by OSS
}
```

Example of error handling

The following code is used to demonstrate error handling:

```
package main
import (
```



```

    "fmt"
    "os"
    "strings"
    "github.com/aliyun/aliyun-oss-go-sdk/oss"
)
// Error handling function
func HandleError(err error) {
    fmt.Println("Error:", err)
    os.Exit(-1)
}
func main() {
    // Create an OSSClient instance.
    client, err := oss.New("<yourEndpoint>", "<yourAccessKeyId>", "<
yourAccessKeySecret>")
    if err != nil {
        HandleError(err)
    }
    bucketName := "<yourBucketName>"
    objectName := "<yourObjectName>"
    // Obtain the bucket.
    bucket, err := client.Bucket(bucketName)
    if err != nil {
        HandleError(err)
    }
    // Simple upload: string upload
    err = bucket.PutObject(objectName, strings.NewReader("yourObject
ValueContentString"))
    if err != nil {
        HandleError(err)
    }
}

```

OSS error codes

The following table lists the OSS error codes.

Error code	Description	HTTP status code
AccessDenied	The access is denied.	403
BucketAlreadyExists	The bucket already exists.	409
BucketNotEmpty	The bucket is not empty.	409
EntityTooLarge	The entity is too large.	400
EntityTooSmall	The entity is too small.	400
FileGroupTooLarge	The object group is too large.	400
InvalidLinkName	The name of the object link is the same as the linked object.	400
LinkPartNotExist	The object to which the object link is linked does not exist.	400
ObjectLinkTooLarge	The object link has too many objects.	400

Error code	Description	HTTP status code
FieldItemTooLong	The table field in the post request is too large.	400
FilePartIntegrity	The object part has been changed.	400
FilePartNotExist	The object part does not exist.	400
FilePartStale	The object part has expired.	400
IncorrectNumberOfFilesInPOSTRequest	The number of objects in the post request is incorrect.	400
InvalidArgument	The parameter format is invalid.	400
InvalidAccessKeyId	The AccessKeyId does not exist.	403
InvalidBucketName	The bucket name is invalid.	400
InvalidDigest	The digest is invalid.	400
InvalidEncryptionAlgorithmError	The specified entropy encryption algorithm is invalid.	400
InvalidObjectName	The object name is invalid.	400
InvalidPart	The part is invalid.	400
InvalidPartOrder	The part order is invalid.	400
InvalidPolicyDocument	The policy document is invalid.	400
InvalidTargetBucketForLogging	A target bucket for logging is invalid.	400
InternalError	An error occurs in OSS.	500
MalformedXML	The XML format is invalid.	400
MalformedPOSTRequest	The format of the body in the post request is invalid.	400
MaxPOSTPreDataLengthExceededError	The body, except the object content, uploaded in the post request is too large.	400
MethodNotAllowed	The method is not supported.	405
MissingArgument	A parameter is missing.	411
MissingContentLength	The content length is missing.	411

Error code	Description	HTTP status code
NoSuchBucket	The bucket does not exist.	404
NoSuchKey	The object does not exist.	404
NoSuchUpload	The multipart upload ID does not exist.	404
NotImplemented	The method cannot be implemented.	501
PreconditionFailed	The preconditioning fails.	412
RequestTimeTooSkewed	Client local time and OSS server time differ by more than 15 minutes.	403
RequestTimeout	The request times out.	400
RequestIsNotMultiPartContent	The content type in the post request is invalid.	400
SignatureDoesNotMatch	The signature is incorrect.	403
TooManyBuckets	The number of the user's buckets exceeds the limit.	400
InvalidEncryptionAlgorithmError	The specified entropy encryption algorithm is invalid.	400

**Note:**

In the preceding table, the **Error code** is `OssServiceError.Code`, and the **HTTP status code** is `OssServiceError.StatusCode`.

6 C

6.1 Preface

This document is written based on OSS C SDK 3.5.0.

Compatibility

- For SDK series of 3.*.*: compatible
- For SDK series of 2.*.*:
 - Windows: compatible
 - Linux API: compatible except for the linked list (`aos_list_t`) traversal interface.
 - `os_list_for_each_entry`
 - `aos_list_for_each_entry_reverse`
 - `aos_list_for_each_entry_safe`
 - `aos_list_for_each_entry_safe_reverse`
- For SDK series of 1.0.0: incompatible for only the following APIs
 - `oss_request_options_t`
 - `oss_get_object_to_buffer`
 - `oss_get_object_to_file`
 - `oss_get_object_to_buffer_by_url`
 - `oss_get_object_to_file_by_url`
 - `oss_init_multipart_upload`
 - `oss_complete_multipart_upload`
- For SDK series of 0.0.*: incompatible

SDK source code

For the Java SDK source code, see [GitHub](#).

Code samples

OSS SDK for C provides a variety of code samples for your reference or use. The following table describes the content of code samples:

Sample file	Content
oss_put_object_sample	Upload objects

Sample file	Content
oss_get_object_sample.c	Download objects
oss_append_object_sample.c	Append upload
oss_multipart_upload_sample.c	Multipart upload
oss_resumable_sample.c	Resumable upload , Resumable download
oss_head_object_sample.c	Manage the metadata of an object
oss_list_object_sample.c	List objects
oss_delete_object_sample.c	Delete an object
oss_callback_sample.c	Upload callback
oss_progress_sample.c	Progress bar , Progress bar
oss_crc_sample.c	CRC check during upload or download
oss_image_sample.c	Image processing

6.2 Installation

Install OSS C SDK in Linux

- Install CMake and third-party libraries

When installing OSS C SDK in Linux, you must install CMake and the following third-party libraries: curl, apr, apr-util and minixml.

The following parameters are required to install the environment:

Parameter	Description	Version requirement
CMake	Build and installation tool	Version 2.6.0 and later
curl	Focuses on network problems	Version 7.32.0 and later
apr-util	Focuses on memory management and cross-platform operations.	Version 1.5.2 and later
minixml	Parses XML returned by a request.	We recommend you use version 2.9.

Select the operation system that you need to install CMake and third-party libraries.

— Ubuntu/Debian

- Install CMake

```
sudo apt-get install cmake
```

- Install third-party libraries

```
sudo apt-get install libcurl4-openssl-dev libapr1-dev  
libaprutil1-dev libmxml-dev
```

If the mxml installation package is not included in the yum source, you can install the libraries using RPM. Download the rpm installation package based on your operation system:

- 64-bit: [mxml-2.9-1.x86_64.rpm](#)
- 32-bit: [mxml-2.9-1.i386.rpm](#)

Run the following code to install mxml with the rpm installation package:

```
rpm -ivh mxml-2.9-1.x86_64.rpm
```

— RedHat/Aliyun/CentOS

- Install CMake

```
sudo yum install cmake
```

- Install third-party libraries

```
sudo yum install curl-devel apr-devel apr-util-devel mxml mxml  
-devel
```

— SuSE

- Install CMake

```
zypper install cmake
```

- Install third-party libraries

```
zypper install libcurl-devel libapr1-devel libapr-util1-devel  
mxml-devel
```

— Other Linux

- Install CMake: [Download link](#)

The common installation method is as follows:

```
./configure  
make
```

```
make install
```

**Note:**

When running `./configure`, the default installation path is `/usr/local/`. If you want to specify another path, use the `./configure --prefix` option.

- Install libcurl: [Download link](#)

The common installation method is as follows:

```
./configure
make
make install
```

- Install apr: [Download link](#)

The common installation method is as follows:

```
./configure
make
make install
```

- Install apr-util: [Download link](#)

The common installation method is as follows:

```
// You must specify the --with-apr option in the installation.
./configure --with-apr=/your/apr/install/path
make
make install
```

- Install minixml: [Download link](#)

The common installation method is as follows:

```
./configure
make
sudo make install
```

- Download SDK

- [Download SDK directly](#)

- [Download SDK from GitHub](#)

- [Download historical SDK](#)

- Install SDK

Use **cmake**. If third-party libraries, such as url, apr, apr-util and mxml are not installed in the default method during the compiling process, you must specify the path of their header files and library files.

Install the SDK as follows:

```
cmake .
make
make install
```

An installation example in CentOS is as follows:

```
cmake -f CMakeLists.txt
// The compilation type is Release. Common compilation types include
: Debug, Release, RelWithDebInfo, and MinSizeRel, in which Debug is
the default type.
-DCMAKE_BUILD_TYPE=Release
// Customize the installation directory.
-DCMAKE_INSTALL_PREFIX=/usr/local/
// Specify the path where the header files and library files of
third party libraries, such as curl, apr, apr-util, and xml, are
located,
-DCURL_INCLUDE_DIR=/usr/include/curl
-DCURL_LIBRARY=/usr/lib64/libcurl.so
-DAPR_INCLUDE_DIR=/usr/include/apr-1
-DAPR_LIBRARY=/usr/lib64/libapr-1.so
-DAPR_UTIL_INCLUDE_DIR=/usr/include/apr-1
-DAPR_UTIL_LIBRARY=/usr/lib64/libaprutil-1.so
-DMINIXML_INCLUDE_DIR=/usr/include
-DMINIXML_LIBRARY=/usr/lib64/libmxml.so
// If the "Could not find apr-config/apr-1-config" error occurs
during the compiling process, it indicates that the apr-1-config
file cannot be found in the default path. Add this option.
-DAPR_CONFIG_BIN=/path/to/bin/apr-1-config
// If the "Could not find apu-config/apu-1-config" error occurs, add
this option.
-DAPU_CONFIG_BIN=/path/to/bin/apu-1-config
```

Install OSS C SDK in Windows

- Download SDK
 - [Download SDK directly](#)
 - [Download SDK from GitHub](#)
 - [Download historical SDK](#)
- Install SDK

For detailed steps and common problems when using Visual Studio to compile OSS C SDK, see [Compile and Use Alibaba Cloud OSS C SDK in Windows](#).



Note:

If you use Visual Studio 2012 and later versions, it prompts you to upgrade the project to the latest compiler and libraries. We recommended you to determine whether to upgrade based on your project. You can upgrade if your project uses the latest compiler and libraries.

6.3 Quick start

This topic describes how to use OSS C SDK to complete routine operations such as bucket creation, objects uploads, and object downloads.

Demo

- Linux demo

Linux-based demo: [aliyun-oss-c-sdk-demo.tar.gz](#).

1. Download and extract the demo project.
2. You must specify the installation directory for oss-c-sdk-demo-specified-installation: `/home/your/oss/csdk`. You do not need to specify installation directories for other demo projects because they are automatically installed based on the OSS C SDK and other dependent third-party libraries.
3. Replace the `OSS_ENDPOINT`, `ACCESS_KEY_ID`, `ACCESS_KEY_SECRET`, and `BUCKET_NAME` in the demo with valid values. Use `LD_LIBRARY_PATH` to specify the directory of the OSS C SDK and the dynamic libraries of the dependent libraries if they are not in the system directory.
4. Enter the directory of the project (oss-c-sdk-demo-xxx), run the `make` command to compile the demo project. Then, run the `./main` command to run the executable program. If the project needs to be re-compiled, run the `make clean`

command first before compiling. <https://yq.aliyun.com/articles/60924>

- Windows demo

Windows-based demo: [aliyun-oss-c-sdk-sample.zip](#). You can download more demo projects from [GitHub](#).

1. Download and extract the demo project.
2. Use Visual Studio to open the demo project, and then replace the following parameters in the `oss_config.c` with valid values: `OSS_ENDPOINT`, `ACCESS_KEY_ID`, `ACCESS_KEY_SECRET`, `BUCKET_NAME`, `OBJECT_NAME`, `MULTIPART_UPLOAD_FILE_PATH`, and `DIR_NAME`. Compile and run the project. You can develop your own project based on the demo project.



Note:

For detailed steps in running demo projects with Visual Studio, see related documents. <https://yq.aliyun.com/articles/57947>

Create a bucket

A bucket is a global namespace on OSS used to store objects. It is equivalent to a data container.

The following code creates a bucket:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates the CNAME is
not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as the network and memory. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Create the bucket. */
    aos_status_t *resp_status;
    aos_table_t *resp_headers;
    oss_acl_t oss_acl = OSS_ACL_PRIVATE;
    aos_string_t bucket;
    /* Assign a char* to the bucket. */
    aos_str_set(&bucket, bucket_name);
    resp_status = oss_create_bucket(oss_client_options, &bucket,
oss_acl, &resp_headers);
    /* Identify whether the request succeeds */
    if (aos_status_is_ok(resp_status)) {
        printf("create bucket succeeded\n");
    } else {
        printf("create bucket failed\n");
    }
}
```

```

    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Upload an object

You can run the following code to upload an object to OSS:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates the CNAME is
not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) { = AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pool. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memory in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Initialization parameters */
    aos_string_t bucket;
    aos_string_t object;
    aos_status_t *resp_status;
    aos_table_t *headers;
    aos_table_t *resp_headers;

```

```

aos_list_t buffer;
aos_buf_t *content = NULL;
const char *data = "More than just cloud.";
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
headers = aos_table_make(pool, 0);
/* Convert the char* type data to the aos_list_t type data. */
aos_list_init(&buffer);
content = aos_buf_pack(oss_client_options->pool, data, strlen(data
));
aos_list_add_tail(&content->node, &buffer);
/* Upload an object. */
resp_status = oss_put_object_from_buffer(oss_client_options, &
bucket, &object, &buffer, headers, &resp_headers);
/* Determine whether the upload request is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("put file succeeded\n");
} else {
    printf("put file failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

Download an object

You can run the following code to download a specified object:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *download_filename = "<yourDownloadedFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates the CNAME is
not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
}

```

```

/* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
aos_pool_t *pool;
/* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
aos_pool_create(&pool, NULL);
/* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options */
init_options(oss_client_options);
/* Initialization parameters */
aos_string_t bucket;
aos_string_t object;
aos_string_t file;
aos_status_t *resp_status;
aos_table_t *headers = NULL;
aos_table_t *params = NULL;
aos_table_t *resp_headers = NULL;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_str_set(&file, download_filename);
headers = aos_table_make(pool, 0);
/* Download an object. */
resp_status = oss_get_object_to_file(oss_client_options, &bucket,
&object, headers, params, &file, &resp_headers);
/* Determine whether the download request is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("get object to local file succeeded\n");
} else {
    printf("get object to local file failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

List objects in a bucket

You can run the following code to list objects stored in a specified bucket.

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
}

```

```

/* Determine whether the CNAME is used. 0 indicates the CNAME is
not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool = NULL;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pool. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    acces_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options = NULL;
    /* Allocate memory in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Initialization parameters */
    aos_string_t bucket;
    aos_status_t *resp_status = NULL;
    oss_list_object_params_t *params = NULL;
    oss_list_object_content_t *content = NULL;
    int size = 0;
    char *line = NULL;
    aos_str_set(&bucket, bucket_name);
    params = oss_create_list_object_params(pool);
    /* List objects */
    resp_status = oss_list_object(oss_client_options, &bucket, params
, NULL);
    /* Determine whether the list request is successful. */
    if (! aos_status_is_ok(resp_status))
    {
        printf("list object failed\n");
    }
    else{
        /* Print objects. */
        printf("Object\tSize\tLastModified\n");
        aos_list_for_each_entry(oss_list_object_content_t, content, &
params->object_list, node) {
            ++size;
            line = apr_psprintf(pool, "%.s\t%.s\t%.s\n", content->
key.len, content->key.data,
                content->size.len, content->size.data,
                content->last_modified.len, content->last_modified.
data);
            printf("%s", line);
        }
        printf("Total %d\n", size);
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);

```

```

    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Delete an object.

You can run the following code to delete an object:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates the CNAME is
not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    apr_pool_t *pool = NULL;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pool. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options = NULL;
    /* Allocate memory in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Initialization parameters */
    aos_string_t bucket;
    aos_string_t object;
    aos_status_t *resp_status = NULL;
    aos_table_t *resp_headers = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    /* Delete an object. */
    resp_status = oss_delete_object(oss_client_options, &bucket, &
object, &resp_headers);
}

```

```

/* Determine whether the delete request is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("delete object succeeded\n");
} else {
    printf("delete object failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.4 Initialization

To use OSS C SDK, you must initialize request options (`oss_request_options_t`) and specify an endpoint. For more information about endpoint, see [Regions and endpoints](#) and [Bind a custom domain name](#).

Use the OSS domain name to initialize request options.

You can run the following code to initialize request options with the OSS domain name:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main() {
    aos_pool_t *p;
    oss_request_options_t *options;
    /* Initialize global variables, which are run first before the
program starts. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        return -1;
    }
    /* Initialize the memory pool and options. */
    aos_pool_create(&p, NULL);
    options = oss_request_options_create(p);
    init_options(options);
    /* Logical code, which is not listed here. */
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
}

```



```

aos_pool_destroy(p);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

**Note:**

For the configuration of request options, see related documents. <http://bbs.aliyun.com/read/261421.html?spm=5176.bbsr248504.0.0.NoFhRX>

Use a custom domain name to initialize request options.

You can run the following code to initialize request options with a domain name:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourCustomEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
void init_options(oss_request_options_t *options) {
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Enable the CNAME and bind the custom domain name to the bucket. */
options->config->is_cname = 1;
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main() {
    aos_pool_t *p;
    oss_request_options_t *options;
    /* Initialize global variables, which are run before the program starts. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        return -1;
    }
    /* Initialize the memory pool and options. */
    aos_pool_create(&p, NULL);
    options = oss_request_options_create(p);
    init_options(options);
    /* Logical code, which is not listed here. */
    /* Release the memory pool, that is, memories allocated to resources during the request. */
    aos_pool_destroy(p);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Use STS to initialize request options

You can run the following code to initialize request options with STS:

```

#include "oss_api.h"

```

```

#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *sts_token = "<yourSecurityToken>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Configure STS */
    aos_str_set(&options->config->sts_token, sts_token);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main() {
    aos_pool_t *p;
    oss_request_options_t *options;
    /* Initialize global variables, which are run first before the
program starts. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        return -1;
    }
    /* Initialize the memory pool and options. */
    aos_pool_create(&p, NULL);
    options = oss_request_options_create(p);
    init_options(options);
    /* Logical code, which is not listed here. */
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(p);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Set the timeout value.

You can run the following code to set the timeout value:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;

```

```

/* Used to configure network parameters, such as timeout */
options->ctl = aos_http_controller_create(options->pool, 0);
/* Set the connection timeout value, which is 10 seconds by
default. */
options->ctl->options->connect_timeout = 10;
/* Set the DNS timeout value, which is 60 seconds by default. */
options->ctl->options->dns_cache_timeout = 60;
/* Set the request timeout value:
Set the value of speed_limit to specify the minimum speed that can
be accepted, which is 1,024 Bytes/s by default.
Set the value of speed_time to specify the maximum time period
that can be accepted, which is 15 seconds by default.
The following code indicates that if the transmission speed is
continuously lower than 1,024 Bytes/s for 15 seconds, the request is
time-out. */
options->ctl->options->speed_limit = 1024;
options->ctl->options->speed_time = 15;
}

```

6.5 Bucket

A bucket serves as a container that stores objects. Objects belong to a bucket.

Create a bucket

Run the following code to create a bucket:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
}

```

```

/* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
oss_acl_t oss_acl = OSS_ACL_PRIVATE;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
/* Assign a char* to the aos_string_t bucket. */
aos_str_set(&bucket, bucket_name);
/* Create a bucket. */
resp_status = oss_create_bucket(oss_client_options, &bucket,
oss_acl, &resp_headers);
/* Determine whether the request is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("create bucket succeeded\n");
} else {
    printf("create bucket failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

For more information about bucket naming rules, see naming conventions in [Basic concepts](#). You can specify the ACL and the storage class when you create a bucket, as shown in [Bucket-level permissions](#) and [Storage class](#).

You can run the following code to create a bucket with a specified ACL:

```

/* Create a bucket and set the bucket ACL to public read (which is
private by default). */
resp_status = oss_create_bucket(oss_client_options, &bucket,
OSS_ACL_PUBLIC_READ, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("create bucket succeeded\n");
} else {
    printf("Create Bucket failed \n");
}

```

You can run the following code to create a bucket of the archive class:

```

resp_status = oss_create_bucket_with_storage_class(oss_client
_options, &bucket, OSS_ACL_PRIVATE, OSS_STORAGE_CLASS_ARCHIVE);
/* Determine whether the request is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("create bucket succeeded\n");
} else {
    printf("create bucket failed\n");
}

```

```
}

```

You can run the following code to create a bucket of the Infrequent Access class:

```
resp_status = oss_create_bucket_with_storage_class(oss_client
_options, &bucket, OSS_ACL_PRIVATE, OSS_STORAGE_CLASS_IA);
/* Determine whether the request is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("create bucket succeeded\n");
} else {
    printf("create bucket failed\n");
}
```

List buckets

Run the following code to list all buckets:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout.
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not
    inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration
    information, such as endpoint, access_key_id, access_key_secret,
    is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
```

```

init_options(oss_client_options);
/* Initialization parameters. */
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
oss_list_buckets_params_t *params = NULL;
oss_list_bucket_content_t *content = NULL;
int size = 0;
params = oss_create_list_buckets_params(pool);
/* List all buckets. */
resp_status = oss_list_bucket(oss_client_options, params, &
resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("list buckets succeeded\n");
} else {
    printf("list buckets failed\n");
}
/* Print bucket information. */
aos_list_for_each_entry(oss_list_bucket_content_t, content, &
params->bucket_list, node) {
    printf("BucketName: %s\n", content->name.data);
    ++size;
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

Configure an ACL for a bucket

The ACL of a bucket includes the following permissions.

Permission	Description	Value
Private	The bucket owner and the authorized users can read and write objects in the bucket. Other users cannot perform any operation on the objects.	OSS_ACL_PRIVATE
Public read	The bucket owner and the authorized users can read and write objects in the bucket. Other users can only read the objects in the bucket. Authorize this permission with caution.	OSS_ACL_PUBLIC_READ
Public read-write	All users can read and write objects in the bucket. Authorize this permission with caution.	OSS_ACL_PUBLIC_READ_WRITE

For more information about the ACL, see [Access control](#) in the developer guide.

You can run the following code to configure an ACL for a bucket:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout.
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as
    networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not
    inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration
    information, such as endpoint, access_key_id, access_key_secret,
    is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    /* Assign a char* to the aos_string_t bucket. */
    aos_str_set(&bucket, bucket_name);
    /* Set the bucket ACL to public read.
    resp_status = oss_put_bucket_acl(oss_client_options, &bucket,
    OSS_ACL_PUBLIC_READ, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
```

```

        printf("set bucket acl succeeded\n");
    } else {
        printf("set bucket acl failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Obtain an ACL for a bucket

Run the following code to obtain the ACL for a bucket:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as
networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not
inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration
information, such as endpoint, access_key_id, acces_key_secret,
is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);

```



```

/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_string_t oss_acl;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
/* Assign a char* to the aos_string_t bucket */
aos_str_set(&bucket, bucket_name);
/* Obtain the ACL for a bucket. */
resp_status = oss_get_bucket_acl(oss_client_options, &bucket, &
oss_acl, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("get bucket acl succeeded : %s \n", oss_acl.data);
} else {
    printf("get bucket acl failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

Obtain the region of a bucket

Run the following code to obtain the region (or location) for a bucket:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout.
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as
networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;

```

```

    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not
    inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration
    information, such as endpoint, access_key_id, access_key_secret,
    is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t oss_location;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    /* Assign a char* to the aos_string_t bucket. */
    aos_str_set(&bucket, bucket_name);
    /* Obtain the region of the bucket. */
    resp_status = oss_get_bucket_location(oss_client_options, &bucket,
    &oss_location, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket location succeeded : %s \n", oss_location.
data);
    } else {
        printf("get bucket location failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Obtain bucket information

Run the following code to obtain bucket information:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
}

```

```

    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as
    networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not
    inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration
    information, such as endpoint, access_key_id, acces_key_secret,
    is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    oss_bucket_info_t bucket_info;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    /* Assign a char* to the aos_string_t bucket. */
    aos_str_set(&bucket, bucket_name);
    /* Obtain the bucket information. */
    resp_status = oss_get_bucket_info(oss_client_options, &bucket, &
    bucket_info, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket info succeeded\n");
        printf("location: %s\n", bucket_info.location.data);
        printf("owner_id: %s\n", bucket_info.owner_id.data);
        printf("owner_name: %s\n", bucket_info.owner_name.data);
        printf("created_date: %s\n", bucket_info.created_date.data);
        printf("location: %s\n", bucket_info.location.data);
    } else {
        printf("get bucket info failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

```
}
```

Delete a bucket

Before a bucket is deleted, ensure that all objects in the bucket and fragments that are generated from multipart upload are deleted.



Note:

To delete the fragments that are generated from multipart upload, use `oss_list_upload_part` to list all fragments, and then use `oss_abort_multipart_upload` to delete the fragments. For more information, see [Multipart upload](#).

Run the following code to delete a bucket:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as
    networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not
    inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration
    information, such as endpoint, access_key_id, acces_key_secret,
    is_cname, and curl. */
```

```

    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    /* Assign a char* to the aos_string_t bucket. */
    aos_str_set(&bucket, bucket_name);
    /* Delete the bucket. */
    resp_status = oss_delete_bucket (oss_client_options, &bucket, &
resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("delete bucket succeeded\n");
    } else {
        printf("delete bucket failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

6.6 Upload objects

6.6.1 Overview

In OSS, an object is the basic unit for data operations. OSS C SDK provides the following file upload methods:

- [Simple upload](#): supports the upload of a file up to 5 GB in size. It includes streaming upload and file upload.
- [Append upload](#): supports the upload of a file up to 5 GB in size.
- [Resumable upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files. It also supports concurrent upload and you can define the size of each part.
- [Multipart upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files.



Note:

For more information about the usage scenarios of each upload method, see “Upload files” in OSS Developer Guide.

During the file upload, you can set [Object Meta](#), and check the upload progress in [upload progress bar](#). After you complete the file upload, you can perform [upload callback](#).

6.6.2 Simple upload

For the complete code of simple upload, see [GitHub](#)

Upload data from memory to OSS

You can run the following code to upload data from memory to OSS:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *object_content = "More than just cloud.";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    acces_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_list_t buffer;
    aos_buf_t *content = NULL;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
```

```

    aos_str_set(&object, object_name);
    aos_list_init(&buffer);
    content = aos_buf_pack(oss_client_options->pool, object_content,
strlen(object_content));
    aos_list_add_tail(&content->node, &buffer);
    /* Upload a file. */
    resp_status = oss_put_object_from_buffer(oss_client_options, &
bucket, &object, &buffer, headers, &resp_headers);
    /* Determine whether the upload is successful. */
    if (aos_status_is_ok(resp_status)) {
        printf("put object from buffer succeeded\n");
    } else {
        printf("put object from buffer failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Upload a local file to OSS

You can run the following code to upload a local file to OSS:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
}

```

```

/* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_string_t object;
aos_string_t file;
aos_table_t *headers = NULL;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_str_set(&file, local_filename);
/* Upload a file. */
resp_status = oss_put_object_from_file(oss_client_options, &bucket
, &object, &file, headers, &resp_headers);
/* Determine whether the upload is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("put object from file succeeded\n");
} else {
    printf("put object from file failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.6.3 Append upload

You cannot perform copyObject for appended objects.

Append data from memory

Run the following code to append data from memories

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *object_content = "More than just cloud.";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
}

```



```

    /* Determine whether the CNAME is used. The value 0 indicates that
    the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
    The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
    indicating that the new pool does not inherit any other memory pool.
    */
    aos_pool_create(&p, NULL);
    /* Create and initialize options. This parameter includes global
    configuration information, such as endpoint, access_key_id, acces_key_
    secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate the memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_list_t buffer;
    int64_t position = 0;
    char *next_append_position = NULL;
    aos_buf_t *content = NULL;
    aos_table_t *headers1 = NULL;
    aos_table_t *headers2 = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    headers1 = aos_table_make(pool, 0);
    /* Obtain the position where the object is appended for the first
    time. */
    resp_status = oss_head_object(oss_client_options, &bucket, &object
    , headers1, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        next_append_position = (char*)(apr_table_get(resp_headers, "x-
    oss-next-append-position"));
        position = atoi(next_append_position);
    }
    /* Append the file. */
    headers2 = aos_table_make(pool, 0);
    aos_list_init(&buffer);
    content = aos_buf_pack(pool, object_content, strlen(object_content
    ));
    aos_list_add_tail(&content->node, &buffer);
    resp_status = oss_append_object_from_buffer(oss_client_options, &
    bucket, &object, position, &buffer, headers2, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("append object from buffer succeeded\n");
    } else {

```

```

        printf("append object from buffer failed\n");
    }
    /* Release the memory pool, that is, the memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Append data from a local file

Run the following code to append data from a local file:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
options->config->is_cname = 0;
/* Configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
    The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
    indicating that the new pool does not inherit any other memory pool.
    */
    aos_pool_create(&p, NULL);
    /* Create and initialize options. This parameter includes global
    configuration information, such as endpoint, access_key_id, acces_key_
    secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate the memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_string_t object;

```

```

aos_string_t file;
int64_t position = 0;
char *next_append_position = NULL;
aos_table_t *headers1 = NULL;
aos_table_t *headers2 = NULL;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_str_set(&file, local_filename);
/* Obtain the position where the object is appended for the first
time. */
resp_status = oss_head_object(oss_client_options, &bucket, &object
, headers1, &resp_headers);
if(aos_status_is_ok(resp_status)) {
    next_append_position = (char*)(apr_table_get(resp_headers, "x-
oss-next-append-position"));
    position = atoi(next_append_position);
}
/* Append the file. */
resp_status = oss_append_object_from_file(oss_client_options, &
bucket, &object, position, &file, headers2, &resp_headers);
/* Determine whether the append upload is successful. */
if (aos_status_is_ok(resp_status)) {
    printf("append object from file succeeded\n");
} else {
    printf("append object from file failed\n");
}
/* Release the memory pool, that is, the memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

If the file already exists, the following may occur:

- If the file cannot be uploaded with append upload, an `ObjectNotAppendable` exception occurs.
- If the file can be uploaded with append upload, the file is upload by the Put Object method and overwrites the existing object. The object type is changed to Normal Object. After the Head Object operation is performed, the system returns `x-oss-object-type`, which indicates the type of the object.

6.6.4 Resumable upload

In resumable upload, the object is divided into multiple parts, which are then uploaded separately. After all the parts are uploaded, they are merged into a complete object to finish the upload.

Current upload progress is recorded into a checkpoint file during the upload. If a part fails to be uploaded during the process, the object is uploaded from the part recorded in the checkpoint file when the upload restarts, that is, the resumable upload. After the upload is complete, the checkpoint is deleted.

You can use the `oss_resumable_clt_params_t` method to achieve resumable upload.

Common parameters used in this method are listed as follows:

Parameter	Description
<code>thread_num</code>	The number of concurrent threads, which is 1 by default.
<code>enable_checkpoint</code>	Whether to enable resumable upload, which is disabled by default.
<code>partSize</code>	The part size, ranging from 100 KB to 5 GB.
<code>checkpoint_path</code>	The path that the checkpoint file is stored, which is <code>{upload_file_path}.cp</code> by default.

You can run the following code to perform resumable upload:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that it is not
used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
```

```

    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_list_t resp_body;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    oss_resumable_clt_params_t *clt_params;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    aos_str_set(&file, local_filename);
    aos_list_init(&resp_body);
    /* Resumable upload. */
    clt_params = oss_create_resumable_clt_params_content(pool, 1024 *
100, 3, AOS_TRUE, NULL);
    resp_status = oss_resumable_upload_file(oss_client_options, &
bucket, &object, &file, headers, NULL, clt_params, NULL, &resp_headers
, &resp_body);
    if (aos_status_is_ok(resp_status)) {
        printf("resumable upload succeeded\n");
    } else {
        printf("resumable upload failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

6.6.5 Multipart upload

To enable multipart upload, perform the following steps:

1. Initiate a multipart upload event.

You can call `ossClient.initiateMultipartUpload` to return the globally unique uploadId created in OSS.

2. Upload parts.

You can call `ossClient.uploadPart` to upload part data.



Note:

- For parts with a same uploadId, parts are sequenced by their part numbers. If you have uploaded a part and use the same part number to upload another part, the later part will replace the former part.
- OSS places the MD5 value of part data in ETag and returns the MD5 value to the user.

- SDK automatically configures Content-MD5. OSS calculates the MD5 value of uploaded data and compares it with the MDS value calculated by SDK. If the two values vary, the error code of InvalidDigest is returned.

3. Complete multipart upload.

After you have uploaded all parts, call `partossClient.completeMultipartUpload` to combine these parts into a complete object.

The following code is used as a complete example that describes the process of multipart upload:

```
#include "oss_api.h"
#include "aos_http_io.h"
#include <sys/stat.h>
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int64_t get_file_size(const char *file_path)
{
    int64_t filesize = -1;
    struct stat statbuff;
    if(stat(file_path, &statbuff) < 0){
        return filesize;
    } else {
        filesize = statbuff.st_size;
    }
    return filesize;
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
```

```

/* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_string_t object;
oss_upload_file_t *upload_file = NULL;
aos_string_t upload_id;
aos_table_t *headers = NULL;
aos_table_t *complete_headers = NULL;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_str_null(&upload_id);
headers = aos_table_make(p, 1);
complete_headers = aos_table_make(p, 1);
int part_num = 1;
/* Initialize multipart upload and obtain an upload ID (upload_id)
). */
resp_status = oss_init_multipart_upload(oss_client_options, &
bucket, &object, &upload_id, headers, &resp_headers);
/* Determines whether the slice upload Initialization is
successful. */
if (aos_status_is_ok(resp_status)) {
    printf("Init multipart upload succeeded, upload_id:%.*s\n",
        upload_id.len, upload_id.data);
} else {
    printf("Init multipart upload failed, upload_id:%.*s\n",
        upload_id.len, upload_id.data);
}
/* Upload the parts. */
int64_t file_length = 0;
int64_t pos = 0;
file_length = get_file_size(local_filename);
while(pos < file_length) {
    upload_file = oss_create_upload_file(pool);
    aos_str_set(&upload_file->filename, local_filename);
    upload_file->file_pos = pos;
    pos += 100 * 1024;
    upload_file->file_last = pos < file_length ? pos : file_length
;
    resp_status = oss_upload_part_from_file(oss_client_options, &
bucket, &object, &upload_id, part_num++, upload_file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("Multipart upload part from file succeeded\n");
    } else {
        printf("Multipart upload part from file failed\n");
    }
}
oss_list_upload_part_params_t *params = NULL;
aos_list_t complete_part_list;
/* Obtain uploaded parts. */
params = oss_create_list_upload_part_params(pool);
params->max_ret = 1000;
aos_list_init(&complete_part_list);

```

```

    resp_status = oss_list_upload_part(oss_client_options, &bucket, &
object, &upload_id, params, &resp_headers);
    /* Determine whether the part list is successfully obtained. */
    if (aos_status_is_ok(resp_status)) {
        printf("List multipart succeeded\n");
    } else {
        printf("List multipart failed\n");
    }
    oss_complete_part_content_t *complete_part_content = NULL;
    oss_list_part_content_t *part_content = NULL;
    aos_list_for_each_entry(oss_list_part_content_t, part_content, &
params->part_list, node) {
        complete_part_content = oss_create_complete_part_content(pool
);
        aos_str_set(&complete_part_content->part_number, part_content-
>part_number.data);
        aos_str_set(&complete_part_content->etag, part_content->etag.
data);
        aos_list_add_tail(&complete_part_content->node, &complete_p
art_list);
    }
    /* Complete multipart upload. */
    resp_status = oss_complete_multipart_upload(oss_client_options, &
bucket, &object, &upload_id,
        &complete_part_list, complete_headers, &resp_headers);
    /* Determine whether the multipart upload is complete. */
    if (aos_status_is_ok(resp_status)) {
        printf("Complete multipart upload from file succeeded,
upload_id:%.*s\n",
            upload_id.len, upload_id.data);
    } else {
        printf("Complete multipart upload from file failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

**Note:**

You must provide all valid PartETags when you call `oss_complete_multipart_upload` to obtain uploaded parts. The ETags can be obtained in two methods: 1. The ETag of a part is included in the returned result when the part is uploaded. 2. You can call `oss_list_upload_part` to obtain the ETag of an uploaded part. In the example, the second method is used.

Cancel a multipart upload event

Run the following code to cancel a multipart upload event:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";

```



```

const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as

networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not

inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration

information, such as endpoint, access_key_id, acces_key_secret,
is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t upload_id;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    aos_str_null(&upload_id);
    /* Initialize multipart upload and obtain an upload ID (upload_id
    ). */
    resp_status = oss_init_multipart_upload(oss_client_options, &
    bucket, &object, &upload_id, headers, &resp_headers);
    /* Determine whether the multipart upload is initialized
    successfully. */
    if (aos_status_is_ok(resp_status)) {
        printf("Init multipart upload succeeded, upload_id:%.*s\n",
        upload_id.len, upload_id.data);
    }
}

```

```

    } else {
        printf("Init multipart upload failed, upload_id:%.*s\n",
            upload_id.len, upload_id.data);
    }
    /* Cancel the multipart upload. */
    resp_status = oss_abort_multipart_upload(oss_client_options, &
        bucket, &object, &upload_id, &resp_headers);
    /* Determine whether the multipart upload is canceled successfully
    . */
    if (aos_status_is_ok(resp_status)) {
        printf("Abort multipart upload succeeded, upload_id:%.*s\n",
            upload_id.len, upload_id.data);
    } else {
        printf("Abort multipart upload failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

**Note:**

If you cancel a multipart upload event, you are not allowed to perform any other operations with this upload_id anymore. The uploaded parts will be deleted.

6.6.6 Upload progress bars

You can use progress bars to indicate the upload or download progress.

For the complete code of upload progress bar, see [GitHub](#).

The following code is used as an example to describe how to view progress information with PutObject:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */

```

```

    options->ctl = aos_http_controller_create(options->pool, 0);
}
void percentage(int64_t consumed_bytes, int64_t total_bytes)
{
    assert(total_bytes >= consumed_bytes);
    printf("%%%" APR_INT64_T_FMT "\n", consumed_bytes * 100 /
total_bytes);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_list_t resp_body;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    aos_str_set(&file, local_filename);
    /* Upload with a progress bar displayed. */
    resp_status = oss_do_put_object_from_file(oss_client_options,
&bucket, &object, &file, NULL, NULL, percentage, &resp_headers, &
resp_body);
    if (aos_status_is_ok(resp_status)) {
        printf("put object from file succeeded\n");
    } else {
        printf("put object from file failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

oss_put_object_from_file and oss_put_object_from_buffer do not support progress bars.

6.6.7 Upload callback

For the complete code of upload callback, see [GitHub](#).

Run the following code for upload callback:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *object_content = "More than just cloud.";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    aos_pool_t *p = NULL;
    aos_status_t *s = NULL;
    aos_string_t bucket;
    aos_string_t object;
    aos_table_t *headers = NULL;
    oss_request_options_t *options = NULL;
    aos_table_t *resp_headers = NULL;
    aos_list_t resp_body;
    aos_list_t buffer;
    aos_buf_t *content;
    char *buf = NULL;
    int64_t len = 0;
    int64_t size = 0;
    int64_t pos = 0;
    char b64_buf[1024];
    int b64_len;
    /* Use the JSON format. */
    char *callback = "{
        \"callbackUrl\": \"http://oss-demo.aliyuncs.com:23450\",
        \"callbackHost\": \"oss-cn-hangzhou.aliyuncs.com\",
        \"callbackBody\": \"bucket=${bucket}&object=${object}&size=${
size}&mimeType=${mimeType}\",
        \"callbackBodyType\": \"application/x-www-form-urlencoded\"
    }";
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Initialize parameters. */
    aos_pool_create(&p, NULL);
```

```

options = oss_request_options_create(p);
init_options(options);
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_list_init(&resp_body);
aos_list_init(&buffer);
content = aos_buf_pack(options->pool, object_content, strlen(
object_content));
aos_list_add_tail(&content->node, &buffer);
/* Add callback into the header. */
b64_len = aos_base64_encode((unsigned char*)callback, strlen(
callback), b64_buf);
b64_buf[b64_len] = '\0';
headers = aos_table_make(p, 1);
apr_table_set(headers, OSS_CALLBACK, b64_buf);
/* Start upload callback. */
s = oss_do_put_object_from_buffer(options, &bucket, &object, &
buffer,
    headers, NULL, NULL, &resp_headers, &resp_body);
if (aos_status_is_ok(s)) {
    printf("put object from buffer succeeded\n");
} else {
    printf("put object from buffer failed\n");
}
/* Obtain the buffer length. */
len = aos_buf_list_len(&resp_body);
buf = (char *)aos_palloc(p, (apr_size_t)(len + 1));
buf[len] = '\0';
/* Copy the content in the buffer to the memory. */
aos_list_for_each_entry(aos_buf_t, content, &resp_body, node) {
    size = aos_buf_size(content);
    memcpy(buf + pos, content->pos, (size_t)size);
    pos += size;
}
/* Release the memory pool, that is, the memories allocated to
resources during the request. */
aos_pool_destroy(p);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

For more information about upload callback, see [Upload callback](#). For detailed debugging methods and troubleshooting information, see [Upload callback error and exclusion](#).

6.7 Download objects

6.7.1 Overview

For the complete code of object download, see [GitHub](#).

OSS C SDK provides the following download methods:

- [Download to your local file](#)
- [Download to local memory](#)

- [Range download](#)
- [Resumable download](#)

You can view the download progress shown in the [download progress bar](#).

6.7.2 Download an object to a local file

For the complete code of downloading OSS object, see [GitHub](#).

You can run the following code to download the specified OSS object to a local file.

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_table_t *params;
```

```

aos_table_t *headers = NULL;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_str_set(&file, local_filename);
params = aos_table_make(pool, 0);
/* Download the object. A new local file is created if the
specified file does not exist. If the specified local file exists, it
is overwritten. */
resp_status = oss_get_object_to_file(oss_client_options, &bucket,
&object, headers, params, &file, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("Get object from file succeeded\n");
} else {
    printf("Get object from file failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

**Note:**

Compared to the 1.0.0 version, the params parameter is added to the `oss_get_object_to_file` interface, and the value of the headers and params parameters can be NULL.

6.7.3 Download to your local memory

For the complete code of object download, see [GitHub](#).

Run the following code to download a specified object to local memory:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])

```

```

{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_list_t buffer;
    aos_buf_t *content = NULL;
    aos_table_t *params = NULL;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    char *buf = NULL;
    int64_t len = 0;
    int64_t size = 0;
    int64_t pos = 0;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    aos_list_init(&buffer);
    /* Download an object to local memory. */
    resp_status = oss_get_object_to_buffer(oss_client_options, &bucket
, &object,
                                     headers, params, &buffer, &resp_heade
rs);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to buffer succeeded\n");
        /* Copy the downloaded content to the buffer. */
        len = aos_buf_list_len(&buffer);
        buf = aos_palloc(pool, len + 1);
        buf[len] = '\0';
        aos_list_for_each_entry(aos_buf_t, content, &buffer, node) {
            size = aos_buf_size(content);
            memcpy(buf + pos, content->pos, size);
            pos += size;
        }
    }
    else {
        printf("get object to buffer failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```



```
}
```

6.7.4 Range download

If you only need part of the data in an object, you can use range downloads to download specified content.

Run the following code for range download:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_list_t buffer;
    aos_buf_t *content = NULL;
    aos_table_t *params = NULL;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
```

```

char *buf = NULL;
int64_t len = 0;
int64_t size = 0;
int64_t pos = 0;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_list_init(&buffer);
headers = aos_table_make(pool, 1);
/* Set the download range, which ranges from the 20th byte to the
100th byte. */
apr_table_set(headers, "Range", "bytes=20-100");
/* Download the object to memory. */
resp_status = oss_get_object_to_buffer(oss_client_options, &bucket
, &object, headers, params, &buffer, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("get object to buffer succeeded\n");
    /* Obtain the buffer length. */
    aos_list_for_each_entry(aos_buf_t, content, &buffer, node) {
        len += aos_buf_size(content);
    }
    buf = aos_palloc(pool, (apr_size_t)(len + 1));
    buf[len] = '\0';
    /* Copy the content in the buffer to memory. */
    aos_list_for_each_entry(aos_buf_t, content, &buffer, node) {
        size = aos_buf_size(content);
        memcpy(buf + pos, content->pos, (size_t)size);
        pos += size;
    }
}
else {
    printf("get object to buffer failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.7.5 Resumable download

Large-sized objects may fail to be downloaded because of unstable network or other exceptions, and the entire object needs to be downloaded again. However, the object may still fail to be downloaded after multiple attempts. Therefore, OSS provides resumable download.

To enable resumable download, you need to split the object you want to download into multiple parts and download them separately. After you have downloaded all parts, these parts will be combined into a complete object.

You can use `oss_resumable_clt_params_t` to enable resumable download. `oss_resumable_clt_params_t` contains the following parameters:

Parameter	Description
thread_num	The number of concurrent threads, which is 1 by default.
enable_checkpoint	Determines whether to enable resumable download, which is disabled by default.
partSize	Specifies the size of a part. The value can be between 1 byte to 5 GB and the unit is byte.
checkpoint_path	The path where the checkpoint file is located, which is under {upload_file_path}.cp by default.

This `checkpoint` file stores information about the download progress. If you fail to download a part, the download will continue based on the progress recorded in the checkpoint file. After the object is downloaded, the checkpoint file will be deleted.

Run the following code for resumable download:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
```

```

/* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_string_t object;
aos_string_t file;
aos_table_t *headers = NULL;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
oss_resumable_clt_params_t *clt_params;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_str_set(&file, local_filename);
/* Download the object using resumable download. */
clt_params = oss_create_resumable_clt_params_content(pool, 1024 *
100, 3, AOS_TRUE, NULL);
resp_status = oss_resumable_download_file(oss_client_options, &
bucket, &object, &file, headers, NULL, clt_params, NULL, &resp_headers
);
if (aos_status_is_ok(resp_status)) {
    printf("download succeeded\n");
} else {
    printf("download failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.7.6 Download progress bars

You can use progress bars to indicate the upload or download progress.

For the complete code of download progress bar, see [GitHub](#).

The following code is used as an example to describe how to use the download progress bar.

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
const char *download_filename = "<yourDownloadFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
}

```

```

    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
void percentage(int64_t consumed_bytes, int64_t total_bytes)
{
    assert(total_bytes >= consumed_bytes);
    printf("%%%" APR_INT64_T_FMT "\n", consumed_bytes * 100 /
total_bytes);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_table_t *resp_headers = NULL;
    aos_list_t resp_body;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    aos_str_set(&file, local_filename);
    /* Upload with a progress bar displayed. */
    resp_status = oss_do_put_object_from_file(oss_client_options,
    &bucket, &object, &file, NULL, NULL, percentage, &resp_headers, &
    resp_body);
    if (aos_status_is_ok(resp_status)) {
        printf("put object from file succeeded\n");
    } else {
        printf("put object from file failed\n");
    }
    /* Download with a progress bar displayed. */
    aos_pool_create(&pool, NULL);
    oss_client_options = oss_request_options_create(pool);
    init_options(oss_client_options);
    aos_str_set(&file, download_filename);
    resp_status = oss_do_get_object_to_file(oss_client_options, &
    bucket, &object, NULL, NULL, &file, percentage, NULL);

```

```
if (aos_status_is_ok(resp_status)) {
    printf("get object to file succeeded\n");
} else {
    printf("get object to file failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}
```

oss_get_object_from_file and oss_get_object_from_buffer do not support progress bars.

6.8 Manage objects

6.8.1 Overview

You can perform the following operations on objects in a bucket with APIs:

- [Manage ACL for an object](#)
- [Manage Object Meta](#)
- [List objects](#)
- [Copy objects](#)
- [Delete objects](#)
- [Restore an archive object](#)
- [Manage a symbolic link](#)

6.8.2 Manage ACL for an object

The following table describes the permissions included in the Access Control List (ACL) for an object.

Permission	Description	Value
default	The ACL of an object is the same with that of its bucket.	OSS_ACL_DEFAULT
Private	Only the object owner and authorized users can read and write the object.	OSS_ACL_PRIVATE
Public read	Only the object owner and authorized users can read and write the object. Other users can only read the object	OSS_ACL_PUBLIC_READ

Permission	Description	Value
	. Authorize this permission with caution.	
Public read-write	All users can read and write the object. Authorize this permission with caution.	OSS_ACL_PUBLIC_READ_WRITE

The ACL of objects take precedence over that of buckets. For example, if the ACL of a bucket is private, while the object ACL is public read-write, all users can read and write the object. If an object is not configured with an ACL, its ACL is the same as that of its bucket by default.

Configure an ACL for an object

You can run the following code to configure an ACL for an object:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
```

```

/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_string_t object;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
oss_acl_e oss_acl = OSS_ACL_PUBLIC_READ;
/* Configure an ACL for an object. */
resp_status = oss_put_object_acl(oss_client_options, &bucket, &
object, oss_acl, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("put object acl success! \n");
} else {
    printf("put object acl failed! \n");
}
/* Obtain the ACL for an object. */
aos_string_t oss_acl_string;
resp_status = oss_get_object_acl(oss_client_options, &bucket, &
object, &oss_acl_string, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("get object acl success! \n");
    printf("acl: %s \n", oss_acl_string.data);
} else {
    printf("get object acl failed! \n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.8.3 Manage Object Meta

Object Meta includes HTTP headers and user-defined Object Meta. For more information, see [Object Meta](#) in OSS Developer Guide.

Obtain Object Meta

After uploading files to OSS or before reading objects from OSS, you can use the `oss_get_object_meta` interface to obtain some of meta information about the objects, such as the length and type. Run the following code to configure and obtain Object Meta:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
}

```



```

    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
indicating that the new pool does not inherit any other memory pool.
*/
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes global
configuration information, such as endpoint, access_key_id, access_key_
secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate the memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_table_t *headers;
    aos_list_t buffer;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_buf_t *content = NULL;
    char *content_length_str = NULL;
    char *object_type = NULL;
    char *object_author = NULL;
    int64_t content_length = 0;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    headers = aos_table_make(pool, 2);
    // Configure custom Object Meta. */
    apr_table_set(headers, "Expires", "Fri, 28 Feb 2032 05:38:42 GMT
");
    apr_table_set(headers, "x-oss-meta-author", "oss");
    aos_list_init(&buffer);
    content = aos_buf_pack(oss_client_options->pool, object_content,
strlen(object_content));
    aos_list_add_tail(&content->node, &buffer);
    /* Set object permissions and upload the object from the cache. */
    resp_status = oss_put_object_from_buffer(oss_client_options, &
bucket, &object,
        &buffer, headers, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put object from buffer with md5 succeeded\n");
    }
}

```

```

    } else {
        printf("put object from buffer with md5 failed\n");
    }
    /* Obtain the object permission. */
    resp_status = oss_get_object_meta(oss_client_options, &bucket, &
object, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        content_length_str = (char*)apr_table_get(resp_headers,
OSS_CONTENT_LENGTH);
        if (content_length_str != NULL) {
            content_length = atol(content_length_str);
        }
        object_author = (char*)apr_table_get(resp_headers, OSS_AUTHOR
IZATION);
        object_type = (char*)apr_table_get(resp_headers, OSS_OBJECT
_TYPE);
        printf("get object meta succeeded, object author:%s, object
type:%s, content_length:%ld\n", object_author, object_type, content_le
ngth);
    } else {
        printf("req:%s, get object meta failed\n", resp_status->req_id
);
    }
    /* Release the memory pool, that is, the memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

**Note:**

For detailed information about HTTP header, see [RFC2616](#).

6.8.4 List objects

For the complete code for listing objects, see [GitHub](#).

OSS objects are listed alphabetically. You can use `oss_list_object` to list all objects in a bucket. The following table describes common parameters used to list objects.

Parameter	Description
delimiter	Specifies a delimiter used to group objects. All those objects whose names contain the specified prefix and after which the delimiter occurs for the first time, act as a group of elements, that is, commonPrefixes.
prefix	Specifies the prefix that the listed objects must contain.
max_ret	Specifies the maximum number of objects that can be listed. The default value is 1000.

Parameter	Description
marker	Specifies the initial object that is listed.

List all objects

You can run the following code to list all objects in the current bucket.

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_status_t *resp_status = NULL;
    oss_list_object_params_t *params = NULL;
    oss_list_object_content_t *content = NULL;
    int size = 0;
    char *line = NULL;
    char *prefix = "";
    char *nextMarker = "";
    aos_str_set(&bucket, bucket_name);
    params = oss_create_list_object_params(pool);
```

```

    params->max_ret = 100;
    aos_str_set(&params->prefix, prefix);
    aos_str_set(&params->marker, nextMarker);
    printf("Object\tSize\tLastModified\n");
    /* List all objects. */
    do {
        resp_status = oss_list_object(oss_client_options, &bucket,
params, NULL);
        if (! aos_status_is_ok(resp_status))
        {
            printf("list object failed\n");
            break;
        }
        aos_list_for_each_entry(oss_list_object_content_t, content, &
params->object_list, node) {
            ++size;
            line = apr_psprintf(pool, "%.s\t%.s\t%.s\n", content->
key.len, content->key.data,
                content->size.len, content->size.data,
                content->last_modified.len, content->last_modified.
data);
            printf("%s", line);
        }
        nextMarker = apr_psprintf(pool, "%.s", params->next_marker.
len, params->next_marker.data);
        aos_str_set(&params->marker, nextMarker);
        aos_list_init(&params->object_list);
        aos_list_init(&params->common_prefix_list);
    } while (params->truncated == AOS_TRUE);
    printf("Total %d\n", size);
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

**Note:**

By default, if a bucket contains more than 1,000 objects, only the first 1,000 objects are returned and the truncated parameter in the returned results is true. Additionally, the next_marker is returned to serve as the start point of next read. To adjust the number of returned objects, you can modify the max_ret parameter or use the marker parameter for multiple reads.

List specified number of objects

You can run the following code to list specified number of objects.

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{

```

```

    options->config = oss_config_create(options->pool);
    /* aos_str_set uses a char* string to initialize the aos_string_t
type.*/
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used.*/
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout.*/
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories.*/
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    apr_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pool. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Memories for options are allocated by the memory pool and are
released after the memory pool is released. Therefore, you do not need
to release the memory for options individually. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters */
    aos_string_t bucket;
    aos_status_t *resp_status = NULL;
    oss_list_object_params_t *params = NULL;
    oss_list_object_content_t *content = NULL;
    int size = 0;
    char *line = NULL;
    char *prefix = "";
    char *nextMarker = "";
    aos_str_set(&bucket, bucket_name);
    params = oss_create_list_object_params(pool);
    /* Set the maximum number of listed objects to 200. */
    params->max_ret = 200;
    aos_str_set(&params->prefix, prefix);
    aos_str_set(&params->marker, nextMarker);
    printf("Object\tSize\tLastModified\n");
    /* List all objects */
    resp_status = oss_list_object(oss_client_options, &bucket, params
, NULL);
    if (! aos_status_is_ok(resp_status))
    {
        printf("list object failed\n");
    }
    aos_list_for_each_entry(oss_list_object_content_t, content, &
params->object_list, node) {
        ++size;

```

```

        line = apr_psprintf(pool, "%.s\t%.s\t%.s\n", content->key.
len, content->key.data,
        content->size.len, content->size.data,
        content->last_modified.len, content->last_modified.data);
        printf("%s", line);
    }
    printf("Total %d\n", size);
    /* Release the memory pool after a request is executed, which
means that memories allocated for all resources during the request are
released. */
    aos_pool_destroy(pool);
    /* Before the project ends, call the aos_http_io_deinitialize
method to release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

List objects with specified prefix

You can run the following code to list objects with specified prefix.

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* aos_str_set uses a char* string to initialize the aos_string_t
data type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, including networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    /*
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;

```

```

/* Memories for options are allocated by the memory pool and are
released after the memory pool is released. Therefore, you do not need
to release the memory for options individually. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters */
aos_string_t bucket;
aos_status_t *resp_status = NULL;
oss_list_object_params_t *params = NULL;
oss_list_object_content_t *content = NULL;
int size = 0;
char *line = NULL;
/* List objects with specified prefix. */
char *prefix = "<yourObjectPefix>";
char *nextMarker = "";
aos_str_set(&bucket, bucket_name);
params = oss_create_list_object_params(pool);
params->max_ret = 100;
aos_str_set(&params->prefix, prefix);
aos_str_set(&params->marker, nextMarker);
printf("Object\tSize\tLastModified\n");
/* List all objects. */
do {
    resp_status = oss_list_object(oss_client_options, &bucket,
params, NULL);
    if (! aos_status_is_ok(resp_status))
    {
        printf("list object failed\n");
        break;
    }
    aos_list_for_each_entry(oss_list_object_content_t, content, &
params->object_list, node) {
        ++size;
        line = apr_psprintf(pool, "%.s\t%.s\t%.s\n", content->
key.len, content->key.data,
        content->size.len, content->size.data,
        content->last_modified.len, content->last_modified.
data);
        printf("%s", line);
    }
    nextMarker = apr_psprintf(pool, "%.s", params->next_marker.
len, params->next_marker.data);
    aos_str_set(&params->marker, nextMarker);
    aos_list_init(&params->object_list);
    aos_list_init(&params->common_prefix_list);
} while (params->truncated == AOS_TRUE);
printf("Total %d\n", size);
/* Release the memory pool after a request is executed, which
means that memories allocated for all resources during the request are
released. */
aos_pool_destroy(pool);
/* Before the project ends, call the aos_http_io_deinitialize
method to release allocated global resources. */
aos_http_io_deinitialize();
return 0;

```

```
}
```

Specifies the initial object that is listed.

The value of marker is the name of the initial object. You can run the following code to list objects after marker in alphabetic order.

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* aos_str_set uses a char* string to initialize the aos_string_t
type.*/
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used.*/
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout.*/
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as network and memories.*/
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Memories for options are allocated by the memory pool and are
released after the memory pool is released. Therefore, you do not need
to release the memory for options individually. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters */
    aos_string_t bucket;
    aos_status_t *resp_status = NULL;
    oss_list_object_params_t *params = NULL;
    oss_list_object_content_t *content = NULL;
    int size = 0;
    char *line = NULL;
    char *prefix = "";
    Specifies the initial object that is listed. */
    char *nextMarker = "<yourObjectMarker>";
```



```

aos_str_set(&bucket, bucket_name);
params = oss_create_list_object_params(pool);
params->max_ret = 100;
aos_str_set(&params->prefix, prefix);
aos_str_set(&params->marker, nextMarker);
printf("Object\tSize\tLastModified\n");
/* List all objects */
do {
    resp_status = oss_list_object(oss_client_options, &bucket,
params, NULL);
    if (! aos_status_is_ok(resp_status))
    {
        printf("list object failed\n");
        break;
    }
    aos_list_for_each_entry(oss_list_object_content_t, content, &
params->object_list, node) {
        ++size;
        line = apr_psprintf(pool, "%.s\t%.s\t%.s\n", content->
key.len, content->key.data,
        content->size.len, content->size.data,
        content->last_modified.len, content->last_modified.
data);
        printf("%s", line);
    }
    nextMarker = apr_psprintf(pool, "%.s", params->next_marker.
len, params->next_marker.data);
    aos_str_set(&params->marker, nextMarker);
    aos_list_init(&params->object_list);
    aos_list_init(&params->common_prefix_list);
} while (params->truncated == AOS_TRUE);
printf("Total %d\n", size);
/* Release the memory pool after a request is executed, which
means that memories allocated for all resources during the request are
released. */
aos_pool_destroy(pool);
/* Before the project ends, call the aos_http_io_deinitialize
method to release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.8.5 Delete objects



Warning:

Delete objects with caution because deleted objects cannot be recovered.

For the complete code of deleting objects, see [GitHub](#).

Delete an object

Run the following code to delete a single object:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";

```

```

const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    /* Assign char* data to the aos_string_t bucket. */
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    /* Delete an object. */
    resp_status = oss_delete_object(oss_client_options, &bucket, &
object, &resp_headers);
    /* Determine whether the object is deleted successfully. */
    if (aos_status_is_ok(resp_status)) {
        printf("delete object succeed\n");
    } else {
        printf("delete object failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

```
}
```

Delete multiple objects

Run the following code to delete multiple objects simultaneously:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name1 = "<yourObjectName1>";
const char *object_name2 = "<yourObjectName2>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object1;
    aos_string_t object2;
    int is_quiet = 1;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object1, object_name1);
    aos_str_set(&object2, object_name2);
    /* Construct the list of objects to be deleted. */
    aos_list_t object_list;
```

```

aos_list_t deleted_object_list;
oss_object_key_t *content1;
oss_object_key_t *content2;
aos_list_init(&object_list);
aos_list_init(&deleted_object_list);
content1 = oss_create_oss_object_key(pool);
aos_str_set(&content1->key, object_name1);
aos_list_add_tail(&content1->node, &object_list);
content2 = oss_create_oss_object_key(pool);
aos_str_set(&content2->key, object_name2);
aos_list_add_tail(&content2->node, &object_list);
/* Delete objects in the list. `is_quiet` is used to determine
whether the result of deletion is returned. */
resp_status = oss_delete_objects(oss_client_options, &bucket, &
object_list, is_quiet, &resp_headers, &deleted_object_list);
if (aos_status_is_ok(resp_status)) {
    printf("delete objects succeeded\n");
} else {
    printf("delete objects failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

Delete multiple objects with a specified prefix

You can delete a directory by deleting multiple objects with a specified prefix. For example, you can delete the `dir` directory by deleting objects with the prefix `dir/`. Run the following code to delete multiple objects with a specified prefix simultaneously:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_prefix = "<yourObjectNamePrefix>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
}

```

```

    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t prefix;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&prefix, object_prefix);
    /* Delete objects with a specified prefix. */
    resp_status = oss_delete_objects_by_prefix(oss_client_options, &
    bucket, &prefix);
    if (aos_status_is_ok(resp_status)) {
        printf("delete objects by prefix succeeded\n");
    } else {
        printf("delete objects by prefix failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```



Warning:

If the prefix is an empty string or null, all objects in the bucket will be deleted. Perform this operation with caution.

6.8.6 Copy objects

Copy a small-sized object

You must note the following limits before copy a small-sized object:

- The user must have the read and write permission on the source object.
- You cannot copy an object from a region to another region. For example, you cannot copy an object from a bucket in Hangzhou region to a bucket in Qingdao.
- The object size must be smaller than 1 GB.

Run the following code to copy a small-sized object:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *source_bucket_name = "<yourSourceBucketName>";
const char *source_object_name = "<yourSourceObjectName>";
const char *dest_bucket_name = "<yourDestBucketName>";
const char *dest_object_name = "<yourDestObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t source_bucket;
    aos_string_t source_object;
    aos_string_t dest_bucket;
    aos_string_t dest_object;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&source_bucket, source_bucket_name);
    aos_str_set(&source_object, source_object_name);
    aos_str_set(&dest_bucket, dest_bucket_name);
    aos_str_set(&dest_object, dest_object_name);
    headers = aos_table_make(pool, 0);
    /* Copy an object. */
```

```

    resp_status = oss_copy_object(oss_client_options, &source_bucket,
    &source_object, &dest_bucket, &dest_object, headers, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("copy object succeeded\n");
    } else {
        printf("copy object failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Copy a large-sized object

For objects larger than 1 GB, we recommend that you should use **oss_upload_part_copy** to perform multipart copy (UploadPartCopy). Run the following code for multipart copy:

```

#include "oss_api.h"
#include "aos_http_io.h"
#include <sys/stat.h>
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *source_bucket_name = "<yourSourceBucketName>";
const char *source_object_name = "<yourSourceObjectName>";
const char *dest_bucket_name = "<yourDestBucketName>";
const char *dest_object_name = "<yourDestObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int64_t get_file_size(const char *file_path)
{
    int64_t filesize = -1;
    struct stat statbuff;
    if(stat(file_path, &statbuff) < 0){
        return filesize;
    } else {
        filesize = statbuff.st_size;
    }
    return filesize;
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */

```

```

    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t dest_bucket;
    aos_string_t dest_object;
    aos_string_t upload_id;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    oss_list_upload_part_params_t *list_upload_part_params;
    oss_upload_part_copy_params_t *upload_part_copy_params1;
    oss_upload_part_copy_params_t *upload_part_copy_params2;
    oss_list_part_content_t *part_content;
    aos_list_t complete_part_list;
    oss_complete_part_content_t *complete_content;
    aos_table_t *list_part_resp_headers = NULL;
    aos_table_t *complete_resp_headers = NULL;
    int part1 = 1;
    int part2 = 2;
    int64_t range_start1 = 0;
    int64_t range_end1 = 60000000; //not less than 5MB
    int64_t range_start2 = 60000001;
    int64_t range_end2;
    int max_ret = 1000;
    headers = aos_table_make(pool, 0);
    aos_str_set(&dest_bucket, dest_bucket_name);
    aos_str_set(&dest_object, dest_object_name);
    resp_status = oss_init_multipart_upload(oss_client_options, &
    dest_bucket, &dest_object, &upload_id, headers, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("init multipart upload succeeded, upload_id is %s\n",
        upload_id.data);
    } else {
        printf("init multipart upload failed\n");
    }
    /* Copy the first part of the object. */
    upload_part_copy_params1 = oss_create_upload_part_copy_params(pool
    );
    aos_str_set(&upload_part_copy_params1->source_bucket, source_buc
    ket_name);
    aos_str_set(&upload_part_copy_params1->source_object, source_obj
    ect_name);
    aos_str_set(&upload_part_copy_params1->dest_bucket, dest_bucke
    t_name);
    aos_str_set(&upload_part_copy_params1->dest_object, dest_objec
    t_name);
    aos_str_set(&upload_part_copy_params1->upload_id, upload_id.data);

```



```

        upload_part_copy_params1->part_num = part1;
        upload_part_copy_params1->range_start = range_start1;
        upload_part_copy_params1->range_end = range_end1;
        headers = aos_table_make(pool, 0);
        resp_status = oss_upload_part_copy(oss_client_options, upload_part_copy_params1, headers, &resp_headers);
        if (aos_status_is_ok(resp_status)) {
            printf("upload part 1 copy succeeded\n");
        } else {
            printf("upload part 1 copy failed\n");
        }
        /* Copy the second part of the object. */
        range_end2 = get_file_size(local_filename) - 1;
        upload_part_copy_params2 = oss_create_upload_part_copy_params(pool);
        aos_str_set(&upload_part_copy_params2->source_bucket, source_bucket_name);
        aos_str_set(&upload_part_copy_params2->source_object, source_object_name);
        aos_str_set(&upload_part_copy_params2->dest_bucket, dest_bucket_name);
        aos_str_set(&upload_part_copy_params2->dest_object, dest_object_name);
        aos_str_set(&upload_part_copy_params2->upload_id, upload_id.data);
        upload_part_copy_params2->part_num = part2;
        upload_part_copy_params2->range_start = range_start2;
        upload_part_copy_params2->range_end = range_end2;
        headers = aos_table_make(pool, 0);
        resp_status = oss_upload_part_copy(oss_client_options, upload_part_copy_params2, headers, &resp_headers);
        if (aos_status_is_ok(resp_status)) {
            printf("upload part 2 copy succeeded\n");
        } else {
            printf("upload part 2 copy failed\n");
        }
        /* Lists the parts. */
        headers = aos_table_make(pool, 0);
        list_upload_part_params = oss_create_list_upload_part_params(pool);
        list_upload_part_params->max_ret = max_ret;
        aos_list_init(&complete_part_list);
        resp_status = oss_list_upload_part(oss_client_options, &dest_bucket, &dest_object, &upload_id, list_upload_part_params, &list_part_resp_headers);
        aos_list_for_each_entry(oss_list_part_content_t, part_content, &list_upload_part_params->part_list, node) {
            complete_content = oss_create_complete_part_content(pool);
            aos_str_set(&complete_content->part_number, part_content->part_number.data);
            aos_str_set(&complete_content->etag, part_content->etag.data);
            aos_list_add_tail(&complete_content->node, &complete_part_list);
        }
        /* Complete the multipart copy. */
        resp_status = oss_complete_multipart_upload(oss_client_options, &dest_bucket, &dest_object, &upload_id, &complete_part_list, headers, &complete_resp_headers);
        if (aos_status_is_ok(resp_status)) {
            printf("complete multipart upload succeeded\n");
        } else {
            printf("complete multipart upload failed\n");
        }
    }
}

```

```

    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

6.8.7 Restore an archive object

You must restore an archive object before you read it. Do not call `restoreObject` for non-archive objects.

The state conversion process of an archive object is as follows:

- An archive object is in the frozen state.
- After you submit it for restoration, the server restores the object. The object is in the restoring state.
- You can read the object after it is restored. The restored state of the object lasts one day by default. You can prolong this period to a maximum of seven days. Once this period expires, the object returns to the frozen state.

Run the following code to restore an object:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *object_content = "More than just cloud.";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
}

```

```

/* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
aos_pool_t *pool;
/* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
aos_pool_create(&pool, NULL);
/* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_string_t object;
aos_list_t buffer;
oss_acl_t oss_acl = OSS_ACL_PRIVATE;
aos_buf_t *content = NULL;
aos_table_t *headers = NULL;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
headers = aos_table_make(pool, 0);
/* Create a bucket of the archive storage class. */
resp_status = oss_create_bucket_with_storage_class(oss_client_options, &bucket, oss_acl, OSS_STORAGE_CLASS_ARCHIVE, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("create bucket succeeded\n");
} else {
    printf("create bucket failed\n");
}
aos_list_init(&buffer);
content = aos_buf_pack(oss_client_options->pool, object_content,
strlen(object_content));
aos_list_add_tail(&content->node, &buffer);
/* Upload a file. */
resp_status = oss_put_object_from_buffer(oss_client_options, &
bucket, &object, &buffer, headers, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("put object from buffer succeeded\n");
} else {
    printf("put object from buffer failed\n");
}
/* Restore the object. */
do {
    headers = aos_table_make(pool, 0);
    resp_status = oss_restore_object(oss_client_options, &bucket,
&object, headers, &resp_headers);
    printf("restore object resp_status->code: %d \n", resp_status->code);
    if (resp_status->code != 409) {
        break;
    } else {
        printf("restore object is already in progress, resp_status->code: %d \n", resp_status->code);
        apr_sleep(5000);
    }
} while (1);

```

```

/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

For more information about the archive storage classes, see [Introduction to storage classes](#). For more information about related status code, see [RestoreObject](#).

6.8.8 Manage a symbolic link

Create a symbolic link

A symbolic link is a special object that maps to an object similar to a shortcut used in Windows.

You can configure user-defined object meta for symbolic links.

Run the following code to create a symbolic link:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *link_object_name = "<yourLinkObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Used to configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */

```

```

    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t sym_object;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    aos_str_set(&sym_object, link_object_name);
    resp_status = oss_put_symlink(oss_client_options, &bucket, &
sym_object, &object, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put symlink succeeded\n");
    } else {
        printf("put symlink failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Obtain object content for a symbolic link

To obtain a symbolic link, you must have the read permission on it. Run the following code to obtain the object content for a symbolic link:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *link_object_name = "<yourLinkObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {

```

```

        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t link_object;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    char *target_object_name = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&link_object, link_object_name);
    resp_status = oss_get_symlink(oss_client_options, &bucket, &
    link_object, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get symlink succeeded\n");
        target_object_name = (char*)(apr_table_get(resp_headers,
    OSS_CANNONICALIZED_HEADER_SYMLINK));
        printf("target_object_name: %s \n", target_object_name);
    } else {
        printf("get symlink failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

6.9 Authorized access

Use STS for temporary access authorization

OSS supports Alibaba Cloud Security Token Service (STS) for temporary access authorization.

STS is a web service that provides a temporary access token to a cloud computing user. Through the STS, you can assign a third-party application or a RAM user (you can manage the user ID) an access credential with a custom validity period and permissions. For more information about STS, see [STS introduction](#).

STS advantages:

- Your long-term key (AccessKey) is not exposed to a third-party application. You only need to generate an access token and send the access token to the third-party application. You can customize access permissions and the validity of this token.
- You do not need to keep track of permission revocation issues. The access token automatically becomes invalid when it expires.

For more information about the process of access to OSS with STS, see [RAM and STS scenario practices](#) in OSS Developer Guide.

Create a signature request with STS

Run the following code to create a signature request with STS:

```
#include "oss_api.h"
#include "aos_http_io.h"

const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *sts_token = "<yourStsToken>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *object_content = "More than just cloud.";

void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
    aos_str_set(&options->config->sts_token, sts_token);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME is
    not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}

int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }

    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
```

```

oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);

    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_list_t buffer;
    aos_buf_t *content = NULL;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    /* Assign the char* data to the bucket. */
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);

    aos_list_init(&buffer);
    content = aos_buf_pack(oss_client_options->pool, object_content,
strlen(object_content));
    aos_list_add_tail(&content->node, &buffer);

    /* Upload an object. */
    resp_status = oss_put_object_from_buffer(oss_client_options, &
bucket, &object, &buffer, headers, &resp_headers);
    /* Determine whether the upload is successful. */
    if (aos_status_is_ok(resp_status)) {
        printf("put object from buffer succeeded\n");
    } else {
        printf("put object from buffer failed\n");
    }

    /* Release the memory pool, that is, memories allocated to resources
during the request. */
    aos_pool_destroy(pool);

    /* Release allocated global resources. */
    aos_http_io_deinitialize();

    return 0;
}

```

Sign a URL to authorize temporary access

You can provide a signed URL to a visitor for temporary access. When you sign a URL, you can specify the expiration time for a URL to restrict the period of access from visitors.

- Use a signed URL to upload an object

Run the following code to upload an object with a signed URL:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";

```



```

void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}

int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL, indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes global configuration information, such as endpoint, access_key_id, access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_table_t *headers = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_http_request_t *req;
    apr_time_t now;
    char *url_str;
    aos_string_t url;
    int64_t expire_time;
    int one_hour = 3600;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    aos_str_set(&file, local_filename);
    expire_time = now / 1000000 + one_hour;
    headers = aos_table_make(pool, 0);
    req = aos_http_request_create(pool);
    req->method = HTTP_PUT;
    now = apr_time_now(); /* Unit: microseconds */
    expire_time = now / 1000000 + one_hour;
    /* Generate the signed URL. */
    url_str = oss_gen_signed_url(oss_client_options, &bucket, &object, expire_time, req);
    aos_str_set(&url, url_str);
}

```

```

    printf("Temporary upload URL: %s\n", url_str);
    /* Use the signed URL to upload an object. */
    resp_status = oss_put_object_from_file_by_url(oss_client_options
, &url, &file, headers, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put objects by signed url succeeded\n");
    } else {
        printf("put objects by signed url failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

- Use a signed URL to download an object

Run the following code to upload an object with a signed URL:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
const char *local_filename = "<yourLocalFilename>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize the aos_string_t type. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key
_secret);
    /* Determine whether the CNAME is used. 0 indicates that the
CNAME is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to
initialize global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library.
*/
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&p, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;

```

```

/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Use oss_client_options to initialize client options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_string_t object;
aos_string_t file;
aos_table_t *headers = NULL;
aos_table_t *params = NULL;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_http_request_t *req;
apr_time_t now;
char *url_str;
aos_string_t url;
int64_t expire_time;
int one_hour = 3600;
aos_str_set(&bucket, bucket_name);
aos_str_set(&object, object_name);
aos_str_set(&file, local_filename);
expire_time = now / 1000000 + one_hour;
headers = aos_table_make(pool, 0);
params = aos_table_make(pool, 0);
req = aos_http_request_create(pool);
req->method = HTTP_GET;
now = apr_time_now(); /* Unit: microseconds */
expire_time = now / 1000000 + one_hour;
/* Generate the signed URL. */
url_str = oss_gen_signed_url(oss_client_options, &bucket, &
object, expire_time, req);
aos_str_set(&url, url_str);
/* Use the signed URL to download an object. */
resp_status = oss_get_object_to_file_by_url(oss_client_options,
&url, headers, params, &file, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("get object succeeded\n");
} else {
    printf("get object failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.10 Manage lifecycle rules

You can use OSS to configure lifecycle rules to reduce storage costs. The lifecycle management rules can be used for automatic deletion of expired objects and fragments, or storage class conversion to Infrequent Access for objects that will expire soon. Each rule includes:

- Rule ID: It identifies a rule. Ensure that each rule ID in a bucket is unique.
- Policy: You can configure a policy by using the following configuration methods. Only one method can be configured for a bucket.

- Configure by Prefix: You can create multiple rules with this method. Ensure that each prefix is unique.
- Configure for Entire Bucket: You can configure only one rule with this method.
- Expired: You can configure the following configuration methods:
 - Set by Number of Days: It specifies the number of days from the last modification time of objects.
 - Set by Date: It specifies the date prior to which objects are created. If objects are created prior to the date, these objects are deleted.
- Status: This lifecycle rule takes effect or not.

The parts uploaded by uploadPart method also support lifecycle rules. The last modification time of an object is the time the multipart upload event is initiated.

For more information about lifecycle management, see [Manage object lifecycle](#).

Configure lifecycle rules

Run the following code to configure lifecycle rules:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
```

```

    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_list_t lifecycle_rule_list;
    /* Create a lifecycle rule for the bucket. */
    aos_str_set(&bucket, bucket_name);
    aos_list_init(&lifecycle_rule_list);
    /* Specify the expiration duration. */
    oss_lifecycle_rule_content_t *rule_content_days = oss_create_
_lifecycle_rule_content(pool);
    aos_str_set(&rule_content_days->id, "rule-1");
    aos_str_set(&rule_content_days->prefix, "obsoleted");
    aos_str_set(&rule_content_days->status, "Enabled");
    rule_content_days->days = 3;
    aos_list_add_tail(&rule_content_days->node, &lifecycle_rule_list);
    /* Specify the expiration date. */
    oss_lifecycle_rule_content_t *rule_content_date = oss_create_
_lifecycle_rule_content(pool);
    aos_str_set(&rule_content_date->id, "rule-2");
    aos_str_set(&rule_content_date->prefix, "delete");
    aos_str_set(&rule_content_date->status, "Enabled");
    aos_str_set(&rule_content_date->date, "2022-10-11T00:00:00.000Z");
    aos_list_add_tail(&rule_content_date->node, &lifecycle_rule_list);
    /* Configure a lifecycle rule. */
    resp_status = oss_put_bucket_lifecycle(oss_client_options, &bucket
, &lifecycle_rule_list, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put bucket lifecycle succeeded\n");
    } else {
        printf("put bucket lifecycle failed, code:%d, error_code:%s,
error_msg:%s, request_id:%s\n",
            resp_status->code, resp_status->error_code, resp_status->
error_msg, resp_status->req_id);
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

View lifecycle rules

Run the following code to view lifecycle rules:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";

```

```

const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_list_t lifecycle_rule_list;
    oss_lifecycle_rule_content_t *rule_content;
    char *rule_id;
    char *prefix;
    char *status;
    int days = INT_MAX;
    char* date = "";
    aos_str_set(&bucket, bucket_name);
    /* Obtain and print the lifecycle of the bucket. */
    aos_list_init(&lifecycle_rule_list);
    resp_status = oss_get_bucket_lifecycle(oss_client_options, &bucket
, &lifecycle_rule_list, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket lifecycle succeeded\n");
        aos_list_for_each_entry(oss_lifecycle_rule_content_t,
rule_content, &lifecycle_rule_list, node) {
            rule_id = apr_psprintf(pool, "%.s", rule_content->id.len
, rule_content->id.data);
            prefix = apr_psprintf(pool, "%.s", rule_content->prefix.
len, rule_content->prefix.data);

```

```

        status = apr_psprintf(pool, "%.s", rule_content->status.
len, rule_content->status.data);
        date = apr_psprintf(pool, "%.s", rule_content->date.len,
rule_content->date.data);
        days = rule_content->days;
    }
    printf("rule_id: %s \n", rule_id);
    printf("prefix: %s \n", prefix);
    printf("status: %s \n", status);
    printf("date: %s \n", date);
    printf("days: %d \n", days);
} else {
    printf("get bucket lifecycle failed, code:%d, error_code:%s,
error_msg:%s, request_id:%s\n",
        resp_status->code, resp_status->error_code, resp_status->
error_msg, resp_status->req_id);
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

Clear lifecycle rules

Run the following code to clear lifecycle rules:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Used to configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */

```

```

    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Use oss_client_options to initialize client options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    /* Delete bucket lifecycle rules. */
    aos_str_set(&bucket, bucket_name);
    resp_status = oss_delete_bucket_lifecycle(oss_client_options, &
    bucket, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("delete bucket lifecycle succeeded\n");
    } else {
        printf("delete bucket lifecycle failed, code:%d, error_code:%s
, error_msg:%s, request_id:%s\n",
            resp_status->code, resp_status->error_code, resp_status->
error_msg, resp_status->req_id);
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

6.11 Image processing

Image Processing (IMG) is a massive, secure, cost-effective and highly reliable image processing service. After source images are uploaded to OSS, you can process images on any Internet device at any anytime, from anywhere through simple RESTful APIs.

For more information about IMG, see [Image Processing](#).

For the complete code of IMG, see [GitHub](#).

Basic features

OSS offers the following IMG features:

- [Retrieve dominant image tones](#)
- [Format conversion](#)
- [Resize images](#)
- [Incircle](#)
- [Adaptive orientation](#)

- [Brightness](#)
- [Add watermarks](#): allows you to add images, texts, or image-text watermarks to another image.
- [Image processing](#)
- [Image processing access rules](#): calls multiple IMG functions.

Usage

IMG uses standard HTTP GET. You can configure IMG parameters in QueryString of a URL.

If the ACL of an image object is private read and write, only authorized users are allowed for access.

- Anonymous access

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction>,<yourParamValue>
```

Parameter	Description
bucket	Specifies the name of a bucket.
endpoint	Specifies endpoint used to access a region.
object	Specifies the name of an image object.
image	Specifies the reserved identifier for IMG.
action	Specifies the operations on an image, such as scaling, cropping, and rotating.
param	Specifies the parameter that indicates the operation on an image.

— Basic operations

For example, scale an image to a width of 100 px. Adjust the height based on the ratio.

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

— Customized image styles

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=style/<yourStyleName>
```

- **style**: specifies a reserved identifier of a customized image style.

- `yourStyleName`: specifies the name of a custom image style. It is the name specified in the rule that is created on the OSS console.

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=style/oss-pic-style-w-100
```

— Cascade operations

Cascade operations allow you to perform multiple operations on an image sequentially.

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction1>,<yourParamValue1>/<yourAction2>,<yourParamValue2>/...
```

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100/rotate,90
```

— HTTPS access

IMG supports access through HTTPS. Example:

```
https://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

- Authorized access

Authorized access allows you to customize an image style, HTTPS access, and cascade operations.

Use the following code to generate a signed URL for IMG:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
    /* Determine whether the CNAME is used. The value 0 indicates that the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
```

```

}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to
    initialize global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t
    . The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
    indicating that the new pool does not inherit any other memory pool.
    */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate the memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_table_t *params = NULL;
    aos_http_request_t *req;
    char *url_str;
    apr_time_t now;
    int64_t expire_time;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    /* Start image processing. */
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/resize,m_fixed,w_100,
    h_100");
    req = aos_http_request_create(pool);
    req->method = HTTP_GET;
    req->query_params = params;
    /* Specify the expiration time (expire_time) in seconds. */
    now = apr_time_now();
    expire_time = now / 1000000 + 10 * 60;
    /* Generate a signed URL. */
    url_str = oss_gen_signed_url(oss_client_options, &bucket, &
    object, expire_time, req);
    printf("url: %s\n", url_str);
    /* Release the memory pool, that is, the memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

- Access with SDK

You can use SDK to access and process an image object.

SDK allows you to customize image styles, HTTPS access, and cascade operations.

— Basic operations

Run the following code to perform basic operations on an image:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
    /* Determine whether the CNAME is used. The value 0 indicates that the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL, indicating that the new pool does not inherit any other memory pool. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes global configuration information, such as endpoint, access_key_id, access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_table_t *headers = NULL;
    aos_table_t *params = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    /* Scale the image.
    params = aos_table_make(pool, 1);
```

```

    apr_table_set(params, OSS_PROCESS, "image/resize,m_fixed,w_100,h_100");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-resize.jpg");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Crop the image.
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/crop,w_100,h_100,x_100,y_100,r_1");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-crop.jpg");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Rotate the image.
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/rotate,90");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-rotate.jpg");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Sharpen the image.
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/sharpen,100");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-sharpen.jpg");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Add watermarks.
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/watermark,text_SGVsb
G8g5Zu-54mH5pyN5YqhIQ");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-watermark.jpg");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Convert the image format.

```

```

    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/format,png");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-format.png");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Obtain image information.
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/info");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-info.txt");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Release the memory pool, that is, the memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

— Customize an image style

Run the following code to customize an image style:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key
_secret);
    /* Determine whether the CNAME is used. The value 0 indicates
that the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to
initialize global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {

```

```

        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to
apr_pool_t. The implementation code is included in the apr library
. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
indicating that the new pool does not inherit any other memory
pool. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes
global configuration information, such as endpoint, access_key_id
, acces_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate the memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_table_t *headers = NULL;
    aos_table_t *params = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    /* Customize the image style. */
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "style/<yourCustomStyleName
>");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-custom-style.jpg");
    resp_status = oss_get_object_to_file(oss_client_options, &
bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Release the memory pool, that is, the memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

— Cascade operations

Run the following code to perform cascade operations on an image:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *object_name = "<yourObjectName>";
void init_options(oss_request_options_t *options)

```

```

{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
    /* Determine whether the CNAME is used. The value 0 indicates that the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL, indicating that the new pool does not inherit any other memory pool. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes global configuration information, such as endpoint, access_key_id, access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate the memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_string_t object;
    aos_string_t file;
    aos_table_t *headers = NULL;
    aos_table_t *params = NULL;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&object, object_name);
    /* Perform cascade operations. */
    params = aos_table_make(pool, 1);
    apr_table_set(params, OSS_PROCESS, "image/resize,m_fixed,w_100,h_100");
    /* Download processed images to a local file. */
    aos_str_set(&file, "example-cascade.jpg");
    resp_status = oss_get_object_to_file(oss_client_options, &bucket, &object, headers, params, &file, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get object to file succeeded\n");
    } else {
        printf("get object to file failed\n");
    }
    /* Release the memory pool, that is, the memories allocated to resources during the request. */
    aos_pool_destroy(pool);
}

```



```

    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

IMG tools

You can use the IMG viewer [ImageStyleViewer](#) to directly view the IMG result.

6.12 CORS

Cross-origin resource sharing (CORS) allows web applications to access resources that belong to another region. OSS provides CORS APIs for convenient cross-origin access control.

For more information, see [Cross-origin resource sharing](#) and [PutBucketcors](#) in OSS Developer Guide.

Configure CORS rules

Run the following code to configure CORS rules for a specified bucket:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */

```

```

    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_list_t cors_rule_list;
    oss_cors_rule_t *cors_rule1 = NULL, *cors_rule2 = NULL;
    aos_str_set(&bucket, bucket_name);
    aos_list_init(&cors_rule_list);
    cors_rule1 = oss_create_cors_rule(pool);
    aos_list_add_tail(&cors_rule1->node, &cors_rule_list);
    oss_create_sub_cors_rule(pool, &cors_rule1->allowed_origin_list, "
allowed_origin_1_1");
    oss_create_sub_cors_rule(pool, &cors_rule1->allowed_origin_list, "
allowed_origin_1_1");
    oss_create_sub_cors_rule(pool, &cors_rule1->allowed_method_list, "
PUT");
    oss_create_sub_cors_rule(pool, &cors_rule1->allowed_method_list, "
GET");
    oss_create_sub_cors_rule(pool, &cors_rule1->allowed_head_list, "
Authorization");
    oss_create_sub_cors_rule(pool, &cors_rule1->expose_head_list, "
expose_head_1_1");
    oss_create_sub_cors_rule(pool, &cors_rule1->expose_head_list, "
expose_head_1_1");
    cors_rule2 = oss_create_cors_rule(pool);
    aos_list_add_tail(&cors_rule2->node, &cors_rule_list);
    oss_create_sub_cors_rule(pool, &cors_rule2->allowed_origin_list, "
allowed_origin_2_1");
    oss_create_sub_cors_rule(pool, &cors_rule2->allowed_origin_list, "
allowed_origin_2_2");
    oss_create_sub_cors_rule(pool, &cors_rule2->allowed_method_list, "
PUT");
    oss_create_sub_cors_rule(pool, &cors_rule2->allowed_method_list, "
GET");
    oss_create_sub_cors_rule(pool, &cors_rule2->allowed_head_list, "
Authorization");
    oss_create_sub_cors_rule(pool, &cors_rule2->expose_head_list, "
expose_head_2_1");
    oss_create_sub_cors_rule(pool, &cors_rule2->expose_head_list, "
expose_head_2_2");
    /* Configure the CORS rule. */
    resp_status = oss_put_bucket_cors(oss_client_options, &bucket, &
cors_rule_list, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put bucket cors succeeded\n");
    } else {
        printf("put bucket cors failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;

```

```
}
```

Obtain CORS rules

Run the following code to obtain CORS rules:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
    is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_list_t cors_rule_list;
    oss_cors_rule_t *cors_rule = NULL;
    oss_sub_cors_rule_t *sub_cors_rule = NULL;
    aos_str_set(&bucket, bucket_name);
    /* Obtain CORS rules. */
    aos_list_init(&cors_rule_list);
    resp_status = oss_get_bucket_cors(oss_client_options, &bucket, &
    cors_rule_list, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket cors succeeded\n");
    }
}
```

```

        aos_list_for_each_entry(oss_cors_rule_t, cors_rule, &
cors_rule_list, node) {
            printf("max_age_seconds: %d\n", cors_rule->max_age_seconds
);
            aos_list_for_each_entry(oss_sub_cors_rule_t, sub_cors_rule
, &cors_rule->allowed_origin_list, node) {
                printf("allowed_origin_list: %s \n", sub_cors_rule->
rule.data);
            }
            aos_list_for_each_entry(oss_sub_cors_rule_t, sub_cors_rule
, &cors_rule->allowed_method_list, node) {
                printf("allowed_method_list: %s \n", sub_cors_rule->
rule.data);
            }
            aos_list_for_each_entry(oss_sub_cors_rule_t, sub_cors_rule
, &cors_rule->allowed_head_list, node) {
                printf("allowed_head_list: %s \n", sub_cors_rule->rule
.data);
            }
            aos_list_for_each_entry(oss_sub_cors_rule_t, sub_cors_rule
, &cors_rule->expose_head_list, node) {
                printf("expose_head_list: %s \n", sub_cors_rule->rule.
data);
            }
        }
    } else {
        printf("get bucket cors failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Delete CORS rules

Run the following code to delete all CORS rules for the specified bucket:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])

```

```

{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    /* Delete all CORS rules. */
    resp_status = oss_delete_bucket_cors(oss_client_options, &bucket,
    &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket cors succeeded\n");
    } else {
        printf("get bucket cors failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

6.13 Set logging

You can enable access logs to record bucket access to log files, which are stored in a specified bucket.

The log file format is as follows:

<TargetPrefix><SourceBucket>-YYYY-mm-DD-HH-MM-SS-UniqueString

For more information about access log files, see [Set access logging](#).

Enable access logging

Run the following code to enable bucket access logging:

```

#include "oss_api.h"
#include "aos_http_io.h"

```

```

const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
const char *target_bucket_name = "<yourTargetBucketName>";
const char *target_logging_prefix = "<yourTargetPrefix>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the maid method at the program portal to initialize global
resources such as network, memory, and so on. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
indicating that the new pool does not inherit any other memory pool.
*/
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes global
configuration information, such as endpoint, access_key_id, acces_key_
secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    oss_logging_config_content_t *content;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    content = oss_create_logging_rule_content(pool);
    aos_str_set(&content->target_bucket, target_bucket_name);
    aos_str_set(&content->prefix, target_logging_prefix);
    /* Enable bucket access logging. */
    resp_status = oss_put_bucket_logging(oss_client_options, &bucket,
content, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put symlink succeeded\n");
    } else {
        printf("put symlink failed, code:%d, error_code:%s, error_msg:
%s, request_id:%s\n",
            resp_status->code, resp_status->error_code, resp_status->
error_msg, resp_status->req_id);
    }
}

```

```

/* Release the memory pool, that is, the memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

View access logging configurations

Run the following code to view the access logging configurations for a bucket:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
indicating that the new pool does not inherit any other memory pool.
*/
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes global
configuration information, such as endpoint, access_key_id, acces_key_
secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    oss_logging_config_content_t *content;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    content = oss_create_logging_rule_content(pool);

```

```

    /* View bucket access logging configurations. */
    resp_status = oss_get_bucket_logging(oss_client_options, &bucket,
content, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket logging succeeded\n");
    } else {
        printf("get bucket logging failed, code:%d, error_code:%s,
error_msg:%s, request_id:%s\n",
            resp_status->code, resp_status->error_code, resp_status->
error_msg, resp_status->req_id);
    }
    printf("bucket:%s, prefix:%s\n", content->target_bucket.data,
content->prefix.data);
    /* Release the memory pool, that is, the memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Disable access logging

Run the following code to disable access logging for a bucket:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
indicating that the new pool does not inherit any other memory pool.
*/
    aos_pool_create(&pool, NULL);
}

```



```

/* Create and initialize options. This parameter includes global
configuration information, such as endpoint, access_key_id, acces_key_
secret, is_cname, and curl. */
oss_request_options_t *oss_client_options;
/* Allocate memories in the memory pool to options. */
oss_client_options = oss_request_options_create(pool);
/* Initialize oss_client_options. */
init_options(oss_client_options);
/* Initialization parameters. */
aos_string_t bucket;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
aos_str_set(&bucket, bucket_name);
/* Disable access logging. */
resp_status = oss_delete_bucket_logging(oss_client_options, &
bucket, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("delete bucket logging succeeded\n");
} else {
    printf("delete bucket logging failed, code:%d, error_code:%s,
error_msg:%s, request_id:%s\n",
        resp_status->code, resp_status->error_code, resp_status->
error_msg, resp_status->req_id);
}
/* Release the memory pool, that is, the memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.14 Anti-leech

This topic describes how to use anti-leech.

To prevent your data on OSS from being leeches, OSS supports anti-leeching through the referer field settings in the HTTP header, including the following parameters:

- **Referer whitelist:** Used to allow access only for specified domains to OSS data.
- **Empty referer:** Determines whether the referer can be empty. If it is not allowed, only requests with the referer filed in their HTTP or HTTPS headers can access OSS data.

For more information about anti-leaching, see [Anti-leeching settings](#).

Configure the referer whitelist

Run the following code to configure the referer whitelist:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)

```

```

{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    oss_referer_config_t referer_config;
    aos_str_set(&bucket, bucket_name);
    aos_list_init(&referer_config.referer_list);
    oss_create_and_add_refer(pool, &referer_config, "http://www.aliyun
.com");
    oss_create_and_add_refer(pool, &referer_config, "https://www.
aliyun.com");
    referer_config.allow_empty_referer = 0;
    /* Add the referer field. The referer field allows question marks
(?) and asterisks (*) for wildcard use. */
    resp_status = oss_put_bucket_referer(oss_client_options, &bucket,
&referer_config, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put bucket referer succeeded\n");
    } else {
        printf("put bucket referer failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

```
}
```

Obtain a referer whitelist

Run the following code to obtain a referer whitelist:

```
#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
global configuration information, such as endpoint, access_key_id,
access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    oss_referer_config_t referer_config;
    oss_referer_t *referer;
    aos_str_set(&bucket, bucket_name);
    aos_list_init(&referer_config.referer_list);
    /* Obtain the referer list for a bucket. */
    resp_status = oss_get_bucket_referer(oss_client_options, &bucket,
&referer_config, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket referer succeeded\n");
    }
}
```

```

        aos_list_for_each_entry(oss_referer_t, referer, &referer_config.referer_list, node) {
            printf("get referer %s\n", referer->referer.data);
        }
    } else {
        printf("get bucket referer failed\n");
    }
    /* Release the memory pool, that is, memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Clear a referer whitelist

Run the following code to clear a referer whitelist:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. 0 indicates that the CNAME
is not used. */
options->config->is_cname = 0;
/* Configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, which is equivalent to
    apr_pool_t. The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a new memory pool. The second parameter is NULL,
    indicating that it does not inherit from any other memory pools. */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter mainly includes
    global configuration information, such as endpoint, access_key_id,
    access_key_secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
}

```

```

aos_string_t bucket;
aos_table_t *resp_headers = NULL;
aos_status_t *resp_status = NULL;
oss_referer_config_t referer_config;
aos_str_set(&bucket, bucket_name);
aos_list_init(&referer_config.referer_list);
referer_config.allow_empty_referer = 1;
/* You cannot clear a referer whitelist directly. To clear a
referer whitelist, you need to create the rule that allows an empty
referer field and replace the original rule with the new rule. */
resp_status = oss_put_bucket_referer(oss_client_options, &bucket,
&referer_config, &resp_headers);
if (aos_status_is_ok(resp_status)) {
    printf("delete bucket referer succeeded\n");
} else {
    printf("delete bucket referer failed\n");
}
/* Release the memory pool, that is, memories allocated to
resources during the request. */
aos_pool_destroy(pool);
/* Release the allocated global resources. */
aos_http_io_deinitialize();
return 0;
}

```

6.15 Static website hosting

You can set your bucket to static website hosting mode. After the configuration takes effect, you can access this static website with the bucket domain and be redirected to a specified index page or error page.

For more information about static website hosting, see [Configure static website hosting](#).

Configure static website hosting

Run the following code to configure static website hosting:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret);
};
/* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
options->config->is_cname = 0;
/* Configure network parameters, such as timeout. */
options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])

```

```

{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
    The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
    indicating that the new pool does not inherit any other memory pool.
    */
    aos_pool_create(&p, NULL);
    /* Create and initialize options. This parameter includes global
    configuration information, such as endpoint, access_key_id, acces_key_
    secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    oss_website_config_t website_config;
    aos_str_set(&bucket, bucket_name);
    aos_str_set(&website_config.suffix_str, "index.html");
    aos_str_set(&website_config.key_str, "error.html");
    /* Configure static web hosting: The index page is index.html and
    the error page is error.html. */
    resp_status = oss_put_bucket_website(oss_client_options, &bucket,
    &website_config, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("put bucket website succeeded\n");
    } else {
        printf("put bucket website failed\n");
    }
    /* Release the memory pool, that is, the memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

View static website hosting configurations

Run the following code to view static website hosting configurations:

```

#include "oss_api.h"
#include "aos_http_io.h"
const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
}

```

```

    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. The value 0 indicates that
    the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
    global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
    The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
    indicating that the new pool does not inherit any other memory pool.
    */
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes global
    configuration information, such as endpoint, access_key_id, acces_key_
    secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialization parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    oss_website_config_t website_config;
    aos_str_set(&bucket, bucket_name);
    /* View static web hosting configurations. */
    resp_status = oss_get_bucket_website(oss_client_options, &bucket,
    &website_config, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("get bucket website succeeded\n");
        printf("website_config: %s %s\n", website_config.suffix_str.
data, website_config.key_str.data);
    } else {
        printf("get bucket website failed\n");
    }
    /* Release the memory pool, that is, the memories allocated to
    resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```

Delete static website hosting configurations

Run the following code to delete static website hosting configurations:

```

#include "oss_api.h"
#include "aos_http_io.h"

```

```

const char *endpoint = "<yourEndpoint>";
const char *access_key_id = "<yourAccessKeyId>";
const char *access_key_secret = "<yourAccessKeySecret>";
const char *bucket_name = "<yourBucketName>";
void init_options(oss_request_options_t *options)
{
    options->config = oss_config_create(options->pool);
    /* Use a char* string to initialize aos_string_t. */
    aos_str_set(&options->config->endpoint, endpoint);
    aos_str_set(&options->config->access_key_id, access_key_id);
    aos_str_set(&options->config->access_key_secret, access_key_secret
);
    /* Determine whether the CNAME is used. The value 0 indicates that
the CNAME is not used. */
    options->config->is_cname = 0;
    /* Configure network parameters, such as timeout. */
    options->ctl = aos_http_controller_create(options->pool, 0);
}
int main(int argc, char *argv[])
{
    /* Call the aos_http_io_initialize method in main() to initialize
global resources, such as networks and memories. */
    if (aos_http_io_initialize(NULL, 0) != AOSE_OK) {
        exit(1);
    }
    /* Memory pool used to manage memories, equivalent to apr_pool_t.
The implementation code is included in the apr library. */
    aos_pool_t *pool;
    /* Re-create a memory pool. The second parameter is NULL,
indicating that the new pool does not inherit any other memory pool.
*/
    aos_pool_create(&pool, NULL);
    /* Create and initialize options. This parameter includes global
configuration information, such as endpoint, access_key_id, acces_key_
secret, is_cname, and curl. */
    oss_request_options_t *oss_client_options;
    /* Allocate the memories in the memory pool to options. */
    oss_client_options = oss_request_options_create(pool);
    /* Initialize oss_client_options. */
    init_options(oss_client_options);
    /* Initialize parameters. */
    aos_string_t bucket;
    aos_table_t *resp_headers = NULL;
    aos_status_t *resp_status = NULL;
    aos_str_set(&bucket, bucket_name);
    /* Delete static website hosting configurations. */
    resp_status = oss_delete_bucket_website(oss_client_options, &
bucket, &resp_headers);
    if (aos_status_is_ok(resp_status)) {
        printf("delete bucket website succeeded\n");
    } else {
        printf("delete bucket website failed\n");
    }
    /* Release the memory pool, that is, the memories allocated to
resources during the request. */
    aos_pool_destroy(pool);
    /* Release the allocated global resources. */
    aos_http_io_deinitialize();
    return 0;
}

```



```
}
```

6.16 Error handling

Exception handling

If a request error occurs in the use of OSS C SDK, the corresponding error message is output in `aos_status_s`. The attributes of `aos_status_s` include:

Error code	Description	Type
code	The HTTP status code of the error request	Integer
error_code	Error code returned by OSS	Character string
error_msg	Error message returned by OSS	Character string
req_id	The UUID that identifies the request. You can provide the <code>req_id</code> to OSS development engineers for further help.	Character string

Timeout handling

If the code in the returned `aos_status_t` is not "2XX", and the `error_code` is -992 or -995, it indicates a connection timeout error or a request timeout error occurs. You can try again.

You can use the `aos_should_retry(aos_status_t *)` in the `aos_status.h` to determine whether the returned error code requires a retry. If the returned value is 1, you must try again.

Common error codes

Error code	Description	HTTP status code
AccessDenied	Access denied	403
BucketAlreadyExists	The bucket already exists.	409
BucketNotEmpty	The bucket is not empty.	409
EntityTooLarge	The entity size exceeds the maximum limit.	400
EntityTooSmall	The entity size is below the minimum limit.	400
FileGroupTooLarge	The total file group size exceeds the maximum limit.	400

Error code	Description	HTTP status code
FilePartNotExist	The file part does not exist.	400
FilePartStale	The file part has expired.	400
InvalidArgument	The parameter format is invalid.	400
InvalidAccessKeyId	The AccessKeyId does not exist.	403
InvalidBucketName	The bucket name is invalid.	400
InvalidDigest	The digest is invalid.	400
InvalidObjectName	The object name is invalid.	400
InvalidPart	The part is invalid.	400
InvalidPartOrder	The part order is invalid.	400
InvalidTargetBucketForLogging	The buckets that store log files are invalid.	400
InternalError	Internal OSS error	500
MalformedXML	The XML format is invalid.	400
MethodNotAllowed	The method is not supported.	405
MissingArgument	Parameters are not configured.	411
MissingContentLength	The content length is not configured.	411
NoSuchBucket	The bucket does not exist.	404
NoSuchKey	The object does not exist	404
NoSuchUpload	The multipart upload ID does not exist.	404
NotImplemented	The method cannot be processed.	501
PreconditionFailed	Pre-processing error.	412
RequestTimeTooSkewed	The local time set for OSSClient is deviated from the time set for the OSS server by over 15 minutes.	403
RequestTimeout	Request timeout	400
SignatureDoesNotMatch	Signature mismatch	403

Error code	Description	HTTP status code
TooManyBuckets	The number of buckets exceed the limits,.	400

6.17 FAQ

This topic lists the FAQs about OSS C SDK.

- [How to configure the output of application logs in OSS C SDK.](#)
- [How to configure parameters for cURL-based communication in OSS C SDK.](#)
- [How to upload data using callback of cURL in OSS C SDK.](#)
- [How to upload data using callback of cURL in OSS C SDK.](#)
- [How to download data using callback of cURL in OSS C SDK.](#)
- [How to upload and download objects with names containing Chinese characters in OSS C SDK \(for Windows\).](#)

7 . NET

7.1 Preface

The OSS C# SDK supports .NET Framework 2.0 and later. This document is written based on OSS C# SDK 2.8.0.

Compatibility

- For SDK series of 2.x.x
 - API: compatible
 - Namespace: compatible
- For SDK series of 1.0.x
 - API: compatible
 - Namespace: incompatible. Aliyun.OpenServices.OpenStorageService is changed to Aliyun.OSS

SDK source code and API documents

For the SDK source code, see [GitHub](#). For more information, see [API documents](#).

Code samples

OSS SDK for C# provides a variety of code samples for your reference or use. You can obtain the code samples from [GitHub](#). The following table describes the content of code samples.

Sample file	Content
PutObjectSample.cs	Upload objects
AppendObjectSample.cs	Append upload
DoesObjectExistSample.cs	Determine whether an object exists
DeleteObjectsSample.cs	Delete objects
CopyObjectSample.cs	Copy objects
ModifyObjectMetaSample.cs	Manage Object Meta
MultipartUploadSample.cs	Multipart upload
ResumableSample.cs	Resumable upload
GetObjectSample.cs	Download objects
GetObjectByRangeSample.cs	Range download

Sample file	Content
GetObjectAclSample.cs	Manage ACL for an object
SetObjectAclSample.cs	Manage ACL for an object
ListObjectsSample.cs	List objects
UrlSignatureSample.cs	Authorized access
UploadCallbackSample.cs	Upload callback
ProgressSample.cs	Upload progress bars and Download progress bars
CNameSample.cs	Use custome domain name to access OSS (CNAME)
PostPolicySample.cs	Form upload
CreateBucketSample.cs	Create a bucket
DeleteBucketSample.cs	Delete a bucket
Doesbucketexistsample. CS	Determine whether a bucket exists
ListBucketsSample.cs	List buckets
SetBucketAclSample.cs	Configure an ACL for a bucket
SetBucketLifecycleSample.cs	Lifecycle management
SetBucketLoggingSample.cs	Access log files
SetBucketRefererSample.cs	Anti-leech
SetBucketWetbsiteSample.cs	Static website hosting
SetBucketCorsSample.cs	CORS
ImageProcessSample.cs	Image processing

7.2 Installation

This topic describes how to install OSS C# SDK.

Preparation

- Windows
 - Applicable to .NET 2.0 and later.
 - Applicable to Visual Studio 2010 and later.
- Linux Mac
 - Applicable to Mono 3.12 and later.

Download SDK

- [Direct download](#)
- [Download from GitHub](#)
- [Download previous versions](#)

Install SDK

- Install OSS C# SDK in Windows

— Install SDK through NuGet

1. If your Visual Studio does not have NuGet installed, install [NuGet](#) first.
2. Create a project or open an existing project in Visual Studio, select **Tools > NuGet Package Manager > Management Solution NuGet Package**.
3. Search for aliyun.oss.sdk and find Aliyun.OSS.SDK in the search results. Select the latest version, and click **Install**.

— Install SDK through DLL reference

1. Download and unzip the C# SDK package.
2. In the Visual Studio, access **Solution Resource Manager**, select your project, right click Project Name. Select **Reference > Add Reference**, and then select **Browse** in the prompt dialog box.
3. Find the directory that the SDK package is unzipped to, select *Aliyun.OSS.dll* in the bin directory, and click **OK**.

— Install SDK through project introduction

If you download SDK package or the source code from GitHub and you want to install SDK package using the source code, you can

1. right click **Solution** in Visual Studio and select **Add** in the dialog box menu to add an existing project.
2. In the prompt dialog box, select *aliyun-oss-sdk.csproj*, and click **Open**.
3. Right click Your Projects and select **Reference > Add Reference**. In the prompt dialog box, click the **Project** tab, select the aliyun-oss-sdk project, and then click **OK**.

- Install OSS C# SDK in Windows

— Install SDK through NuGet

1. In Xamarin, create a project or open an existing project, and select **Add NuGet Packages** from Tool.

2. Search and find aliyun.oss.sdk, select the latest version, and click **Add Package** to add the package to project application.
- Install SDK through DLL reference
1. Download and unzip the C# SDK package.
 2. In Xamarin, select your project in **Solution**, right click **Reference**, and then select **Edit References** in the prompt menu.
 3. In the Edit References dialog box, select *.Net Assembly*, click **Browse**. Find the directory that SDK is unzipped to, select *Aliyun.OSS.dll* in the bin directory, and then click **Open**.

7.3 Quick start

This topic describes how to use OSS .NET SDK to perform routine operations such as bucket creation, object uploads, and object downloads.

Create a bucket

A bucket is a global namespace in OSS. It is similar to a data container that stores files.

Run the following code to create a bucket:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Create a bucket.
    var bucket = client.CreateBucket(bucketName);
    Console.WriteLine("Create bucket succeeded, {0} ", bucket.Name);
}
catch (Exception ex)
{
    Console.WriteLine("Create bucket failed, {0}", ex.Message);
}
```

For more information about bucket naming rules, see naming conventions in [Basic concepts](#).

Upload objects

Run the following code to upload a file to OSS:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
```

```

var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Upload a file
    var result = client.PutObject(bucketName, objectName, localFilename);
    Console.WriteLine("Put object succeeded, ETag: {0} ", result.ETag);
}
catch (Exception ex)
{
    Console.WriteLine("Put object failed, {0}", ex.Message);
}

```

For more information, see [Upload an object](#).

Download objects

Run the following code to download specified object to a local file:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
var downloadFilename = "<yourDownloadFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    client.PutObject(bucketName, objectName, localFilename);
    // Download the object.
    var result = client.GetObject(bucketName, objectName);
    using (var requestStream = result.Content)
    {
        using (var fs = File.Open(downloadFilename, FileMode.OpenOrCreate))
        {
            int length = 4 * 1024;
            var buf = new byte[length];
            do
            {
                length = requestStream.Read(buf, 0, length);
                fs.Write(buf, 0, length);
            } while (length != 0);
        }
    }
    Console.WriteLine("Get object succeeded");
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \n
    nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}

```



```

}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}

```

List objects

Run the following code to list objects in a specified bucket:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var objects = new List<string>();
    ObjectListing result = null;
    String nextmarker = string. empty;
    do
    {
        var listObjectsRequest = new ListObjectsRequest(bucketName)
        {
            Marker = nextMarker,
        };
        // List objects.
        result = client.ListObjects(listObjectsRequest);
        foreach (var summary in result.ObjectSummaries)
        {
            Console.WriteLine(summary.Key);
            objects.Add(summary.Key);
        }
        nextMarker = result.NextMarker;
    } while (result.IsTruncated);
    Console.WriteLine("List objects of bucket:{0} succeeded ",
bucketName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}

```

Delete objects

Run the following code to delete a specified object:

```

using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";

```

```
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Delete an object.
    client.DeleteObject(bucketName, objectName);
    Console.WriteLine("Delete object succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("Delete object failed, {0}", ex.Message);
}
```

7.4 Initialization

OSSClient serves as the OSS C# client to manage OSS resources such as buckets and objects.

Create an OSSClient instance

To create an OSSClient instance, you need to specify an endpoint. For more information about endpoints, see [Regions and endpoints](#) and [Bind a custom domain name](#).

- Use an OSS domain to create an OSSClient instance

Run the following code to create an OSSClient instance with a domain assigned by OSS:

```
using Aliyun.OSS;

const string accessKeyId = "<yourAccessKeyId>";
const string accessKeySecret = "<yourAccessKeySecret>";
const string endpoint = "http://oss-cn-hangzhou.aliyuncs.com";

// Create a new OSSClient instance with the OSS access address
// specified by the user and the AccessKeyId/AccessKeySecret granted by
// Alibaba Cloud.
var ossClient = new OssClient(endpoint, accessKeyId, accessKeySecret
);
```

- Use a custom domain (CNAME) to create an OSSClient instance

Run the following code to create an OSSClient instance with CNAME:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;

const string accessKeyId = "<yourAccessKeyId>";
const string accessKeySecret = "<yourAccessKeySecret>";
const string endpoint = "<yourDomain>";

// Create a ClientConfiguration instance. Modify parameters as
// required.
var conf = new ClientConfiguration();

// Enable CNAME. CNAME indicates a custom domain bound to a bucket.
conf.IsCname = true;
```

```
// Create an OSSClient instance.  
var client = new OssClient(endpoint, accessKeyId, accessKeySecret,  
conf);
```

**Note:**

The `ossClient.listBuckets` method cannot be used when a CNAME is used.

Configure an OSSClient instance

`ClientConfiguration` is a configuration class of `OSSClient`. `ClientConfiguration` is used to configure parameters such as user agents, host proxies, connection timeout, and the maximum number of connections. You can configure the following parameters.

Parameter	Description	Configuration method
ConnectionLimit	Specifies the maximum number of HTTP connections that can be enabled.	512
MaxErrorRetry	Specifies the maximum number of retry attempts in the case of a request error.	3
ConnectionTimeout	Specifies the timeout time in milliseconds when connections are established. The default value is -1, indicating that the connections are not time-out.	-1
IsCname	Specifies whether CNAME can be used as an endpoint.	false
ProgressUpdateInterval	Specifies the update interval of the progress bar, which is calculated by bytes.	8096

A code example is given as follows:

```
using Aliyun.OSS;  
using Aliyun.OSS.Common;  
  
var conf = new ClientConfiguration();  
conf.ConnectionLimit = 512;  
conf.MaxErrorRetry = 3;  
conf.ConnectionTimeout = 300;
```

```
var client = new OssClient(endpoint, accessKeyId, accessKeySecret,
conf);
```

- Data verification

Run the following code for MD5 data verification:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;

var conf = new ClientConfiguration();
// Enable MD5 verification. Set EnableMD5Check to perform MD5
// verification on the uploaded or downloaded data. MD5 verification is
// disabled by default.
conf.EnableMD5Check = true;

var client = new OssClient(endpoint, accessKeyId, accessKeySecret,
conf);
```

**Note:**

System performance reduces when MD5 verification is disabled.

- Proxy network

If you use proxy networks, you can configure the following parameters to access OSS:

Parameter	Description	Default value
ProxyHost	A proxy server, such as 8.8.8.8 or abc.def.com.	Null
ProxyPort	A proxy port, such as 3128 or 8080.	Null
ProxyUserName	The proxy service account, which is optional	Null
ProxyPassword	The proxy service password, which is optional	Null

An example of proxy network access without using the account and password is as follows:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;

var conf = new ClientConfiguration();
conf.ProxyHost = "8.8.8.8";
conf.ProxyPort = 3128;
```

```
var client = new OssClient(endpoint, accessKeyId, accessKeySecret,
conf);
```

An example of proxy network access using the account and password is as follows:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;

var conf = new ClientConfiguration();
conf.ProxyHost = "8.8.8.8";
conf.ProxyPort = 3128;
conf.ProxyUserName = "user";
conf.ProxyPassword = "6666";

var client = new OssClient(endpoint, accessKeyId, accessKeySecret,
conf);
```

7.5 Manage a bucket

A bucket serves as a container that stores objects. Objects belong to a bucket.

Create a bucket

For the complete code of creating a bucket, see [GitHub](#).

You can run the following code to create a bucket:

```
using Aliyun.OSS;

// Initialize an OSSClient.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);

// Create a new bucket.
public void CreateBucket(string bucketName)
{
    try
    {
        // Create a bucket. The bucketName is globally unique.
        client.CreateBucket(bucketName);
        Console.WriteLine("Create bucket succeeded");
    }
    catch (Exception ex)
    {
        Console.WriteLine("Create bucket failed. {0}", ex.Message);
    }
}
```

List buckets

For the complete code of listing buckets, see [GitHub](#).

You can run the following code to list all buckets under an account:

```
using Aliyun.OSS;

// Initialize an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
```

```
// List the information about all buckets under an account.
public void ListBuckets()
{
    try
    {
        var buckets = client.ListBuckets();

        Console.WriteLine("List bucket succeeded");
        foreach (var bucket in buckets)
        {
            Console.WriteLine("Bucket name : {0}, Location : {1}, Owner : {2}", bucket.Name, bucket.Location, bucket.Owner);
        }
    }
    catch (Exception ex)
    {
        Console.WriteLine("List bucket failed. {0}", ex.Message);
    }
}
```

Determine whether a bucket exists

For the complete code of determining whether a bucket exists, see [GitHub](#).

You can run the following code to determine whether a bucket exists:

```
using Aliyun.OSS;

//Initialize an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);

// Determine whether a bucket exists.
public void DoesBucketExist(string bucketName)
{
    try
    {
        var exist = client.DoesBucketExist(bucketName);

        Console.WriteLine("Check object Exist succeeded");
        Console.WriteLine("exist ? {0}", exist);
    }
    catch (Exception ex)
    {
        Console.WriteLine("Check object Exist failed. {0}", ex.Message);
    }
}
```

Configure an ACL for a bucket

For the complete code of configuring ACL, see [GitHub](#).

The ACL of a bucket includes the following permissions.

Permission	Description	Value
Private	The bucket owner and the authorized users can read and write objects in the bucket. Other users cannot perform any operation on the objects.	oss.ACLPrivate
Public read	The bucket owner and the authorized users can read and write objects in the bucket . Other users can only read the objects in the bucket. Authorize this permission with caution.	oss.ACLPublicRead
Public read-write	All users can read and write objects in the bucket. Authorize this permission with caution.	oss.ACLPublicReadWrite

You can run the following code to configure an ACL for a bucket:

```
using Aliyun.OSS;

// Initialize an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);

// Configure an access ACL for the bucket
public void SetBucketAcl(string bucketName)
{
    try
    {
        // Set the ACL of the bucket to public read.
        client.SetBucketAcl(bucketName, CannedAccessControlList.
        PublicRead);
        Console.WriteLine("Set bucket ACL succeeded");
    }
    catch (Exception ex)
    {
        Console.WriteLine("Set bucket ACL failed. {0}", ex.Message);
    }
}
```

Obtain the ACL for a bucket

For the complete code of obtaining the ACL for a bucket, see [GitHub](#).

You can run the following code to obtain the ACL for a bucket:

```
using Aliyun.OSS;

// Initialize an OSSClient instance.
```

```
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);

// Obtain the ACL for the bucket.
public void GetBucketAcl(string bucketName)
{
    try
    {
        string bucketName = "your-bucket";
        var acl = client.GetBucketAcl(bucketName);

        Console.WriteLine("Get bucket ACL success", acl.ACL.ToString());
    }
    catch (Exception ex)
    {
        Console.WriteLine("Get bucket ACL failed. {0}", ex.Message);
    }
}
```

Delete a bucket

For the complete code of deleting a bucket, see [GitHub](#).

Before a bucket is deleted, ensure that all objects in the bucket and fragments that are generated from multipart upload are deleted.



Note:

To delete the fragments that are generated from multipart upload, use [Bucket.ListMultipartUploads](#) to list all fragments, and then use [Bucket.AbortMultipartUpload](#) to delete the fragments.

You can run the following code to delete a bucket:

```
using Aliyun.OSS;

// Initialize an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);

// Delete the bucket.
public void DeleteBucket(string bucketName)
{
    try
    {
        client.DeleteBucket(bucketName);

        Console.WriteLine("Delete bucket succeeded");
    }
    catch (Exception ex)
    {
        Console.WriteLine("Delete bucket failed. {0}", ex.Message);
    }
}
```



```
}
```

7.6 Upload objects

7.6.1 Overview

In OSS, an object is the basic unit for data operations. OSS .NET SDK provides the following file upload methods:

- [Simple upload](#): supports the upload of a file up to 5 GB in size.
- [Append upload](#): supports the upload of a file up to 5 GB in size.
- [Resumable upload](#): supports concurrent upload and you can define the size of each part. It applies to the upload of large files. Resumable upload supports the upload of a file up to 48.8 TB in size.
- [Multipart upload](#): supports the upload of a file up to 48.8 TB in size. It applies to the upload of large files.

**Note:**

For more information about the usage scenarios of each upload method, see “Upload files” in OSS Developer Guide.

During the file upload, you can set [Object Meta](#), and view the [upload progress](#). After you complete the file upload, you can perform [upload callback](#).

7.6.2 Simple upload

Upload a string

For the complete code of uploading a string, see [GitHub](#).

You can run the following code to upload a string:

```
using System.Text;
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var objectContent = "More than just cloud." ;
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    byte[] binaryData = Encoding.ASCII.GetBytes(objectContent);
    MemoryStream requestContent = new MemoryStream(binaryData);
    // Upload a file.
```

```
        client.PutObject(bucketName, objectName, requestContent);
        Console.WriteLine("Put object succeeded");
    }
    catch (Exception ex)
    {
        Console.WriteLine("Put object failed, {0}", ex.Message);
    }
}
```

Upload a specified local file

For the complete code of uploading a specified local file, see [Git Hub](#).

You can run the following code to upload a specified local file:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Upload a local file.
    client.PutObject(bucketName, objectName, localFilename);
    Console.WriteLine("Put object succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("Put object failed, {0}", ex.Message);
}
}
```

Upload a file with MD5 verification

To ensure the consistency between the data sent by the SDK and the data received by the OSS client, you can add a Content-MD5 value in ObjectMeta. Then OSS checks the received data against the MD5 value.

For the complete code of uploading a file with MD5 verification, see [GitHub](#).

```
using Aliyun.OSS;
using Aliyun.OSS.Util;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Calculate the MD5 value.
    string md5;
    using (var fs = File.Open(localFilename, FileMode.Open))
```

```

    {
        md5 = OssUtils.ComputeContentMd5(fs, fs.Length);
    }
    var objectMeta = new ObjectMetadata
    {
        ContentMd5 = md5
    };
    // Upload a file.
    client.PutObject(bucketName, objectName, localFilename, objectMeta
);
    Console.WriteLine("Put object succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("Put object failed, {0}", ex.Message);
}

```

**Note:**

MD5 verification may cause a reduction in performance.

Asynchronous upload

For the complete code of asynchronous upload, see [GitHub](#).

You can run the following code to perform asynchronous upload:

```

using System;
using System.IO;
using System.Threading;

using Aliyun.OSS;
using Aliyun.OSS.Common;

// Upload a file asynchronously.
namespace AsyncPutObject
{
    class Program
    {
        static string endpoint = "<yourEndpoint>";
        static string accessKeyId = "<yourAccessKeyId>";
        static string accessKeySecret = "<yourAccessKeySecret>";
        static string bucketName = "<yourBucketName>";
        static string objectName = "<yourObjectName>";
        static string localFilename = "<yourLocalFilename>";

        static AutoResetEvent _event = new AutoResetEvent(false);

        // Create an OSSClient instance.
        static OssClient client = new OssClient(endpoint, accessKeyId
, accessKeySecret);

        private static void PutObjectCallback(IAsyncResult ar)
        {
            try
            {
                client.EndPutObject(ar);
                Console.WriteLine(ar.AsyncState as string);
                Console.WriteLine("Put object succeeded");
            }
            catch { }
        }
    }
}

```

```

    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.Message);
    }
    finally
    {
        _event.Set();
    }
}

public static void AsyncPutObject()
{
    try
    {
        using (var fs = File.Open(localFilename, FileMode.Open
))
        {
            var metadata = new ObjectMetadata();
            // Add custom meta information.
            metadata.UserMetadata.Add("mykey1", "myval1");
            metadata.UserMetadata.Add("mykey2", "myval2");
            metadata.CacheControl = "No-Cache";
            metadata.ContentType = "text/html";
            string result = "Notice user: put object finish";

            // Upload a file asynchronously.
            client.BeginPutObject(bucketName, objectName, fs,
metadata, PutObjectCallback, result.ToCharArray());

            _event.WaitOne();
        }
    }
    catch (OssException ex)
    {
        Console.WriteLine("Failed with error code: {0}; Error
info: {1}. \nRequestID:{2}\tHostID:{3}",
            ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId
);
    }
    catch (Exception ex)
    {
        Console.WriteLine("Failed with error info: {0}", ex.
Message);
    }
}

static void Main(string[] args)
{
    Program.AsyncPutObject();
}
}

```

**Note:**

When using asynchronous upload, you must implement your own callback handler.

7.6.3 Append upload

For the complete code of append upload, see [GitHub](#).

You cannot perform copyObject for appended objects. When you call AppendObject to upload data, if the target object does not exist, an appendable object is created. If the object already exists, data is appended to the object.

Run the following code for append upload:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
// If the object is appended for the first time, the append position
// is 0, and the returned value is the position for the next append. The
// position for the next append is the length of object before the append
long position = 0;
try
{
    var metadata = client.GetObjectMetadata(bucketName, objectName);
    position = metadata.ContentLength;
}
catch (Exception) { }
try
{
    using (var fs = File.Open(localFilename, FileMode.Open))
    {
        var request = new AppendObjectRequest(bucketName, objectName)
        {
            ObjectMetadata = new ObjectMetadata(),
            Content = fs,
            Position = position
        };
        // Append the object.
        var result = client.AppendObject(request);
        // Configure the position where the object is appended
        position = result.NextAppendPosition;
        Console.WriteLine("Append object succeeded, next append
position:{0}", position);
    }
    // Obtain the start position for the next append.
    using (var fs = File.Open(localFilename, FileMode.Open))
    {
        var request = new AppendObjectRequest(bucketName, objectName)
        {
            ObjectMetadata = new ObjectMetadata(),
            Content = fs,
            Position = position
        };
        var result = client.AppendObject(request);
        position = result.NextAppendPosition;
    }
}
```

```

        Console.WriteLine("Append object succeeded, next append
position:{0}", position);
    }
}
catch (Exception ex)
{
    Console.WriteLine("Append object failed, {0}", ex.Message);
}

```

7.6.4 Resumable upload

You can use resumable upload to split a file you want to upload into several parts and upload them simultaneously. After you have uploaded all parts, you can combine these parts into a complete object. Thus, you can complete uploading the entire object.

Current upload progress is recorded into a checkpoint file during the upload. If a part fails to be uploaded during the process, the object is uploaded from the part recorded in the checkpoint file when the upload restarts, that is, the resumable upload. After the upload is complete, the checkpoint is deleted.

For the complete code of resumable upload, see [GitHub](#).

Run the following code for resumable upload:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
string checkpointDir = "<yourCheckpointDir>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Configure parameters with UploadFileRequest.
    UploadObjectRequest request = new UploadObjectRequest(bucketName,
objectName, localFilename)
    {
        // Specify the size of a part you want to upload.
        PartSize = 8 * 1024 * 1024,
        // Specify the number of threads for simultaneous upload.
        ParallelThreadCount = 3,
        // The progress information of a resumable upload is stored
in the checkpointDir directory. If a part fails to be uploaded, the
progress information is used to continue the upload. If the checkpoint
Dir directory is null, the resumable upload does not take effect, and
the file that failed to be uploaded is uploaded all over again.
        CheckpointDir = checkpointDir,
    };
    // Start resumable upload.
    client.ResumableUploadObject(request);
    Console.WriteLine("Resumable upload object:{0} succeeded",
objectName);
}

```

```
}  
catch (OssException ex)  
{  
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \nRequestID:{2}\\tHostID:{3}",  
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);  
}  
catch (Exception ex)  
{  
    Console.WriteLine("Failed with error info: {0}", ex.Message);  
}
```

7.6.5 Multipart upload

For the complete code of multipart upload, see [GitHub](#).

To enable multipart upload, perform the following steps:

1. Initiate a multipart upload event.

You can call `OssClient.initiateMultipartUpload` to return the globally unique uploadId created in OSS.

2. Upload parts.

You can call `OssClient.uploadPart` to upload part data.



Note:

- For parts with a same uploadId, parts are sequenced by their part numbers. If you have uploaded a part and use the same part number to upload another part, the later part will replace the former part.
- OSS places the MD5 value of part data in ETag and returns the MD5 value to the user.
- SDK automatically configures Content-MD5. OSS calculates the MD5 value of uploaded data and compares it with the MD5 value calculated by SDK. If the two values vary, the error code of InvalidDigest is returned.

3. Complete multipart upload.

After you have uploaded all parts, call `partOssClient.completeMultipartUpload` to combine these parts into a complete object.

The following code is used as a complete example that describes the process of multipart upload:

```
using Aliyun.OSS;  
var endpoint = "<yourEndpoint>";  
var accessKeyId = "<yourAccessKeyId>";  
var accessKeySecret = "<yourAccessKeySecret>";  
var bucketName = "<yourBucketName>";  
var objectName = "<yourObjectName>";
```

```

var localFilename = "<yourLocalFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
// Initiate the multipart upload.
var uploadId = "";
try
{
    // Specifiy the name and the bucket of the uploaded object. You
    can configure ObjectMeta when using InitiateMultipartUploadRequest.
    However, you do not need to specify the ContentLength.
    var request = new InitiateMultipartUploadRequest(bucketName,
objectName);
    var result = client.InitiateMultipartUpload(request);
    uploadId = result.UploadId;
    // Print the UploadId
    Console.WriteLine("Init multi part upload succeeded");
    Console.WriteLine("Upload Id:{0}", result.UploadId);
}
catch (Exception ex)
{
    Console.WriteLine("Init multi part upload failed, {0}", ex.Message
);
}
// Calculate the total number of parts.
var partSize = 100 * 1024;
var fi = new FileInfo(localFilename);
var fileSize = fi.Length;
var partCount = fileSize / partSize;
if (fileSize % partSize != 0)
{
    partCount++;
}
// Start the multipart upload. partETags is a list of partETags. OSS
verifies the validity of all parts one by one after it receives the
partETags. After part verification is successful, OSS combines these
parts into a complete object.
var partETags = new List<PartETag>();
try
{
    using (var fs = File.Open(localFilename, FileMode.Open))
    {
        for (var i = 0; i < partCount; i++)
        {
            var skipBytes = (long)partSize * i;
            // Locate to the start position of the upload.
            fs.Seek(skipBytes, 0);
            // Calculate the size of the uploaded part. The size of
the last part is the size of the data remained after being splited by
the part size.
            var size = (partSize < fileSize - skipBytes) ? partSize :
(fileSize - skipBytes);
            var request = new UploadPartRequest(bucketName, objectName
, uploadId)
            {
                InputStream = fs,
                PartSize = size,
                PartNumber = i + 1
            };
            // Call the UploadPart interface to upload the object. The
returned results contain the ETag value of the uploaded part.
            var result = client.UploadPart(request);
            partETags.Add(result.PartETag);

```



```

        Console.WriteLine("finish {0}/{1}", partETags.Count,
partCount);
    }
    Console.WriteLine("Put multi part upload succeeded");
}
}
catch (Exception ex)
{
    Console.WriteLine("Put multi part upload failed, {0}", ex.Message
);
}
// List uploaded parts.
try
{
    var listPartsRequest = new ListPartsRequest(bucketName, objectName
, uploadId);
    var listPartsResult = client.ListParts(listPartsRequest);
    Console.WriteLine("List parts succeeded");
    // Upload each part simultaneously until all parts are uploaded.
    var parts = listPartsResult.Parts;
    foreach (var part in parts)
    {
        Console.WriteLine("partNumber: {0}, ETag: {1}, Size: {2}",
part.PartNumber, part.ETag, part.Size);
    }
}
catch (Exception ex)
{
    Console.WriteLine("List parts failed, {0}", ex.Message);
}
// Complete the multipart upload.
try
{
    var completeMultipartUploadRequest = new CompleteMultipartUplo
adRequest(bucketName, objectName, uploadId);
    foreach (var partETag in partETags)
    {
        completeMultipartUploadRequest.PartETags.Add(partETag);
    }
    var result = client.CompleteMultipartUpload(completeMultipartUplo
adRequest);
    Console.WriteLine("complete multi part succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("complete multi part failed, {0}", ex.Message);
}
}

```

Cancel a multipart upload event

For the complete code of canceling a multipart upload event, see [GitHub](#).

Run the following code to cancel a multipart upload event:

```

using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var uploadId = "";

```

```
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
// Initiate the multipart upload.
try
{
    var request = new InitiateMultipartUploadRequest(bucketName,
objectName);
    var result = client.InitiateMultipartUpload(request);
    uploadId = result.UploadId;
    // Print the UploadId.
    Console.WriteLine("Init multi part upload succeeded");
    Console.WriteLine("Upload Id:{0}", result.UploadId);
}
catch (Exception ex)
{
    Console.WriteLine("Init multi part upload failed, {0}", ex.Message
);
}
// Cancel the multipart upload.
try
{
    var request = new AbortMultipartUploadRequest(bucketName,
objectName, uploadId);
    client.AbortMultipartUpload(request);
    Console.WriteLine("Abort multi part succeeded , {0}", uploadId);
}
catch (Exception ex)
{
    Console.WriteLine("Abort multi part failed, {0}", ex.Message);
}
}
```

List uploaded parts

For the complete code of listing uploaded parts, see [GitHub](#).

Run the following code to list uploaded parts:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var uploadId = "<yourUploadId>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    PartListing listPartsResult = null;
    var nextMarker = 0;
    do
    {
        var listPartsRequest = new ListPartsRequest(bucketName,
objectName, uploadId)
        {
            PartNumberMarker = nextMarker,
        };
        // List uploaded parts.
        listPartsResult = client.ListParts(listPartsRequest);
        Console.WriteLine("List parts succeeded");
    }
    while (listPartsResult.IsTruncated);
}
catch (Exception ex)
{
    Console.WriteLine("List parts failed, {0}", ex.Message);
}
}
```

```

// Upload each part simultaneously until all parts are
uploaded.
var parts = listPartsResult.Parts;
foreach (var part in parts)
{
    Console.WriteLine("partNumber: {0}, ETag: {1}, Size: {2}
", part.PartNumber, part.ETag, part.Size);
}
nextMarker = listPartsResult.NextPartNumberMarker;
} while (listPartsResult.IsTruncated);
}
catch (Exception ex)
{
    Console.WriteLine("List parts failed, {0}", ex.Message);
}

```

List multipart upload events

Call `ossClient.listMultipartUploads` to list all ongoing part upload events (events that have been initiated but not completed or have been canceled). You can configure the following parameters:

Parameter	Description	Configuration method
prefix	Specifies the prefix that must be included in the returned object name. Note that if you use a prefix for query, the returned object name will contain the prefix.	ListMultipartUploadsRequest. setPrefix(String prefix)
delimiter	Specifies a delimiter of a forward slash (/) used to group object names. The object between the specified prefix and the first occurrence of a delimiter of a forward slash (/) is commonPrefixes.	ListMultipartUploadsRequest. setDelimiter(String delimiter)
maxUploads	Specifies the maximum number of part upload events . The maximum value (also default value) you can set is 1,000.	ListMultipartUploadsRequest .setMaxUploads(Integer maxUploads)
keyMarker	Lists all part upload events with the object whose names start with a letter that comes after the keyMarker value in the alphabetical order. You can use this parameter with the uploadIdMarker parameter to	ListMultipartUploadsRequest .setKeyMarker(String keyMarker)

Parameter	Description	Configuration method
	specify the initial position for the specified returned result.	
uploadIdMarker	You can use this parameter with the keyMarker parameter to specify the initial position for the specified returned result. If you do not configure keyMarker, the uploadIdMarker parameter is invalid. If you configure keyMarker, the query result contains: - All objects whose names start with a letter that comes after the keyMarker value. - All objects whose names start with a letter that is the same as the keyMarker value in the alphabetical order and the value of uploadId greater than that of uploadIdMarker.	ListMultipartUploadsRequest.setUploadIdMarker(String uploadIdMarker)

For the complete code of listing multipart upload events, see [GitHub](#).

Run the following code to list all multipart upload events:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    MultipartUploadListing multipartUploadListing = null;
    var nextMarker = string.Empty;
    do
    {
        // List multipart upload events.
        var request = new ListMultipartUploadsRequest(bucketName)
        {
            KeyMarker = nextMarker,
        };
        multipartUploadListing = client.ListMultipartUploads(request);
        Console.WriteLine("List multi part succeeded");
        // List the information about multipart upload events.
    }
}
```

```

        foreach (var mu in multipartUploadListing.MultipartUploads)
        {
            Console.WriteLine("Key: {0}, UploadId: {1}", mu.Key, mu.
UploadId);
        }
        // If the returned result shows that the value of isTruncate
d is false, the values of nextKeyMarker and nextUploadIdMarker are
returned and used as the initial position for the next object reading.
        nextMarker = multipartUploadListing.NextKeyMarker;
    } while (multipartUploadListing.IsTruncated);
}
catch (Exception ex)
{
    Console.WriteLine("List multi part uploads failed, {0}", ex.
Message);
}

```

Specify the prefix and maximum number of returned results

Run the following code to perform multipart upload with a specified prefix and maximum number of returned results:

```

using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Define prefix.
var prefix = "<yourObjectPrefix>";
// Set the maximum number of returned result to 100.
var maxUploads = 100;
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    MultipartUploadListing multipartUploadListing = null;
    var nextMarker = string.Empty;
    do
    {
        // List multipart upload events. By default, 1,000 parts are
listed.
        var request = new ListMultipartUploadsRequest(bucketName)
        {
            KeyMarker = nextMarker,
            // Specify the prefix.
            Prefix = prefix,
            // Specify the maximum number of returned result.
            MaxUploads = maxUploads,
        };
        multipartUploadListing = client.ListMultipartUploads(request);
        Console.WriteLine("List multi part succeeded");
        // List the information about each multipart upload event.
        foreach (var mu in multipartUploadListing.MultipartUploads)
        {
            Console.WriteLine("Key: {0}, UploadId: {1}", mu.Key, mu.
UploadId);
        }
        nextMarker = multipartUploadListing.NextKeyMarker;
    } while (multipartUploadListing.IsTruncated);
}

```

```
catch (Exception ex)
{
    Console.WriteLine("List multi part uploads failed, {0}", ex.
Message);
}
```

7.6.6 Upload progress bars

You can use progress bars to indicate the upload or download progress.

For the complete code of progress bars, see [GitHub](#).

The following code is used as an example to describe how to view progress information with PutObject:

```
using System;
using System.IO;
using System.Text;
using Aliyun.OSS;
using Aliyun.OSS.Common;
namespace PutObjectProgress
{
    class Program
    {
        static void Main(string[] args)
        {
            Program.PutObjectProgress();
            Console.ReadKey();
        }
        public static void PutObjectProgress()
        {
            var endpoint = "<yourEndpoint>";
            var accessKeyId = "<yourAccessKeyId>";
            var accessKeySecret = "<yourAccessKeySecret>";
            var bucketName = "<yourBucketName>";
            var objectName = "<yourObjectName>";
            var localFilename = "<yourLocalFilename>";
            // Create an OSSClient instance.
            var client = new OssClient(endpoint, accessKeyId,
accessKeySecret);
            // Upload with a progress bar displayed.
            try
            {
                using (var fs = File.Open(localFilename, FileMode.Open
))
                {
                    var putObjectRequest = new PutObjectRequest(
bucketName, objectName, fs);
                    putObjectRequest.StreamTransferProgress +=
streamProgressCallback;
                    client.PutObject(putObjectRequest);
                }
                Console.WriteLine("Put object:{0} succeeded",
objectName);
            }
            catch (OssException ex)
            {
                Console.WriteLine("Failed with error code: {0}; Error
info: {1}. \nRequestID: {2}\tHostID: {3}",
```

```

        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId
    );
    }
    catch (Exception ex)
    {
        Console.WriteLine("Failed with error info: {0}", ex.
Message);
    }
    }
    // Obtain the upload progress.
    private static void streamProgressCallback(object sender,
StreamTransferProgressArgs args)
    {
        System.Console.WriteLine("ProgressCallback - Progress: {0
}% , TotalBytes:{1}, TransferredBytes:{2} ",
            args.TransferredBytes * 100 / args.TotalBytes, args.
TotalBytes, args.TransferredBytes);
    }
}
}

```

7.6.7 Upload callback

For the complete code of upload callback, see [GitHub](#).

Run the following code for upload callback:

```

using System;
using System.IO;
using System.Text;
using Aliyun.OSS;
using Aliyun.OSS.Common;
using Aliyun.OSS.Util;
namespace Callback
{
    class Program
    {
        static void Main(string[] args)
        {
            Program.PutObjectCallback();
            Console.ReadKey();
        }
        public static void PutObjectCallback()
        {
            var endpoint = "<yourEndpoint>";
            var accessKeyId = "<yourAccessKeyId>";
            var accessKeySecret = "<yourAccessKeySecret>";
            var bucketName = "<yourBucketName>";
            var objectName = "<yourObjectName>";
            var localFilename = "<yourLocalFilename>";
            // Specify the IP address of the server you want to send
the callback request to.
            const string callbackUrl = "http://oss-demo.aliyuncs.com:
23450";
            # Configure the value of the body field carried in the
callback request.
            const string callbackBody = "bucket=${bucket}&object=${
object}&etag=${etag}&size=${size}&mimeType=${mimeType}&" +
                "my_var1=${x:var1}&my_var2=${x
:var2}";

```

```

        // Create an OSSClient instance.
        var client = new OssClient(endpoint, accessKeyId,
accessKeySecret);
        try
        {
            string responseContent = "";
            var metadata = BuildCallbackMetadata(callbackUrl,
callbackBody);
            using (var fs = File.Open(localFilename, FileMode.Open
))
            {
                var putObjectRequest = new PutObjectRequest(
bucketName, objectName, fs, metadata);
                var result = client.PutObject(putObjectRequest);
                responseContent = GetCallbackResponse(result);
            }
            Console.WriteLine("Put object:{0} succeeded, callback
response content:{1}", objectName, responseContent);
        }
        catch (OssException ex)
        {
            Console.WriteLine("Failed with error code: {0}; Error
info: {1}. \nRequestID: {2}\tHostID: {3}",
                ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId
);
        }
        catch (Exception ex)
        {
            Console.WriteLine("Failed with error info: {0}", ex.
Message);
        }
    }
    // Configure upload callback.
    private static ObjectMetadata BuildCallbackMetadata(string
callbackUrl, string callbackBody)
    {
        string callbackHeaderBuilder = new CallbackHeaderBuilder(
callbackUrl, callbackBody). Build();
        string CallbackVariableHeaderBuilder = new CallbackVa
riableHeaderBuilder().
            AddCallbackVariable("x:var1", "x:value1"). AddCallbac
kVariable("x:var2", "x:value2"). Build();
        var metadata = new ObjectMetadata();
        metadata.AddHeader(HttpHeaders.Callback, callbackHe
aderBuilder);
        metadata.AddHeader(HttpHeaders.CallbackVar, CallbackVa
riableHeaderBuilder);
        return metadata;
    }
    // Read the message returned from upload callback.
    private static string GetCallbackResponse(PutObjectResult
putObjectResult)
    {
        string callbackResponse = null;
        using (var stream = putObjectResult.ResponseStream)
        {
            var buffer = new byte[4 * 1024];
            var bytesRead = stream.Read(buffer, 0, buffer.Length);
            callbackResponse = Encoding.Default.GetString(buffer,
0, bytesRead);
        }
        return callbackResponse;
    }

```



```
}  
}  
}
```

**Note:**

For more information about upload callback, see [Upload callback](#) in the Developer Guide.

7.7 Download objects

7.7.1 Overview

OSS .NET SDK provides the following download methods:

- [Streaming download](#)
- [Range download](#)
- [Resumable download](#)

You can view the download progress shown in [download progress bars](#).

7.7.2 Streaming download

If you have a large object to download or it is time-consuming to download the entire object at a time, you can use streaming download. Streaming download enables you to download part of the object each time until you have downloaded the entire object.

For the complete code of streaming download, see [GitHub](#).

Run the following code to download a specified OSS object to a stream:

```
using Aliyun.OSS;  
var endpoint = "<yourEndpoint>";  
var accessKeyId = "<yourAccessKeyId>";  
var accessKeySecret = "<yourAccessKeySecret>";  
var bucketName = "<yourBucketName>";  
var objectName = "<yourObjectName>";  
var downloadFilename = "<yourDownloadFilename>";  
// Create an OSSClient instance.  
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);  
try  
{  
    // Download an object to a stream. OssObject includes object  
    information, such as the bucket that contains the object, object name  
    , metadata, and an input stream.  
    var obj = client.GetObject(bucketName, objectName);  
    using (var requestStream = obj.Content)  
    {  
        byte[] buf = new byte[1024];  
        var fs = File.Open(downloadFilename, FileMode.OpenOrCreate);  
        var len = 0;  
        // Use the input stream to read the object content into a file  
        or the memory.  
    }  
}
```

```
        while ((len = requestStream.Read(buf, 0, 1024)) != 0)
        {
            fs.Write(buf, 0, len);
        }
        fs.Close();
    }
    Console.WriteLine("Get object succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("Get object failed. {0}", ex.Message);
}
```

7.7.3 Range download

If you only need part of the data in an object, you can use range downloads to download specified content.

For the complete code of range download, see [GitHub](#).

Run the following code for range download:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var downloadFilename = "<yourDownloadFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var getObjectRequest = new GetObjectRequest(bucketName, objectName);
    // Set the range, which is from the 20th byte to the 100th byte.
    getObjectRequest.SetRange(20, 100);
    // Start range download. The setRange of getObjectRequest can be
    used to implement multipart download and resumable download.
    var obj = client.GetObject(getObjectRequest);
    // Download the data and write it into a file.
    using (var requestStream = obj.Content)
    {
        byte[] buf = new byte[1024];
        var fs = File.Open(downloadFilename, FileMode.OpenOrCreate);
        var len = 0;
        while ((len = requestStream.Read(buf, 0, 1024)) != 0)
        {
            fs.Write(buf, 0, len);
        }
        fs.Close();
    }
    Console.WriteLine("Get object succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("Get object failed. {0}", ex.Message);
}
```

```
}
```

You can configure the following parameters of `GetObjectRequest`.

Parameter	Description
Range	Specifies the transmission range of an object.
ModifiedSinceConstraint	If the specified time is earlier than the actual modification time of the file, the file is transmitted normally. Otherwise, a 304 Not Modified exception is thrown.
UnmodifiedSinceConstraint	If the time passed to the parameter is equal to or later than the actual modification time of the file, the file is transmitted normally. Otherwise, a 412 precondition failed exception is thrown.
MatchingETagConstraints	Passes in a group of ETags. If the ETags match the ETag of the file, the file is transmitted normally. Otherwise, a 412 precondition failed exception is thrown.
NonmatchingEtagConstraints	Passes in a group of ETags. If the ETags do not match the ETag of the file, the file is transmitted normally. Otherwise, a 304 Not Modified exception is thrown.
ResponseHeaderOverrides	Customizes some headers in requests returned by OSS.

7.7.4 Resumable download

Large-sized objects may fail to be downloaded because the network is unstable or the Java program exits abnormally and the entire object needs to be downloaded again. However, the object may still fail to be downloaded after multiple attempts. Therefore, OSS provides resumable download.

Run the following code for resumable download:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;

var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
var downloadFilename = "<yourDownloadFilename>";
var checkpointDir = "<yourCheckpointDir>";
```

```
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Configure parameters with DownloadObjectRequest.
    DownloadObjectRequest request = new DownloadObjectRequest(
        bucketName, objectName, downloadFilename)
    {
        // Specify the size of a part you want to download.
        PartSize = 8 * 1024 * 1024,
        // Specifies the number of concurrent download threads.
        ParallelThreadCount = 3,
        // Specify the checkpointDir to store the download progress
        // information. If the download fails, it can be continued based on the
        // progress information. If the checkpointDir directory is null, the
        // resumable upload is not enabled, which means that objects that fails
        // to be downloaded are downloaded all over again.
        CheckpointDir = checkpointDir,
    };
    // Start resumable download.
    client.ResumableDownloadObject(request);
    Console.WriteLine("Resumable download object:{0} succeeded",
        objectName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \n
        nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}
```

For more information about resumable download, see [Resumable download](#) in OSS Developer Guide.

7.7.5 Download progress bars

You can use progress bars to indicate the upload or download progress.

For the complete code of download progress bar, see [GitHub](#).

The following code is used as an example to describe how to view progress information with `GetObject`:

```
using System;
using System.IO;
using Aliyun.OSS;
using Aliyun.OSS.Common;
namespace GetObjectProgress
{
    class Program
    {
        static void Main(string[] args)
        {
            Program.GetObjectProgress();
        }
    }
}
```

```

        Console.ReadKey();
    }
    public static void GetObjectProgress()
    {
        var endpoint = "<yourEndpoint>";
        var accessKeyId = "<yourAccessKeyId>";
        var accessKeySecret = "<yourAccessKeySecret>";
        var bucketName = "<yourBucketName>";
        var objectName = "<yourObjectName>";
        // Create an OSSClient instance.
        var client = new OssClient(endpoint, accessKeyId,
accessKeySecret);
        try
        {
            var getObjectRequest = new GetObjectRequest(bucketName
, objectName);
            getObjectRequest.StreamTransferProgress += streamProg
ressCallback;
            // Download an object.
            var ossObject = client.GetObject(getObjectRequest);
            using (var stream = ossObject.Content)
            {
                var buffer = new byte[1024 * 1024];
                var bytesRead = 0;
                while ((bytesRead = stream.Read(buffer, 0, buffer.
Length)) > 0)
                {
                    // Process the read data (detailed code is not
                    listed here).
                }
            }
            Console.WriteLine("Get object:{0} succeeded",
objectName);
        }
        catch (OssException ex)
        {
            Console.WriteLine("Failed with error code: {0}; Error
info: {1}. \nRequestID:{2}\tHostID:{3}",
                ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId
);
        }
        catch (Exception ex)
        {
            Console.WriteLine("Failed with error info: {0}", ex.
Message);
        }
    }
    private static void streamProgressCallback(object sender,
StreamTransferProgressArgs args)
    {
        System.Console.WriteLine("ProgressCallback - Progress: {0
}% , TotalBytes:{1}, TransferredBytes:{2} ",
            args.TransferredBytes * 100 / args.TotalBytes, args.
TotalBytes, args.TransferredBytes);
    }
}
}

```

7.8 Manage objects

7.8.1 Overview

This topic is the overview of object management in OSS .NET SDK.

You can perform the following operations on objects in a bucket with APIs:

- [Determine whether an object exists](#)
- [Manage ACL for an object](#)
- [Manage Object Meta](#)
- [List objects](#)
- [Delete an object](#)
- [Copy an object](#)
- [Restore an archive object](#)
- [Manage a symbolic link](#)

7.8.2 Determine whether a specified object exists

Run the following code to determine whether a specified object exists:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;

var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";

// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Determine whether a specified object exists.
    var exist = client.DoesObjectExist(bucketName, objectName);
    Console.WriteLine("Object exist ? " + exist);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \n
nRequestID:{2}\\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

7.8.3 Manage ACL for an object

The following table describes the permissions included in the Access Control List (ACL) for an object.

Permission	Description	Value
default	The ACL of an object is the same with that of its bucket.	CannedAccessControlList.Default
Private	Only the object owner and authorized users can read and write the object.	CannedAccessControlList.Private
Public read	Only the object owner and authorized users can read and write the object. Other users can only read the object . Authorize this permission with caution.	CannedAccessControlList.PublicRead
Public read-write	All users can read and write the object. Authorize this permission with caution.	CannedAccessControlList.PublicReadWrite

The ACL of objects take precedence over that of buckets. For example, if the ACL of a bucket is private, while the object ACL is public read-write, all users can read and write the object. If an object is not configured with an ACL, its ACL is the same as that of its bucket by default.

For the complete code of configuring an ACL for an object, see [GitHub](#). For the complete code of obtaining the ACL for an object, see [GitHub](#).

You can run the following code to configure an ACL for an object and obtain the ACL for an object:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;

var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";

// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
// Configure an ACL for an object.
try
{
    // Use SetObjectAcl to configure an ACL for an object.
    client.SetObjectAcl(bucketName, objectName, CannedAccessControll
ist.PublicRead);
    Console.WriteLine("Set Object:{0} ACL succeeded ", objectName);
}
catch (Exception ex)
{
    Console.WriteLine("Set Object ACL failed with error info: {0}", ex
.Message);
}
```

```
// Obtain the ACL for an object.
try
{
    // Use GetObjectAcl to obtain the ACL for an object.
    var result = client.GetObjectAcl(bucketName, objectName);
    Console.WriteLine("Get Object ACL succeeded, Id: {0}  ACL: {1}",
        result.Owner.Id, result.ACL.ToString());
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \n
nRequestID: {2}\\tHostID: {3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

For details about object ACL, see [Access control](#).

7.8.4 Manage Object Meta

Object Meta includes HTTP headers and user-defined Object Meta. For more information, see [Object Meta](#) in OSS Developer Guide.

For the complete code of configuring Object Meta, see [GitHub](#). For the complete code of modifying Object Meta, see [GitHub](#).

Run the following code to configure, modify, and obtain Object Meta:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var localFilename = "<yourLocalFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    using (var fs = File.Open(localFilename, FileMode.Open))
    {
        // Create Object Meta. You can configure HTTP headers with
        Object Meta.
        var metadata = new ObjectMetadata()
        {
            // Specify the object type.
            ContentType = "text/html",
            // Configure the expiration time (GMT is used).
            ExpirationTime = DateTime.Parse("2025-10-12T00:00:00.000Z
"),
        };
        // Configure the length of the object you want to upload.
        If the object length is greater than the configured length, only
        the configured length of the object is uploaded. If the configured
```



```

length is greater than the actual object length, the entire object is
uploaded.
    metadata.ContentLength = fs.Length;
    // Configure the cache action of a webpage when an object is
downloaded.
    metadata.CacheControl = "No-Cache";
    // Set the value of metadata mykey1 to myval1.
    metadata.UserMetadata.Add("mykey1", "myval1");
    // Set the value of metadata mykey2 to myval2.
    metadata.UserMetadata.Add("mykey2", "myval2");
    var saveAsFilename = "Filetest123.txt";
    var contentDisposition = string.Format("attachment;filename*=
utf-8''{0}", HttpUtils.EncodeUri(saveAsFilename, "utf-8"));
    // Provide a default file name when saving the requested
content as a file.
    metadata.ContentDisposition = contentDisposition;
    // Upload a file and configure the Object Meta.
    client.PutObject(bucketName, objectName, fs, metadata);
    Console.WriteLine("Put object succeeded");
    //Obtain Object Meta.
    var oldMeta = client.GetObjectMetadata(bucketName, objectName
);
    // Configure new Object Meta.
    var newMeta = new ObjectMetadata()
    {
        ContentType = "application/octet-stream",
        ExpirationTime = DateTime.Parse("2035-11-11T00:00:00.000Z
"),
        // Specify the encoding format of a download object.
        ContentEncoding = null,
        CacheControl = ""
    };
    // Add custom Object Meta.
    newMeta.UserMetadata.Add("author", "oss");
    newMeta.UserMetadata.Add("flag", "my-flag");
    newMeta.UserMetadata.Add("mykey2", "myval2-modified-value");
    // Use the ModifyObjectMeta method to modify Object Meta.
    client.ModifyObjectMeta(bucketName, objectName, newMeta);
}
}
catch (Exception ex)
{
    Console.WriteLine("Put object failed, {0}", ex.Message);
}

```


Note:

- For detailed information about HTTP header, see [RFC2616](#).
- The size of Object Meta with custom HTTP headers is no larger than 8 KB.

7.8.5 List objects

For the complete code of listing objects, see [GitHub](#).

Objects are listed alphabetically. You can use ListObjects to list objects in a bucket. The following table describes the parameters of ListObjects

Parameter	Description
Delimiter	Specifies a delimiter of a forward slash (/) used to group object names. CommonPrefixes is a set of objects which are ended with the delimiter and have the same prefix.
Marker	Specifies the initial object in the list.
MaxKeys	Specifies the maximum number of objects that can be listed. The default value of MaxKeys is 100. The maximum value of MaxKeys is 1,000.
Prefix	Specifies the prefix you configure to list required objects.

Simple list

For the complete code of simple list, see [GitHub](#).

Run the following code to list objects in a specified bucket.

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var listObjectsRequest = new ListObjectsRequest(bucketName);
    // Simply list the objects in a specified bucket. 100 records are
    returned by default.
    var result = client.ListObjects(listObjectsRequest);
    Console.WriteLine("List objects succeeded");
    foreach (var summary in result.ObjectSummaries)
    {
        Console.WriteLine("File name:{0}", summary.Key);
    }
}
catch (Exception ex)
{
    Console.WriteLine("List objects failed. {0}", ex.Message);
}
```

List a specified number of objects

Use the following code to list a specified number of objects:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
```

```
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var listObjectsRequest = new ListObjectsRequest(bucketName)
    {
        // A maximum of 200 records can be returned.
        MaxKeys = 200,
    };
    var result = client.ListObjects(listObjectsRequest);
    Console.WriteLine("List objects succeeded");
    foreach (var summary in result.ObjectSummaries)
    {
        Console.WriteLine(summary.Key);
    }
}
catch (Exception ex)
{
    Console.WriteLine("List objects failed, {0}", ex.Message);
}
```

List objects by a specified prefix

Use the following code to list objects with a specified prefix:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var prefix = "<yourObjectPrefix>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var keys = new List<string>();
    ObjectListing result = null;
    string nextMarker = string.Empty;
    do
    {
        var listObjectsRequest = new ListObjectsRequest(bucketName)
        {
            Marker = nextMarker,
            MaxKeys = 100,
            Prefix = prefix,
        };
        result = client.ListObjects(listObjectsRequest);
        foreach (var summary in result.ObjectSummaries)
        {
            Console.WriteLine(summary.Key);
            keys.Add(summary.Key);
        }
        nextMarker = result.NextMarker;
    } while (result.IsTruncated);
    Console.WriteLine("List objects of bucket:{0} succeeded ",
bucketName);
}
catch (OssException ex)
{
}
```

```

        Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
            ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
    }
    catch (Exception ex)
    {
        Console.WriteLine("Failed with error info: {0}", ex.Message);
    }

```

List objects by marker

The marker parameter indicates the name of an object from which the listing begins. Run the following code to specify an object (specified with marker) after which the listing begins:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var marker = "<yourObjectMarker>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var keys = new List<string>();
    ObjectListing result = null;
    string nextMarker = marker;
    do
    {
        var listObjectsRequest = new ListObjectsRequest(bucketName)
            // To increase the number of returned objects, you can modify
the MaxKeys parameter or use the Marker parameter for multiple reads.
        {
            Marker = nextMarker,
            MaxKeys = 100,
        };
        result = client.ListObjects(listObjectsRequest);
        foreach (var summary in result.ObjectSummaries)
        {
            Console.WriteLine(summary.Key);
            keys.Add(summary.Key);
        }
        nextMarker = result.NextMarker;
        // If the value of IsTruncated is true, the next read starts from
NextMarker.
    } while (result.IsTruncated);
    Console.WriteLine("List objects of bucket:{0} succeeded ",
        bucketName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}

```

```
}
```

List objects in an asynchronous mode

For the complete code of listing objects in an asynchronous mode, see [GitHub](#).

Run the following code to list objects in an asynchronous mode:

```
using System;
using System.IO;
using System.Threading;
using Aliyun.OSS;
namespace AsyncListObjects
{
    class Program
    {
        static string endpoint = "<yourEndpoint>";
        static string accessKeyId = "<yourAccessKeyId>";
        static string accessKeySecret = "<yourAccessKeySecret>";
        static string bucketName = "<yourBucketName>";
        static AutoResetEvent _event = new AutoResetEvent(false);
        // Create an OSSClient instance.
        static OssClient client = new OssClient(endpoint, accessKeyId
, accessKeySecret);
        static void Main(string[] args)
        {
            Program.AsyncListObjects();
            Console.ReadKey();
        }
        public static void AsyncListObjects()
        {
            try
            {
                var listObjectsRequest = new ListObjectsRequest(
bucketName);
                client.BeginListObjects(listObjectsRequest, ListObject
Callback, null);
                _event.WaitOne();
            }
            catch (Exception ex)
            {
                Console.WriteLine("Async list objects failed. {0}", ex
.Message);
            }
            // The ListObjectCallback method is implemented after an
asynchronous call. Similar interfaces must be used when an asynchrono
us interface is called to list objects.
            private static void ListObjectCallback(IAsyncResult ar)
            {
                try
                {
                    var result = client.EndListObjects(ar);
                    foreach (var summary in result.ObjectSummaries)
                    {
                        Console.WriteLine ("Object name: 0", summary.Key);
                    }
                    _event.Set();
                    Console.WriteLine("Async list objects succeeded");
                }
                catch (Exception ex)
            }
        }
    }
}
```

```

        {
            Console.WriteLine("Async list objects failed. {0}", ex
        .Message);
        }
    }
}

```

List all objects in a bucket

Run the following code to list all objects in a bucket:

```

using Aliyun.OSS;
// Initialize OssClient.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
// List all objects in the bucket.
public void ListObject(string bucketName)
{
    try
    {
        ObjectListing result = null;
        string nextMarker = string.Empty;
        do
        {
            // The number of objects listed in each page is specified
            by the maxKeys parameter. If the object number is larger than the
            specified value, other files are listed in another page.
            var listObjectsRequest = new ListObjectsRequest(bucketName
        )
            {
                Marker = nextMarker,
                MaxKeys = 100
            };
            result = client.ListObjects(listObjectsRequest);
            Console.WriteLine("File:");
            foreach (var summary in result.ObjectSummaries)
            {
                Console.WriteLine("Name:{0}", summary.Key);
            }
            nextMarker = result.NextMarker;
        } while (result.IsTruncated);
    }
    catch (Exception ex)
    {
        Console.WriteLine("List object failed. {0}", ex.Message);
    }
}

```

7.8.6 Delete objects

This topic describes how to delete objects.



Warning:

Delete objects with caution because deleted objects cannot be recovered.

For the complete code of deleting objects, see [GitHub](#).

Delete an object

Run the following code to delete a single object:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    /// Delete an object.
    client.DeleteObject(bucketName, objectName);
    Console.WriteLine("Delete object succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("Delete object failed. {0}", ex.Message);
}
```

Delete multiple objects

You can delete a maximum of 1,000 objects simultaneously. Objects can be deleted in two modes : detail (verbose) and simple (quiet) modes.

- verbose: returns the list of objects that you have deleted successfully. The default mode is verbose.
- quiet: returns the list of objects that you failed to delete.

Run the following code to delete multiple objects simultaneously:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var keys = new List<string>();
    var listResult = client.ListObjects(bucketName);
    foreach (var summary in listResult.ObjectSummaries)
    {
        keys.Add(summary.Key);
    }
    // If the quietMode is true, the quiet mode is used. If the
    quietMode is false, the verbose mode is used. The default mode is
    verbose.
    var quietMode = false;
    // The third parameter of the DeleteObjectsRequest specifies the
    return mode.
    var request = new DeleteObjectsRequest(bucketName, keys, quietMode
);
```

```
// Delete multiple objects.
var result = client.DeleteObjects(request);
if ((! quietMode) && (result.Keys != null))
{
    foreach (var obj in result.Keys)
    {
        Console.WriteLine("Delete successfully : {0} ", obj.Key);
    }
    Console.WriteLine("Delete objects succeeded");
}
catch (Exception ex)
{
    Console.WriteLine("Delete objects failed. {0}", ex.Message);
}
```

7.8.7 Copy objects

Copy a small-sized object

For the complete code of copying a small-sized object, see [GitHub](#).

Note the following limits before copying a small-sized object:

- You must have the read and write permission on the source object.
- You cannot copy an object from a region to another region. For example, you cannot copy an object from a bucket in Hangzhou region to a bucket in Qingdao region.
- The object size is limited to a maximum of 1 GB.

Run the following code to copy a small-sized object:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var sourceBucket = "<yourSourceBucketName>";
var sourceObject = "<yourSourceObjectName>";
var targetBucket = "<yourDestBucketName>";
var targetObject = "<yourDestObjectName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var metadata = new ObjectMetadata();
    metadata.AddHeader("mk1", "mv1");
    metadata.AddHeader("mk2", "mv2");
    var req = new CopyObjectRequest(sourceBucket, sourceObject,
    targetBucket, targetObject)
    {
        // If the value of NewObjectMetadata is null, the COPY mode is
        // used (the metadata of the source object is copied). If the value of
        // NewObjectMetadata is not null, the REPLACE mode is used (the metadata
        // of the source object is replaced).
        NewObjectMetadata = metadata
    };
    // Copy an object.
```



```

        client.CopyObject(req);
        Console.WriteLine("Copy object succeeded");
    }
    catch (OssException ex)
    {
        Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID: {2} \tHostID: {3}",
            ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
    }
    catch (Exception ex)
    {
        Console.WriteLine("Failed with error info: {0}", ex.Message);
    }
}

```

Copy a large-sized object

For the complete code of copying large-sized objects, see [GitHub](#).

- UploadPartCopy

To copy an object larger than 1 GB, you need to use UploadPartCopy.

1. Use InitiateMultipartUploadRequest to initiate an UploadPartCopy event.
2. Use the UploadPartCopy method to perform a multipart copy.
3. Use the CompleteMultipartUpload method to complete the object copy.

Run the following code for UploadPartCopy task:

```

using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var sourceBucket = "<yourSourceBucketName>";
var sourceObject = "<yourSourceObjectName>";
var targetBucket = "<yourDestBucketName>";
var targetObject = "<yourDestObjectName>";
var uploadId = "";
var partSize = 50 * 1024 * 1024;
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Initiate a copy task. You can use the InitiateMultipartUp
    loadRequest method to specify the metadata information about the
    target object.
    var request = new InitiateMultipartUploadRequest(targetBucket,
    targetObject);
    var result = client.InitiateMultipartUpload(request);
    // Print the uploadId.
    uploadId = result.UploadId;
    Console.WriteLine("Init multipart upload succeeded, Upload Id:
    {0}", result.UploadId);
    // Calculate the number of parts.
    var metadata = client.GetObjectMetadata(sourceBucket, sourceObje
    ct);
    var fileSize = metadata.ContentLength;
    var partCount = (int)fileSize / partSize;
    if (fileSize % partSize != 0)

```

```

    {
        partCount++;
    }
    // Start the UploadPartCopy task.
    var partETags = new List<PartETag>();
    for (var i = 0; i < partCount; i++)
    {
        var skipBytes = (long)partSize * i;
        var size = (partSize < fileSize - skipBytes) ? partSize : (
fileSize - skipBytes);
        // Create UploadPartCopyRequest. You can specify conditions
with UploadPartCopyRequest.
        var uploadPartCopyRequest = new UploadPartCopyRequest(
targetBucket, targetObject, sourceBucket, sourceObject, uploadId)
        {
            PartSize = size,
            PartNumber = i + 1,
            // Beginindex is used to locate the location that
the last UploadPartCopy starts.
            BeginIndex = skipBytes
        };
        // Call the uploadPartCopy method to copy each part.
        var uploadPartCopyResult = client.UploadPartCopy(uploadPart
CopyRequest);
        Console.WriteLine("UploadPartCopy : {0}", i);
        partETags.Add(uploadPartCopyResult.PartETag);
    }
    // Complete the UploadPartCopy task.
    var completeMultipartUploadRequest =
new CompleteMultipartUploadRequest(targetBucket, targetObject,
uploadId);
    // The partETags refers to the list of partETags saved during
the multipart upload. After OSS receives the part list submitted
by the user, it verifies the validity of each data part one by one
. After the verification is passed, OSS combine these parts into a
complete object.
    foreach (var partETag in partETags)
    {
        completeMultipartUploadRequest.PartETags.Add(partETag);
    }
    var completeMultipartUploadResult = client.CompleteMultipartUploa
d(completeMultipartUploadRequest);
    Console.WriteLine("CompleteMultipartUpload succeeded");
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}.
\nRequestID: {2} \tHostID: {3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}

```

- Resumable copy

If the copy is interrupted, you can use resumable copy to continue the copy. For the complete code of resumable copy, see [GitHub](#).

Run the following code for resumable copy:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var sourceBucket = "<yourSourceBucketName>";
var sourceObject = "<yourSourceObjectName>";
var targetBucket = "<yourDestBucketName>";
var targetObject = "<yourDestObjectName>";
var checkpointDir = @"<yourCheckpointDir>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var request = new CopyObjectRequest(sourceBucket, sourceObject,
    targetBucket, targetObject);
    // The checkpointDir directory stores the intermediate state
    information of a resumable upload. The information will be used when
    a failed upload task is resumed. // If the checkpointDir directory
    is null, resumable copy will not take effect, and the object that
    previously failed to be copied will be copied all over again.
    client.ResumableCopyObject(request, checkpointDir);
    Console.WriteLine("Resumable copy new object:{0} succeeded",
    request.DestinationKey);
}
catch (Exception ex)
{
    Console.WriteLine("Resumable copy new object failed, {0}", ex.
    Message);
}
```

7.8.8 Restore an archive object

For the complete code of restoring an archive object, see [GitHub](#).

You must restore an archive object before you read it. Do not call `restoreObject` for non-archive objects.

The state conversion process of an archive object is as follows:

- An archive object is in the frozen state.
- After you submit it for restoration, the server restores the object. The object is in the restoring state.
- You can read the object after it is restored. The restored state of the object lasts one day by default. You can prolong this period to a maximum of seven days. Once this period expires, the object returns to the frozen state.

Run the following code to restore an object:

```
using Aliyun.OSS;
using Aliyun.OSS.Model;
var endpoint = "<yourEndpoint>";
```

```

var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var objectContent = "More than just cloud.";
int maxWaitTimeInSeconds = 600;
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Create a bucket of the archive storage class..
    var bucket = client.CreateBucket(bucketName, StorageClass.Archive
);
    Console.WriteLine("Create Archive bucket succeeded, {0} ", bucket.
Name);
}
catch (Exception ex)
{
    Console.WriteLine("Create Archive bucket failed, {0}", ex.Message
);
}
// Upload a file.
try
{
    byte[] binaryData = Encoding.ASCII.GetBytes(objectContent);
    MemoryStream requestContent = new MemoryStream(binaryData);
    client.PutObject(bucketName, objectName, requestContent);
    Console.WriteLine("Put object succeeded, {0}", objectName);
}
catch (Exception ex)
{
    Console.WriteLine("Put object failed, {0}", ex.Message);
}
var metadata = client.GetObjectMetadata(bucketName, objectName);
string storageClass = metadata.HttpMetadata["x-oss-storage-class"] as
string;
if (storageClass != "Archive")
{
    Console.WriteLine("StorageClass is {0}", storageClass);
    return;
}
// Restore the object.
RestoreObjectResult result = client.RestoreObject(bucketName,
objectName);
Console.WriteLine("RestoreObject result HttpStatusCode : {0}", result.
HttpStatusCode);
if (result.HttpStatusCode != HttpStatusCode.Accepted)
{
    throw new OssException(result.RequestId + ", " + result.HttpStatus
Code + " ,");
}
while (maxWaitTimeInSeconds > 0)
{
    var meta = client.GetObjectMetadata(bucketName, objectName);
    string restoreStatus = meta.HttpMetadata["x-oss-restore"] as
string;
    if (restoreStatus != null && restoreStatus.StartsWith("ongoing-
request=\"false\"", StringComparison.InvariantCultureIgnoreCase))
    {
        break;
    }
    Thread.Sleep(1000);
}

```

```
        maxWaitTimeInSeconds--;  
    }  
    if (maxWaitTimeInSeconds == 0)  
    {  
        Console.WriteLine("RestoreObject is timeout. ");  
        throw new TimeoutException();  
    }  
    else  
    {  
        Console.WriteLine("RestoreObject is successful. ");  
    }  
}
```

For more information about the archive storage classes, see [Introduction to storage classes](#). For detailed information about related status code, see [RestoreObject](#).

7.8.9 Manage a symbolic link

A symbolic link is a special object that maps to an object similar to a shortcut used in Windows . You can configure user-defined Object Meta for symbolic links. To obtain a symbolic link, you must have the read permission on it.

Run the following code to create and obtain a symbolic link:

```
using Aliyun.OSS;  
var endpoint = "<yourEndpoint>";  
var accessKeyId = "<yourAccessKeyId>";  
var accessKeySecret = "<yourAccessKeySecret>";  
var bucketName = "<yourBucketName>";  
var targetObjectName = "<yourTargetObjectName>";  
var symlinkObjectName = "<yourSymlinkObjectName>";  
var objectContent = "More than just cloud." ;  
// Create an OSSClient instance.  
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);  
try  
{  
    // Upload the target file.  
    byte[] binaryData = Encoding.ASCII.GetBytes(objectContent);  
    MemoryStream requestContent = new MemoryStream(binaryData);  
    client.PutObject(bucketName, targetObjectName, requestContent);  
    // Create a symbolic link.  
    client.CreateSymlink(bucketName, symlinkObjectName, targetObject  
ctName);  
    // Obtain a symbolic link.  
    var ossSymlink = client.GetSymlink(bucketName, symlinkObjectName);  
    Console.WriteLine("Target object is {0}", ossSymlink.Target);  
}  
catch (Exception ex)  
{  
    Console.WriteLine("Failed with error info: {0}", ex.Message);  
}
```

For more information about creating symbolic links, see [PutSymlink](#).

For more information about obtaining symbolic links, see [GetSymlink](#).

7.9 Authorized access

Use STS for temporary access authorization

OSS supports Alibaba Cloud Security Token Service (STS) for temporary access authorization. STS is a web service that provides a temporary access token to a cloud computing user. Through the STS, you can assign a third-party application or a RAM user (you can manage the user ID) an access credential with a custom validity period and permissions. For more information about STS, see [STS introduction](#).

STS advantages:

- Your long-term key (AccessKey) is not exposed to a third-party application. You only need to generate an access token and send the access token to the third-party application. You can customize access permissions and the validity of this token.
- You do not need to keep track of permission revocation issues. The access token automatically becomes invalid when it expires.

For more information about the process of access to OSS with STS, see [RAM and STS scenario practices](#) in OSS Developer Guide.

Run the following code to create a signature request with STS:

```
using Aliyun.OSS;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var securityToken = "<yourSecurityToken>";
// After a user obtains a temporary STS credential, the OSSClient is
// generated with the security token and temporary access key (AccessKeyID
// and AccessKeySecret).
// Create an OSSClient instance.
var ossStsClient = new OssClient(endpoint, accessKeyId, accessKeySecret, securityToken);
// Perform operations on OSS.
```

Sign a URL to authorize temporary access

You can provide a signed URL to a visitor for temporary access. When you sign a URL, you can specify the expiration time for a URL to restrict the period of access from visitors.

For the complete code of signing a URL to authorize temporary access, see [GitHub](#).

- Use a signed URL to upload a file

Run the following code to upload a file with a signed URL:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
```

```

var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var objectContent = "More than just cloud." ;
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Generate a signed URL for upload.
    var generatePresignedUriRequest = new GeneratePresignedUri
Request(bucketName, objectName, SignHttpMethod.Put)
    {
        Expiration = DateTime.Now.AddHours(1),
    };
    var signedUrl = client.GeneratePresignedUri(generatePresignedUri
Request);
    // Upload a file with the signed URL.
    var buffer = Encoding.UTF8.GetBytes(objectContent);
    using (var ms = new MemoryStream(buffer))
    {
        client.PutObject(signedUrl, ms);
    }
    Console.WriteLine("Put object by signatrue succeeded. {0} ",
signedUrl.ToString());
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}.
\nRequestId:{2}\tHostId:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}

```

- Use a signed URL to download an object

Run the following code to download an object with a signed URL:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
var downloadFilename = "<yourDownloadFilename>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var metadata = client.GetObjectMetadata(bucketName, objectName);
    var etag = metadata.ETag;
    // Generate a signed URL for download.
    var req = new GeneratePresignedUriRequest(bucketName, objectName
, SignHttpMethod.Get);
    var uri = client.GeneratePresignedUri(req);
    // Download an object with the signed URL.
}
}

```

```

OssObject ossObject = client.GetObject(uri);
using (var file = File.Open(downloadFilename, FileMode.
OpenOrCreate))
{
    using (Stream stream = ossObject.Content)
    {
        int length = 4 * 1024;
        var buf = new byte[length];
        do
        {
            length = stream.Read(buf, 0, length);
            file.Write(buf, 0, length);
        } while (length != 0);
    }
}
Console.WriteLine("Get object by signatrue succeeded. {0} ", uri
.ToString());
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}.
\nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}

```

7.10 Manage lifecycle rules

You can use OSS to configure lifecycle rules to reduce storage costs. The lifecycle management rules can be used for automatic deletion of expired objects and fragments, or storage class conversion to Infrequent Access for objects that will expire soon. Each rule includes:

- Rule ID: It identifies a rule. Ensure that each rule ID in a bucket is unique.
- Policy: You can configure a policy by using the following configuration methods. Only one method can be configured for a bucket.
 - Configure by Prefix: You can create multiple rules with this method. Ensure that each prefix is unique.
 - Configure for Entire Bucket: You can configure only one rule with this method.
- Expired: You can configure the following configuration methods:
 - Set by Number of Days: It specifies the number of days from the last modification time of objects.
 - Set by Date: It specifies the date prior to which objects are created. If objects are created prior to the date, these objects are deleted.
- Status: This lifecycle rule takes effect or not.

The parts uploaded by `uploadPart` method also support lifecycle rules. The last modification time of an object is the time the multipart upload event is initiated.

For more information about lifecycle management, see [Manage object lifecycle](#).

For the complete code of lifecycle management, see [GitHub](#).

Configure lifecycle rules

Run the following code to configure lifecycle rules:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var setBucketLifecycleRequest = new SetBucketLifecycleRequest(
        bucketName);
    // Create the first lifecycle rule that is valid within 3 days.
    LifecycleRule lcr1 = new LifecycleRule()
    {
        ID = "delete obsoleted files",
        Prefix = "obsoleted/",
        Status = RuleStatus.Enabled,
        ExpirationDays = 3
    };
    // Create the second lifecycle rule.
    LifecycleRule lcr2 = new LifecycleRule()
    {
        ID = "delete temporary files",
        Prefix = "temporary/",
        Status = RuleStatus.Enabled,
        ExpirationDays = 20
    };
    setBucketLifecycleRequest.AddLifecycleRule(lcr1);
    setBucketLifecycleRequest.AddLifecycleRule(lcr2);
    // Configure the lifecycle.
    client.SetBucketLifecycle(setBucketLifecycleRequest);
    Console.WriteLine("Set bucket:{0} Lifecycle succeeded ",
        bucketName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \n
        nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

```
}
```

View lifecycle rules

For the complete code of viewing lifecycle rules, see [GitHub](#).

Run the following code to view lifecycle rules:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // View the lifecycle rules.
    var rules = client.GetBucketLifecycle(bucketName);
    Console.WriteLine("Get bucket:{0} Lifecycle succeeded ",
bucketName);
    foreach (var rule in rules)
    {
        Console.WriteLine("ID: {0}", rule.ID);
        Console.WriteLine("Prefix: {0}", rule.Prefix);
        Console.WriteLine("Status: {0}", rule.Status);
        if (rule.ExpirationDays.HasValue)
            Console.WriteLine("ExpirationDays: {0}", rule.Expiration
Days);
    }
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

Clear lifecycle rules

Run the following code to clear lifecycle rules:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Clear the lifecycle rules
    client.DeleteBucketLifecycle(bucketName);
}
```

```

        Console.WriteLine("Delete bucket:{0} Lifecycle succeeded ",
        bucketName);
    }
    catch (OssException ex)
    {
        Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
        nRequestID:{2}\tHostID:{3}",
            ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
    }
    catch (Exception ex)
    {
        Console.WriteLine("Failed with error info: {0}", ex.Message);
    }
}

```

7.11 Set logging

You can enable access logs to record bucket access to log files, which are stored in a specified bucket.

The log file format is as follows:

<TargetPrefix><SourceBucket>-YYYY-mm-DD-HH-MM-SS-UniqueString

For more information about access log files, see [Set access logging](#). For the complete code of access logging, see [GitHub](#).

Enable access logging

Run the following code to enable bucket access logging:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var targetBucketName = "<yourTargetBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // The targetBucketName parameter is the name of the bucket that
    logs are stored. The logging- option indicates the prefix of log files
    . The bucketName and targetBucketName can be the same bucket.
    var request = new SetBucketLoggingRequest(bucketName, targetBuck
    etName, "logging-");
    // Enable access logging.
    client.SetBucketLogging(request);
    Console.WriteLine("Set bucket:{0} Logging succeeded ", bucketName
    );
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \
    nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}

```

```
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

View access logging configurations

For the complete code of viewing access logging configurations, see [GitHub](#).

Run the following code to view the access logging configurations for a bucket:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // View bucket access logging configurations.
    var result = client.GetBucketLogging(bucketName);
    Console.WriteLine("Get bucket:{0} Logging succeeded, prefix:{1}",
        bucketName, result.TargetPrefix);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

Disable access logging

For the complete code of disabling access logging, see [GitHub](#).

Run the following code to disable access logging for a bucket:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Disable access logging. Existing log files are not affected.
    client.DeleteBucketLogging(bucketName);
    Console.WriteLine("Delete bucket:{0} Logging succeeded ",
        bucketName);
}
catch (OssException ex)
```

```
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

7.12 CORS

Cross-origin resource sharing (CORS) allows web applications to access resources that belong to another region. OSS provides CORS APIs for convenient cross-origin access control.

For more information, see [Cross-origin resource sharing](#) and [PutBucketcors](#) in OSS Developer Guide.

For the complete code of CORS, see [GitHub](#).

Configure CORS rules

For complete code of configuring CORS rules, see [GitHub](#).

Run the following code to configure CORS rules for a specified bucket:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Creates an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var request = new SetBucketCorsRequest(bucketName);
    var rule1 = new CORSRule();
    // Specify the allowed source of the cross-origin access request.
    rule1.AddAllowedOrigin("http://www.a.com");
    // Specify the cross-region request methods (GET, PUT, DELETE,
    POST, and HEAD) that are allowed.
    rule1.AddAllowedMethod("POST");
    // AllowedHeaders and ExposeHeaders do not support wildcards.
    rule1.AddAllowedHeader("*");
    // Specify the response header that allows user access from
    applications.
    rule1.AddExposeHeader("x-oss-test");
    // A maximum of 10 rules is allowed.
    request.AddCORSRule(rule1);
    var rule2 = new CORSRule();
    // AllowedOrigins and AllowedMethods allow only one wildcard
    asterisk (*). Wildcard asterisks (*) indicate that all sources of the
    cross-origin requests and operations are allowed.
    rule2.AddAllowedOrigin("http://www.b.com");
    rule2.AddAllowedMethod("GET");
}
```

```

// Determine whether the header specified in the Access-Control-
Headers in the pre-flight (OPTIONS) requests is allowed.
rule2. AddExposeHeader("x-oss-test2");
// Specify the cache time (seconds) for the response of browser
pre-flight (OPTIONS) requests to a specific resource.
rule2. MaxAgeSeconds = 100;
request.AddCORSRule(rule2);
// Configure CORS rules.
client.SetBucketCors(request);
Console.WriteLine("Set bucket:{0} Cors succeeded ", bucketName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}

```

Obtain CORS rules

For the complete code of obtaining CORS rules, see [GitHub](#).

Run the following code to obtain CORS rules:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Obtain CORS rules.
    var result = client.GetBucketCors(bucketName);
    Console.WriteLine("Get bucket:{0} Cors succeeded ", bucketName);
    foreach (var rule in result)
    {
        foreach (var origin in rule.AllowedOrigins)
        {
            Console.WriteLine("Allowed origin:{0}", origin);
        }
    }
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}

```

```
}
```

Delete CORS rules

For the complete code of deleting CORS rules, see [GitHub](#).

Run the following code to delete all CORS rules for a specified bucket:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Delete CORS rules.
    client.DeleteBucketCors(bucketName);
    Console.WriteLine("Delete bucket:{0} Cors succeeded ", bucketName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0} ; Error info: {1}.
    \nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

7.13 Anti-leech

This topic describes how to use anti-leech.

To prevent your data on OSS from being leeches, OSS supports anti-leeching through the referer field settings in the HTTP header, including the following parameters:

- **Referer whitelist:** Used to allow access only for specified domains to OSS data.
- **Empty referer:** Determines whether the referer can be empty. If it is not allowed, only requests with the referer filed in their HTTP or HTTPS headers can access OSS data.

For more information about anti-leaching, see [Anti-leeching settings](#).

For the complete code of configuring anti-leech, see [GitHub](#).

Configure the referer whitelist

Run the following code to configure the referer whitelist:

```
using Aliyun.OSS;
```

```

using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var refererList = new List<string>();
    // Add the referer field. The referer field allows question marks
    (?) and asterisks (*) for wildcard use.
    refererList.Add(" http://www.aliyun.com");
    refererList.Add(" http://www. *.com");
    refererList.Add(" http://www.?.aliyuncs.com");
    var srq = new SetBucketRefererRequest(bucketName, refererList);
    // Configure the referer list for a bucket.
    client.SetBucketReferer(srq);
    Console.WriteLine("Set bucket:{0} Referer succeeded ", bucketName
);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}

```

Obtain a referer whitelist

For the complete code of obtaining a referer whitelist, see [GitHub](#).

Run the following code to obtain a referer whitelist:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Obtain the referer list for a bucket.
    var rc = client.GetBucketReferer(bucketName);
    Console.WriteLine("Get bucket:{0} Referer succeeded ", bucketName
);
    Console.WriteLine("allow?" + (rc.AllowEmptyReferer ? "yes" : "no
"));
    if (rc.RefererList.Referers != null)
    {
        for (var i = 0; i < rc.RefererList.Referers.Length; i++)
            Console.WriteLine(rc.RefererList.Referers[i]);
    }
    else
    {

```



```

        Console.WriteLine("Empty Referer List");
    }
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
finally
{
    client.SetBucketReferer(new SetBucketRefererRequest(bucketName));
}

```

Clear a referer whitelist

Run the following code to clear a referer whitelist:

```

using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // You cannot clear a referer whitelist directly. To clear a
    referer whitelist, you need to create the rule that allows an empty
    referer field and replace the original rule with the new rule.
    var srq = new SetBucketRefererRequest(bucketName);
    client.SetBucketReferer(srq);
    Console.WriteLine("Set bucket:{0} Referer succeeded ", bucketName
);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}

```

```
}
```

7.14 Image processing

Image Processing (IMG) is a massive, secure, cost-effective and highly reliable image processing service. After source images are uploaded to OSS, you can process images on any Internet device at any anytime, from anywhere through simple RESTful APIs.

For more information about IMG, see [Image Processing](#).

Basic features

OSS offers the following IMG features:

- [Retrieve dominant image tones](#)
- [Format conversion](#)
- [Resize images](#)
- [Incircle](#)
- [Adaptive orientation](#)
- [Brightness](#)
- [Add watermarks](#): allows you to add images, texts, or image-text watermarks to another image.
- [Image processing](#)
- [Image processing access rules](#): calls multiple IMG functions.

Usage

IMG uses standard HTTP GET. You can configure IMG parameters in QueryString of a URL.

If the ACL of an image object is private read and write, only authorized users are allowed for access.

- Anonymous access

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction>,<yourParamValue>
```

Parameter	Description
bucket	Specifies the name of a bucket.
endpoint	Specifies endpoint used to access a region.
object	Specifies the name of an image object.

Parameter	Description
image	Specifies the reserved identifier for IMG.
action	Specifies the operations on an image, such as scaling, cropping, and rotating.
param	Specifies the parameter that indicates the operation on an image.

— Basic operations

For example, scale an image to a width of 100 px. Adjust the height based on the ratio.

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

— Customized image styles

You can use the following format in level-3 domains to access a processed image:

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=style/<yourStyleName>
```

- style: specifies a reserved identifier of a customized image style.
- yourStyleName: specifies the name of a custom image style. It is the name specified in the rule that is created on the OSS console.

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=style/oss-pic-style-w-100
```

— Cascade operations

Cascade operations allow you to perform multiple operations on an image sequentially.

```
http://<yourBucketName>.<yourEndpoint>/<yourObjectName>?x-oss-process=image/<yourAction1>,<yourParamValue1>/<yourAction2>,<yourParamValue2>/...
```

Example:

```
http://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100/rotate,90
```

— HTTPS access

IMG supports access through HTTPS. Example:

```
https://image-demo.oss-cn-hangzhou.aliyuncs.com/example.jpg?x-oss-process=image/resize,w_100
```

- Authorized access

Authorized access allows you to customize an image style, HTTPS access, and cascade operations.

Run the following code to generate a signed URL for IMG:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
var objectName = "<yourObjectName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    var process = "image/resize,m_fixed,w_100,h_100";
    var req = new GeneratePresignedUriRequest(bucketName, objectName, SignHttpMethod.Get)
    {
        Expiration = DateTime.Now.AddHours(1),
        Process = process
    };
    // Generate a signed URI.
    var uri = client.GeneratePresignedUri(req);
    Console.WriteLine("Generate Presigned Uri:{0} with process:{1} succeeded ", uri, process);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error code: {0}; Error info: {1}. \nRequestId:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

- Access with SDK

You can use SDK to access and process an image object.

SDK allows you to customize image styles, HTTPS access, and cascade operations.

— Basic operations

Run the following code to perform basic operations on an image:

```
using System;
```

```

using System.IO;
using Aliyun.OSS;
using Aliyun.OSS.Common;
using Aliyun.OSS.Util;
namespace ImageProcess
{
    class Program
    {
        static void Main(string[] args)
        {
            Program.ImageProcess();
            Console.ReadKey();
        }
        public static void ImageProcess()
        {
            var endpoint = "<yourEndpoint>";
            var accessKeyId = "<yourAccessKeyId>";
            var accessKeySecret = "<yourAccessKeySecret>";
            var bucketName = "<yourBucketName>";
            var objectName = "<yourObjectName>";
            var localImageFilename = "<yourLocalImageFilename>";
            var downloadDir = "<yourDownloadDir>";
            // Create an OSSClient instance.
            var client = new OssClient(endpoint, accessKeyId,
accessKeySecret);
            try
            {
                client.PutObject(bucketName, objectName,
localImageFilename);
                // Scale the image.
                var process = "image/resize,m_fixed,w_100,h_100";
                var ossObject = client.GetObject(new GetObjectRe
equest(bucketName, objectName, process));
                WriteToFile(downloadDir + "/sample-resize.jpg",
ossObject.Content);
                // Crop the image.
                process = "image/crop,w_100,h_100,x_100,y_100,r_1
";
                ossObject = client.GetObject(new GetObjectRequest(
bucketName, objectName, process));
                WriteToFile(downloadDir + "/sample-crop.jpg",
ossObject.Content);
                // Rotate the image.
                process = "image/rotate,90";
                ossObject = client.GetObject(new GetObjectRequest(
bucketName, objectName, process));
                WriteToFile(downloadDir + "/sample-rotate.jpg",
ossObject.Content);
                // Sharpen the image.
                process = "image/sharpen,100";
                ossObject = client.GetObject(new GetObjectRequest(
bucketName, objectName, process));
                WriteToFile(downloadDir + "/sample-sharpen.jpg",
ossObject.Content);
                // Add watermarks.
                process = "image/watermark,text_SGVsbG8g5Zu-
54mH5pyN5YqhIQ";
                ossObject = client.GetObject(new GetObjectRequest(
bucketName, objectName, process));
                WriteToFile(downloadDir + "/sample-watermark.jpg
", ossObject.Content);
                // Convert the image format.

```

```

        process = "image/format,png";
        ossObject = client.GetObject(new GetObjectRequest(
bucketName, objectName, process));
        WriteToFile(downloadDir + "/sample-format.png",
ossObject.Content);
        // Obtain image information.
        process = "image/info";
        ossObject = client.GetObject(new GetObjectRequest(
bucketName, objectName, process));
        WriteToFile(downloadDir + "/sample-info.txt",
ossObject.Content);
        Console.WriteLine("Get Object:{0} with process:{1
} succeeded ", objectName, process);
    }
    catch (OssException ex)
    {
        Console.WriteLine("Failed with error code: {0};
Error info: {1}. \nRequestID:{2}\tHostID:{3}",
ex.ErrorCode, ex.Message, ex.RequestId, ex.
HostId);
    }
    catch (Exception ex)
    {
        Console.WriteLine("Failed with error info: {0}",
ex.Message);
    }
}
private static void WriteToFile(string filePath, Stream
stream)
{
    using (var requestStream = stream)
    {
        using (var fs = File.Open(filePath, FileMode.
OpenOrCreate))
        {
            IoUtils.WriteTo(stream, fs);
        }
    }
}
}
}
}

```

— Customize an image style

Use the following code to customize an image style:

```

using System;
using System.IO;
using Aliyun.OSS;
using Aliyun.OSS.Common;
using Aliyun.OSS.Util;
namespace ImageProcessCustom
{
    class Program
    {
        static void Main(string[] args)
        {
            Program.ImageProcessCustomStyle();
            Console.ReadKey();
        }
        public static void ImageProcessCustomStyle()

```

```

    {
        var endpoint = "<yourEndpoint>";
        var accessKeyId = "<yourAccessKeyId>";
        var accessKeySecret = "<yourAccessKeySecret>";
        var bucketName = "<yourBucketName>";
        var objectName = "<yourObjectName>";
        var localImageFilename = "<yourLocalImageFilename>";
        var downloadDir = "<yourDownloadDir>";
        // Create an OSSClient instance.
        var client = new OssClient(endpoint, accessKeyId,
accessKeySecret);
        try
        {
            client.PutObject(bucketName, objectName,
localImageFilename);
            // Customize the image style: "style/<yourCustom
StyleName>".
            var process = "style/oss-pic-style-w-100";
            var ossObject = client.GetObject(new GetObjectR
equest(bucketName, objectName, process));
            WriteToFile(downloadDir + "/sample-style.jpg",
ossObject.Content);
            Console.WriteLine("Get Object:{0} with process:{1
} succeeded ", objectName, process);
        }
        catch (OssException ex)
        {
            Console.WriteLine("Failed with error code: {0};
Error info: {1}. \nRequestID:{2}\tHostID:{3}",
ex.ErrorCode, ex.Message, ex.RequestId, ex.
HostId);
        }
        catch (Exception ex)
        {
            Console.WriteLine("Failed with error info: {0}",
ex.Message);
        }
    }
    private static void WriteToFile(string filePath, Stream
stream)
    {
        using (var requestStream = stream)
        {
            using (var fs = File.Open(filePath, FileMode.
OpenOrCreate))
            {
                IoUtils.WriteTo(stream, fs);
            }
        }
    }
}

```

— Cascade operations

Use the following code to perform cascade operations on an image:

```

using System;
using System.IO;
using Aliyun.OSS;
using Aliyun.OSS.Common;

```

```

using Aliyun.OSS.Util;
namespace ImageProcessCascade
{
    class Program
    {
        static void Main(string[] args)
        {
            Program.ImageProcessCascade();
            Console.ReadKey();
        }
        public static void ImageProcessCascade()
        {
            var endpoint = "<yourEndpoint>";
            var accessKeyId = "<yourAccessKeyId>";
            var accessKeySecret = "<yourAccessKeySecret>";
            var bucketName = "<yourBucketName>";
            var objectName = "<yourObjectName>";
            var localImageFilename = "<yourLocalImageFilename>";
            var downloadDir = "<yourDownloadDir>";
            // Create an OSSClient instance.
            var client = new OssClient(endpoint, accessKeyId,
accessKeySecret);
            try
            {
                client.PutObject(bucketName, objectName,
localImageFilename);
                // Perform cascade operations.
                var process = "image/resize,m_fixed,w_100,h_100/
rotate,90";
                var ossObject = client.GetObject(new GetObjectR
equest(bucketName, objectName, process));
                WriteToFile(downloadDir + "/sample-style.jpg",
ossObject.Content);
                Console.WriteLine("Get Object:{0} with process:{1
} succeeded ", objectName, process);
            }
            catch (OssException ex)
            {
                Console.WriteLine("Failed with error code: {0};
Error info: {1}. \nRequestID:{2}\tHostID:{3}",
ex.ErrorCode, ex.Message, ex.RequestId, ex.
HostId);
            }
            catch (Exception ex)
            {
                Console.WriteLine("Failed with error info: {0}",
ex.Message);
            }
        }
        private static void WriteToFile(string filePath, Stream
stream)
        {
            using (var requestStream = stream)
            {
                using (var fs = File.Open(filePath, FileMode.
OpenOrCreate))
                {
                    IoUtils.WriteTo(stream, fs);
                }
            }
        }
    }
}

```



```
}
```

IMG tools

You can use the IMG viewer [ImageStyleViewer](#) to directly view the IMG result.

7.15 Static website hosting

You can set your bucket configuration to the static website hosting mode. After the configuration takes effect, you can access this static website with the bucket domain and be redirected to a specified index page or error page.

For more information about static website hosting, see [Static website hosting](#).

Configure static website hosting

Run the following code to configure static website hosting:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Configure static website hosting.
    var request = new SetBucketWebsiteRequest(bucketName, "index.html", "error.html");
    client.SetBucketWebsite(request);
    Console.WriteLine("Set bucket:{0} Website succeeded ", bucketName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \n\nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
```

View static website hosting configurations

Run the following code to view static website hosting configurations:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
```

```
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // View static website hosting configurations.
    var result = client.GetBucketWebsite(bucketName);
    Console.WriteLine("Get bucket:{0} Website succeeded, index doc:{1}
, error doc:{2}", bucketName, result.IndexDocument, result.
ErrorDocument);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}
```

Delete static website hosting configurations

Run the following code to delete static website hosting configurations:

```
using Aliyun.OSS;
using Aliyun.OSS.Common;
var endpoint = "<yourEndpoint>";
var accessKeyId = "<yourAccessKeyId>";
var accessKeySecret = "<yourAccessKeySecret>";
var bucketName = "<yourBucketName>";
// Create an OSSClient instance.
var client = new OssClient(endpoint, accessKeyId, accessKeySecret);
try
{
    // Delete static website hosting configurations.
    client.DeleteBucketWebsite(bucketName);
    Console.WriteLine("Delete bucket:{0} Website succeeded ",
bucketName);
}
catch (OssException ex)
{
    Console.WriteLine("Failed with error info: {0}; Error info: {1}. \
nRequestID:{2}\tHostID:{3}",
        ex.ErrorCode, ex.Message, ex.RequestId, ex.HostId);
}
catch (Exception ex)
{
    Console.WriteLine("Failed with error info: {0}", ex.Message);
}
}
```

```
}
```

7.16 Exception handling

OSS .NET SDK has two types of exceptions: `ClientException` and `OSSEException`. Both share the properties of `RuntimeException`.

ClientException

The `ClientException` exception occurs when the client attempts to send requests and when the data is transmitted to OSS. For example, when a request is sent, `ClientException` may occur due to unavailable network connections. `ClientException` may occur during file uploads due to IO exceptions.

OSSEException

`OSSEException` indicates a server exception. The exception occurs because a server error message is parsed. `OSSEException` includes the error code and information returned from OSS. It is used to locate and handle problems.

The following table describes common `OSSEException` information.

Parameter	Description
Code	Specifies the error code returned by OSS.
Message	Specifies the detailed error information returned by OSS.
RequestId	Specifies the UUID. It is unique and used to identify a request. If a problem persists, send the RequestId to OSS developers for help.
HostId	Identifies an OSS cluster. Ensure that the value of HostId is consistent with the Host (endpoint to access a bucket) used in the request.

OSS error codes

Error code	Description
AccessDenied	Access denied
BucketAlreadyExists	The bucket already exists.
BucketNotEmpty	The bucket is not empty.
EntityTooLarge	The entity size exceeds the maximum limit.

Error code	Description
EntityTooSmall	The entity size is below the minimum limit.
FileGroupTooLarge	The total file group size exceeds the maximum limit.
FilePartNotExist	No such part exists.
FilePartStale	The part has expired.
InvalidArgument	The parameter format is invalid.
InvalidAccessKeyId	No such AccessKeyId exists.
InvalidBucketName	The bucket name is invalid.
InvalidDigest	The digest is invalid.
InvalidObjectName	The object name is invalid.
InvalidPart	The part is invalid.
InvalidPartOrder	The part order is invalid.
InvalidTargetBucketForLogging	The buckets that store log files are invalid.
InternalError	Internal OSS error
MalformedXML	The XML format is invalid.
MethodNotAllowed	The method is not allowed.
MissingArgument	Parameters are not configured.
MissingContentLength	The content length is not configured.
NoSuchBucket	No such bucket exists.
NoSuchKey	No such object exists.
NoSuchUpload	No such uploadId exists.
NotImplemented	The methods are not implemented.
PreconditionFailed	Precondition error
RequestTimeTooSkewed	The local time set for OSSClient is deviated from the time set for the OSS server by over 15 minutes.
RequestTimeout	Request timeout
SignatureDoesNotMatch	Signature mismatch
TooManyBuckets	The number of buckets exceeds the limit.